



PRODUCT SERVICE

ETS PRODUCT SERVICE AG

TEST - REPORT

**FCC RULES PART 15 / SUBPART B
IC RSS-GEN ISSUE 1**

Test report no.:

G0M20610-0938-C-2



Certificate 1983.01

ETS
PRODUCT SERVICE AG

STORKOWER STRASSE 38C,
PHONE +49-33631-888 00

D-15526 REICHENWALDE B. BERLIN
FAX +49-33631-888 660

TABLE OF CONTENTS

1	General Information	2
1.1	Notes	2
1.2	Tester	4
1.3	Testing laboratory	5
1.3.1	Location	5
1.3.2	Details of accreditation status	5
1.3.3	Test location, where different	5
1.4	Details of applicant	6
1.5	Application details	6
1.6	Test item	6
1.6.1	Description of test item	6
1.6.2	Manufacturer (if different from applicant in point 1.4)	7
1.6.3	Frequency behavior	7
1.7	Test standards	7
2	Technical test	7
2.1	Summary of test results	7
2.2	Test environment	8
2.3	Test equipment utilized	9
2.4	Test results	19
2.4.1	Conducted Emission	20
2.4.2	Spurious Emission	21
2.5	Test protocols	22
2.6	Equipment Modification	24
3	Normative references	25

Annex: Pictures and diagrams

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The tests were carried out and passed in accordance to the standards:

FCC part 15 : August 2006

IC RSS-Gen Issue 1

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification (only telecommunication products).

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.6.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the ETS PRODUCT SERVICE AG.

Important Notes:

Proper labeling is required for each device. Devices shall be labeled in accordance with labeling requirements pursuant to section 15.19 and section 2.1074 of the FCC rules and RSP100 of the IC-Canada specification.

Devices subject to a Declaration of Conformity shall be uniquely identified by the responsible party.

This identification shall not be of a format which could be confused with the FCC Identifier required on certified, notified type accepted or type approved equipment.

The responsible party shall maintain adequate identification records to facilitate positive identification for each device.

The user manual or instruction manual shall included also a warning statement that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Reference Section 15.21

Furthermore information to the user regarding to the interference potential of the device and about simple measures that can be taken to correct interference is required.

Reference Section 15.105

The responsible party must warrant that each unit of equipment marketed under a Declaration of Conformity is identical to the unit tested and found acceptable with the standards and that the records maintained by the responsible party continue to reflect the equipment being produced under the Declaration of Conformity within the variation that can be expected due to quantity production and testing on a statistical basis.

1.2 Tester

23.11.2006

M. Schlaps



Date

ETS-Lab.

Name

Signature

Technical responsibility for area of testing:

23.11.2006

N. Kaspar



Date

ETS

Name

Signature

1.3 Testing laboratory

1.3.1 Location

ETS PRODUCT SERVICE AG

Storkower Strasse 38c

D- 15526 Reichenwalde

Germany

Telephone : + 49 33631 888 00

Telefax : + 49 33631 888 660

1.3.2 Details of accreditation status

ACCREDITED TESTING LABORATORY

DAR-REGISTRATION NUMBER: DAT-P-201/96

ACCREDITED COMPETENT BODY

DAR-REGISTRATION NUMBER: BNetzA-zS-026/96

FCC FILED TEST LABORATORY:

REG. NO. 96970

INDUSTRY CANADA FILED TEST LABORATORY

REG. NO. IC 3470

A2LA ACCREDITED

CERTIFICATE NUMBER: 1983.01

BLUETOOTH QUALIFICATION TEST FACILITY (BQTF)

ACCREDITED BY: BLUETOOTH QUALIFICATION REVIEW BOARD (BQRF)

1.3.3 Test location, where different

Name	: ./.
Street	: ./.
Town	: ./.
Country	: ./.
Telephone	: ./.
Fax	: ./.
Teletex	: ./.

1.4 Details of applicant

Name : OraMetrix GmbH
Street : Rungestrasse 19
Town : 10179 Berlin
Country : Germany
Telephone : +49.30.24309125
Fax : +49 +30 . 24 30 91

Contact : Herr Christoph Radinger
E-mail : christoph.radinger@orametrix.de

1.5 Application details

Date of receipt of application : 25.10.2006
Date of receipt of test item : 25.10.2006
Date of test : 03..11.2006; 14.11.2006

1.6 Test item

1.6.1 Description of test item

Type of product : Wireless Footswitch
Type identification : ASSY-000363
Serial number : without
Photos : Please find in Appendix.
Power supply : 5 V DC (powered by PS2-PORT)

1.6.2 Manufacturer (if different from applicant in point 1.4)

Name : OraMetrix GmbH
Street : Rungestrasse 19
Town : 10179 Berlin
Country : Germany

Contact : Herr Christoph Radinger
Phone : +49.30.24309125

1.6.3 Frequency behavior

Highest clock Frequency	< 200 MHz
-------------------------	-----------

1.7 Test standards

FCC part 15 : August 2006
IC RSS-Gen Issue 1 : September 2005

2 Technical test**2.1 Summary of test results**

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified in 2.4 were ascertained in the course of the tests performed.



2.2 Test environment

Temperature	: 18 ... 25 °C
Relative humidity content	: 20 ... 75 %
Air pressure	: 860 ... 1030 hPa
Details of power supply	: 5 V DC (powered by PS2-PORT)
Other parameters	: Computer configuration

Pos.	Type	Description	
1.	CPU	Intel Pentium	500 MHz
2.	RAM	SDRAM	128MB
3.	Motherboard	P6 I 440BX-BrillanX-1S/2K	
4.	Hard disk	Seagate Medalist 2132	ST32 132A
5.	Floppy disk	TEAC-Corporation	FD-235HF
6.	CD-ROM	ATAPI	44x max
7.	Monitor	SMILE 17"	CA1716CL
8.	Keyboard	Alcatel	MF II German
9.	Mouse	LOGITECH	Serial Mouse
10.	ATX Power Supply	Achieve	AX250
11.	ATI RAGE	128	
12.	Computer Housing	DESKTOP	Fully shielded
13.	Cable	All cable inside housing have been installed with Split ferrites	

2.3 Test equipment utilized

No.	Test equipment	Type	Manufacturer
ETS 0001	ESD Gun	SESD 30000	Schlöder
ETS 0002	Test receiver	ESVP	R & S
ETS 0003	Diode Power Sensor	NRV-Z2	R & S
ETS 0004	Spektrum- and Network-Analyzer	FSMS 26	R & S
ETS 0005	RF amplifier matrix	RSU-ETS-CTR6	ETS
ETS 0006	HP-Filter	H1G04G01	Microwave
ETS 0007	Horn antenna	AT 4004	ar
ETS 0008	Antenna	Loop antenna	Siemens
ETS 0009	Comb Generator Emitter	CGE 02	York EMC Services
ETS 0011	Antenna (van Veen/Frame)	HM020Z3	R & S
ETS 0012	Biconical Antenna	HK 116	R & S
ETS 0013	LPD Antenna	HL 223	R & S
ETS 0014	Log Periodical Antenna	HL 025	R & S
ETS 0015	Log Periodical Antenna	HL 025	R & S
ETS 0016	Precision antenna kit	VHAP	Schwarzbeck
ETS 0017	Precision antenna kit	UHAP	Schwarzbeck
ETS 0018	Horn antenna	BBHA 9120 D	Schwarzbeck
ETS 0019	Horn antenna	BBHA 9120 D	Schwarzbeck
ETS 0020	Antenna	DP 21	MEB
ETS 0021	Antenna	DP 3	MEB
ETS 0022	Antenna	SAS-200/ 521	A.H. Systeme+D65
ETS 0023	Antenna	DP 1	MEB
ETS 0024	Antenna mast	AF 2	MEB
ETS 0025	Antenna mast	AF 2	MEB
ETS 0026	Tripod		Heinrich Deisel
ETS 0027	Tripod		Heinrich Deisel
ETS 0028	Tripod	STA 2	C. Lorenz AG
ETS 0029	Tripod		Berlebach
ETS 0030	Biconical Antenna	HK 116	R & S
ETS 0031	Turn table	DS 412	Heinrich Deisel
ETS 0032	Controller	HD 050	Heinrich Deisel
ETS 0033	Calibr. Set CDN	3x Adaptor 50-150 Ohm	ETS
ETS 0034	RF Generator/ Amplifier	SMLR	R & S
ETS 0035	RF Generator/ Amplifier	SMLM	R & S
ETS 0036	Zirc. Antenna	3102	EMCO
ETS 0037	Zirc. Antenna	3102L	EMCO
ETS 0038	RF amplifier	150L	Amplifier Research
ETS 0039	Absorbing clamp	MDS 21	R & S
ETS 0040	Artificial Mains Network	ESH3-Z5	R & S
ETS 0041	T-Artificial Mains Network	ESH3-Z4	R & S

No.	Test equipment	Type	Manufacturer
ETS 0042	Artificial Mains	ESH3-Z6	R & S
ETS 0043	Directional Coupler	1850	KRYTAR
ETS 0046	Power supply	2224.7	Statron
ETS 0047	Power supply	2224.7	Statron
ETS 0048	Power supply	2224.7	Statron
ETS 0049	Power supply	2228.1	Statron
ETS 0050	Power supply	2224.2	Statron
ETS 0051	Oscilloscope	TDS 640A	Tektronix
ETS 0051a	Probe a	P6139A	Tektronix
ETS 0051b	Probe b	P6139A	Tektronix
ETS 0052	Audio analyzer	UPA 4	R & S
ETS 0056	Ultra Compact Simulator	UCS 500 M4	EM Test
ETS 0057	Motor Variac	MV 2616	EM Test
ETS 0058	Capacitive coupling clamp	E 502 B	Keytek/ EMC
ETS 0059	Kikusui amplifier	PCR 2000L	Keytek/ EMC
ETS 0064	CDN IEC 61000-4-6		Keytek/ EMC
ETS 0066	EM Injection Clamp		FCC/ EMC
ETS 0067	Calibration Fixture	IEC 801-2031 CF	FCC/ EMC
ETS 0068	CDN IEC 1000-4-6	CDN	FCC/ EMC
ETS 0069	EM Radiation Monitor	EMR-20	W & G
ETS 0070	PC Transfer set EMR-20	EMR-20	W & G
ETS 0071	Video camera system	KMB012	Kocom
ETS 0072	Interphone system	JS-1400	Jiuh Sheng
ETS 0073	Audio noise meter	GSM 2	MKD/ RFT
ETS 0075	NF Generator	GF 22	Präcitronic
ETS 0076	Feeding bridge A	SBA 1000	ESP
ETS 0078	LCR meter	SR 720	SRS
ETS 0079	Functional Generator	MX-2020	Maxcom
ETS 0082	PC Novell network system	Novell	Esotronic
ETS 0085	Shielded room	SR 1	Frankonia
ETS 0086	Semi-Anechoic chamber	AC 1	Frankonia
ETS 0087	Climatic cell	HC 4033	Heraeus
ETS 0088	Color TV pattern Generator	PM 5518-TX VPS	Philips
ETS 0089	Radio Communication tester	CMS 54	R & S
ETS 0091	Signal Generator	SME 03	R & S
ETS 0092	Power Amplifier	150W1000	AR Amplifier Research
ETS 0093	Attenuator	57-20-33	Weinschel
ETS 0094	Power Sensor	NRV-Z55	R & S
ETS 0095	DECT system controller	PSMD	R & S
ETS 0096	DECT Signaling unit	PSMD-B11	R & S
ETS 0097	Rack, 19", 36 HU	TS 89RA	R & S
ETS 0098	System engineering and software	CS 893BE	R & S
ETS 0099	Extension unit for basic version	TS 8930B	R & S
ETS 0100	Signal Generator	SME-06	R & S
ETS 0101	Power Amplifier	50W1000B	AR Amplifier Research
ETS 0102	CDN	M3-801/6	MEB
ETS 0103	Magnetic field test set	MF1000	EMC-Partner

Registration number: G0M20610-0938-C-2

No.	Test equipment	Type	Manufacturer
ETS 0105	RF Signal Generator (High power synthesizer/ sweeper)	SMP 02 (SMP 22 / 02)	R & S
ETS 0106	Antenna	Vamp 9243	Schwarzbeck
ETS 0108	DECT protocol tester TBR 22	TS 1220	R & S
ETS 0110	Real time Signaling unit	PSMD-B2	R & S
ETS 0111	PCM Real-time audio interface for PSM	PSMD-B3	R & S
ETS 0112	Synthesizer Module	PSMD-B4	R & S
ETS 0114	RF step attenuator	RSG	R & S
ETS 0116	Protokolltester	PTW 70	R & S
ETS 0117	Insertion unit	URV5-Z2	R & S
ETS 0120	RF step attenuator	TRI-50-20	INCO
ETS 0123	RF attenuator	RBU	R & S
ETS 0124	Tripod	STA 2	R & S
ETS 0136	Attenuator	33-6-34	Weinschel
ETS 0140	High voltage Generator	IP 6Wa	TPW
ETS 0141	Sliding bridge	J 573	RFT
ETS 0143	Impedance converter	TK 12	RFT
ETS 0144	Notch filter	WRCT 24000/2497-80-20SS	Wainwright
ETS 0145	Coaxial Directional	3002-20	Narda
ETS 0146	Active Voltage Probe	ESH2-Z2	R & S
ETS 0148	RF Current Probe	F-65	FCC
ETS 0149	Power divider	ZAPD-21	MCL
ETS 0150	Switcher	HR07-720	Wisi
ETS 0151	Interference pulse Generator	NSG 500C	Schaffner
ETS 0152	Simulator for Load-Dump-Impulse	NSG 506C (I)	Schaffner
ETS 0153	Simulator for Load-Dump-Impulse	NSG 506C (II)	Schaffner
ETS 0155	Signal Generator	SMG	R & S
ETS 0159	Programmable power supply	TOE 8815	Toellner
ETS 0160	Amplifier	AR 1W1000	Amplifier Research
ETS 0161	Harmonic / Flicker Analyzer	HFA 3000	Schlöder
ETS 0162	Acoustic chamber	403-A	IAC
ETS 0163	Test head	BK 4602	Brüel & Kjær
ETS 0164	Simulator ear	BK 4185	Brüel & Kjær
ETS 0165	Simulator mouth	BK 4227	Brüel & Kjær
ETS 0166	Sound level calibrator	BK 4231	Brüel & Kjær
ETS 0167	Communication Analysis System	CAS TE I	HEAD acoustics
ETS 0168	Acoustical test for DECT	CTR 10	HEAD acoustics
ETS 0169	Measurement - Front-end (analog)	MFE III	HEAD acoustics
ETS 0170	Measurement - Front-end (digital)	MFE IV	HEAD acoustics
ETS 0171	Electronic test cradle	TEH	HEAD acoustics
ETS 0172	Noise Generator	HNG III.1	HEAD acoustics
ETS 0173	Speaker	Canton S Pluss	HEAD acoustics

Registration number: G0M20610-0938-C-2

No.	Test equipment	Type	Manufacturer
ETS 0174	Measurement - Front-end line interface	MFE V	HEAD acoustics
ETS 0175	Software Line interface (analog)	COPTZV5	HEAD acoustics
ETS 0176	Acoustic volt meter	COP 4	HEAD acoustics
ETS 0177	Feeding bridge B	SBB 1000	ESP
ETS 0178	Open area test side	10m	ETS
ETS 0179	Open area test side	3 m	ETS
ETS 0186	Power supply	DF 1730	WJG
ETS 0189	Spectrum Analyzer	FSEB	R & S
ETS 0191	Sweep function Generator	7202	Dagatron
ETS 0218	RF probe	URV5-Z7	R & S
ETS 0219	Power sensor	NRV-Z2	R & S
ETS 0221	ISDN-S0-Analyzer	K1403	Siemens
ETS 0222	ISDN Protocol Analyzer	TE965	Tekelec Teleco.
ETS 0223	GSM/ PCN/ PCS-Simul.	TS8916B	R & S
	Radio Channel Simulator	SOFI 05	Sofimation
ETS 0224A	Millivolt meter	URV5	R & S
ETS 0224B	Diode Power Sensor	NRV-Z1	R & S
ETS 0224C	Programmable high resolution timer counter	PM6654G	Philips
ETS 0224D	RF Stepp Attenuator	RSP	R & S
ETS 0224E	Signal Generator	SMG	R & S
ETS 0225	SIM Simulator		Orga
ETS 0226	SIM Editor		Orga
ETS 0227	Vibration table	TIRA vib	GenRad
	Accelerator	PCB M353B33	PCB Piezotronics Inc.
ETS 0228	Climatic chamber	VT 4010	Vötsch
ETS 0229	Radio Communication. Tester	CMT 54	R & S
ETS 0230	Radio Communication. Tester	CMD 65	R & S
ETS 0232	Radiation test source	VSQ 1	MEB
ETS 0233	Direction coupler	RK 100	MEB
ETS 0234	Power meter	NRVD	R & S
ETS 0235	RF-network-Analyzer	8752 C	HP
ETS 0236	RF-amplifier	100A100	ar
ETS 0237	RF-amplifier	100W1000M1	ar
ETS 0238	Field strong meter	FM 2000	ar
ETS 0239	Isotropic field probe 40 GHz	FP 2080 Kit	ar
ETS 0240	Isotropic field probe 1 GHz	FP 2000 Kit	ar
ETS 0241	Pulse Generator	4050	PicoSecond PL
ETS 0244	Ultra Compact Simulator	UCS 200 M	EM-Test
ETS 0245	Load dump Generator	LD 200 B1	EM-Test
ETS 0246	Voltage drop simulator	VDS 200	EM-Test
ETS 0247	Calibration adaptor	KW50	EM-Test
ETS 0248	Calibration adaptor	KW1000	EM-Test
ETS 0251	Climatic chamber	VT 4004	Vötsch
ETS 0252	System controller	PSM 12	R & S
ETS 0253	Spectrum Analyzer	FSIQ 26	R & S
ETS 0254	RF Generator	SMIQ 03	R & S

Registration number: G0M20610-0938-C-2

No.	Test equipment	Type	Manufacturer
ETS 0255	RF Generator	SMIQ 03	R & S
ETS 0256	RF Generator	SMR 27	R & S
ETS 0257	Step attenuator	RSP	R & S
ETS 0258	Rubidium standard	RSTU	DATUM GmbH
ETS 0259	Power meter	NRVD	R & S
ETS 0260	Power sensor	NRV-Z1	R & S
ETS 0261	Power sensor	NRV-Z1	R & S
ETS 0262	Switching unit	SSCU	R & S
ETS 0263	Signaling unit	PTW 60	R & S
ETS 0265	Loop antenna	HFRA 9150	Schwarzbeck
ETS 0266	Messadapter 1:100	50 Ohm	
ETS 0267	RF Signal Generator	SMT 03	R & S
ETS 0268	Signal Generator	SMP 02	R & S
ETS 0269	RF bridge 50 Ohm	86205 A	Agilent
ETS 0270	Signal Generator	SMP 04	R & S
ETS 0271	Spectrum Analyzer	FSEK 30	R & S
ETS 0272	Signal Generator	SME 03	R & S
ETS 0273	Signal Generator	SME 03	R & S
ETS 0274	Signal Generator	SMY 01	R & S
ETS 0275	Power sensor	NRV-Z51	R & S
ETS 0276	Audio Analyzer	UPL 16	R & S
ETS 0277	Power sensor	NRV-Z1	R & S
ETS 0278	Power sensor	NRV-Z31	R & S
ETS 0279	Step attenuator	RSP	R & S
ETS 0280	Power meter	NRVD	R & S
ETS 0281	Spectrum Analyzer	FSM	R & S
ETS 0282	RF bridge 75 Ohm	86207 A	HP
ETS 0283	RF bridge 50 Ohm	86205 A	HP
ETS 0284	Field probe	11940 A	HP
ETS 0285	Field probe	11941 A	HP
ETS 0286	Limither	11867 A	HP
ETS 0287	EMI Test receiver	ESHS10	R & S
ETS 0288	Artificial mains	ESH2-Z5	R & S
ETS 0289	Audio Generator	TAG 101	Troneer
ETS 0290	Audio Generator	TAG 101	Troneer
ETS 0291	Loop antenna	HFH2-Z2	R & S
ETS 0292	RF Generator	SMHU	R & S
ETS 0293	Artificial mains	NNBM 8125	Schwarzbeck
ETS 0294	Biconical antenna	HK 116	R & S
ETS 0295	LPD antenna	HL 223	R & S
ETS 0296	GTEM cell	GTEM 500	Schaffner
ETS 0297	Power pulse Generator	IGUF 2910	Schwarzbeck
ETS 0299	DECT protocol tester	TS 1220	R & S
ETS 0300	RF amplifier	75 A 250	ar
ETS 0301	Relay switch unit	RSU	R & S
ETS 0302	Data line CDN	CM-I/O CD	Keytek
ETS 0303	Telecom line CDN	CM-TEL CD	Keytek
ETS 0306	Function Generator	HP 33120A	HP

Registration number: G0M20610-0938-C-2

No.	Test equipment	Type	Manufacturer
ETS 0307	Commu. Sign. Analyzer	CSA 803 A	Tektronix
ETS 0308	Spectrum analyzer	R 3361A	Advantest
ETS 0309	Anechoic chamber	AC 2	Frankonia
ETS 0310	Anechoic chamber	AC 3	Frankonia
ETS 0311	Anechoic chamber	AC 4	Frankonia
ETS 0313	Power sensor	NRV-Z51	R & S
ETS 0314	LPD antenna	HL 223	R & S
ETS 0315	Biconical antenna	HK 116	R & S
ETS 0316	Switcher	Hr 07-720	WISI
ETS 0318	Dial pulse/ DTMF tester	210	HE
ETS 0319	Opto link	GPIB 140	NI
ETS 0320	Opto link	GPIB 140	NI
ETS 0322	Insertion unit	URV5-Z4	R & S
ETS 0328	ELF Field Strenght Measurement System	HI-3604	Holaday Ind., INC.
ETS 0329	VDT / VLF Radiation Measurement System	HI-3603	Holaday Ind., INC.
ETS 0330	Fiber Optic Remote Control	HI-3616	Holaday Ind., INC.
ETS 0331	TS 1220		
ETS 0332	PSM		
ETS 0333	Turn table	DE 350	Heinrich Deisel
ETS 0334	Controller	HD 100	Heinrich Deisel
ETS 0336	LPD antenna	HL 223	R & S
ETS 0338	Coupling network	KN002	ETS
ETS 0339	Isolating Transformer	KN003	ETS
ETS 0347	Current Probe	EZ-17	R & S
ETS 0348	RF Millivolt meter	URV 55	R & S
ETS 0349			
ETS 0350	Horn Antenna	BBHA 9120-C	Schwarzbeck
ETS 0351	RF amplifier	DWT-18057	Microwave
ETS 0352	RF amplifier		
ETS 0353	Hochpassfilter		
ETS 0354	RF amplifier	DBS-0408N423	Microwave
ETS 0355	high pass	H03G12G3	Microwave
ETS 0356	high pass	H03G12G3	Microwave
ETS 0357	high pass	H08G18G3	Microwave
ETS 0358	RF amplifier	AFD3-010040-15-ln	MITEQ
ETS 0359	RF amplifier	M/N AM-1331	MITEQ
ETS 0360	RF amplifier	DBS-0408N423	Microwave
ETS 0361	RF amplifier	DBS 1826N515	Microwave
ETS 0362	high pass	H03G12G3	Microwave
ETS 0363	high pass	H08G18G3	Microwave
ETS 0364	high pass	H08G18G3	Microwave
ETS 0365	Notch filter 2.4 GHz	WRCT2.40/248	Wain Wright
ETS 0366	high pass	H08G18G3	Microwave
ETS 0367	high pass	H03G12G3	Microwave
ETS 0368	Notch filter 0.5-1 GHz	BN86883	Schomandl
ETS 0369	Notch filter 210-500 MHz	BN86882	Schomandl

Registration number: G0M20610-0938-C-2

No.	Test equipment	Type	Manufacturer
ETS 0370	Notch filter 15-90 MHz	BN86880	Schomandl
ETS 0371	Notch filter 85-250 MHz	BN86881	Schomandl
ETS 0372	Direction coupler	RK 100	MEB
ETS 0373	Direction coupler	DC3001	EMC
ETS 0374	DC Power Supply	NGSM32	R & S
ETS 0375	Vector Signal Gener.	SMIQ03B	R & S
ETS 0376	Signal Generator	SMP22	R & S
ETS 0377	Advanced Signal Conditioning Unit	ASCU850	R & S
ETS 0378	Advanced Signal Conditioning Unit	ASCU190	R & S
ETS 0379	Advanced Signal Conditioning Unit	ASCU180	R & S
ETS 0380	Advanced Signal Conditioning Unit	ASCU900	R & S
ETS 0381	Ethernet HUB	CS-HUB	R & S
ETS 0382	Vector Signal Gener.	SMIQ03B	R & S
ETS 0383	Spectrum Analyzer	FSU26	R & S
ETS 0384	Main Frame Signal and Conditioning Unit	SSCU-GW	R & S
ETS 0385	Protocol Slave	CRTU-RU (CRTU-G)	R & S
ETS 0386	Power meter	NRVD	R & S
ETS 0387	Power Sensor	NRV-Z1	R & S
ETS 0388	Power Sensor	NRV-Z1	R & S
ETS 0389	Fading Simulator	ABFS	R & S
ETS 0390	System PC PC3600	TS-PC36	R & S
ETS 0391	Rubidium Frequency Standard	DATUM 8040	DATUM GmbH
ETS 0392	RF Distribution	DATUM 6502	DATUM GmbH
ETS 0393	Insertion unit	URV5-Z4	R & S
ETS 0394	Advanced Signal Conditioning Unit	ASCUFDD-WCDMA	R & S
ETS 0395	Universal Protocol Tester	CRTU-G	R & S
ETS 0396	Protocol Slave	CRTU-S	R & S
ETS 0397	Protocol Slave	CRTU-S	R & S
ETS 0398	Fading Simulator	ABFS	R & S
ETS 0399	Univ. Protocol Tester (Protocol Unit) (Radio Unit)	CRTU-W (CRTU-PU) (CRTU-RU)	R & S
ETS 0400	Univ. Protocol Tester (Protocol Unit) (Radio Unit)	CRTU-W (CRTU-PU) (CRTU-RU)	R & S
ETS 0401	MPEG2 Generator	DVG	R & S
ETS 0402	TV Messenger	SFQ	R & S
ETS 0403	RF Current Probe	F-140	FCC
ETS 0404	Exposure Level Tester	ELT-400	Narda
ETS 0405	Magnetic Field Probe 100 cm ²	2300/90.10	Narda
ETS 0406	Signal Generator	SML 02	R & S
ETS 0407	EMC Emission tester	Harmonics 1000	EMC Partner
ETS 0408	Transient 2000	TRA1Z191N	EMC Partner
ETS 0409	Stripline	DC220	Schwarzbeck

Registration number: G0M20610-0938-C-2

No.	Test equipment	Type	Manufacturer
ETS 0410	BAN	1	ETS
ETS 0411	Universal Protocol Tester	CRTU-G	R & S
ETS 0412	Spectrum Analyzer	FSU 3	R & S
ETS 0413	Signal Analyzer	FSIQ 26	R & S
ETS 0416	Power Supply	EX752M	TTi
ETS 0417	Beacon Tester	BT100S	WS Tech. Inc.
ETS 0418	High pass filter 4 - 8 G		Microwave
ETS 0419	High pass filter 8 - 18 G		Microwave
ETS 0420	Amplifier 0.1-1 GHz	M/N AM-1331	MITEQ
ETS 0421	Amplifier 1-4 GHz	AFD3-010040-15-LN	MITEQ
ETS 0422	Amplifier 4-8 GHz	DBS-0408N423	Narda
ETS 0423	Amplifier 8-18 GHz	DWT-18057	Narda
ETS 0424	Amplifier 18-26.5 GHz	DBS-1826N515	Narda
ETS 0425	T-Artificial Mains Network	ESH3-Z4	R & S
ETS 0426	CDN	T4 HF	MEB
ETS 0427	Power sensor	NRV-Z6	R & S
ETS 0428	4-WIRE ISN with B1	ENY41	R & S
ETS 0429	Current Probe Test Jig	SW14 7LY	Chase
ETS 0430	Signal Generator	SML02	R&S
ETS 0431	AC Mains Adaptor	BS5733	Travel Emporium
ETS 0432	RF amplifier matrix	RSU-ETS-BT	ETS
ETS 0433	RF amplifier matrix	RSU-ETS-CTR6	ETS
ETS 0434	Reserviert Tre	RSU-ETS-GSM	
ETS 0435	HP-Filter	H1G04G01	Microwave
ETS 0436	HP-Filter	H1G04G01	Microwave
ETS 0437	HP-Filter	H04G08G1	Microwave
ETS 0438	HP-Filter	H0G408G1	Microwave
ETS 0439	Amplifier	DBS-1826N515	Narda-DBS-Microwave
ETS 0440	Amplifier	AM-1331	MITEQ
ETS 0441	Bluetooth Protocol Tester	PTW 60	R & S
ETS 0445	RF-Attenuator 6dB	50FH-006-300	JFK
ETS 0446	RF-Attenuator 30dB	50FH-030-300	JFK
ETS 0447	Artificial Mains Network	LN-KFZ/200	Heine
ETS 0448	RF Power Amplifier	AR 60S1G3	AR Amplifier Research
ETS 0449	Stäubli Robot	RX90B L	Stäubli
ETS 0450	Stäubli Robot Controller	CS/MBs&p	Stäubli
ETS 0451	DASY 4 Measurement Server		Schmid & Partner
ETS 0452	Control Pendant		Stäubli
ETS 0453	Compaq Computer	Pentium IV, 2GHz	Schmid & Partner
ETS 0454	Data Acquisition Electronics	DAE3V1	Schmid & Partner
ETS 0455	Dummy Probe		Schmid & Partner
ETS 0456	Dosimetric E-Field Probe	ET3DV6	Schmid & Partner
ETS 0457	Dosimetric E-Field Probe	ET3DV6	Schmid & Partner
ETS 0458	Dosimetric H-Field Probe	H3DV6	Schmid & Partner
ETS 0459	System Validation Kit	D900V2	Schmid & Partner
ETS 0460	System Validation Kit	D1800V2	Schmid & Partner
ETS 0461	System Validation Kit	D1900V2	Schmid & Partner
ETS 0462	System Validation Kit	D2450V2	Schmid & Partner

Registration number: G0M20610-0938-C-2

No.	Test equipment	Type	Manufacturer
ETS 0463	Probe Alignment Unit	LBV2	Schmid & Partner
ETS 0464	SAM Twin phantom	V 4.0	
ETS 0465	Mounting Device	V 3.1	
ETS 0466	Directional Coupler	HP 87300B	HP
ETS 0467	Oval flat phantom	ELI 4	Schmid & Partner
ETS 0468	Isotropic E-Field Probe	ER3DV6	Schmid & Partner
ETS 0469	Dielectric Probe Kit	85070D	Agilent
ETS 0470	Amplifier	AM-1300-1103	withEQ
ETS 0472	Antenna	BTA-H	Frankonia
ETS 0473	GSM / UMTS System Simulator	TS 8950	R&S
ETS 0474	EMI Test Receiver	ESCS 30	R&S
ETS 0475	Amplifier	AFS4-00101800-U	withEQ
ETS 0476	EMI Test receiver	ESCS 30	R&S
ETS 0477	GPS-System (active GPS-antenne)	4490	HOPF
ETS 0478	Crystal filter	MQF 127.50-2400/F	Vectron International
ETS 0479	System Validation Dipoles	D300V3	Schmid & Partner
ETS 0480	System Validation Dipoles	D450V3	Schmid & Partner
ETS 0481	40GHz Standard Gain Horn with Amplifier	22240-25 CBL26402075	Flann Microwave
ETS 0482	40GHz High Gain Antenna	AT4560	Amplifier research
ETS 0483	Amplifier	AFD3010040-15-LN	MITEQ
ETS 0484	Radio Communication Tester	CMU 200	R&S
ETS 0485	Radio Communication Tester	CMU 200	R&S
ETS 0486	Circular polarized antenna	3101L	EMCO
ETS 0487	Torso simulator		ETS
ETS 0488	EMI Test Receiver	ESHS10	R & S
ETS 0489	Rubidium Frequency Standard	MFS	DATUM
ETS 0490	Rubidium Frequency Standard	8040	DATUM
ETS 0491	RF Distribution	DATUM 6502	DATUM
ETS 0492	Industrial Controller	PSM12	R & S
ETS 0493	Protokoll Tester	PTW60	R & S
ETS 0494	Switching unit	SSCU	R & S
ETS 0495	RF Step Attenuator	RSP	R & S
ETS 0496	Spectrum Analyzer	FSP	R & S
ETS 0497	Power Meter	NRVD	R & S
ETS 0498	Diode Power Sensor	NRV-Z1	R & S
ETS 0499	Diode Power Sensor	NRV-Z1	R & S
ETS 0500	Signal Generator	SMIQ03	R & S
ETS 0501	Signal Generator	SMIQ03	R & S
ETS 0502	Power Splitter	DS-808-4	Macom
ETS 0503	Directional Coupler	IAW	Microwave Filter Company
ETS 0504	AMTS-Simulator A	Feeding Bridge A	Emmerich
ETS 0505	Diode Power Sensor	NRV-Z1	R & S
ETS 0506	Diode Power Sensor	NRV-Z6	R & S
ETS 0507	Power Divider	PS-Z101-4S	UMCC
ETS 0508	Power Divider	T-1000	Macom
ETS 0509	Power Divider	T-1000	Macom

Registration number: G0M20610-0938-C-2

No.	Test equipment	Type	Manufacturer
ETS 0510	Power Divider	T-1000	Macom
ETS 0511	Power Divider	DS-409-4	Anzac
ETS 0512	Log Periodical Antenna	HL 025	R & S
ETS 0513	Flat Phantom	V4.4	Schmid & Partner

2.4 Test results

☒ 1st test☐ test after modification☐ production test

Test Emission / Immunity				Done	Test passed	Test failed
Emission	Conducted Emission	FCC part 15.107	RSS-Gen 7.2.2	☒	☒	☐
Emission	Radiated Emission	FCC part 15.109	RSS-Gen 7.2.3	☒	☒	☐

2.4.1 Conducted Emission

2.4.1.1 Test Equipment

- a) Artificial mains (ESH3-Z5)
For your reference please find it in our test equipment list at page 10 to 19 as number: **40.**
- b) Artificial mains (ESH3-Z4)
For your reference please find it in our test equipment list at page 10 to 19 as number: **41.**
- c) EMI test receiver ESCS-30
For your reference please find it in our test equipment list at page 10 to 19 as number: **474.**
- d) Monitoring System
For your reference please find it in our test equipment list at page 10 to 19 as number: **71.**
- e) Inter phone System
For your reference please find it in our test equipment list at page 10 to 19 as number: **72.**
- f) Shielded room
For your reference please find it in our test equipment list at page 10 to 19 as number: **85.**

2.4.1.2 Test Procedures

- Test configuration

The test configuration is contained inside of a shielded chamber and corresponds to the standard ANSI C.63.4: 2003. The equipment under test is placed in the facility on a wooden table 0.8m high. The equipment under test is connected with the artificial mains network (AMN) in a distance of 0,8m and also 0,8m from other subassembly and metallic area. The measurement receiver is placed in a special room adjacent to the chamber. The observation of the equipment under test is realized by 3 video cameras and by a microphone.

- Test parameters and marginal conditions

The tests are carried out with nominal impedance by $50 \Omega / 50 \mu\text{H}$ of the AMN in a frequency range 150 kHz to 30 MHz. This measurement was transacted first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector, Further information please find in test report.

2.4.2 Spurious Emission

2.4.2.1 Test Equipment

- a) Antenna (HK116)
For your reference please find it in our test equipment list at page 10 to 19 as number: **12.**
- b) Antenna (HL223)
For your reference please find it in our test equipment list at page 10 to 19 as number: **13.**
- c) Video camera system
For your reference please find it in our test equipment list at page 10 to 19 as number: **71.**
- d) Interphone System
For your reference please find it in our test equipment list at page 10 to 19 as number: **72.**
- e) Semi anechoic chamber
For your reference please find it in our test equipment list at page 10 to 19 as number: **86.**
- g) EMI test receiver ESCS-30
For your reference please find it in our test equipment list at page 10 to 19 as number: **476.**

2.4.2.2 Test Procedures

- Test configuration

The test configuration corresponds to the standard ANSI C 63.4: 2003. The equipment under test is placed on a non metallic table with 0,8 m height. The power supply and the RF connection points are close to the equipment under test at the floor inside a connection box. The cables to this connection box are shielded and below the double floor. The receiving antenna is placed in a height at 1,0 to 4,0 m, in a distance of 10 m. The measurement receiver is placed in a special room. The observation of the equipment under test is realized by 3 video cameras and by a microphone.

- Test parameters and marginal conditions

The test are carried out with horizontal and vertical polarization of the antenna in a frequency range of 30 MHz to 5 000 MHz. Further information please find in the test protocol.

2.5 Test protocols

Conducted Emission

Emission

Standard : FCC part 15.107; RSS-Gen 7.2.2

Reg.-no. : G0M20610-0938-C-2

Device : ASSY-000363

Date : 23.11.2006

Operator : _____

Class : B

Temperature : 23 °C
Pressure : 979 hPa
Rel. humidity: 35 %

Frequency Range	Limit dB μ V		Passed	Failed	Number of rechecks
	Quasi- peak	Average			
150 kHz - 500 kHz AC	66 to 56*	56 to 46*	☒	☐	0
500 kHz - 5 MHz AC	56	46	☒	☐	0
5 MHz - 30 MHz AC	60	50	☒	☐	0

* Decreases with logarithm of the frequency

Uncertainty: $U_{\text{lab(cond)}} = 2,52 \text{ dB}$

Comment: See attached diagrams.

Radio Noise Field Strength**Emission**

Standard : FCC part 15.109; RSS-Gen 7.2.3

Reg.-no. : G0M20610-0938-C-2

Device : ASSY-000363

Date : 23.11.2006

Operator : _____

Class : B

Temperature : 23 °C
Pressure : 979 hPa
Rel. humidity: 35 %

Frequency Range Polarization	Limit μV/m	Passed	Failed	Number of rechecks
30 MHz - 88 MHz	90	☒	☐	0
88 MHz - 216 MHz	150	☒	☐	0
216 MHz - 960 MHz	210	☒	☐	0
960 MHz - 5000 MHz	300	☒	☐	0

Uncertainty: $U_{\text{lab(rad)}} = 4,54 \text{ dB}$

Comment: Above 1 GHz no relevant disturbances
See attached diagrams.

2.6 Equipment Modification


No modifications were installed by ETS PRODUCT SERVICE AG.

3 Normative references

- /1/ FCC part 15: August 2006
Radio Frequency Devices
- /2/ CISPR 22: 1997 + Corrigendum: +A1: 2000 + A2: 2003
Limits and Methods of Measurement of Radio Interference Characteristics of Information Technology Equipment
- /3/ ANSI C 63.4: 2003
American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
- /4/ IC RSS-Gen Issue 1 September 2005
General Requirements and Information for the Certification of Radio communication Equipment


EMI voltage test in the ac-mains according to FCC part 15

EUT: Wireless Footswitch
Manufacturer: OraMetrix GmbH
Operating Condition: Unom: 120 V AC (AC/DC adaptor), Tnom: 23°C
Test Site: ETS
Operator: Mr. Mees
Test Specification: V-Network: ESH2-Z5 (L1)
Comment: model: ASSY-000363
Computer: Panasonic CF-27




EMI voltage test in the ac-mains according to FCC part 15

EUT: Wireless Footswitch
Manufacturer: OraMetrix GmbH
Operating Condition: Unom: 120 V AC (AC/DC adaptor), Tnom: 23°C
Test Site: ETS
Operator: Mr. Mees
Test Specification: V-Network: ESH2-Z5 (N)
Comment: model: ASSY-000363
Computer: Panasonic CF-27




Field Strength under normal conditions
FCC RULES PART 15, SUBPART B

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq:194.890MHz Pmax:32.35dBµV/m RBW: 100 kHz




Field Strength under normal conditions
FCC RULES PART 15, SUBPART B

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq:194.208MHz Pmax:32.03dBµV/m RBW: 100 kHz




Field Strength under normal conditions
FCC RULES PART 15, SUBPART B

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Comment 2: Freq:972.745MHz Pmax:22.25dBµV/m RBW: 100 kHz




Field Strength under normal conditions
FCC RULES PART 15, SUBPART B

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Comment 2: Freq:911.824MHz Pmax:24.50dBµV/m RBW: 100 kHz




Field Strength under normal conditions
FCC RULES PART 15, SUBPART B

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.
Comment 2: Freq:3.934GHz Pmax:49.91dBµV/m RBW: 1 MHz




Field Strength under normal conditions
FCC RULES PART 15, SUBPART B

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.
Comment 2: Freq:3.910GHz Pmax:49.62dBµV/m RBW: 1 MHz




Field Strength under normal conditions
FCC RULES PART 15, SUBPART B

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.
Comment 2: Freq:7.936GHz Pmax:41.57dBµV/m RBW: 1 MHz




Field Strength under normal conditions
FCC RULES PART 15, SUBPART B

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.
Comment 2: Freq:7.511GHz Pmax:42.06dBµV/m RBW: 1 MHz




Field Strength under normal conditions
FCC RULES PART 15, SUBPART B

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.
Comment 2: Freq:11.920GHz Pmax:46.33dBµV/m RBW: 1 MHz




Field Strength under normal conditions
FCC RULES PART 15, SUBPART B

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 025, ampl.
Comment 2: Freq:11.928GHz Pmax:47.10dBµV/m RBW: 1 MHz




Field Strength under normal conditions
Standards Industry Canada, RSS-GEN

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to RSS-Gen Issue 1
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq:192.846MHz Emax:32.84dBµV/m RBW: 100 kHz




Field Strength under normal conditions
Standards Industry Canada, RSS-GEN

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to RSS-Gen Issue 1
Comment 1: Dist.: 3m, Ant.: HK 116
Comment 2: Freq:197.615MHz Emax:32.82dBµV/m RBW: 100 kHz




Field Strength under normal conditions
Standards Industry Canada, RSS-GEN

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to RSS-Gen Issue 1
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Comment 2: Freq:903.808MHz Emax:25.32dBµV/m RBW: 100 kHz




Field Strength under normal conditions
Standards Industry Canada, RSS-GEN

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to RSS-Gen Issue 1
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Comment 2: Freq:903.808MHz Emax:25.37dBµV/m RBW: 100 kHz




Field Strength under normal conditions
Standards Industry Canada, RSS-GEN

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to RSS-Gen Issue 1
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Comment 2: Freq:3.970GHz Emax:50.32dBμV/m RBW: 1 MHz




Field Strength under normal conditions
Standards Industry Canada, RSS-GEN

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to RSS-Gen Issue 1
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Comment 2: Freq:3.874GHz Emax:51.01dBµV/m RBW: 1 MHz




Field Strength under normal conditions
Standards Industry Canada, RSS-GEN

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to RSS-Gen Issue 1
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Comment 2: Freq:7.455GHz Emax:47.82dBµV/m RBW: 1 MHz




Field Strength under normal conditions
Standards Industry Canada, RSS-GEN

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to RSS-Gen Issue 1
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Comment 2: Freq:7.912GHz Emax:47.48dBµV/m RBW: 1 MHz



Field Strength under normal conditions
Standards Industry Canada, RSS-GEN

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to RSS-Gen Issue 1
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Comment 2: Freq:11.824GHz Emax:46.74dBµV/m RBW: 1 MHz



Field Strength under normal conditions
Standards Industry Canada, RSS-GEN

Approval Holder: OraMetrix GmbH
EUT: WIRELESS FOOTSWITCH
Model: ASSY-000363
Test Site / Operator: ETS / Mr. Schlaps
Operating Conditions: 23°C / Unom.: 5.0 V DC (POWERED BY PS/2-PORT)
Test Specification: according to RSS-Gen Issue 1
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Comment 2: Freq:11.816GHz Emax:47.31dBµV/m RBW: 1 MHz

