

TEST REPORT

Reference No. : WTS15S1035227E
FCC ID : RJE190671
Applicant..... : Monster, LLC
Address..... : 7251 West Lake Mead Blvd, Suite 342, Las Vegas, NV 89128, USA
Manufacturer : The same as above
Address..... : The same as above
Product Name..... : ClarityHD Wireless&ADIDAS
Model No. : 190671, 190660
Brand..... : Monster(190671), ADIDAS (190660)
Standards..... : FCC CFR47 Part 15 Section 15.247:2014
Date of Receipt sample : Aug. 28, 2015
Date of Test..... : Aug. 31 ~ Sep. 11, 2015
Date of Issue..... : Oct. 22, 2015
Test Result..... : **Pass**
Remark..... : This report is based on the original report WTS15S0832825E for adding product name, model, brand and appearance.

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China
Tel :+86-755-83551033
Fax:+86-755-83552400

Compiled by:

Lake Xie

Lake Xie / Test Engineer

Approved by:

Philo Zhong


Philo Zhong / Manager

2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
20dB Bandwidth	15.247(a)(1)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Frequency Separation	15.247(a)(1)	PASS
Number of Hopping Frequency	15.247(a)(1)(iii)	PASS
Dwell time	15.247(a)(1)(iii)	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

3 Contents

	Page
1 COVER PAGE.....	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	5
4.1 GENERAL DESCRIPTION OF E.U.T.	5
4.2 DETAILS OF E.U.T.	5
4.3 CHANNEL LIST.....	5
4.4 TEST MODE	6
4.5 TEST FACILITY.....	6
5 EQUIPMENT USED DURING TEST	7
5.1 EQUIPMENTS LIST	7
5.2 DESCRIPTION OF SUPPORT UNITS	8
5.3 MEASUREMENT UNCERTAINTY	8
5.4 TEST EQUIPMENT CALIBRATION	8
6 CONDUCTED EMISSION	9
6.1 E.U.T. OPERATION	9
6.2 EUT SETUP.....	9
6.3 MEASUREMENT DESCRIPTION	9
6.4 CONDUCTED EMISSION TEST RESULT	10
7 RADIATED SPURIOUS EMISSIONS.....	12
7.1 EUT OPERATION.....	12
7.2 TEST SETUP	13
7.3 SPECTRUM ANALYZER SETUP	14
7.4 TEST PROCEDURE	15
7.5 SUMMARY OF TEST RESULTS.....	16
8 BAND EDGE MEASUREMENT	22
8.1 TEST PROCEDURE	22
8.2 TEST RESULT	23
9 20 DB BANDWIDTH MEASUREMENT	29
9.1 TEST PROCEDURE	29
9.2 TEST RESULT	29
10 MAXIMUM PEAK OUTPUT POWER	35
10.1 TEST PROCEDURE.....	35
10.2 TEST RESULT	35
11 HOPPING CHANNEL SEPARATION	41
11.1 TEST PROCEDURE.....	41
11.2 TEST RESULT	41
12 NUMBER OF HOPPING FREQUENCY	47
12.1 TEST PROCEDURE.....	47
12.2 TEST RESULT	47
13 DWELL TIME	49
13.1 TEST PROCEDURE.....	49
13.2 TEST RESULT	49
14 ANTENNA REQUIREMENT	55

15	RF EXPOSURE.....	56
15.1	REQUIREMENTS.....	56
15.2	THE PROCEDURES / LIMIT	56
16	PHOTOGRAPHS – MODEL 190671 TEST SETUP	57
16.1	PHOTOGRAPH – CONDUCTED EMISSION TEST SETUP AT TEST SITE 1#	57
16.2	PHOTOGRAPH – RADIATION SPURIOUS EMISSION TEST SETUP.....	57
17	PHOTOGRAPHS - CONSTRUCTIONAL DETAILS	59
17.1	MODEL 190671 EXTERNAL VIEW	59
17.2	MODEL 190671 INTERNAL VIEW.....	64

4 General Information

4.1 General Description of E.U.T.

Product Name:	ClarityHD Wireless& ADIDAS
Model No.:	190671, 190660
Model Description:	There is only mode name and appearance are different.
Remark	The model 190671 is the main tested sample, The model 190660 is tested sample only for Transmitter unwanted emissions.
Bluetooth Version:	4.0(including EDR to 3Mbps)
Frequency Range:	2402-2480MHz, 79 Channels in total
Type of Modulation:	GFSK, Pi/4DQPSK, 8DPSK,
The lowest oscillator:	26MHz
Antenna installation:	Integrated Antenna
Antenna Gain:	0dBi

4.2 Details of E.U.T.

Technical Data:	DC 3.7V, 60mAh by battery
	USB input: DC 5V 0.5A

4.3 Channel List

EDR

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2403	2	2404	3	2405
4	2406	5	2407	6	2408	7	2409
8	2410	9	2411	10	2412	11	2413
12	2414	13	2415	14	2416	15	2417
16	2418	17	2419	18	2420	19	2421
20	2422	21	2423	22	2424	23	2425
24	2426	25	2427	26	2428	27	2429
28	2430	29	2431	30	2432	31	2433
32	2434	33	2435	34	2436	35	2437
36	2438	37	2439	38	2440	39	2441
40	2442	41	2443	42	2444	43	2445
44	2446	45	2447	46	2448	47	2449
48	2450	49	2451	50	2452	51	2453
52	2454	53	2455	54	2456	55	2457
56	2458	57	2459	58	2460	59	2461
60	2462	61	2463	62	2464	63	2465
64	2466	65	2467	66	2468	67	2469
68	2470	69	2471	70	2472	71	2473
72	2474	73	2475	74	2476	75	2477
76	2478	77	2479	78	2480	-	-

4.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Table 1 Tests Carried Out Under FCC part 15.247

Bluetooth mode	Test mode	Low channel	Middle channel	High channel
EDR	Transmitting	2402MHz	2441MHz	2480MHz

Table 2 Tests Carried Out Under FCC part 15.207 and 15.209

Test Item	Test Mode
Radiated Emissions	Communication
Conducted Emissions	Communication

4.5 Test Facility

The test facility has a test site registered with the following organizations:

- **IC – Registration No.: 7760A-1**

Waltek Services(Shenzhen) Co., Ltd. has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration 7760A-1, October 15, 2015..

- **FCC Test Site 1#– Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

- **FCC Test Site 2#– Registration No.: 328995**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014.

5 Equipment Used during Test

5.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	Sep.15,2015	Sep.14,2016
2.	LISN	R&S	ENV216	101215	Sep.15,2015	Sep.14,2016
3.	Cable	Top	TYPE16(3.5M)	-	Sep.15,2015	Sep.14,2016
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	Sep.15,2015	Sep.14,2016
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	Sep.15,2015	Sep.14,2016
3.	Limiter	York	MTS-IMP-136	261115-001-0024	Sep.15,2015	Sep.14,2016
4.	Cable	LARGE	RF300	-	Sep.15,2015	Sep.14,2016
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMC Analyzer	Agilent	E7405A	MY45114943	Sep.15,2015	Sep.14,2016
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	Sep.15,2015	Sep.14,2016
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	Apr.19,2015	Apr.18,2016
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	Sep.15,2015	Sep.14,2016
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr.19,2015	Apr.18,2016
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	Apr.19,2015	Apr.18,2016
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Mar.17,2015	Mar.16,2016
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	Apr.10,2015	Apr.09,2016
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	Sep.15,2015	Sep.14,2016
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	Sep.15,2015	Sep.14,2016
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	Sep.15,2015	Sep.14,2016
4	Cable	HUBER+SUHNER	CBL2	525178	Sep.15,2015	Sep.14,2016

RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	Sep.15,2015	Sep.14,2016
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	Sep.15,2015	Sep.14,2016
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	Sep.15,2015	Sep.14,2016

5.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
Notebook	Apple	Macbook Air	/

5.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Conducted Spurious Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)

5.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.4:2003
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth)

6.1 E.U.T. Operation

Operating Environment :


Temperature:	25.5 °C
Humidity:	51 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in BT mode, the test data were shown in the report.

6.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.4:2003.




6.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


6.4 Conducted Emission Test Result

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1500	39.38	10.13	49.51	65.99	-16.48	QP	
2	0.1500	17.00	10.13	27.13	55.99	-28.86	AVG	
3	0.1980	44.33	10.15	54.48	63.69	-9.21	QP	
4	0.1980	26.28	10.15	36.43	53.69	-17.26	AVG	
5	0.2100	42.58	10.15	52.73	63.20	-10.47	QP	
6	0.2100	24.04	10.15	34.19	53.20	-19.01	AVG	
7	0.2620	36.82	10.16	46.98	61.36	-14.38	QP	
8	0.2620	17.50	10.16	27.66	51.36	-23.70	AVG	
9	3.7700	28.84	10.30	39.14	56.00	-16.86	QP	
10	3.7700	16.08	10.30	26.38	46.00	-19.62	AVG	
11	4.0380	26.88	10.30	37.18	56.00	-18.82	QP	
12	4.0380	14.89	10.30	25.19	46.00	-20.81	AVG	

Neutral line:



7 Radiated Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: DA 00-705

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

7.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in BT mode, the test data were shown in the report.


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2003.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
IF Bandwidth.....10kHz
Video Bandwidth.....10kHz
Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth.....100kHz
Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth.....1MHz
Video Bandwidth.....3MHz
Detector Ave.
Resolution Bandwidth.....1MHz
Video Bandwidth.....10Hz

7.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

7.5 Summary of Test Results

Model: 190671

Test Frequency: 26MHz to 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 18GHz

Remark: only the worst data(GFSK modulation mode) were reported.

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Low Channel									
268.25	36.10	QP	94	1.8	H	-13.35	22.75	46.00	-23.25
268.25	40.96	QP	26	1.3	V	-13.35	27.61	46.00	-18.39
4804.00	46.65	PK	277	1.3	V	-1.06	45.59	74.00	-28.41
4804.00	42.46	Ave	277	1.3	V	-1.06	41.40	54.00	-12.60
7206.00	40.91	PK	148	1.5	H	1.33	42.24	74.00	-31.76
7206.00	35.51	Ave	148	1.5	H	1.33	36.84	54.00	-17.16
2322.94	46.69	PK	70	1.6	V	-13.19	33.50	74.00	-40.50
2322.94	37.69	Ave	70	1.6	V	-13.19	24.50	54.00	-29.50
2351.03	44.86	PK	17	1.8	H	-13.14	31.72	74.00	-42.28
2351.03	36.65	Ave	17	1.8	H	-13.14	23.51	54.00	-30.49
2498.30	42.28	PK	279	1.7	V	-13.08	29.20	74.00	-44.80
2498.30	37.34	Ave	279	1.7	V	-13.08	24.26	54.00	-29.74

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Middle Channel									
268.25	37.51	QP	181	1.7	H	-13.35	24.16	46.00	-21.84
268.25	41.39	QP	191	1.4	V	-13.35	28.04	46.00	-17.96
4882.00	46.33	PK	318	1.4	V	-0.62	45.71	74.00	-28.29
4882.00	42.48	Ave	318	1.4	V	-0.62	41.86	54.00	-12.14
7323.00	42.12	PK	169	1.2	H	2.21	44.33	74.00	-29.67
7323.00	34.99	Ave	169	1.2	H	2.21	37.20	54.00	-16.80
2349.56	46.58	PK	272	1.8	V	-13.19	33.39	74.00	-40.61
2349.56	38.79	Ave	272	1.8	V	-13.19	25.60	54.00	-28.40
2367.99	43.49	PK	356	1.9	H	-13.14	30.35	74.00	-43.65
2367.99	36.49	Ave	356	1.9	H	-13.14	23.35	54.00	-30.65
2500.00	43.75	PK	19	1.6	V	-13.08	30.67	74.00	-43.33
2500.00	36.60	Ave	19	1.6	V	-13.08	23.52	54.00	-30.48

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK High Channel									
268.25	38.58	QP	36	1.8	H	-13.35	25.23	46.00	-20.77
268.25	40.25	QP	10	1.8	V	-13.35	26.90	46.00	-19.10
4960.00	45.97	PK	93	1.6	V	-0.24	45.73	74.00	-28.27
4960.00	41.72	Ave	93	1.6	V	-0.24	41.48	54.00	-12.52
7440.00	42.88	PK	98	1.7	H	2.84	45.72	74.00	-28.28
7440.00	34.88	Ave	98	1.7	H	2.84	37.72	54.00	-16.28
2319.87	45.12	PK	221	1.5	V	-13.19	31.93	74.00	-42.07
2319.87	39.63	Ave	221	1.5	V	-13.19	26.44	54.00	-27.56
2362.16	44.25	PK	74	1.8	H	-13.14	31.11	74.00	-42.89
2362.16	38.36	Ave	74	1.8	H	-13.14	25.22	54.00	-28.78
2486.94	42.69	PK	175	1.5	V	-13.08	29.61	74.00	-44.39
2486.94	36.75	Ave	175	1.5	V	-13.08	23.67	54.00	-30.33

Test Frequency : 18GHz to 25GHz

The measurements were more than 20 dB below the limit and not reported

Model: 190660**Test Frequency: 26MHz to 30MHz**

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 18GHz

Remark: only the worst data(GFSK modulation mode) were reported.

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Low Channel									
268.32	36.26	QP	277	1.6	H	-13.35	22.91	46.00	-23.09
268.32	42.56	QP	5	2.0	V	-13.35	29.21	46.00	-16.79
4804.00	45.66	PK	265	1.5	V	-1.06	44.60	74.00	-29.40
4804.00	42.56	Ave	265	1.5	V	-1.06	41.50	54.00	-12.50
7206.00	42.18	PK	33	2.0	H	1.33	43.51	74.00	-30.49
7206.00	35.39	Ave	33	2.0	H	1.33	36.72	54.00	-17.28
2348.97	45.15	PK	332	1.7	V	-13.19	31.96	74.00	-42.04
2348.97	37.74	Ave	332	1.7	V	-13.19	24.55	54.00	-29.45
2351.15	43.62	PK	96	1.8	H	-13.14	30.48	74.00	-43.52
2351.15	37.75	Ave	96	1.8	H	-13.14	24.61	54.00	-29.39
2484.24	43.76	PK	266	1.0	V	-13.08	30.68	74.00	-43.32
2484.24	38.04	Ave	266	1.0	V	-13.08	24.96	54.00	-29.04

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Middle Channel									
268.32	35.05	QP	352	1.4	H	-13.35	21.70	46.00	-24.30
268.32	42.18	QP	10	1.2	V	-13.35	28.83	46.00	-17.17
4882.00	45.05	PK	358	1.7	V	-0.62	44.43	74.00	-29.57
4882.00	43.88	Ave	358	1.7	V	-0.62	43.26	54.00	-10.74
7323.00	42.12	PK	246	1.3	H	2.21	44.33	74.00	-29.67
7323.00	34.83	Ave	246	1.3	H	2.21	37.04	54.00	-16.96
2322.20	45.16	PK	110	1.3	V	-13.19	31.97	74.00	-42.03
2322.20	39.32	Ave	110	1.3	V	-13.19	26.13	54.00	-27.87
2385.33	43.29	PK	254	1.9	H	-13.14	30.15	74.00	-43.85
2385.33	37.97	Ave	254	1.9	H	-13.14	24.83	54.00	-29.17
2485.44	44.31	PK	86	1.2	V	-13.08	31.23	74.00	-42.77
2485.44	37.60	Ave	86	1.2	V	-13.08	24.52	54.00	-29.48

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK High Channel									
268.32	34.06	QP	250	2.0	H	-13.35	20.71	46.00	-25.29
268.32	42.81	QP	271	1.1	V	-13.35	29.46	46.00	-16.54
4960.00	44.67	PK	8	1.8	V	-0.24	44.43	74.00	-29.57
4960.00	42.61	Ave	8	1.8	V	-0.24	42.37	54.00	-11.63
7440.00	42.27	PK	187	1.0	H	2.84	45.11	74.00	-28.89
7440.00	33.77	Ave	187	1.0	H	2.84	36.61	54.00	-17.39
2330.43	46.91	PK	253	1.1	V	-13.19	33.72	74.00	-40.28
2330.43	37.49	Ave	253	1.1	V	-13.19	24.30	54.00	-29.70
2383.02	42.41	PK	6	1.3	H	-13.14	29.27	74.00	-44.73
2383.02	38.11	Ave	6	1.3	H	-13.14	24.97	54.00	-29.03
2490.98	42.46	PK	128	1.8	V	-13.08	29.38	74.00	-44.62
2490.98	38.40	Ave	128	1.8	V	-13.08	25.32	54.00	-28.68

Test Frequency : 18GHz to 25GHz

The measurements were more than 20 dB below the limit and not reported

8 Band Edge Measurement

Test Requirement:	Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	DA 00-705
Test Limit:	Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting and Hopping

8.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

8.2 Test Result


Test plots



EDR mode



GFSK Transmitting Band edge-left side







GFSK Hopping Band edge-left side















9 20 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: DA 00-705
Test Mode: Test in fixing operating frequency at low, Middle, high channel.

9.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 30kHz, VBW = 100kHz

9.2 Test Result


Modulation	Test Channel	Bandwidth
GFSK	Low	0.916MHz
GFSK	Middle	0.916MHz
GFSK	High	0.916MHz
Pi/4 DQPSK	Low	1.222MHz
Pi/4 DQPSK	Middle	1.222MHz
Pi/4 DQPSK	High	1.222MHz
8DPSK	Low	1.209MHz
8DPSK	Middle	1.209MHz
8DPSK	High	1.209MHz



Test plots



GFSK Low Channel






GFSK Middle Channel











10 Maximum Peak Output Power

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	DA 00-705
Test Limit:	Regulation 15.247 (b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts. Refer to the result "Number of Hopping Frequency" of this document. The 0.125watts (20.97 dBm) limit applies.
Test mode:	Test in fixing frequency transmitting mode.

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3 MHz. VBW =3 MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

10.2 Test Result


EDR mode

Test Mode	Data Rate	Peak Power(dBm)			Limit (dBm)
		CH00	CH39	CH78	
GFSK	1Mbps	-4.69	-1.66	-3.16	20.97
4* π 4DQPSK	2Mbps	-6.59	-2.63	-5.15	20.97
8DPSK	3Mbps	-6.17	-2.37	-4.85	20.97


Test plots



EDR mode



GFSK Low Channel






GFSK Middle Channel











11 Hopping Channel Separation

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	DA 00-705
Test Limit:	Regulation 15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 1W.
Test Mode:	Test in hopping transmitting operating mode.

11.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 30KHz. VBW = 100KHz , Span = 3MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

11.2 Test Result


Modulation	Test Channel	Separation (MHz)	Result
GFSK	Low	1.000	PASS
GFSK	Middle	1.000	PASS
GFSK	High	1.000	PASS
Pi/4 DQPSK	Low	1.000	PASS
Pi/4 DQPSK	Middle	1.000	PASS
Pi/4 DQPSK	High	1.000	PASS
8DPSK	Low	1.000	PASS
8DPSK	Middle	1.000	PASS
8DPSK	High	1.000	PASS



Test plots



GFSK Low Channel






GFSK Middle Channel











12 Number of Hopping Frequency


Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	DA 00-705
Test Limit:	Regulation 15.247 (a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.
Test Mode:	Test in hopping transmitting operating mode.



12.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1MHz. VBW = 1MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.483GHz. Sweep=auto;

12.2 Test Result

Test Plots: 79 Channels in total





13 Dwell Time

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	DA 00-705
Test Limit:	Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Mode:	Test in hopping transmitting operating mode.

13.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. Centred on a hopping channel;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

13.2 Test Result


DH5 Packet permit maximum $1600 / 79 / 6$ hops per second in each channel (5 time slots RX, 1 time slot TX).



DH3 Packet permit maximum $1600 / 79 / 4$ hops per second in each channel (3 time slots RX, 1 time slot TX).


DH1 Packet permit maximum $1600 / 79 / 2$ hops per second in each channel (1 time slot RX, 1 time slot TX). So, the Dwell Time can be calculated as follows:



Data Packet	Dwell Time(s)
DH5	$1600/79/6*0.4*79*(MkrDelta)/1000$
DH3	$1600/79/4*0.4*79*(MkrDelta)/1000$
DH1	$1600/79/2*0.4*79*(MkrDelta)/1000$
Remark: Mkr Delta is once pulse time. Only the worst data(DH5) were show as follow.	



Modulation	Data Packet	Channel	pulse time(ms)	Dwell Time(s)	Limits(s)
GFSK	DH5	Low	2.888	0.308	0.400
		middle	2.888	0.308	0.400
		High	2.888	0.308	0.400
Pi/4DQPSK	DH5	Low	2.904	0.310	0.400
		middle	2.904	0.310	0.400
		High	2.904	0.310	0.400
8DPSK	DH5	Low	2.904	0.310	0.400
		middle	2.904	0.310	0.400
		High	2.904	0.310	0.400











14 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has a Integrated Antenna. fulfil the requirement of this section.

15 RF Exposure

Test Requirement: FCC Part 1.1307

Evaluation Method 447498 D01 General RF Exposure Guidance v05r02

15.1 Requirements

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \left[\sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR where}$$

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz
2. Power and distance are rounded to the nearest mW and mm before calculation
3. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

15.2 The procedures / limit

Conducted Peak power(dBm)	Conducted Peak power(mW)	Source-based time-averaged maximum conducted output power(mW)	Minimum test separation distance required for the exposure conditions (mm)	SAR Test Exclusion Thresholds(mW)
-1.66	-1.47	-1.47	5	10

Remark: Max. duty factor is 1

Calculation formula: Source-based time-averaged maximum conducted output power(mW) = Conducted peak power(mW) * 1

The minimum test separation distance from extremity is 5mm.


16 Photographs – Model 190671 Test Setup

16.1 Photograph – Conducted Emission Test Setup at Test Site 1#




16.2 Photograph – Radiation Spurious Emission Test Setup

Below 30MHz at Test Site 2#



30MHz-1GHz at Test Site 2#




Above 1GHz at Test Site 1#



17 Photographs - Constructional Details


17.1 Model 190671 External View


Model: 190671








Model: 190660














17.2 Model 190671 Internal View









===== End of Report =====