



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

| | |
|------------------------|--|
| Applicant's company | HOLUX Technology, Inc. |
| Applicant Address | No. 1-1, Innovation Road 1, Science-Based Industrial Park, Hsinchu 30076, Taiwan |
| FCC ID | RJIM-241PLUS |
| Manufacturer's company | HOLUX Technology, Inc. |
| Manufacturer Address | No. 1-1, Innovation Road 1, Science-Based Industrial Park, Hsinchu 30076, Taiwan |

| | |
|------------------|---------------------------------------|
| Product Name | Wireless GPS Logger |
| Brand Name | HOLUX |
| Model Name | M-241 Plus |
| Test Rule | 47 CFR FCC Part 15 Subpart C § 15.247 |
| Test Freq. Range | 2402 ~ 2480MHz |
| Received Date | Feb. 07, 2017 |
| Final Test Date | Mar. 09, 2017 |
| Submission Type | Original Equipment |

Statement

Test result included is only for the Bluetooth LE of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C** and **KDB558074 D01 v03r05**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

| | |
|--|----------------|
| 1. VERIFICATION OF COMPLIANCE | 1 |
| 2. SUMMARY OF THE TEST RESULT | 2 |
| 3. GENERAL INFORMATION | 3 |
| 3.1. Product Details..... | 3 |
| 3.2. Accessories..... | 3 |
| 3.3. Table for Filed Antenna..... | 3 |
| 3.4. Table for Carrier Frequencies | 4 |
| 3.5. Table for Test Modes..... | 4 |
| 3.6. Table for Testing Locations..... | 5 |
| 3.7. Table for Supporting Units | 5 |
| 3.8. Table for Parameters of Test Software Setting | 5 |
| 3.9. EUT Operation during Test | 6 |
| 3.10. Duty Cycle..... | 6 |
| 3.11. Test Configurations | 7 |
| 4. TEST RESULT | 10 |
| 4.1. AC Power Line Conducted Emissions Measurement..... | 10 |
| 4.2. Maximum Conducted Output Power Measurement..... | 14 |
| 4.3. Power Spectral Density Measurement | 16 |
| 4.4. 6dB Spectrum Bandwidth Measurement | 19 |
| 4.5. Radiated Emissions Measurement | 23 |
| 4.6. Emissions Measurement | 33 |
| 4.7. Antenna Requirements | 41 |
| 5. LIST OF MEASURING EQUIPMENTS | 42 |
| 6. MEASUREMENT UNCERTAINTY | 44 |
| APPENDIX A. TEST PHOTOS | A1 ~ A5 |
| PHOTOGRAPHS OF EUT V01 | |

1. VERIFICATION OF COMPLIANCE

Product Name : Wireless GPS Logger
Brand Name : HOLUX
Model No. : M-241 Plus
Applicant : HOLUX Technology, Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Feb. 07, 2017 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.


Cliff Chang
SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

| Applied Standard: 47 CFR FCC Part 15 Subpart C | | | |
|--|--------------|-----------------------------------|----------|
| Part | Rule Section | Description of Test | Result |
| 4.1 | 15.207 | AC Power Line Conducted Emissions | Complies |
| 4.2 | 15.247(b)(3) | Maximum Conducted Output Power | Complies |
| 4.3 | 15.247(e) | Power Spectral Density | Complies |
| 4.4 | 15.247(a)(2) | 6dB Spectrum Bandwidth | Complies |
| 4.5 | 15.247(d) | Radiated Emissions | Complies |
| 4.6 | 15.247(d) | Band Edge Emissions | Complies |
| 4.7 | 15.203 | Antenna Requirements | Complies |

3. GENERAL INFORMATION

3.1. Product Details

| Items | Description |
|--------------------------------|---|
| Power Type | From battery or host system |
| Modulation | DSSS |
| Data Rate (Mbps) | GFSK: 1 |
| Frequency Range | 2402 ~ 2480MHz |
| Channel Number | 40 (37 hopping + 3 advertising channel) |
| Channel Bandwidth (99%) | 1.01 MHz |
| Maximum Conducted Output Power | 2.65 dBm |
| Carrier Frequencies | Please refer to section 3.4 |
| Antenna | Please refer to section 3.3 |

3.2. Accessories

| Power | Brand | Model | Rating |
|----------------------------|--------------|---------|--------|
| Battery | GP Batteries | 15A LR6 | 1.5V |
| Others | | | |
| USB cable*1: Shielded 0.5m | | | |

3.3. Table for Filed Antenna

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) |
|------|---------|-----------------|--------------|-----------|------------|
| 1 | ONSHINE | LA5220P2450-A04 | Chip | N/A | 2 |

3.4. Table for Carrier Frequencies

| Frequency Band | Channel No. | Frequency | Channel No. | Frequency |
|----------------|-------------|-----------|-------------|-----------|
| 2400~2483.5MHz | 0 | 2402 MHz | 20 | 2442 MHz |
| | 1 | 2404 MHz | : | : |
| | 2 | 2406 MHz | 37 | 2476 MHz |
| | : | : | 38 | 2478 MHz |
| | 18 | 2438 MHz | 39 | 2480 MHz |
| | 19 | 2440 MHz | - | - |

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. The following table is a list of the test modes shown in this test report.

| Test Items | Mode | Data Rate | Channel | Chain |
|--|-------------|-----------|---------|-------|
| AC Power Line Conducted Emissions | Normal Link | - | - | - |
| Maximum Conducted Output Power Power Spectral Density | GFSK | 1 Mbps | 0/19/39 | 1 |
| 6dB Spectrum Bandwidth | GFSK | 1 Mbps | 0/19/39 | 1 |
| Radiated Emissions 9kHz~1GHz | Normal Link | - | - | - |
| Radiated Emissions 1GHz~10 th Harmonic | GFSK | 1 Mbps | 0/19/39 | 1 |
| Band Edge Emissions | GFSK | 1 Mbps | 0/19/39 | 1 |

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. Normal Link + USB cable

For Radiated Emission test below 1GHz:

Mode 1. Normal Link + USB cable - Place EUT in Z axis

Mode 2. Normal Link + USB cable - Place EUT in Y axis

Mode 3. Normal Link + USB cable - Place EUT in X axis

Mode 1 has been evaluated to be the worst case among Mode 1~3, thus measurement for Mode 4 will follow this same test mode.

Mode 4. Normal Link + Battery - Place EUT in Z axis

Mode 1 is the worst case, so it was selected to record in this test report3

For Radiated Emission test Above1GHz:

The EUT was performed at X axis, Y axis and Z axis position for Radiated emission test, and the worst case was found at X axis. So the measurement will follow this same test configuration.

Mode 1. CTX + Battery - Place EUT in X axis

3.6. Table for Testing Locations

| Test Site Location | | | | |
|--------------------|--|----------|---------------------|-------------|
| Address: | No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C. | | | |
| TEL: | 886-3-656-9065 | | | |
| FAX: | 886-3-656-9085 | | | |
| Test Site No. | Site Category | Location | FCC Designation No. | IC File No. |
| 03CH01-CB | SAC | Hsin Chu | TW0006 | IC 4086D |
| CO01-CB | Conduction | Hsin Chu | TW0006 | IC 4086D |
| TH01-CB | OVEN Room | Hsin Chu | - | - |

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units

For Test Site No: 03CH01-CB

| Support Unit | Brand | Model | FCC ID |
|--------------|------------|----------|--------|
| Mouse | Logitech | M-U0026 | DoC |
| Earphone | SHYARO CHI | MIC-04 | DoC |
| Smart phone | SAMSUNG | SM-J200Y | DoC |
| Notebook | DELL | E4300 | DoC |

For Test Site No: CO01-CB

| Support Unit | Brand | Model | FCC ID |
|--------------|------------|----------|--------|
| Smart phone | SAMSUNG | SM-J200Y | DoC |
| Notebook | DELL | E6430 | DoC |
| Earphone | SHYARO CHI | MIC-04 | DoC |
| Mouse | HP | FM100 | DoC |

For Test Site No: TH01-CB

| Support Unit | Brand | Model | FCC ID |
|--------------|-------|-------|--------|
| Notebook | DELL | E4300 | DoC |

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters:

| Test Software Version | nRFGo Studio.exe | | |
|-----------------------|------------------|----------|----------|
| Frequency | 2402 MHz | 2440 MHz | 2480 MHz |
| Power Parameters | Default | Default | Default |

3.9. EUT Operation during Test

For CTX Mode:

The EUT was programmed to be in continuously transmitting mode.

For Normal Link:


During the test, the EUT operation to normal function.

3.10. Duty Cycle

| Mode | On Time (ms) | On+Off Time (ms) | Duty Cycle (%) | Duty Factor (dB) | 1/T Minimum VBW (kHz) |
|------|--------------|------------------|----------------|------------------|-----------------------|
| GFSK | 0.140 | 0.624 | 22.44% | 6.49 | 7.14 |

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test Configuration



| Item | Connection | Shielded | Length |
|------|-------------|----------|--------|
| 1 | Power cable | No | 2.6m |
| 2 | Audio cable | No | 1.8m |
| 3 | USB cable | Yes | 1.8m |
| 4 | USB cable | Yes | 0.5m |


3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



| Item | Connection | Shielded | Length |
|------|-------------|----------|--------|
| 1 | USB cable | Yes | 0.5m |
| 2 | USB cable | No | 1.8m |
| 3 | Audio cable | No | 1.1m |
| 4 | Power cable | No | 2.6m |

Test Configuration: above 1GHz



| Item | Connection | Shielded | Length |
|------|-------------|----------|--------|
| 1 | USB cable | Yes | 0.5m |
| 2 | Power cable | No | 2.6m |

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

| Frequency (MHz) | QP Limit (dBuV) | AV Limit (dBuV) |
|-----------------|-----------------|-----------------|
| 0.15~0.5 | 66~56 | 56~46 |
| 0.5~5 | 56 | 46 |
| 5~30 | 60 | 50 |

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.


| Receiver Parameters | Setting |
|---------------------|----------|
| Attenuation | 10 dB |
| Start Frequency | 0.15 MHz |
| Stop Frequency | 30 MHz |
| IF Bandwidth | 9 kHz |

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

| | | | |
|---------------|-------------|----------|------|
| Temperature | 23°C | Humidity | 60% |
| Test Engineer | Deven Huang | Phase | Line |
| Configuration | Normal Link | | |



| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark | Pol/Phase |
|----|---------|-------|------------|------------|------------|-------------|------------|---------|-----------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | | |
| 1 | 0.1500 | 38.16 | -17.84 | 56.00 | 28.17 | 9.95 | 0.04 | Average | LINE |
| 2 | 0.1500 | 52.75 | -13.25 | 66.00 | 42.76 | 9.95 | 0.04 | QP | LINE |
| 3 | 0.1712 | 38.59 | -16.31 | 54.90 | 28.61 | 9.94 | 0.04 | Average | LINE |
| 4 | 0.1712 | 52.03 | -12.87 | 64.90 | 42.05 | 9.94 | 0.04 | QP | LINE |
| 5 | 0.2007 | 38.03 | -15.55 | 53.58 | 28.05 | 9.93 | 0.05 | Average | LINE |
| 6 | 0.2007 | 49.06 | -14.52 | 63.58 | 39.08 | 9.93 | 0.05 | QP | LINE |
| 7 | 0.2378 | 34.30 | -17.87 | 52.17 | 24.33 | 9.92 | 0.05 | Average | LINE |
| 8 | 0.2378 | 43.72 | -18.45 | 62.17 | 33.75 | 9.92 | 0.05 | QP | LINE |
| 9 | 0.4564 | 32.30 | -14.46 | 46.76 | 22.36 | 9.90 | 0.04 | Average | LINE |
| 10 | 0.4564 | 39.02 | -17.74 | 56.76 | 29.08 | 9.90 | 0.04 | QP | LINE |
| 11 | 29.2157 | 22.06 | -27.94 | 50.00 | 11.39 | 10.37 | 0.30 | Average | LINE |
| 12 | 29.2157 | 29.20 | -30.80 | 60.00 | 18.53 | 10.37 | 0.30 | QP | LINE |

| | | | |
|---------------|-------------|----------|---------|
| Temperature | 23°C | Humidity | 60% |
| Test Engineer | Deven Huang | Phase | Neutral |
| Configuration | Normal Link | | |



| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark | Pol/Phase |
|----|---------|-------|------------|------------|------------|-------------|------------|---------|-----------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | | |
| 1 | 0.1500 | 39.37 | -16.63 | 56.00 | 29.39 | 9.94 | 0.04 | Average | NEUTRAL |
| 2 | 0.1500 | 54.42 | -11.58 | 66.00 | 44.44 | 9.94 | 0.04 | QP | NEUTRAL |
| 3 | 0.1731 | 35.80 | -19.01 | 54.81 | 25.80 | 9.96 | 0.04 | Average | NEUTRAL |
| 4 | 0.1731 | 51.11 | -13.70 | 64.81 | 41.11 | 9.96 | 0.04 | QP | NEUTRAL |
| 5 | 0.2106 | 38.58 | -14.60 | 53.18 | 28.55 | 9.98 | 0.05 | Average | NEUTRAL |
| 6 | 0.2106 | 48.42 | -14.76 | 63.18 | 38.39 | 9.98 | 0.05 | QP | NEUTRAL |
| 7 | 0.2256 | 34.62 | -17.99 | 52.61 | 24.59 | 9.98 | 0.05 | Average | NEUTRAL |
| 8 | 0.2256 | 46.67 | -15.94 | 62.61 | 36.64 | 9.98 | 0.05 | QP | NEUTRAL |
| 9 | 0.4686 | 30.55 | -15.99 | 46.54 | 20.54 | 9.97 | 0.04 | Average | NEUTRAL |
| 10 | 0.4686 | 37.85 | -18.69 | 56.54 | 27.84 | 9.97 | 0.04 | QP | NEUTRAL |
| 11 | 28.1520 | 23.01 | -26.99 | 50.00 | 12.39 | 10.33 | 0.29 | Average | NEUTRAL |
| 12 | 28.1520 | 30.07 | -29.93 | 60.00 | 19.45 | 10.33 | 0.29 | QP | NEUTRAL |

Note: Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

The limit for output power is 30dBm.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

| Power Meter Parameter | Setting |
|-----------------------|--|
| Bandwidth | 50MHz bandwidth is greater than the EUT emission bandwidth |
| Detector | Average |

4.2.3. Test Procedures

1. Test procedures refer KDB558074 D01 v03r05 section 9.2.3.2.
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

| | | | |
|----------------------|---------------|-----------------------|------|
| Temperature | 24°C | Humidity | 41% |
| Test Engineer | Brian Sun | Configurations | GFSK |
| Test Date | Feb. 27, 2017 | | |

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|------------------|----------|
| 0 | 2402 MHz | 1.69 | 30.00 | Complies |
| 19 | 2440 MHz | 2.25 | 30.00 | Complies |
| 39 | 2480 MHz | 2.65 | 30.00 | Complies |

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting |
|--------------------|--|
| Attenuation | Auto |
| Span Frequency | 5-30 % greater than the DTS channel bandwidth. |
| RBW | $3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$ |
| VBW | $\geq 3 \times \text{RBW}$ |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | Auto couple |

4.3.3. Test Procedures

1. Test was performed in accordance with KDB558074 D01 v03r05 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 10.2 Method PKPSD (peak PSD).
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

| | | | |
|---------------|-----------|----------------|------|
| Temperature | 24°C | Humidity | 41% |
| Test Engineer | Brian Sun | Configurations | GFSK |

| Channel | Frequency | Power Density (dBm/3kHz) | Power Density Limit (dBm/3kHz) | Result |
|---------|-----------|--------------------------|--------------------------------|----------|
| 0 | 2402 MHz | -12.45 | 8.00 | Complies |
| 19 | 2440 MHz | -12.24 | 8.00 | Complies |
| 39 | 2480 MHz | -10.62 | 8.00 | Complies |

Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.

Power Density Plot on Configuration Bluetooth / 2480 MHz



4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| 6dB Spectrum Bandwidth | |
|------------------------|--------------------------------|
| Spectrum Parameters | Setting |
| Attenuation | Auto |
| Span Frequency | > 6dB Bandwidth |
| RBW | 100kHz |
| VBW | $\geq 3 \times \text{RBW}$ |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | Auto |
| 99% Occupied Bandwidth | |
| Spectrum Parameters | Setting |
| Span | 1.5 times to 5.0 times the OBW |
| RBW | 1 % to 5 % of the OBW |
| VBW | $\geq 3 \times \text{RBW}$ |
| Detector | Peak |
| Trace | Max Hold |

4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB558074 D01 v03r05 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 8.0 DTS bandwidth = > 8.1 Option 1.
3. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth


| | | | |
|----------------------|-----------|-----------------------|------|
| Temperature | 24°C | Humidity | 41% |
| Test Engineer | Brian Sun | Configurations | GFSK |

| Channel | Frequency | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Min. Limit (kHz) | Test Result |
|---------|-----------|---------------------|------------------------------|------------------|-------------|
| 0 | 2402 MHz | 0.69 | 1.01 | 500 | Complies |
| 19 | 2440 MHz | 0.69 | 1.01 | 500 | Complies |
| 39 | 2480 MHz | 0.67 | 1.01 | 500 | Complies |

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

6 dB Bandwidth Plot on Configuration Bluetooth / 2480 MHz



Date: 27.FEB.2017 14:15:21

99% Occupied Bandwidth Plot on Configuration Bluetooth / 2480 MHz



Date: 27.FEB.2017 14:19:33

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(kHz) | 300 |
| 0.490~1.705 | 24000/F(kHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10th carrier harmonic |
| RBW / VBW (Emission in restricted band) | 1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average |
| RBW / VBW (Emission in non-restricted band) | 100kHz / 300kHz for peak |


| Receiver Parameter | Setting |
|------------------------|-----------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RBW 200Hz for QP |
| Start ~ Stop Frequency | 150kHz~30MHz / RBW 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RBW 120kHz for QP |

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



4.5.7. Results of Radiated Emissions (9kHz~30MHz)

| | | | |
|----------------------|-----------------------------------|-----------------------|----------------------|
| Temperature | 22°C | Humidity | 59% |
| Test Engineer | Zero Chen, Peter Wu, Steven Liang | Configurations | Normal Link / Mode 1 |
| Test Date | Feb. 24, 2017 | | |

| Freq. (MHz) | Level (dBuV) | Over Limit (dB) | Limit Line (dBuV) | Remark |
|--------------------|---------------------|------------------------|--------------------------|---------------|
| - | - | - | - | See Note |

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


| | | | |
|---------------|--------------------------------------|----------------|----------------------|
| Temperature | 22°C | Humidity | 59% |
| Test Engineer | Zero Chen, Peter Wu, Steven Liang | Configurations | Normal Link / Mode 1 |

Horizontal



| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Remark | Pol/Phase |
|---|--------|--------|--------|-------|-------|--------------|--------|-------|-------|----------|------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 121.18 | 40.45 | 43.50 | -3.05 | 52.47 | 1.87 | 18.49 | 32.38 | 300 | 179 QP | HORIZONTAL |
| 2 | 124.09 | 40.00 | 43.50 | -3.50 | 52.02 | 1.90 | 18.46 | 32.38 | 150 | 163 QP | HORIZONTAL |
| 3 | 127.00 | 40.41 | 43.50 | -3.09 | 52.44 | 1.92 | 18.43 | 32.38 | 300 | 0 QP | HORIZONTAL |
| 4 | 224.97 | 41.02 | 46.00 | -4.98 | 53.96 | 2.60 | 16.78 | 32.32 | 150 | 178 Peak | HORIZONTAL |
| 5 | 266.68 | 41.26 | 46.00 | -4.74 | 51.25 | 2.83 | 19.47 | 32.29 | 100 | 170 Peak | HORIZONTAL |
| 6 | 306.45 | 42.58 | 46.00 | -3.42 | 51.91 | 3.05 | 19.90 | 32.28 | 150 | 212 QP | HORIZONTAL |

Vertical



| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Remark | Pol/Phase |
|---|--------|--------|--------|-------|-------|--------------|--------|-------|-------|----------|-----------|
| | MHz | dBUV/m | dBUV/m | dB | dBUV | dB | dB/m | dB | cm | deg | |
| 1 | 30.00 | 36.60 | 40.00 | -3.40 | 42.33 | 0.87 | 25.80 | 32.40 | 100 | 183 QP | VERTICAL |
| 2 | 124.09 | 40.03 | 43.50 | -3.47 | 52.05 | 1.90 | 18.46 | 32.38 | 100 | 196 QP | VERTICAL |
| 3 | 126.03 | 39.89 | 43.50 | -3.61 | 51.92 | 1.91 | 18.44 | 32.38 | 150 | 225 QP | VERTICAL |
| 4 | 268.62 | 41.12 | 46.00 | -4.88 | 51.13 | 2.84 | 19.44 | 32.29 | 200 | 168 Peak | VERTICAL |
| 5 | 311.30 | 42.24 | 46.00 | -3.76 | 51.41 | 3.07 | 20.04 | 32.28 | 150 | 260 Peak | VERTICAL |
| 6 | 449.04 | 40.10 | 46.00 | -5.90 | 45.68 | 3.73 | 23.00 | 32.31 | 150 | 187 Peak | VERTICAL |

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

| | | | |
|----------------------|--------------------------------------|-----------------------|-----------|
| Temperature | 22°C | Humidity | 59% |
| Test Engineer | Zero Chen, Peter Wu, Steven Liang | Configurations | Channel 0 |
| Test Date | Feb. 23, 2017 ~ Feb. 24, 2017 | | |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase |
|---|---------|--------|---------------|---------------|---------------|----------------------|-------------------|------------------|-------|-------|---------|------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4804.71 | 47.41 | 74.00 | -26.59 | 42.39 | 9.11 | 32.56 | 36.65 | 230 | 255 | Peak | HORIZONTAL |
| 2 | 4805.38 | 34.33 | 54.00 | -19.67 | 29.31 | 9.11 | 32.56 | 36.65 | 230 | 255 | Average | HORIZONTAL |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase |
|---|---------|--------|---------------|---------------|---------------|----------------------|-------------------|------------------|-------|-------|---------|-----------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4804.32 | 48.38 | 74.00 | -25.62 | 43.36 | 9.11 | 32.56 | 36.65 | 138 | 305 | Peak | VERTICAL |
| 2 | 4805.69 | 35.03 | 54.00 | -18.97 | 30.01 | 9.11 | 32.56 | 36.65 | 138 | 305 | Average | VERTICAL |

| | | | |
|----------------------|--------------------------------------|-----------------------|------------|
| Temperature | 22°C | Humidity | 59% |
| Test Engineer | Zero Chen, Peter Wu, Steven Liang | Configurations | Channel 19 |
| Test Date | Feb. 23, 2017 ~ Feb. 24, 2017 | | |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase |
|---|---------|--------|---------------|---------------|---------------|----------------------|-------------------|------------------|-------|-------|---------|------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4878.63 | 47.84 | 74.00 | -26.16 | 42.65 | 9.16 | 32.68 | 36.65 | 191 | 123 | Peak | HORIZONTAL |
| 2 | 4880.49 | 34.21 | 54.00 | -19.79 | 29.02 | 9.16 | 32.68 | 36.65 | 191 | 123 | Average | HORIZONTAL |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase |
|---|---------|--------|---------------|---------------|---------------|----------------------|-------------------|------------------|-------|-------|---------|-----------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4879.79 | 47.36 | 74.00 | -26.64 | 42.17 | 9.16 | 32.68 | 36.65 | 206 | 193 | Peak | VERTICAL |
| 2 | 4880.57 | 33.74 | 54.00 | -20.26 | 28.55 | 9.16 | 32.68 | 36.65 | 206 | 193 | Average | VERTICAL |

| | | | |
|----------------------|--------------------------------------|-----------------------|------------|
| Temperature | 22°C | Humidity | 59% |
| Test Engineer | Zero Chen, Peter Wu, Steven Liang | Configurations | Channel 39 |
| Test Date | Feb. 23, 2017 ~ Feb. 24, 2017 | | |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase |
|---|---------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|---------|------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4960.32 | 47.41 | 74.00 | -26.59 | 42.01 | 9.21 | 32.83 | 36.64 | 178 | 111 | Peak | HORIZONTAL |
| 2 | 4962.46 | 34.78 | 54.00 | -19.22 | 29.38 | 9.21 | 32.83 | 36.64 | 178 | 111 | Average | HORIZONTAL |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase |
|---|---------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|---------|-----------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4959.23 | 33.88 | 54.00 | -20.12 | 28.48 | 9.21 | 32.83 | 36.64 | 203 | 67 | Average | VERTICAL |
| 2 | 4961.76 | 47.97 | 74.00 | -26.03 | 42.57 | 9.21 | 32.83 | 36.64 | 203 | 67 | Peak | VERTICAL |

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490 | 2400/F(kHz) | 300 |
| 0.490~1.705 | 24000/F(kHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Span Frequency | 100 MHz |
| RBW / VBW (Emission in restricted band) | 1MHz / 3MHz for Peak, 1MHz / 1/T for Average |
| RBW / VBW (30dBc in any 100 kHz bandwidth emission) | 100 kHz / 300 kHz for Peak |

4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3.

For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB558074 D01 v03r05 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 11.0 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.


4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

| | | | |
|---------------|-----------------------------------|----------------|-------------------|
| Temperature | 22°C | Humidity | 59% |
| Test Engineer | Zero Chen, Peter Wu, Steven Liang | Configurations | Channel 0, 19, 39 |


Channel 0



| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase |
|-----|---------|--------|------------|------------|------------|------------|----------------|---------------|-------|-------|---------|-----------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 2387.80 | 47.33 | 54.00 | -6.67 | 16.29 | 3.03 | 28.01 | 0.00 | 165 | 102 | Average | VERTICAL |
| 2 | 2388.08 | 57.55 | 74.00 | -16.45 | 26.51 | 3.03 | 28.01 | 0.00 | 165 | 102 | Peak | VERTICAL |
| 3 @ | 2402.00 | 86.54 | | | 55.52 | 3.04 | 27.98 | 0.00 | 165 | 102 | Average | VERTICAL |
| 4 @ | 2402.20 | 88.42 | | | 57.40 | 3.04 | 27.98 | 0.00 | 165 | 102 | Peak | VERTICAL |

Item 3, 4 are the fundamental frequency at 2402 MHz.


Channel 19



| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase |
|-----|---------|--------|------------|------------|------------|-------------------|---------------|-------|-------|-------------|------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 2350.40 | 57.23 | 74.00 | -16.77 | 26.15 | 3.01 | 28.07 | 0.00 | 114 | 186 Peak | HORIZONTAL |
| 2 | 2389.60 | 47.16 | 54.00 | -6.84 | 16.12 | 3.03 | 28.01 | 0.00 | 114 | 186 Average | HORIZONTAL |
| 3 @ | 2440.00 | 91.18 | | | 60.21 | 3.07 | 27.90 | 0.00 | 114 | 186 Average | HORIZONTAL |
| 4 @ | 2440.00 | 93.08 | | | 62.11 | 3.07 | 27.90 | 0.00 | 114 | 186 Peak | HORIZONTAL |
| 5 | 2497.94 | 47.00 | 54.00 | -7.00 | 16.10 | 3.10 | 27.80 | 0.00 | 114 | 186 Average | HORIZONTAL |
| 6 | 2498.15 | 58.03 | 74.00 | -15.97 | 27.13 | 3.10 | 27.80 | 0.00 | 114 | 186 Peak | HORIZONTAL |

Item 3, 4 are the fundamental frequency at 2440 MHz.

Channel 39



| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Preamp Factor | A/Pos | T/Pos | Remark | Pol/Phase | |
|-----|---------|--------|------------|------------|------------|-------------------|---------------|-------|-------|--------|-----------|------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 @ | 2480.00 | 92.00 | | | 61.07 | 3.09 | 27.84 | 0.00 | 146 | 186 | Average | HORIZONTAL |
| 2 @ | 2480.00 | 93.84 | | | 62.91 | 3.09 | 27.84 | 0.00 | 146 | 186 | Peak | HORIZONTAL |
| 3 | 2496.27 | 57.10 | 74.00 | -16.90 | 26.19 | 3.10 | 27.81 | 0.00 | 146 | 186 | Peak | HORIZONTAL |
| 4 | 2499.39 | 47.11 | 54.00 | -6.89 | 16.21 | 3.10 | 27.80 | 0.00 | 146 | 186 | Average | HORIZONTAL |


Item 1, 2 are the fundamental frequency at 2480 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band
Plot on Configuration / Reference Level




Date: 24.FEB.2017 02:31:45

Plot on Configuration For Bluetooth 4.0 / Channel 0 / 30MHz~2400MHz (down 30dBc)



Date: 24.FEB.2017 02:39:23

Plot on Configuration For Bluetooth 4.0 / Channel 39 / 2483.5MHz~26500MHz (down 30dBc)



4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Remark |
|-----------------------------------|--------------|-------------------|------------------|------------------|------------------|-----------------------|
| EMI Receiver | Agilent | N9038A | My52260123 | 9kHz ~ 8.45GHz | Jan. 23, 2017 | Conduction (CO01-CB) |
| LISN | F.C.C. | FCC-LISN-50-16-2 | 04083 | 150kHz ~ 100MHz | Dec. 14, 2016 | Conduction (CO01-CB) |
| LISN | Schwarzbeck | NSLK 8127 | 8127647 | 9kHz ~ 30MHz | Dec. 21, 2016 | Conduction (CO01-CB) |
| COND Cable | Woken | Cable | 01 | 150kHz ~ 30MHz | May 24, 2016 | Conduction (CO01-CB) |
| Software | Audix | E3 | 6.120210n | - | N.C.R. | Conduction (CO01-CB) |
| BILOG ANTENNA with 6dB Attenuator | TESEQ & EMCI | CBL6112D & N-6-06 | 37880 & AT-N0609 | 20MHz ~ 2GHz | Aug. 30, 2016 | Radiation (03CH01-CB) |
| Loop Antenna | Teseq | HLA 6120 | 24155 | 9kHz - 30 MHz | Mar. 16, 2016* | Radiation (03CH01-CB) |
| Horn Antenna | EMCO | 3115 | 00075790 | 750MHz ~ 18GHz | Nov. 10, 2016 | Radiation (03CH01-CB) |
| Horn Antenna | Schwarzbeck | BBHA 9170 | BBHA9170252 | 15GHz ~ 40GHz | Jul. 25, 2016 | Radiation (03CH01-CB) |
| Pre-Amplifier | Agilent | 8447D | 2944A10991 | 0.1MHz ~ 1.3GHz | Mar. 15, 2016 | Radiation (03CH01-CB) |
| Pre-Amplifier | Agilent | 8449B | 3008A02310 | 1GHz ~ 26.5GHz | Jan. 16, 2017 | Radiation (03CH01-CB) |
| Pre-Amplifier | MITEQ | TTA1840-35-HG | 1864479 | 18GHz ~ 40GHz | Jun. 28, 2016 | Radiation (03CH01-CB) |
| Spectrum Analyzer | R&S | FSP40 | 100056 | 9kHz ~ 40GHz | Nov. 21, 2016 | Radiation (03CH01-CB) |
| EMI Test | R&S | ESCS | 100355 | 9kHz ~ 2.75GHz | May 16, 2016 | Radiation (03CH01-CB) |
| RF Cable-low | Woken | Low Cable-16+17 | N/A | 30 MHz ~ 1 GHz | Oct. 24, 2016 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-16 | N/A | 1 GHz ~ 18 GHz | Oct. 24, 2016 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-16+17 | N/A | 1 GHz ~ 18 GHz | Oct. 24, 2016 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-40G#1 | N/A | 18GHz ~ 40 GHz | Oct. 24, 2016 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-40G#2 | N/A | 18GHz ~ 40 GHz | Oct. 24, 2016 | Radiation (03CH01-CB) |
| Test Software | Audix | E3 | 6.2009-10-7 | N/A | N/A | Radiation (03CH01-CB) |
| Spectrum analyzer | R&S | FSV40 | 100979 | 9kHz~40GHz | Dec. 26, 2016 | Conducted (TH01-CB) |
| RF Cable-high | Woken | RG402 | High Cable-6 | 1 GHz – 26.5 GHz | Oct. 24, 2016 | Conducted (TH01-CB) |
| RF Cable-high | Woken | RG402 | High Cable-7 | 1 GHz –26.5 GHz | Oct. 24, 2016 | Conducted (TH01-CB) |
| RF Cable-high | Woken | RG402 | High Cable-8 | 1 GHz –26.5 GHz | Oct. 24, 2016 | Conducted (TH01-CB) |
| RF Cable-high | Woken | RG402 | High Cable-9 | 1 GHz –26.5 GHz | Oct. 24, 2016 | Conducted (TH01-CB) |
| RF Cable-high | Woken | RG402 | High Cable-10 | 1 GHz –26.5 GHz | Oct. 24, 2016 | Conducted (TH01-CB) |



| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Remark |
|--------------|--------------|-----------|------------|-----------------|------------------|---------------------|
| Power Sensor | Agilent | U2021XA | MY53410001 | 50MHz~18GHz | Nov. 22, 2016 | Conducted (TH01-CB) |

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

| Test Items | Uncertainty | Remark |
|--------------------------------------|-----------------------|--------------------------|
| Conducted Emission (150kHz ~ 30MHz) | 3.2 dB | Confidence levels of 95% |
| Radiated Emission (30MHz ~ 1,000MHz) | 3.6 dB | Confidence levels of 95% |
| Radiated Emission (1GHz ~ 18GHz) | 3.7 dB | Confidence levels of 95% |
| Radiated Emission (18GHz ~ 40GHz) | 3.5 dB | Confidence levels of 95% |
| Conducted Emission | 1.7 dB | Confidence levels of 95% |
| Output Power Measurement | 1.33 dB | Confidence levels of 95% |
| Power Density Measurement | 1.27 dB | Confidence levels of 95% |
| Bandwidth Measurement | 9.74×10^{-8} | Confidence levels of 95% |