

APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
Chuango Security Technology Corporation

SS-20 Indoor Siren
Model No.: SS-20

FCC ID: RJY-SS20

Prepared for : Chuango Security Technology Corporation
Address : 6-17, Overseas Students Pioneer Park, No. 108, Jia
Economic & Technological Development Zone,
Fuzhou 350015, China

Prepared by : ACCURATE TECHNOLOGY CO., LTD
Address : F1, Bldg. A, Chan Yuan New Material Port, Keyuan
Rd. Science & Industry Park, Nan Shan, Shenzhen,
Guangdong P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20170766
Date of Test : May 18, 2017
Date of Report : May 18, 2017

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Special Accessory and Auxiliary Equipment	4
1.3. Description of Test Facility	5
1.4. Measurement Uncertainty	5
2. MEASURING DEVICE AND TEST EQUIPMENT	6
3. OPERATION OF EUT DURING TESTING	7
3.1. Operating Mode	7
3.2. Configuration and peripherals	7
4. TEST PROCEDURES AND RESULTS	8
5. 20DB BANDWIDTH MEASUREMENT	9
5.1. Block Diagram of Test Setup.....	9
5.2. The Requirement For Section 15.215(c).....	9
5.3. Operating Condition of EUT	9
5.4. Test Procedure	9
5.5. Test Result	10
6. BAND EDGE COMPLIANCE TEST	11
6.1. Block Diagram of Test Setup.....	11
6.2. The Requirement For Section 15.249.....	11
6.3. EUT Configuration on Measurement	11
6.4. Operating Condition of EUT	11
6.5. Test Procedure	11
6.6. Test Result	12
7. RADIATED SPURIOUS EMISSION TEST	15
7.1. Block Diagram of Test Setup.....	15
7.2. The Limit For Section 15.249.....	16
7.3. Restricted bands of operation	17
7.4. Configuration of EUT on Measurement	17
7.5. Operating Condition of EUT	17
7.6. Test Procedure	18
7.7. The Field Strength of Radiation Emission Measurement Results	18
8. ANTENNA REQUIREMENT.....	23
8.1. The Requirement	23
8.2. Antenna Construction	23

Test Report Certification

Applicant& address : Chuango Security Technology Corporation
6-17, Overseas Students Pioneer Park, No. 108, Jia Economic & Technological Development Zone, Fuzhou 350015, China

Manufacturer& address : Chuango Security Technology Corporation
6-17, Overseas Students Pioneer Park, No. 108, Jia Economic & Technological Development Zone, Fuzhou 350015, China

Product : SS-20 Indoor Siren

Model No. : SS-20

Trade name : smanos

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.249
ANSI C63.10: 2013

The EUT was tested according to FCC 47CFR 15.249 for compliance to FCC 47CFR 15.249 requirements

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.249 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : May 18, 2017

Date of Report: May 18, 2017

Prepared by :

Bob Wang
(Bob Wang, Engineer)

Approved & Authorized Signer :


(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

The submitted sample is a SS-20 Indoor Siren.

The sample is powered by DC 3V (Powered by Battery).

		SS-20 Indoor Siren
Frequency	:	915MHz
Number of Channels	:	1
Modulation Type	:	FSK
Type of Antenna	:	Integral antenna
Max antenna gain	:	2dBi
Power Supply	:	DC 3V
Date of sample received	:	May 12, 2017
Date of Test	:	May 18, 2017
Sample Number	:	1700579

1.2. Special Accessory and Auxiliary Equipment

N/A

1.3. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC
The Registration Number is 752051

Listed by Industry Canada
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee
for Laboratories
The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO. LTD

Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

1.4. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2
(Above 1GHz)

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 7, 2017	Jan. 6, 2018
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 7, 2017	Jan. 6, 2018
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 7, 2017	Jan. 6, 2018
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 7, 2017	Jan. 6, 2018
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 13, 2017	Jan. 12, 2018
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 13, 2017	Jan. 12, 2018
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 13, 2017	Jan. 12, 2018
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 13, 2017	Jan. 12, 2018
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 7, 2017	Jan. 6, 2018
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 7, 2017	Jan. 6, 2018
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 7, 2017	Jan. 6, 2018
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 7, 2017	Jan. 6, 2018


3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: **Transmitting mode**
TX Channel: 915MHz

3.2.Configuration and peripherals

Block Diagram of Test Setup




4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.215(c)	20dB Bandwidth	Compliant
Section 15.249(d)	Band Edge Compliance Test	Compliant
Section 15.205(a), Section 15.209(a), Section 15.249, Section 15.35	Radiated Spurious Emission Test	Compliant
Section 15.207	AC Power Line Conducted Emission Test	N/A
Section 15.203	Antenna Requirement	Compliant

Note: The power supply mode of the module is DC 3V, According to the FCC standard requirements, conducted emission is not applicable.

5. 20DB BANDWIDTH MEASUREMENT

5.1. Block Diagram of Test Setup



5.2. The Requirement For Section 15.215(c)

The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The hopset shall be such that the near-term distribution of frequencies appears random, with sequential hops randomly distributed in both direction and magnitude of change in the hopset while the long-term distribution appears evenly distributed.

5.3. Operating Condition of EUT

5.3.1. Setup the EUT and simulator as shown as Section 5.1.

5.3.2. Turn on the power of all equipment.

5.3.3. Let the EUT work in TX modes measure it. The transmit frequency is 915MHz.

5.4. Test Procedure

5.4.1. Place the EUT on the table and set it in transmitting mode.

5.4.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

5.4.3. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz, Detector function=peak, Trace=max hold, Sweep=auto.


5.4.4. Set the measured low, middle and high frequency and test 20dB bandwidth with spectrum analyzer.

5.5. Test Result

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
1	915	0.268

The spectrum analyzer plots are attached as below.


Low channel



Comment A:
Date: 18.MAY.2017 14:00:48

6. BAND EDGE COMPLIANCE TEST

6.1. Block Diagram of Test Setup



(EUT: SS-20 Indoor Siren)

6.2. The Requirement For Section 15.249

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

6.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency is 915 MHz.

6.5. Test Procedure

Conducted Band Edge:

6.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz.

Radiate Band Edge:

6.5.3. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.

6.5.4. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

6.5.5. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.


6.5.6. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

6.5.7. RBW=1MHz, VBW=1MHz

6.5.8. The band edges was measured and recorded.

6.6. Test Result

Pass



Comment A:
Date: 18.MAY.2017 14:03:10

Job No.: YJZH #1001

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: SS-20 Indoor Siren

Mode: TX 915MHz

Model: SS-20

Manufacturer: Chuango Security

Polarization: Horizontal

Power Source: DC 3V


Date: 2017/05/16

Time: 19:30:31

Engineer Signature: Nick

Distance: 3m

Note: Report NO.: ATE20170766



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	614.0000	29.19	-8.10	21.09	74.00	-52.91	peak			
2	691.7494	31.93	-6.52	25.41	74.00	-48.59	peak			
3	824.0869	31.79	-3.71	28.08	74.00	-45.92	peak			
4	902.0000	29.53	-2.26	27.27	74.00	-46.73	peak			
5	928.0000	29.41	-1.85	27.56	74.00	-46.44	peak			
6	960.0000	29.04	-1.23	27.81	74.00	-46.19	peak			

Job No.: YJZH #1002

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: SS-20 Indoor Siren

Mode: TX 915MHz

Model: SS-20

Manufacturer: Chuango Security

Polarization: Vertical

Power Source: DC 3V


Date: 2017/05/16

Time: 19:32:35

Engineer Signature: Nick

Distance: 3m

Note: Report NO.: ATE20170766



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	614.0000	30.54	-8.10	22.44	74.00	-51.56	peak			
2	722.8795	31.62	-5.80	25.82	74.00	-48.18	peak			
3	842.8572	31.64	-3.37	28.27	74.00	-45.73	peak			
4	902.0000	28.84	-2.26	26.58	74.00	-47.42	peak			
5	928.0000	28.43	-1.85	26.58	74.00	-47.42	peak			
6	960.0000	29.16	-1.23	27.93	74.00	-46.07	peak			

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:


Result = Reading + Corrected Factor

3. Display the measurement of peak values.

7. RADIATED SPURIOUS EMISSION TEST

7.1. Block Diagram of Test Setup


7.1.1. Block diagram of connection between the EUT and peripherals



Setup: Transmitting mode


(EUT: SS-20 Indoor Siren)

7.1.2. Semi-Anechoic Chamber Test Setup Diagram



Above 1GHz

ANTENNA ELEVATION VARIES FROM 1 TO 4 METERS



7.2.The Limit For Section 15.249

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph A8.4(4), the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

7.3.Restricted bands of operation

7.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

7.4.Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.5.Operating Condition of EUT

7.5.1.Setup the EUT and simulator as shown as Section 7.1.

7.5.2.Turn on the power of all equipment.

7.5.3.Let the EUT work in TX modes measure it. The transmit frequency is 915MHz.

7.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground (Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground (Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 9 kHz in below 30MHz. and set at 120 kHz in 30-1000MHz, and 1MHz in above 1000MHz.

The frequency range from 9 kHz to 10GHz is checked.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

The field strength is calculated by adding the antenna factor, and cable loss, and subtracting the amplifier gain from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

7.7. The Field Strength of Radiation Emission Measurement Results

PASS.

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. *: Denotes restricted band of operation.

Job No.: yjzh #1007

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: SS-20 Indoor Siren

Mode: TX 915MHz

Model: SS-20

Manufacturer: Chuango Security

Polarization: Horizontal

Power Source: DC 3V


Date: 2017/05/16

Time: 19:37:34

Engineer Signature: Nick

Distance: 3m

Note: Report NO.: ATE20170766



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	39.3203	33.66	-17.80	15.86	40.00	-24.14	QP			
2	78.2887	32.92	-22.10	10.82	40.00	-29.18	QP			
3	157.5289	34.02	-21.64	12.38	43.50	-31.12	QP			
4	369.9658	32.90	-13.35	19.55	46.00	-26.45	QP			
5	635.5575	32.11	-7.66	24.45	46.00	-21.55	QP			
6	915.0000	103.53	-1.84	101.69	114.00	-12.31	peak			
7	915.0000	93.53	-1.84	91.69	94.00	-2.31	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: yjzh #1008

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: SS-20 Indoor Siren

Mode: TX 915MHz

Model: SS-20

Manufacturer: Chuango Security

Polarization: Vertical

Power Source: DC 3V


Date: 2017/05/16

Time: 19:37:34

Engineer Signature: Nick

Distance: 3m

Note: Report NO.: ATE20170766



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	39.3203	33.66	-17.80	15.86	40.00	-24.14	QP			
2	78.2887	32.92	-22.10	10.82	40.00	-29.18	QP			
3	157.5289	34.02	-21.64	12.38	43.50	-31.12	QP			
4	369.9658	32.90	-13.35	19.55	46.00	-26.45	QP			
5	635.5575	32.11	-7.66	24.45	46.00	-21.55	QP			
6	915.0000	101.53	-1.84	99.69	114.00	-14.31	peak			
7	915.0000	91.53	-1.84	89.69	94.00	-4.31	AVG			

Job No.: YJZH #999

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: SS-20 Indoor Siren

Mode: TX 915MHz

Model: SS-20

Manufacturer: Chuango Security

Polarization: Vertical

Power Source: DC 3V


Date: 2017/05/16

Time: 19:23:51

Engineer Signature: Nick

Distance: 3m

Note: Report NO.: ATE20170766



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1830.000	61.26	-8.85	52.41	74.00	-21.59	peak			
2	1830.000	51.26	-8.85	42.41	54.00	-11.59	AVG			
3	4575.000	55.21	-0.24	54.97	74.00	-19.03	peak			
4	4575.000	45.21	-0.24	44.97	54.00	-9.03	AVG			
5	5490.000	58.06	2.40	60.46	74.00	-13.54	peak			
6	5490.000	48.06	2.40	50.46	54.00	-3.54	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: YJZH #1000

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: SS-20 Indoor Siren

Mode: TX 915MHz

Model: SS-20

Manufacturer: Chuango Security

Polarization: Horizontal

Power Source: DC 3V


Date: 2017/05/16

Time: 19:25:40

Engineer Signature: Nick

Distance: 3m

Note: Report NO.: ATE20170766



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1830.000	65.63	-8.85	56.78	74.00	-17.22	peak			
2	1830.000	55.63	-8.85	46.78	54.00	-7.22	AVG			
3	2745.000	54.84	-4.58	50.26	74.00	-23.74	peak			
4	2745.000	44.84	-4.58	40.26	54.00	-13.74	AVG			
5	5490.000	55.80	2.40	58.20	74.00	-15.80	peak			
6	5490.000	45.80	2.40	48.20	54.00	-5.80	AVG			


8. ANTENNA REQUIREMENT

8.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2.Antenna Construction

The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b); The Antenna gain of EUT is 2dBi. Therefore, the equipment complies with the antenna requirement.



Antenna