

FCC ID : RJY-W020

RF EXPOSURE

1.1.Limit For Maximum Permissible Exposure (MPE)

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time $ E ^2, H ^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

F = frequency in MHz, * Plane-wave equivalent power density

1.2.MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the WIFI antenna is 2 dBi, the RF power density can be obtained.

1.3.TEST RESULTS

Maximum measured transmitter power
For WIFI 802.11b mode

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Target power (dBm)	Antenna Gain (Numeric)	Power Density Limit (mW/cm ²)	Power Density At 20 cm (mW/cm ²)	Test Results
2412	20.00	9.11	8.15	9± 1	1.585	1.000	0.003	Pass
2437	20.00	9.27	8.45	9± 1	1.585	1.000	0.003	Pass
2462	20.00	9.30	8.51	9± 1	1.585	1.000	0.003	Pass

802.11g mode

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Target power (dBm)	Antenna Gain (Numeric)	Power Density Limit (mW/cm ²)	Power Density At 20 cm (mW/cm ²)	Test Results
2412	20.00	8.14	6.52	8± 1	1.585	1.000	0.002	Pass
2437	20.00	8.33	6.81	8± 1	1.585	1.000	0.002	Pass
2462	20.00	8.47	7.03	8± 1	1.585	1.000	0.002	Pass

802.11n20 mode

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Target power (dBm)	Antenna Gain (Numeric)	Power Density Limit (mW/cm ²)	Power Density At 20 cm (mW/cm ²)	Test Results
2412	20.00	7.07	5.09	7± 1	1.585	1.000	0.002	Pass
2437	20.00	7.24	5.30	7± 1	1.585	1.000	0.002	Pass
2462	20.00	7.63	5.79	7± 1	1.585	1.000	0.002	Pass

802.11n40 mode

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Target power (dBm)	Antenna Gain (Numeric)	Power Density Limit (mW/cm ²)	Power Density At 20 cm (mW/cm ²)	Test Results
2422	20.00	5.63	3.66	6± 1	1.585	1.000	0.001	Pass
2437	20.00	5.88	3.87	6± 1	1.585	1.000	0.001	Pass
2452	20.00	6.08	4.06	6± 1	1.585	1.000	0.001	Pass

1.4.FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, Human proximity to the antenna shall not be less than 20cm(8 inches) during normal operation. Proposed RF exposure safety information to include in User's Manual.