

FCC Test Report (Part 15C) WPT

Test Report no.:	EMC_BO_002198 (v1.0)	Date of issue:	11-Feb-2019
Number of pages:	14	Project support engineer:	Ralf Lange, Frank Wittmann
Test period:	17.01.2019-21.01.2019		

Applicant:	Laird Dabendorf GmbH, Märkische Straße 72, 15806 Zossen, Germany, Mr. Michael Schmidt		
Manufacturer:	Laird Dabendorf GmbH, Märkische Straße 72, 15806 Zossen, Germany		
EUT identification:	Laird, WCH-193a		
FCC ID:	RK7193-00	IC ID:	4774A-19300

Testing laboratory:	LairdLab, Laird Bochum GmbH, Meesmannstr.103, 44807 Bochum, Germany		
	Tel.:	+49 234 51668-0	
	e-mail:	Product.Validation.Bochum@lairdtech.com	
	FCC Designation number	DE0017	IC recognition no.: 7847A-1
	Laboratory manager:	Jürgen Mitterer	

Test result The test result complies with the requirements made in the referred test documents.

Approver:	Ines Baufeld	Technical review:	Frank Wittmann
Title:	Laboratory Quality Manager	Title:	Senior EMC Test Engineer

Signature:  **Signature:** 

This test report may not be reproduced, except in full, without written permission of testing laboratory. The test result in this test report relates only to the tested sample, which is mentioned in this test report. Laird cannot be made responsible for any generalisations or conclusions drawn from this test report. Modification of the tested sample is prohibited and leads to invalidity of this test report.

CONTENTS

1. SUMMARY FOR FCC PART 15C TEST REPORT.....	3
1.1. EUT AND ACCESSORY INFORMATION	3
1.2. APPLIED STANDARDS.....	3
1.3. SUMMARY OF TEST RESULTS.....	3
1.4. MEASUREMENT UNCERTAINTIES	4
2. TEST SETUPS.....	5
2.1. CONDUCTED RF TEST SETUP	5
2.2. RADIATED EMISSIONS TEST SETUP.....	5
3. RADIATED EMISSIONS BELOW 30 MHZ.....	6
3.1. TEST METHOD AND LIMIT	6
3.2. TEST RESULTS (FCC).....	7
4. RADIATED EMISSIONS ABOVE 30 MHZ	9
4.1. TEST METHOD AND LIMIT	9
4.2. TEST RESULTS (FCC).....	10
4.3. TEST RESULTS (ISED)	11
5. OCCUPIED BANDWIDTH	12
5.1. TEST METHOD AND LIMIT	12
5.2. TEST RESULTS (FCC).....	12
5.3. TEST RESULTS (ISED)	13
6. TEST EQUIPMENT	14
6.1. RADIATED EMISSION	14
6.2. CONDUCTED RADIO	14

1. Summary for FCC Part 15C Test Report

Date of receipt	20-Dec-2018
Testing completed	11-Jan-2019
The customer's contact person	Mr. Michael Schmidt
Notes	none

1.1. EUT and Accessory Information

The EUT is an inductive wireless power transfer device (wireless charger) with load modulation operating at 111 kHz. The highest output power is available at 111 kHz. The EUT is tested with the highest duty cycle of 100%. Same current consumption was observed between 5% and 95% charging level of the mobile phone, so that measurement was done at around 50%.

Product	Type	SN	HW	MV	SW	DUT
Wireless charging unit	WCH-193a	000002D07DCB	H02	-	0002	DAB190071E
Artificial load	WCH-Rec.	0013	1.0	-	-	NOV16037E
Power cable	-	-	-	-	-	DAB181161E
RF cable cellular	-	-	-	-	-	BOC180610E

1.2. Applied Standards

Standard / Rule Part	Version	Year
CFR 47, FCC Part 15C	-	Jan-2019
ANSI C63.10	-	Jun-2013
ISED RSS-Gen	Issue 5	Apr-2018
ISED RSS-216	Issue 2	Jan-2016

Deviations or clarifications to these standards are noted in the related test result under "test method and limit".

1.3. Summary of Test Results

Section	Section in CFR 47	Section in RSS-Gen	Section in RSS-216	Name of the test	Result
3 & 4	15.205, 15.209	8.9	6.2.2.2 (Type 1 WPT devices)	Radiated emissions	PASSED
-	15.207	-	6.2.2.1	AC powerline conducted emissions	NA
5	15.215 (c)	6.7	-	Occupied bandwidth	PASSED


PASSED: The EUT complies with the essential requirements in the standard.
 FAILED: The EUT does not comply with the essential requirements in the standard.
 NP: The test was not performed.
 NA: The test was not applicable.

1.4. Measurement Uncertainties


Parameter	Measurement Uncertainty
Radio Frequency	$\pm 3.6 \times 10^{-7}$
Total RF Power, conducted	± 0.79 dB
Emissions, conducted	± 1.67 dB
All emissions, radiated	± 5.38 dB
Temperature	± 0.25 °C
Humidity	± 1.0 %

2. Test setups

2.1. Conducted RF test setup



2.2. Radiated emissions test setup



3. Radiated emissions below 30 MHz

EUT with DUT number	DAB190071E
Accessories with DUT numbers	DAB181161E, BOC180610E, NOV16037E
Operation Voltage [V] / [Hz]	12 V / DC
Result	PASSED
Remarks	none
Temp [°C] / Humidity [%RH]	21.2 °C / 37.0 %
Date of measurements	17.01.2019
Measured by	Oliver Flecke
Test system SW version	V1.7.1

3.1. Test method and limit

The measurement is made according to ANSI C63.10 and RSS-Gen as follows:

The measurement distance is 3m with a shielded loop antenna

The Limit has been adjusted with the distance correction factor according to 15.31(f)(2) (+40 dB for 30 m distance and +80 dB for 300 m distance)

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with measuring antenna at fixed height using 2-axis EUT position system, set on the turntable, which is rotated 360 degrees.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described: $E [\mu V/m] = U_{RX} + A_{CF}$

Where U_{RX} is receiver reading and A_{CF} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{CF} = L_{CABLES} + AF - G_{PREAMP}$).

FCC limits for radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu V/m$]	Limit [dB $\mu V/m$]	Detector
0.009 - 0.09	10000 * 2400 / f[kHz]	128.5 - 93.8	AV
0.09 - 0.11			QP
0.11 - 0.19			AV
0.19 - 0.49			AV
0.490 - 1.705	100 * 24000 / f[kHz]	73.8 - 63.0	QP
1.705 - 30.0	100 * 30	69.5	QP


CISPR11 Induction cooking (group 2) limits (3 m measurement distance)

Frequency range [MHz]	Limit [dB $\mu A/m$]	Limit [dB $\mu V/m$]	Detector
0.009 - 0.070	69.0	120.5	QP
0.070 - 0.1485	69 - 39	120.5 - 90.5	QP
0.1485 - 4.0	39 - 3	90.5 - 54.5	QP
4.0 - 30	3	54.5	QP

Conversion factor between dB $\mu A/m$ and dB $\mu V/m$ is 51.5 dB

3.2. Test results (FCC)

@111 kHz: Peak (< 150 kHz: RBW: 200 Hz, > 150 kHz: RBW 10 kHz)



Quasi-Peak (< 150 kHz: RBW: 200 Hz, >150 kHz: RBW: 9 kHz)

Frequency [MHz]	Level [dBµV/m]	Transducer [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Azimuth [Deg]	Polarisation	Result
0.111116	79.80	23.20	106.70	26.90	170.0	49.00	VERTICAL	PASSED
1.666536	31.90	23.00	63.20	31.30	170.0	264.00	VERTICAL	PASSED
2.111918	31.80	22.90	69.50	37.70	170.0	45.00	VERTICAL	PASSED
3.457133	24.50	23.20	69.50	45.00	170.0	326.00	VERTICAL	PASSED
7.239188	24.70	23.40	69.50	44.80	170.0	142.00	VERTICAL	PASSED
7.714560	24.70	23.40	69.50	44.80	170.0	360.00	VERTICAL	PASSED

No further emissions found less than 20 dB to the regulatory limit and no emission found in the restricted band of operation.


Average (< 150 kHz: RBW: 200Hz, > 150 kHz: RBW: 9 kHz)

Frequency [MHz]	Level [dBµV/m]	Transducer [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Azimuth [Deg]	Polarisation	Result
0.111106	80.30	23.20	106.70	26.40	170.0	44.00	VERTICAL	PASSED
1.666536	28.90	23.00	63.20	34.30	170.0	275.00	VERTICAL	PASSED
2.110918	28.80	22.90	69.50	40.70	170.0	42.00	VERTICAL	PASSED
3.432133	19.30	23.20	69.50	50.20	170.0	336.00	VERTICAL	PASSED
7.275688	19.40	23.40	69.50	50.10	170.0	142.00	VERTICAL	PASSED
7.705560	19.40	23.40	69.50	50.10	170.0	8.00	VERTICAL	PASSED

No further emissions found less than 20 dB to the regulatory limit and no emission found in the restricted band of operation.

Test results (ISED)

@111 kHz: Peak (< 150 kHz: RBW: 200 Hz, > 150 kHz: RBW 10 kHz)



Quasi-Peak (< 150 kHz: RBW: 200 Hz, >150 kHz: RBW: 9 kHz)

Frequency [MHz]	Level [dBµV/m]	Transducer [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Azimuth [Deg]	Polarisation	Result
0.111116	80.20	23.20	102.10	21.90	170.0	49.00	VERTICAL	PASSED
1.666536	32.00	23.00	64.10	32.10	170.0	264.00	VERTICAL	PASSED
2.111918	32.00	22.90	61.50	29.50	170.0	45.00	VERTICAL	PASSED
3.457133	24.50	23.20	56.10	31.60	170.0	326.00	VERTICAL	PASSED
7.239188	24.70	23.40	54.50	29.80	170.0	142.00	VERTICAL	PASSED
7.714560	24.70	23.40	54.50	29.80	170.0	360.00	VERTICAL	PASSED

No further emissions found less than 20 dB to the regulatory limit and no emission found in the restricted band of operation.

Average (< 150 kHz: RBW: 200Hz, > 150 kHz: RBW: 9 kHz)

Frequency [MHz]	Level [dBµV/m]	Transducer [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Azimuth [Deg]	Polarisation	Result
0.111106	80.30	23.20	102.10	21.80	170.0	44.00	VERTICAL	PASSED
1.666536	28.90	23.00	64.10	35.20	170.0	275.00	VERTICAL	PASSED
2.110918	28.80	22.90	61.50	32.70	170.0	42.00	VERTICAL	PASSED
3.432133	19.30	23.20	56.20	36.90	170.0	336.00	VERTICAL	PASSED
7.275688	19.40	23.40	54.50	35.10	170.0	142.00	VERTICAL	PASSED
7.705560	19.40	23.40	54.50	35.10	170.0	7.00	VERTICAL	PASSED

No further emissions found less than 20 dB to the regulatory limit and no emission found in the restricted band of operation.

4. Radiated emissions above 30 MHz

EUT with DUT number	DAB190071E
Accessories with DUT numbers	DAB181161E, BOC180610E, NOV16037E
Operation Voltage [V] / [Hz]	12 V / DC
Result	PASSED
Remarks	none
Temp [°C] / Humidity [%RH]	20.6 °C / 31.5 %
Date of measurements	18.01.2019
Measured by	Oliver Flecke
Test system SW version	V1.7.1

4.1. Test method and limit

The measurement is made according to ANSI C63.10 and RSS-Gen as follows:

The Preliminary Measurement and the Final Measurement is performed in 3 m distance by rotating the turntable of 360 degrees and moving the antenna height between 1-4 m.

The Preliminary Measurement is performed with floor absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed without floor absorbers, if the Preliminary Measurement results are closer than 20 dB to the permissible limit.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The EUT is placed on a nonconductive plate in the center of the turntable.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu V/m] = U_{RX} + A_{CF}$$

Where U_{RX} is receiver reading and A_{CF} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{CF} = L_{CABLES} + AF - G_{PREAMP}$).

FCC limits for radiated emissions measurements (3 m measurement distance)


Frequency range [MHz]	Limit [$\mu V/m$]	Limit [dB $\mu V/m$]	Detector
30 – 88	100	40	QP
88 – 216	150	43.5	QP
216 – 960	200	46	QP
960 – 1000	500	54	QP

CISPR11 Class B group 2 limits (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu V/m$]	Limit [dB $\mu V/m$]	Detector
30 – 80.872	100	40	QP
80.872 – 81.848	1000	60	QP
81.848 – 134.786	100	40	QP
134.786 – 136.414	1000	60	QP
136.414 – 230	100	40	QP
230 - 1000	500	47	QP

4.2. Test results (FCC)

Peak (< 500 MHz: RBW: 300 kHz, > 500 MHz: RBW 1 MHz)




QuasiPeak (RBW: 1 MHz)

Frequency [MHz]	Level [dBµV/m]	Transducer [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Azimuth [Deg]	Polarisation	Result
30.100000	20.60	-8.30	40.00	19.40	226.0	212.00	VERTICAL	PASSED
72.184168	8.10	-25.60	40.00	31.90	326.0	98.00	HORIZONTAL	PASSED
460.771443	12.40	-23.90	46.00	33.60	276.0	168.00	VERTICAL	PASSED
520.691082	13.80	-22.50	46.00	32.20	323.0	230.00	HORIZONTAL	PASSED
718.286874	17.00	-19.30	46.00	29.00	376.0	241.00	HORIZONTAL	PASSED
924.097695	19.80	-16.30	46.00	26.20	173.0	319.00	HORIZONTAL	PASSED

No further emissions found less than 20 dB to the regulatory limit and no emission found in the restricted band of operation.

4.3. Test results (ISED)

Peak (< 500 MHz: RBW: 300 kHz, > 500 MHz: RBW 1 MHz)



QuasiPeak (RBW: 1 MHz)

Frequency [MHz]	Level [dBµV/m]	Transducer [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Azimuth [Deg]	Polarisation	Result
30.100000	20.60	-8.30	40.00	19.40	225.0	212.00	VERTICAL	PASSED
72.184168	8.10	-25.60	40.00	31.90	326.0	98.00	HORIZONTAL	PASSED
460.771443	12.40	-23.90	47.00	34.60	276.0	168.00	VERTICAL	PASSED
520.691082	13.80	-22.50	47.00	33.20	323.0	229.00	HORIZONTAL	PASSED
718.286874	17.00	-19.30	47.00	30.00	376.0	241.00	HORIZONTAL	PASSED
924.097695	19.70	-16.30	47.00	27.30	173.0	319.00	HORIZONTAL	PASSED

No further emissions found less than 20 dB to the regulatory limit and no emission found in the restricted band of operation.

5. Occupied bandwidth

EUT with DUT number	DAB190071E
Accessories with DUT numbers	DAB181161E, BOC180610E, NOV16037E
Operation Voltage [V] / [Hz]	12 V / DC
Result	PASSED
Remarks	none
Temp [°C] / Humidity [%RH]	20.4 °C / 39.5 %
Date of measurements	21.01.2019
Measured by	Bhushan Pawar
Test system SW version	V1.3


5.1. Test method and limit

The measurement is made according to FCC 15.215(c) and RSS-Gen.

Limits for 20 dB / 99 % bandwidth measurements

Limit [MHz]
N/A


5.2. Test results (FCC)



20dB Bandwidth / 0.111MHz / WPT_111kHz_unmodulated
 Date: 21.JAN.2019 10:33:59

frequency [kHz]	20 dB bandwidth [Hz]	Result
111.108	27.244	PASSED

5.3. Test results (ISED)



99% Bandwidth / 0.111MHz / WPT_111kHz_unmodulated
 Date: 21.JAN.2019 10:33:00

frequency [kHz]	99 % bandwidth [Hz]	Result
111.108	22.435	PASSED

6. Test Equipment

6.1. Radiated Emission

Equipment	Manufacturer	Type	SERIAL-NO.	Actual Calibration	Next Calibration
Antenna	Schwarzbeck Mess-Elektronik	FMZB_1519	1519-056	14.07.2017	14.07.2020
EMI Test Receiver	ROHDE & SCHWARZ	ESIB26	827769/010	15.08.2017	15.08.2019
Power Supply	Hewlett Packard - Agilent	E3632A	KR75303301	17.05.2018	17.05.2020
Temp. / Humidity Logger	Lufft	Opus 10	13262	11.01.2017	11.01.2020
Antenna	ROHDE & SCHWARZ	HL562	100191	26.10.2018	26.10.2021
Antenna	Schwarzbeck	BBHA-9120-D	01617	18.08.2016	18.08.2019

6.2. Conducted Radio

Equipment	Manufacturer	Type	SERIAL-NO.	Actual Calibration	Next Calibration
Climatic Chamber	Vötsch	VT4002	521/85094	09.10.2018	09.10.2019
EMI Test Receiver	ROHDE & SCHWARZ	ESU26	100077	16.08.2017	16.08.2019
Power Supply	Hewlett Packard - Agilent	E3632A	MY40011318	23.05.2018	23.05.2020

End of Report