



## 11. Radio Frequency Exposure

### 11.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)  
KDB 447498

### 11.2 EUT Specification

<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2412MHz ~ 2462MHz <input type="checkbox"/> WLAN: 5150MHz ~ 5250MHz <input type="checkbox"/> WLAN: 5250MHz ~ 5350MHz <input type="checkbox"/> WLAN: 5470MHz ~ 5725MHz <input type="checkbox"/> WLAN: 5725MHz ~ 5850MHz <input type="checkbox"/> Bluetooth: 2402MHz ~ 2480MHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	Band: 2412MHz ~ 2462MHz 802.11b: 22.94dBm (196.79mW) 802.11g: 25.10dBm (323.36mW) 802.11n HT20: 27.38dBm (547.22mW) 802.11n HT40: 23.57dBm (227.67mW)
<b>Antenna gain (Max)</b>	2412-2462MHz: ANT 1: 2.8dBi; ANT 2: 3dBi 5150MHz-5250MHz: ANT 1: 3dBi; ANT 2: 3dBi 5725MHz -5850MHz: ANT 1: 2.9dBi; ANT 2: 2.8dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A
<b>Remark:</b>	
<ol style="list-style-type: none"> <li>The maximum output power is <u>27.38dBm (547.22mW)</u> at <u>2437MHz</u> (with <u>numeric 3.78 antenna gain.</u>)</li> <li>DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.</li> <li>For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.</li> </ol>	



### 11.3 Test Results

No non-compliance noted.

#### Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter  
 P = Power in Watts  
 G = Numeric antenna gain  
 d = Distance in meters  
 S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and  
 d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm  
 P = Power in mW  
 G = Numeric antenna gain  
 S = Power density in mW / cm<sup>2</sup>

### 11.4 Maximum Permissible Exposure

Modulation Mode	Frequency band (MHz)	Max. Conducted output power(dBm)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm2)	Limit (mW/cm2)
802.11b	2412-2462	22.94	3.78	20	0.0935	1
802.11g	2412-2462	25.10	3.78	20	0.1536	1
802.11n HT20	2412-2462	27.38	3.78	20	0.2600	1
802.11n HT40	2412-2462	23.57	3.78	20	0.1082	1