

Prüfbericht - Nr.: Test Report No.	14010785 001	Seite 1 von 14 Page 1 of 14	
Auftraggeber: Applicant	i.Tech Dynamic Ltd. Room 1112, Metroplaza, Tower 2 223 Hing Fong Road Kwai Chung, N.T. Hong Kong		
Gegenstand der Prüfung: Test item	i.Tech BlueCON35 lle		
Bezeichnung: Identification	C51-A05049-XX	Serien-Nr.: Serial No.	Engineering sample
Wareneingangs-Nr.: Receipt No.	050823034	Eingangsdatum: Date of receipt	23.08.2005
Prüfort: Testing location	TÜV Rheinland Hong Kong Ltd. Room 8, 25th Floor, Skyline Tower, 39 Wang Kwong Road, Kowloon Bay Kowloon, Hong Kong Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong		
Prüfgrundlage: Test specification	FCC Part 15 Subpart C ANSI C63.4-2003 CISPR 22:1997		
Prüfergebnis: Test Result	Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. The above mentioned product was tested and passed .		
geprüft / tested by:		kontrolliert / reviewed by:	
23.11.2005	Fred Wai	23.11.2005	Thomas Berns
Datum Date	Name Name	Datum Date	Name Name
	Unterschrift Signature		Unterschrift Signature
Sonstiges: Other Aspects		FCCID: RKIC51-A05023-XX	
Abkürzungen:	OK, Pass, P Fail, F N/A NT	= entspricht Prüfgrundlage = entspricht nicht Prüfgrundlage = nicht anwendbar = nicht getestet	Abbreviations: OK, Pass, P Fail, F N/A NT
			= passed = failed = not applicable = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicate in extracts. This test report does not entitle to carry any safety mark on this or similar products.			

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information.....	4
Manufacturers declarations	4
Product function and intended use.....	4
Submitted documents	4
Special accessories and auxiliary equipment.....	4
List of Test and Measurement Instruments.....	5
Result FCC Part 15 – Subpart C	6
Subclause 15.203 – Antenna Information.....	Pass..... 6
Subclause 15.204 – Antenna Information.....	Pass..... 6
Subclause 15.207 – Disturbance Voltage on AC Mains	Pass..... 6
Subclause 15.247 (a) – Carrier Frequency Separation.....	Pass..... 7
Subclause 15.247 (a) – Time of Occupancy (Dwell Time).....	Pass..... 8
Subclause 15.247 (a) – 20 dB Bandwidth	Pass..... 9
Subclause 15.247 (a) – Hopping Sequence.....	Pass..... 9
Subclause 15.247 (a) – Equal Hopping Frequency Use	Pass..... 10
Subclause 15.247 (a) – Receiver Input Bandwidth	Pass..... 11
Subclause 15.247 (a) – Receiver Hopping Capability.....	Pass..... 11
Subclause 15.247 (b) – Peak Output Power	Pass..... 11
Subclause 15.247 (b) – Band edge compliance	Pass..... 12
Subclause 15.247 (c) – Spurious Conducted Emissions.....	Pass..... 12
Subclause 15.247 (c) – Spurious Radiated Emissions.....	Pass..... 13
i.Tech BlueCON35 Ile Overview.....	11
Getting Started.....	12
Charging your Dongle.....	13
Nominal Charging Time.....	14
Talk & Standby Time	14

Low Battery	14
Turning your Dongle on and off	16
Turning On	16
Turning Off	16
Pairing your dongle	18
Care and Maintenance	20
Dongle 20	
Built-in Battery	21
Charging	21
Safety Information	23
Troubleshooting	25
The Dongle	25
Declaration of Conformity (DOC)	27
Product Specifications	29
Appendix 1 – Test protocols	27 pages
Appendix 2 – Test setup	4 pages
Appendix 3 – Photo documentation	9 pages
Appendix 4 – Product documentation	30 pages

Product information

Manufacturers declarations

	Transmitter	Receiver
Operating frequency range	2402 - 2480 MHz	2402 - 2480 MHz
Type of modulation	FHSS modulation	FHSS modulation
Number of channels	79	79
Channel separation	1 MHz	1 MHz
Type of antenna	Integral Antenna	Integral Antenna
Antenna gain (dBi)	2	2
Power level	fix	fix
Type of equipment	stand alone	stand alone
Connection to public utility power line	No	
Nominal voltage	V _{nom} : 3.9 V	V _{nom} : 3.9 V
Independent Operation Modes	Page scan Inquiry scan Connection state - ACL Link Connection state - SCO Link	

Product function and intended use

The test item is a dongle based on the Bluetooth technology.

Bluetooth is a short-range radio link intended to be a cable replacement between portable and/or fixed electronic devices.

Bluetooth operates in the unlicensed ISM Band at 2.4 GHz. In the US a band of 83.5 MHz width is available. In this band, 79 RF channels spaced 1 MHz apart are defined.

The channel is represented by a pseudo-random hopping sequence through the 79 channels. The channel is divided into time slots, with a nominal slot length of 625 µs, where each slot corresponds to different RF hop frequencies. The nominal hop rate is 1600 hops/s. The symbol rate on the channel is 1 Ms/s.

Submitted documents

Circuit Diagram
Block Diagram
Bill of material
User manual

Special accessories and auxiliary equipment

The product has been tested together with the following additional accessory:

1. Manufacturer: FP
Model number: SAW04-05.00-200US
Input: 100-240VAC, 50-60Hz
Output: 5V, 200mA

List of Test and Measurement Instruments

	Kind of Equipment	Manufacturer	Type	S/N
☐	Test Receiver	Rohde & Schwarz	ESH-3	890173/033
☐	L/I/S/N	Rohde & Schwarz	ESH 3-Z5	849876/026
☐	Oscilloscope	HP	54713B	US34510455
☐	Test Receiver	Rohde & Schwarz	ESVP	882402/033
☐	Absorbing Clamp	Rohde & Schwarz	MDS-21	979 3/4
☐	Test Receiver	Rohde & Schwarz	ESVS30	842807/009
☐	Biconical Antenna	Rohde & Schwarz	HK116	841489/015
☐	Log.-Periodic Antenna	Rohde & Schwarz	HL223	841516/017
☐	Universal Power Analyzer	Voltech	PM3000A	9915
☐	Reference Impedance Network	Voltech	IEC 555 Standard	9946
☐	AC Power Source	California Instr.	4500L	HK51895
☐	Trip-Loop Antenna	Chase	LLA6142	1019
☐	Double Ridge Horn Antenna	EMCO	3115	9002-3351
☒	Double Ridge Horn Antenna	EMCO	3115	9002-3347
☐	RF Comms Test Set	HP	8920B	US36492628
☐	Spectrum Analyser + Tracking G.	HP	8596E	3639A00758
☐	Signal Generator	Rohde & Schwarz	SMY 01	844146/024
☐	Signal Generator	Rohde & Schwarz	SMY 01	844146/023
☐	BiLog Antenna	EMCO	3143	9607-1287
☐	Isotropic Field Probe	Holladay	HI-4422	90956
☐	Power Amplifier	Kalmus	757-LC	7620-1
☐	Power Amplifier	Kalmus	122-FC	7620-2
☐	Coupling Clamp	Schaffner	CDN 126	312
☐	Couple Device Network	Fischer	CDN-M2	9604
☒	Spectrum Analyzer	Rohde & Schwarz	FSP30	1093.4495K30
☐	Temperature Chamber	Binder	MK 240	9020-0028
☐	EFT,ESD,SURGE, DIPS tester	Schaffner	Best 96	IN3796-011
☐	Surge Generator	Schaffner	NSG650	280

Result FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Information		Pass
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Result:	Permanent attached antenna	
Verdict:	Pass	

Subclause 15.204 – Antenna Information		Pass
Requirement:	Provide information for every antenna proposed for the use with the EUT	
Result:	a) Antenna type: Integral antenna b) Manufacturer and model no: N.A. c) Gain with reference to an isotropic radiator: 2 dBi	
Verdict:	Pass	

Subclause 15.207 – Disturbance Voltage on AC Mains						Pass
Test Port: AC mains input port of the charger Applied voltage: 110VAC Applicable only to equipment designed to be connected to the public utility power line.						
1) Mode of operation: Charging only						
Live measurement						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dBµV	Average dBµV	Limit QP (dBµV)	Limit AV (dBµV)	Verdict
0,15 – 0,5	0.150000	36.8	29.0	66 - 56	56 - 46	Pass
> 0,5 - 5	0.510000	35.5	23.9	56	46	Pass
> 0,5 - 5	0.714000	36.4	24.7	56	46	Pass
> 0,5 - 5	1.379270	41.5	29.8	56	46	Pass
Neutral measurement						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dBµV	Average dBµV	Limit QP (dBµV)	Limit AV (dBµV)	Verdict
0,15 – 0,5	0.150000	37.9	28.4	0,15 – 0,5	0.150000	37.9
0,15 – 0,5	0.202080	30.8	21.0	0,15 – 0,5	0.202080	30.8
> 0,5 - 5	1.346810	37.0	17.0	> 0,5 - 5	1.346810	37.0
> 0,5 - 5	1.492080	34.9	15.2	> 0,5 - 5	1.492080	34.9

Result: The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz does not exceed the limits. For test results plots refer to Appendix 1, page 2-4.

Subclause 15.247 (a) – Carrier Frequency Separation
Pass

Requirement: Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

Test Specification : FCC Part 15 Subpart A – Subclause 15.31
 Mode of operation : Tx mode (hopping on), DH1 packet
 Port of testing : Temporary antenna port
 Detector : Peak
 RBW/VBW : 100 kHz / 300 kHz
 Supply voltage : 12VDC from AC/DC adapter
 Temperature : 23°C
 Humidity : 50%

Result: The centre frequencies of the hopping channels are separated by more than the 20dB bandwidth. For test results plots refer to Appendix 1, page 2.

Verdict: Pass

Subclause 15.247 (a) – Time of Occupancy (Dwell Time)	Pass
Requirement: Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.	
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (hopping on), DH5 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 12VDC from AC/DC adapter Temperature : 23°C Humidity : 50%	
Result: The screenshot in Appendix 1 page 4 shows the occurrence of a channel in a 31.6 s time period. In normal hopping mode Bluetooth is using 79 hopping channels only. The frequency was used 64 times. The dwell time for the longest supported packet type is about 3 ms. As a result the average time of occupancy will not be greater than 400 ms. i.e. Time period calculation: $0.4 \times 79 = 31.6\text{s}$ Limit calculation: $64 \times 2.928 \times 10^{-3} = 187.392 \times 10^{-3}$ $\leq 400 \times 10^{-3} \text{ s}$ For test protocols please refer to Appendix 1, page 3-4. Verdict: Pass	

Subclause 15.247 (a) – 20 dB Bandwidth**Pass**

Requirement: Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

Test Specification : FCC Part 15 Subpart A – Subclause 15.31
 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH5 packet
 Port of testing : Temporary antenna port
 Detector : Peak
 RBW/VBW : 30 kHz / 100 kHz
 Supply voltage : 12VDC from AC/DC adapter
 Temperature : 23°C
 Humidity : 50%

Results

For test protocols refer to Appendix 1, page 5-7.


Frequency (MHz)	20 dB left (MHz)	20 dB right (MHz)	20dB bandwidth (MHz)
2402	460	464	924
2441	460	412	872
2480	464	408	872

Subclause 15.247 (a) – Hopping Sequence**Pass**

Requirement: The hopping sequence is generated and provided with an example.

Hopping sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master. The X input determines the phase in the 32-hop segment, whereas Y1 and Y2 selects between master-to-slave and slave-to-master transmission. The inputs A to D determine the ordering within the segment, the inputs E and F determine the mapping onto the hop frequencies.



Example data:

Hop sequence {k} for CONNECTION STATE:

CLK start: 0x0000010

ULAP: 0x00000000

#ticks: 00 02 | 04 06 | 08 0a | 0c 0e | 10 12 | 14 16 | 18 1a | 1c 1e |

```

0x0000010: 08 66 | 10 70 | 12 19 | 14 23 | 16 01 | 18 05 | 20 33 | 22 37 |
0x0000030: 24 03 | 26 07 | 28 35 | 30 39 | 32 72 | 34 76 | 36 25 | 38 29 |
0x0000050: 40 74 | 42 78 | 44 27 | 46 31 | 48 09 | 50 13 | 52 41 | 54 45 |
0x0000070: 56 11 | 58 15 | 60 43 | 62 47 | 32 17 | 36 19 | 34 49 | 38 51 |
0x0000090: 40 21 | 44 23 | 42 53 | 46 55 | 48 33 | 52 35 | 50 65 | 54 67 |
0x00000b0: 56 37 | 60 39 | 58 69 | 62 71 | 64 25 | 68 27 | 66 57 | 70 59 |
0x00000d0: 72 29 | 76 31 | 74 61 | 78 63 | 01 41 | 05 43 | 03 73 | 07 75 |
0x00000f0: 09 45 | 13 47 | 11 77 | 15 00 | 64 49 | 66 53 | 68 02 | 70 06 |
0x0000110: 01 51 | 03 55 | 05 04 | 07 08 | 72 57 | 74 61 | 76 10 | 78 14 |
0x0000130: 09 59 | 11 63 | 13 12 | 15 16 | 17 65 | 19 69 | 21 18 | 23 22 |
0x0000150: 33 67 | 35 71 | 37 20 | 39 24 | 25 73 | 27 77 | 29 26 | 31 30 |
0x0000170: 41 75 | 43 00 | 45 28 | 47 32 | 17 02 | 21 04 | 19 34 | 23 36 |
0x0000190: 33 06 | 37 08 | 35 38 | 39 40 | 25 10 | 29 12 | 27 42 | 31 44 |
0x00001b0: 41 14 | 45 16 | 43 46 | 47 48 | 49 18 | 53 20 | 51 50 | 55 52 |
0x00001d0: 65 22 | 69 24 | 67 54 | 71 56 | 57 26 | 61 28 | 59 58 | 63 60 |
0x00001f0: 73 30 | 77 32 | 75 62 | 00 64 | 49 34 | 51 42 | 57 66 | 59 74 |
0x0000210: 53 36 | 55 44 | 61 68 | 63 76 | 65 50 | 67 58 | 73 03 | 75 11 |
0x0000230: 69 52 | 71 60 | 77 05 | 00 13 | 02 38 | 04 46 | 10 70 | 12 78 |
0x0000250: 06 40 | 08 48 | 14 72 | 16 01 | 18 54 | 20 62 | 26 07 | 28 15 |
0x0000270: 22 56 | 24 64 | 30 09 | 32 17 | 02 66 | 06 74 | 10 19 | 14 27 |
0x0000290: 04 70 | 08 78 | 12 23 | 16 31 | 18 03 | 22 11 | 26 35 | 30 43 |
0x00002b0: 20 07 | 24 15 | 28 39 | 32 47 | 34 68 | 38 76 | 42 21 | 46 29 |
0x00002d0: 36 72 | 40 01 | 44 25 | 48 33 | 50 05 | 54 13 | 58 37 | 62 45 |
0x00002f0: 52 09 | 56 17 | 60 41 | 64 49 | 34 19 | 36 35 | 50 51 | 52 67 |
0x0000310: 38 21 | 40 37 | 54 53 | 56 69 | 42 27 | 44 43 | 58 59 | 60 75 |
0x0000330: 46 29 | 48 45 | 62 61 | 64 77 | 66 23 | 68 39 | 03 55 | 05 71 |
0x0000350: 70 25 | 72 41 | 07 57 | 09 73 | 74 31 | 76 47 | 11 63 | 13 00 |
0x0000370: 78 33 | 01 49 | 15 65 | 17 02 | 66 51 | 70 67 | 03 04 | 07 20 |
0x0000390: 68 55 | 72 71 | 05 08 | 09 24 | 74 59 | 78 75 | 11 12 | 15 28 |
0x00003b0: 76 63 | 01 00 | 13 16 | 17 32 | 19 53 | 23 69 | 35 06 | 39 22 |
0x00003d0: 21 57 | 25 73 | 37 10 | 41 26 | 27 61 | 31 77 | 43 14 | 47 30 |
0x00003f0: 29 65 | 33 02 | 45 18 | 49 34 | 19 04 | 21 08 | 23 20 | 25 24 |

```

Subclause 15.247 (a) – Equal Hopping Frequency Use**Pass**

Requirement: Each of the transmitter's hopping channels is used equally on average.

Equal hopping frequency use

The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.

Subclause 15.247 (a) – Receiver Input Bandwidth		Pass
Requirement:	The associated receiver(s) complies with the requirement that its input bandwidth matches the bandwidth of the transmitted signal.	
Receiver input bandwidth		
The receiver bandwidth is equal to the receiver bandwidth in the 79 hopping channel mode, which is 1 MHz. The receiver bandwidth was verified during Bluetooth RF conformance testing.		

Subclause 15.247 (a) – Receiver Hopping Capability		Pass
Requirement:	The associated receiver has the ability to shift frequencies in synchronisation with the transmitted signals.	
Receiver hopping Capability		
The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.		

Subclause 15.247 (b) – Peak Output Power		Pass			
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 12VDC from AC/DC adapter Temperature : 23°C Humidity : 50%					
Requirement:	For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 Watt. For all other frequency hopping systems in the 2400 – 2483.5 MHz band: 0.125 Watts.				
Result All three transmit frequency modes comply with the maximum peak output power limit. For test protocols please refer to Appendix 1, page 8-10.					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	0.47	3.52	3.99	1 / 30.0	Pass
2441	-0.07	3.65	3.58	1 / 30.0	Pass
2480	-3.10	3.60	0.50	1 / 30.0	Pass

Subclause 15.247 (b) – Band edge compliance		Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 300 kHz / 1 MHz Supply voltage : 12VDC from AC/DC adapter Temperature : 23°C Humidity : 50%		
Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.		
Result There is no peak found outside any 100 kHz bandwidth of the operating frequency band in the three transmit frequency. All three transmit frequency modes comply with the limit stated in subclause 15.247(c). For test protocols refer to Appendix 1, page 11-13.		

Subclause 15.247 (c) – Spurious Conducted Emissions			Pass		
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 12VDC from AC/DC adapter Temperature : 23 °C Humidity : 50 %					
Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Result There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency. All three transmit frequency modes comply with the limit stated in subclause 15.247(c). For test protocols refer to Appendix 1, page 14-20.					
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	No peak found	-	-	-	Pass
2441	No peak found	-	-	-	Pass
2480	No peak found	-	-	-	Pass

Subclause 15.247 (c) – Spurious Radiated Emissions						Pass	
Test Specification : ANSI C63.4 - 2003 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 12VDC from car battery Temperature : 23°C Humidity : 50%							
Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.							
Result All three transmit frequency modes comply with the field strength within the restricted bands. For test protocols refer to Appendix 1, page 21-68. The spurious found within the limit from 16 – 30 MHz							
Tx frequency 2402MHz				Vertical Polarization			
Freq MHz	Reading dBuV	AF dB(1/m)	Cable att. dB	Pre-amp dB	Filter att. dB	Level dBuV/m	Limit/ Detector dBuV/m
12.17	29.02	18.55	0.22	-	-	10.25	40.0 / P
25.27	13.36	17.65	0.35	-	-	-4.64	40.0 / P
28.46	12.68	17.41	0.38	-	-	-5.11	40.0 / P
1601.96	41.12	25.40	1.89	36.17	0.60	49.40	74.0 / P
1601.98	39.76	25.40	1.89	36.17	0.60	48.04	54.0 / A
4803.98	49.30	33.40	3.53	32.87	0.33	44.91	74.0 / P
4803.98	43.59	33.40	3.53	32.87	0.33	39.20	54.0 / A
Tx frequency 2402MHz				Horizontal Polarization			
Freq MHz	Reading dBuV	AF dB(1/m)	Cable att. dB	Pre-amp dB	Filter att. dB	Level dBuV/m	Limit/ Detector dBuV/m
25.27	16.63	17.65	0.35	-	-	-1.37	40.0 / P
29.02	15.07	17.37	0.39	-	-	-2.69	40.0 / P
28.46	14.57	17.65	0.40	-	-	-3.48	40.0 / P
1601.94	45.58	25.40	1.89	36.17	0.60	53.86	74.0 / P
1602.04	44.76	25.40	1.89	36.17	0.60	53.04	54.0 / A
4803.86	49.18	33.40	3.53	32.87	0.33	44.79	74.0 / P
4804.08	47.15	33.40	3.53	32.87	0.33	42.76	54.0 / A

Tx frequency 2441MHz				Vertical Polarization			
Freq MHz	Reading dBuV	AF dB(1/m)	Cable att. dB	Pre-amp dB	Filter att. dB	Level dBuV/m	Limit/ Detector dBuV/m
25.27	12.83	17.65	0.35	-	-	-5.17	40.0 / P
29.02	12.92	17.37	0.39	-	-	-4.84	40.0 / P
28.46	12.25	17.65	0.40	-	-	-5.80	40.0 / P
1628.04	40.84	25.40	1.89	36.17	0.60	49.12	74.0 / P
1628.00	39.30	25.40	1.89	36.17	0.60	47.58	54.0 / A
4882.04	50.05	33.40	3.53	32.87	0.33	45.66	74.0 / P
4881.96	47.02	33.40	3.53	32.87	0.33	42.63	54.0 / A
Tx frequency 2441MHz				Horizontal Polarization			
Freq MHz	Reading dBuV	AF dB(1/m)	Cable att. dB	Pre-amp dB	Filter att. dB	Level dBuV/m	Limit/ Detector dBuV/m
25.27	25.27	17.65	0.35	-	-	7.27	40.0 / P
28.46	28.46	17.65	0.40	-	-	10.41	40.0 / P
29.02	29.02	17.37	0.39	-	-	11.26	40.0 / P
1627.98	50.63	25.40	1.89	36.17	0.60	58.91	74.0 / P
1628.00	50.37	25.40	1.89	36.17	0.60	58.66	54.0 / A
4881.98	49.41	33.40	3.53	32.87	0.33	45.02	74.0 / P
4882.04	46.98	33.40	3.53	32.87	0.33	42.59	54.0 / A
Tx frequency 2480MHz				Vertical Polarization			
Freq MHz	Reading dBuV	AF dB(1/m)	Cable att. dB	Pre-amp dB	Filter att. dB	Level dBuV/m	Limit/ Detector dBuV/m
28.46	11.84	17.65	0.40	-	-	-6.21	40.0 / P
1654.04	43.89	25.40	1.89	36.17	0.60	52.17	74.0 / P
1654.06	43.01	25.40	1.89	36.17	0.60	51.29	54.0 / A
4960.00	45.06	33.40	3.53	32.87	0.33	40.67	74.0 / P
4960.08	41.63	33.40	3.53	32.87	0.33	37.24	54.0 / A
Tx frequency 2480MHz				Horizontal Polarization			
Freq MHz	Reading dBuV	AF dB(1/m)	Cable att. dB	Pre-amp dB	Filter att. dB	Level dBuV/m	Limit/ Detector dBuV/m
25.27	16.75	17.65	0.35	-	-	-1.25	40.0 / P
28.46	14.78	17.65	0.40	-	-	-3.27	40.0 / P
29.02	15.42	17.37	0.39	-	-	-2.34	40.0 / P
1653.92	46.02	25.40	1.89	36.17	0.60	54.30	74.0 / P
1654.02	45.48	25.40	1.89	36.17	0.60	53.76	54.0 / A
4960.02	45.58	33.40	3.53	32.87	0.33	41.19	74.0 / P
4959.92	41.96	33.40	3.53	32.87	0.33	37.57	54.0 / A

Appendix 1

Test results

Disturbance Voltage on AC Mains

Date: 28 Sept 2005
EUT: BlueCON35 IIe
Company: i.Tech Dynamics
Humidity: 50%
Temperature: 23°C
Voltage supply: 3.9VDC from AC/DC adapter
Test by: Sharon Li
Op. mode: Charging

Live measurement

Frequency (MHz)	QP reading (dB μ V)	Av reading (dB μ V)	Results
0,15 – 0,5	0.150000	36.8	29.0
> 0,5 - 5	0.510000	35.5	23.9
> 0,5 - 5	0.714000	36.4	24.7
> 0,5 - 5	1.379270	41.5	29.8

Neutral measurement

Frequency (MHz)	QP reading (dB μ V)	Av reading (dB μ V)	Results
0,15 – 0,5	0.150000	37.9	28.4
0,15 – 0,5	0.202080	30.8	21.0
> 0,5 - 5	1.346810	37.0	17.0
> 0,5 - 5	1.492080	34.9	15.2

Carrier Frequency Separation

Date: 28 Sept 2005
 EUT: BlueCON35 Ile
 Company: i.Tech Dynamics
 Humidity: 50%
 Temperature: 23°C
 Voltage supply: 3.9VDC from AC/DC adapter
 Test by: Sharon Li
 Op. mode: Hopping on

Reference frequency (MHz)
2441.000

Channel Separation (MHz)
1.002



DELTA MARKER 3

1.002 MHz

Ref 20 dBm


*Att 30 dB

*RBW 100 kHz Delta 3 [T1]

VBW 300 kHz -0.05 dB

SWT 2.5 ms 1.002000000 MHz

1 PK
MAXH



Center 2.441 GHz

300 kHz/

Span 3 MHz

Date: 14.SEP.2005 15:22:15

Dwell Time

Date: 28 Sept 2005
EUT: BlueCON35 Ile
Company: i.Tech Dynamics
Humidity: 50%
Temperature: 23°C
Voltage supply: 3.9VDC from AC/DC adapter
Test by: Sharon Li
Op. mode: Hopping on

Burst Duration (ms)	Number of hopping	Time of occupancy (s)	Results
2.928	64	$0.002928 \times 64 =$ 0.187392	Pass



DELTA MARKER 2

2.928 ms

Ref 20 dBm

*Att 30 dB

RBW 1 MHz

Delta 2 [T1]


*VBW 3 MHz

-0.01 dB

SWT 4 ms

2.928000 ms


1 PK *
CLRWR



A

TRG

Date: 14.SEP.2005 16:54:21



Date: 14.SEP.2005 16:55:48

20dB Bandwidth

Date: 28 Sept 2005
 EUT: BlueCON35 Ile
 Company: i.Tech Dynamics
 Humidity: 50%
 Temperature: 23°C
 Voltage supply: 3.9VDC from AC/DC adapter
 Test by: Sharon Li
 Op. mode: TX mode, DH5 with PRBS9 payload

Tx frequency (MHz)	Δf_L (MHz)	Δf_H (MHz)	$ \Delta f_H + \Delta f_L $ (MHz)	Results
2402	460	464	924	Pass
2441	460	412	872	Pass
2480	464	408	872	Pass




FREQUENCY LINE 2

2.402464 GHz

Ref 20 dBm

*Att 30 dB

*RBW 30 kHz Delta 2 [T1]
 VBW 100 kHz -20.21 dB
 SWT 2.5 ms -460.000000000 kHz



Date: 14.SEP.2005 17:01:37

Tx frequency: 2402MHz

**FREQUENCY LINE 2**

2.441416 GHz


Ref 20 dBm

*Att 30 dB

*RBW 30 kHz Delta 3 [T1]

VBW 100 kHz -20.14 dB

SWT 2.5 ms 412.00000000 kHz

1 PK
MAXH

Center 2.441 GHz

200 kHz/

Span 2 MHz

Date: 14.SEP.2005 17:10:04

Tx frequency: 2441MHz

**FREQUENCY LINE 2**

2.480416 GHz


Ref 20 dBm

*Att 30 dB

*RBW 30 kHz Delta 3 [T1]

VBW 100 kHz -20.40 dB

SWT 2.5 ms 408.00000000 kHz

**1 PK
MAXH**

Date: 14.SEP.2005 17:17:51

Tx frequency: 2480MHz

Peak Output Power

Date: 28 Sept 2005
 EUT: BlueCON35 Ile
 Company: i.Tech Dynamics
 Humidity: 50%
 Temperature: 23°C
 Voltage supply: 3.9VDC from AC/DC adapter
 Test by: Sharon Li
 Op. mode: TX mode, DH1 with PRBS9 payload

Tx Frequency (MHz)	Power P _{PK} (dBm)	Cable Attenuation (dB)	Actual Peak Power (dBm)	Results
2402	0.47	3.52	3.99	Pass
2441	-0.07	3.65	3.58	Pass
2480	-3.10	3.60	0.50	Pass

**MARKER 1**

2.40184 GHz

*RBW 1 MHz

Marker 1 [T1]

*VBW 3 MHz


0.47 dBm

Ref 20 dBm

*Att 30 dB

SWT 2.5 ms

2.401840000 GHz



Date: 14.SEP.2005 17:19:14

Tx frequency: 2402MHz



MARKER 1

2.44086 GHz

Ref 20 dBm

*Att 30 dB

*RBW 1 MHz

Marker 1 [T1]


*VBW 3 MHz

-0.07 dBm

SWT 2.5 ms

2.440860000 GHz

1 PK
MAXH



Center 2.441 GHz

500 kHz/

Span 5 MHz

Date: 14.SEP.2005 17:20:11

Tx frequency: 2441MHz



MARKER 1

2.47986 GHz

Ref 20 dBm

*Att 30 dB

*RBW 1 MHz

Marker 1 [T1]


*VBW 3 MHz

-3.10 dBm

SWT 2.5 ms

2.479860000 GHz

1 PK
MAXH



Center 2.48 GHz

500 kHz/

Span 5 MHz

Date: 14.SEP.2005 18:03:11

Tx frequency: 2480MHz

Band Edge Compliance

Date: 28 Sept 2005
 EUT: BlueCON35 Ile
 Company: i.Tech Dynamics
 Humidity: 50%
 Temperature: 23°C
 Voltage supply: 3.9VDC from AC/DC adapter
 Test by: Sharon Li
 Op. mode: TX mode, DH1 with PRBS9 payload

Tx Frequency (MHz)	Peak in band Power level (dBm)	RF power outside 100kHz BW (MHz)	RF power difference outside 100kHz BW (dB)	Results
2402	No Peak	-43.43	-	Pass
2480	No Peak	-47.17	-	Pass

**MARKER 3**

2.38604 GHz


Ref 20 dBm

*Att 30 dB

*RBW 300 kHz Marker 3 [T1]

VBW 1 MHz -50.19 dBm

SWT 2.5 ms 2.386040000 GHz



Date: 14.SEP.2005 18:06:37

Tx frequency: 2402MHz



MARKER 2

2.3696 GHz

Ref 20 dBm

*Att 30 dB

*RBW 3 MHz

Marker 2 [T1]


*VBW 10 MHz

-42.78 dBm

SWT 5 ms

2.369600000 GHz

1 PK
MAXH



Center 2.441 GHz

15 MHz/

Span 150 MHz

Date: 14.SEP.2005 18:07:48

Tx frequency: 2441MHz

**MARKER 3**

2.48688 GHz


Ref 20 dBm

*Att 30 dB

*RBW 300 kHz Marker 3 [T1]

*VBW 1 MHz -54.04 dBm

SWT 2.5 ms 2.486880000 GHz

**1 PK
MAXH**

Date: 14.SEP.2005 18:10:47

Tx frequency: 2480MHz

Spurious Emissions - Conducted

Date: 28 Sept 2005
EUT: BlueCON35 Ile
Company: i.Tech Dynamics
Humidity: 50%
Temperature: 23°C
Voltage supply: 3.9VDC from AC/DC adapter
Test by: Sharon Li
Op. mode: TX mode, DH1 with PRBS9 payload

Tx frequency : 2402MHz

Spurious Frequency (MHz)	Power level (dBm)	Reference value (dBm)	Delta to reference level (dB)	Results
No peak found	-	-	-	Pass

Tx frequency : 2441MHz

Spurious Frequency (MHz)	Power level (dBm)	Reference value (dBm)	Delta to reference level (dB)	Results
No peak found	-	-	-	Pass

Tx frequency : 2480MHz

Spurious Frequency (MHz)	Power level (dBm)	Reference value (dBm)	Delta to reference level (dB)	Results
No peak found	-	-	-	Pass



MARKER 1

2.40286 GHz

Ref 20 dBm


*Att 30 dB

*RBW 100 kHz Marker 1 [T1]

*VBW 300 kHz -0.83 dBm

*SWT 60 s 2.402860000 GHz

1 PK
MAXH



Start 30 MHz

997 MHz/

Stop 10 GHz

Date: 14.SEP.2005 18:16:31

Tx frequency: 2402MHz

**MARKER 1**

13.7 GHz


Ref 20 dBm

*Att 30 dB

*RBW 100 kHz Marker 1 [T1]

*VBW 300 kHz -42.03 dBm

*SWT 60 s 13.700000000 GHz

**1 PK
MAXH**

Date: 14.SEP.2005 18:18:42

Tx frequency: 2402MHz



MARKER 1

22.78 GHz

Ref 20 dBm


*Att 30 dB

*RBW 100 kHz Marker 1 [T1]

*VBW 300 kHz -39.59 dBm

*SWT 60 s 22.780000000 GHz

1 PK
MAXH



Start 20 GHz

500 MHz/

Stop 25 GHz

Date: 14.SEP.2005 18:22:24

Tx frequency: 2402MHz

**DELTA MARKER 2**

-1.50556 GHz


Ref 20 dBm

*Att 30 dB

*RBW 100 kHz Delta 2 [T1]

*VBW 300 kHz -49.86 dB

*SWT 60 s -1.505560000 GHz

1 PK
MAXH

Date: 14.SEP.2005 18:27:12

Tx frequency: 2441MHz



MARKER 1

15.58 GHz

Ref 20 dBm


*Att 30 dB

*RBW 100 kHz Marker 1 [T1]

*VBW 300 kHz -42.09 dBm

*SWT 60 s 15.580000000 GHz

1 PK
MAXH



Start 10 GHz

1 GHz/

Stop 20 GHz

Date: 14.SEP.2005 18:19:11

Tx frequency: 2441MHz

**MARKER 1**

23.25 GHz


Ref 20 dBm

*Att 30 dB

*RBW 100 kHz Marker 1 [T1]

*VBW 300 kHz -40.99 dBm

*SWT 60 s 23.25000000 GHz

**1 PK
MAXH**

Date: 14.SEP.2005 18:23:03

Tx frequency: 2441MHz



MARKER 1

2.48262 GHz

Ref 20 dBm


*Att 30 dB

*RBW 100 kHz Marker 1 [T1]

*VBW 300 kHz -2.71 dBm

*SWT 60 s 2.482620000 GHz

1 PK
MAXH



Start 30 MHz

997 MHz/

Stop 10 GHz

Date: 14.SEP.2005 18:31:56

Tx frequency: 2480MHz

**MARKER 1**

16.56 GHz

Ref 20 dBm

*Att 30 dB


*RBW 100 kHz Marker 1 [T1]

*VBW 300 kHz

-42.37 dBm

*SWT 60 s

16.560000000 GHz

**1 PK
MAXH**

Date: 14.SEP.2005 18:19:40

Tx frequency: 2480MHz



MARKER 1

21.63 GHz

Ref 20 dBm


*Att 30 dB

*RBW 100 kHz Marker 1 [T1]

*VBW 300 kHz -41.14 dBm

*SWT 60 s 21.63000000 GHz

1 PK
MAXH



Start 20 GHz

500 MHz/

Stop 25 GHz

Date: 14.SEP.2005 18:23:39

Tx frequency: 2480MHz

Spurious Emissions - Radiated

Date: 28 Sept 2005

EUT: BlueCON35 Ile

Company: i.Tech Dynamics

Voltage supply: 3.9VDC from AC/DC adapter

Test by: Sharon Li

Op. mode: TX mode, DH1 with PRBS9 payload

The spurious found within the limit from 16 – 30 MHz

Tx frequency (MHz)	Polarization	Spurious Frequency (MHz)	Power Level (dBuV/m)	Detector (P/QP/A)
2402	V	25.27	13.36	P
2402	V	12.17	29.02	P
2402	V	28.46	12.68	P
2402	V	1601.96	41.12	P
2402	V	1601.98	39.76	A
2402	V	4803.98	49.30	P
2402	V	4803.98	43.59	A
2402	H	25.27	16.63	P
2402	H	29.02	15.07	P
2402	H	28.46	14.57	P
2402	H	1601.94	45.58	P
2402	H	1602.04	44.76	A
2402	H	4803.86	49.18	P
2402	H	4804.08	47.15	A

Tx frequency (MHz)	Polarization	Spurious Frequency (MHz)	Power Level (dBuV/m)	Detector (P/QP/A)
2441	V	25.27	12.83	P
2441	V	29.02	12.92	P
2441	V	28.46	12.25	P
2441	V	1628.04	40.84	P
2441	V	1628.00	39.30	A
2441	V	4882.04	50.05	P
2441	V	4881.96	47.02	A
2441	V	25.27	25.27	P
2441	V	29.02	29.02	P
2441	V	28.46	28.46	P
2441	H	1627.98	50.63	P
2441	H	1628.00	50.37	A
2441	H	4881.98	49.41	P
2441	H	4882.04	46.98	A

Tx frequency (MHz)	Polarization	Spurious Frequency (MHz)	Power Level (dBuV/m)	Detector (P/QP/A)
2480	V	28.46	11.84	P
2480	V	1654.04	43.89	P

2480	V	1654.06	43.01	A
2480	V	4960.00	45.06	P
2480	V	4960.08	41.63	A
2480	H	25.27	16.75	P
2480	H	28.46	14.78	P
2480	H	29.02	15.42	P
2480	H	1653.92	46.02	P
2480	H	1654.02	45.48	A
2480	H	4960.02	45.58	P
2480	H	4959.92	41.96	A