

Prüfbericht - Nr.: <i>Test Report No.:</i>		14013762 001		Seite 1 von 12 <i>Page 1 of 12</i>																			
Auftraggeber: <i>Client:</i>		i.Tech Dynamic Ltd. 5/F, Harbourfront Landmark 11 Wan Hoi Street, Hung Hom, Kowloon Hong Kong																					
Gegenstand der Prüfung: <i>Test Item:</i>		i.Tech Arrow Lite																					
Bezeichnung: <i>Identification:</i>		C51-A06001-XX	Serien-Nr.: <i>Serial No.:</i>		Engineering sample																		
Wareneingangs-Nr.: <i>Receipt No.:</i>		060719004	Eingangsdatum: <i>Date of Receipt:</i>		19.07.2006																		
Prüfört: <i>Testing Location:</i>		TÜV Rheinland Hong Kong Ltd. Room 8, 25th Floor, Skyline Tower, 39 Wang Kwong Road, Kowloon Bay Kowloon, Hong Kong Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong																					
Prüfgrundlage: <i>Test Specification:</i>		FCC Part 15 Subpart C ANSI C63.4-2003 CISPR 22:1997																					
Prüfergebnis: <i>Test Result:</i>		Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. <i>The a. m. test item passed the test specification.</i>																					
geprüft / tested by:			kontrolliert / checked by:																				
01.08.2006	Sharon Li Project Engineer		01.08.2006	Thomas Berns Manager																			
Datum <i>Date</i>	Name <i>Name</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name <i>Name</i>	Unterschrift <i>Signature</i>																		
Sonstiges: <i>Other Aspects</i>																							
FCCID: RKIC51-A06001-XX																							
<table border="0"> <tr> <td>Abkürzungen:</td> <td>OK, Pass, P</td> <td>= entspricht Prüfgrundlage</td> <td>Abbreviations:</td> <td>OK, Pass, P</td> <td>= passed</td> </tr> <tr> <td></td> <td>Fail, F</td> <td>= entspricht nicht Prüfgrundlage</td> <td></td> <td>Fail, F</td> <td>= failed</td> </tr> <tr> <td></td> <td>N.A.</td> <td>= nicht anwendbar</td> <td></td> <td>N.A.</td> <td>= not applicable</td> </tr> </table>						Abkürzungen:	OK, Pass, P	= entspricht Prüfgrundlage	Abbreviations:	OK, Pass, P	= passed		Fail, F	= entspricht nicht Prüfgrundlage		Fail, F	= failed		N.A.	= nicht anwendbar		N.A.	= not applicable
Abkürzungen:	OK, Pass, P	= entspricht Prüfgrundlage	Abbreviations:	OK, Pass, P	= passed																		
	Fail, F	= entspricht nicht Prüfgrundlage		Fail, F	= failed																		
	N.A.	= nicht anwendbar		N.A.	= not applicable																		
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test centre this test report is not permitted to be duplicate in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i>																							

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information.....	3
Manufacturers declarations	3
Product function and intended use	3
Submitted documents.....	3
List of Test and Measurement Instruments.....	4
Result FCC Part 15 – Subpart C	5
Subclause 15.203 – Antenna Information	Pass..... 5
Subclause 15.204 – Antenna Information	Pass..... 5
Subclause 15.207 – Disturbance Voltage on AC Mains.....	N.A..... 5
Subclause 15.247 (a) – Carrier Frequency Separation	Pass..... 5
Subclause 15.247 (a) – Time of Occupancy (Dwell Time)	Pass..... 6
Subclause 15.247 (a) – 20 dB Bandwidth.....	Pass..... 7
Subclause 15.247 (a) – Hopping Sequence	Pass..... 7
Subclause 15.247 (a) – Equal Hopping Frequency Use.....	Pass..... 8
Subclause 15.247 (a) – Receiver Input Bandwidth.....	Pass..... 9
Subclause 15.247 (a) – Receiver Hopping Capability	Pass..... 9
Subclause 15.247 (b) – Peak Output Power.....	Pass..... 9
Subclause 15.247 (b) – Band edge compliance	Pass..... 10
Subclause 15.247 (c) – Spurious Conducted Emissions	Pass..... 10
Subclause 15.247 (c) – Spurious Radiated Emissions	Pass..... 11
Appendix 1 – Test protocols	15 pages
Appendix 2 – Test setup	2 pages
Appendix 3 – Photo documentation	6 pages
Appendix 4 – Product documentation	33 pages

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	FHSS modulation
Number of channels	79
Channel separation	1 MHz
Type of antenna	Integral Antenna
Antenna gain (dBi)	1.2
Power level	fix
Type of equipment	stand alone
Connection to public utility power line	Yes
Nominal voltage	V_{nom} : 3.7 V
Independent Operation Modes	Page scan Inquiry scan Connection state - ACL Link Connection state - SCO Link

Product function and intended use

The test item is a Bluetooth Headset based on the Bluetooth technology.

Bluetooth is a short-range radio link intended to be a cable replacement between portable and/or fixed electronic devices.

Bluetooth operates in the unlicensed ISM Band at 2.4 GHz. In the US a band of 83.5 MHz width is available. In this band, 79 RF channels spaced 1 MHz apart are defined.

The channel is represented by a pseudo-random hopping sequence through the 79 channels. The channel is divided into time slots, with a nominal slot length of 625 μs , where each slot corresponds to different RF hop frequencies. The nominal hop rate is 1600 hops/s. The symbol rate on the channel is 1 Ms/s.

Submitted documents

Circuit Diagram
 Block Diagram
 Bill of material
 User manual

List of Test and Measurement Instruments

	Kind of Equipment	Manufacturer	Type	S/N
☒	Test Receiver	Rohde & Schwarz	ESH-3	890173/033
☒	L/I/S/N	Rohde & Schwarz	ESH 3-Z5	849876/026
☐	Oscilloscope	HP	54713B	US34510455
☐	Test Receiver	Rohde & Schwarz	ESVP	882402/033
☐	Absorbing Clamp	Rohde & Schwarz	MDS-21	979 3/4
☒	Test Receiver	Rohde & Schwarz	ESVS30	842807/009
☒	Biconical Antenna	Rohde & Schwarz	HK116	841489/015
☒	Log.-Periodic Antenna	Rohde & Schwarz	HL223	841516/017
☐	Universal Power Analyzer	Voltech	PM3000A	9915
☐	Reference Impedance Network	Voltech	IEC 555 Standard	9946
☐	AC Power Source	California Instr.	4500L	HK51895
☐	Trip-Loop Antenna	Chase	LLA6142	1019
☐	Double Ridge Horn Antenna	EMCO	3115	9002-3351
☒	Double Ridge Horn Antenna	EMCO	3115	9002-3347
☐	RF Comms Test Set	HP	8920B	US36492628
☐	Spectrum Analyser + Tracking G.	HP	8596E	3639A00758
☐	Signal Generator	Rohde & Schwarz	SMY 01	844146/024
☐	Signal Generator	Rohde & Schwarz	SMY 01	844146/023
☐	BiLog Antenna	EMCO	3143	9607-1287
☐	Isotropic Field Probe	Holladay	HI-4422	90956
☐	Power Amplifier	Kalmus	757-LC	7620-1
☐	Power Amplifier	Kalmus	122-FC	7620-2
☐	Coupling Clamp	Schaffner	CDN 126	312
☐	Couple Device Network	Fischer	CDN-M2	9604
☒	Spectrum Analyzer	Rohde & Schwarz	FSP30	1093.4495K30
☐	Temperature Chamber	Binder	MK 240	9020-0028
☐	EFT,ESD,SURGE, DIPS tester	Schaffner	Best 96	IN3796-011
☐	Surge Generator	Schaffner	NSG650	280
☒	Active Loop Antenna	EMCO	6502	9107-2651

Result FCC Part 15 – Subpart C

Subclause 15.203 – Antenna Information		Pass
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Result:	Permanent attached antenna	
Verdict:	Pass	


Subclause 15.204 – Antenna Information		Pass
Requirement:	Provide information for every antenna proposed for the use with the EUT	
Result:	a) Antenna type: Integral antenna soldered to the circuit board b) Manufacturer and model no: N.A. c) Gain with reference to an isotropic radiator: 1.2 dBi	
Verdict:	Pass	

Subclause 15.207 – Disturbance Voltage on AC Mains		N.A.
The device is not functioning (no RF radiations) during charging		

Subclause 15.247 (a) – Carrier Frequency Separation		Pass
Requirement:	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.	
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (hopping on), DH1 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%		
Result:	The centre frequencies of the hopping channels are separated by more than the 20dB bandwidth. For test results plots refer to Appendix 1, page 2.	
Verdict:	Pass	

Subclause 15.247 (a) – Time of Occupancy (Dwell Time)	Pass
Requirement: Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.	
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (hopping on), DH5 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%	
Result: The screenshot in Appendix 1 page 9 shows the occurrence of a channel in a 31.6 s time period. In normal hopping mode Bluetooth is using 79 hopping channels only. The frequency was used 64 times. The dwell time for the longest supported packet type is about 3 ms. As a result the average time of occupancy will not be greater than 400 ms. i.e. Time period calculation: $0.4 \times 79 = 31.6\text{s}$ Limit calculation: $64 \times 2.928 \times 10^{-3} = 187.4 \times 10^{-3}$ $\leq 400 \times 10^{-3} \text{ s}$ For test protocols please refer to Appendix 1, page 3-4. Verdict: Pass	

Subclause 15.247 (a) – 20 dB Bandwidth		Pass	
Requirement:	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.		
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH5 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 30 kHz / 100 kHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%			
Results			
For test protocols refer to Appendix 1, page 5-6.			
Frequency (MHz)	20 dB left (MHz)	20 dB right (MHz)	20dB bandwidth (MHz)
2402	0.460	0.468	0.928
2441	0.460	0.464	0.924
2480	0.460	0.476	0.936

Subclause 15.247 (a) – Hopping Sequence	Pass
Requirement:	The hopping sequence is generated and provided with an example.
Hopping sequence The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master. The X input determines the phase in the 32-hop segment, whereas Y1 and Y2 selects between master-to-slave and slave-to-master transmission. The inputs A to D determine the ordering within the segment, the inputs E and F determine the mapping onto the hop frequencies.	
	

Example data:

Hop sequence {k} for CONNECTION STATE:

CLK start: 0x0000010

ULAP: 0x00000000

#ticks: 00 02 | 04 06 | 08 0a | 0c 0e | 10 12 | 14 16 | 18 1a | 1c 1e |

```

0x0000010: 08 66 | 10 70 | 12 19 | 14 23 | 16 01 | 18 05 | 20 33 | 22 37 |
0x0000030: 24 03 | 26 07 | 28 35 | 30 39 | 32 72 | 34 76 | 36 25 | 38 29 |
0x0000050: 40 74 | 42 78 | 44 27 | 46 31 | 48 09 | 50 13 | 52 41 | 54 45 |
0x0000070: 56 11 | 58 15 | 60 43 | 62 47 | 32 17 | 36 19 | 34 49 | 38 51 |
0x0000090: 40 21 | 44 23 | 42 53 | 46 55 | 48 33 | 52 35 | 50 65 | 54 67 |
0x00000b0: 56 37 | 60 39 | 58 69 | 62 71 | 64 25 | 68 27 | 66 57 | 70 59 |
0x00000d0: 72 29 | 76 31 | 74 61 | 78 63 | 01 41 | 05 43 | 03 73 | 07 75 |
0x00000f0: 09 45 | 13 47 | 11 77 | 15 00 | 64 49 | 66 53 | 68 02 | 70 06 |
0x0000110: 01 51 | 03 55 | 05 04 | 07 08 | 72 57 | 74 61 | 76 10 | 78 14 |
0x0000130: 09 59 | 11 63 | 13 12 | 15 16 | 17 65 | 19 69 | 21 18 | 23 22 |
0x0000150: 33 67 | 35 71 | 37 20 | 39 24 | 25 73 | 27 77 | 29 26 | 31 30 |
0x0000170: 41 75 | 43 00 | 45 28 | 47 32 | 17 02 | 21 04 | 19 34 | 23 36 |
0x0000190: 33 06 | 37 08 | 35 38 | 39 40 | 25 10 | 29 12 | 27 42 | 31 44 |
0x00001b0: 41 14 | 45 16 | 43 46 | 47 48 | 49 18 | 53 20 | 51 50 | 55 52 |
0x00001d0: 65 22 | 69 24 | 67 54 | 71 56 | 57 26 | 61 28 | 59 58 | 63 60 |
0x00001f0: 73 30 | 77 32 | 75 62 | 00 64 | 49 34 | 51 42 | 57 66 | 59 74 |
0x0000210: 53 36 | 55 44 | 61 68 | 63 76 | 65 50 | 67 58 | 73 03 | 75 11 |
0x0000230: 69 52 | 71 60 | 77 05 | 00 13 | 02 38 | 04 46 | 10 70 | 12 78 |
0x0000250: 06 40 | 08 48 | 14 72 | 16 01 | 18 54 | 20 62 | 26 07 | 28 15 |
0x0000270: 22 56 | 24 64 | 30 09 | 32 17 | 02 66 | 06 74 | 10 19 | 14 27 |
0x0000290: 04 70 | 08 78 | 12 23 | 16 31 | 18 03 | 22 11 | 26 35 | 30 43 |
0x00002b0: 20 07 | 24 15 | 28 39 | 32 47 | 34 68 | 38 76 | 42 21 | 46 29 |
0x00002d0: 36 72 | 40 01 | 44 25 | 48 33 | 50 05 | 54 13 | 58 37 | 62 45 |
0x00002f0: 52 09 | 56 17 | 60 41 | 64 49 | 34 19 | 36 35 | 50 51 | 52 67 |
0x0000310: 38 21 | 40 37 | 54 53 | 56 69 | 42 27 | 44 43 | 58 59 | 60 75 |
0x0000330: 46 29 | 48 45 | 62 61 | 64 77 | 66 23 | 68 39 | 03 55 | 05 71 |
0x0000350: 70 25 | 72 41 | 07 57 | 09 73 | 74 31 | 76 47 | 11 63 | 13 00 |
0x0000370: 78 33 | 01 49 | 15 65 | 17 02 | 66 51 | 70 67 | 03 04 | 07 20 |
0x0000390: 68 55 | 72 71 | 05 08 | 09 24 | 74 59 | 78 75 | 11 12 | 15 28 |
0x00003b0: 76 63 | 01 00 | 13 16 | 17 32 | 19 53 | 23 69 | 35 06 | 39 22 |
0x00003d0: 21 57 | 25 73 | 37 10 | 41 26 | 27 61 | 31 77 | 43 14 | 47 30 |
0x00003f0: 29 65 | 33 02 | 45 18 | 49 34 | 19 04 | 21 08 | 23 20 | 25 24 |

```

Subclause 15.247 (a) – Equal Hopping Frequency Use**Pass**

Requirement: Each of the transmitter's hopping channels is used equally on average.

Equal hopping frequency use

The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.

Subclause 15.247 (a) – Receiver Input Bandwidth	Pass
Requirement: The associated receiver(s) complies with the requirement that its input bandwidth matches the bandwidth of the transmitted signal.	
Receiver input bandwidth The receiver bandwidth is equal to the receiver bandwidth in the 79 hopping channel mode, which is 1 MHz. The receiver bandwidth was verified during Bluetooth RF conformance testing.	

Subclause 15.247 (a) – Receiver Hopping Capability	Pass
Requirement: The associated receiver has the ability to shift frequencies in synchronisation with the transmitted signals.	
Receiver hopping Capability The EUT complies with the Bluetooth RF specifications. For details refer to the Bluetooth standard.	

Subclause 15.247 (b) – Peak Output Power		Pass			
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 1 MHz / 3 MHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%					
Requirement: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 Watt. For all other frequency hopping systems in the 2400 – 2483.5 MHz band: 0.125 Watts.					
Result All three transmit frequency modes comply with the maximum peak output power limit. For test protocols please refer to Appendix 1, page 7-8.					
Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	-4.88	3.52	-1.36	1 / 30.0	Pass
2441	-4.38	3.65	-0.73	1 / 30.0	Pass
2480	-3.53	3.60	0.07	1 / 30.0	Pass

Subclause 15.247 (b) – Band edge compliance		Pass
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 1 MHz Supply voltage : 3.7VDC from DC power supply Temperature : 23°C Humidity : 50%		
Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.		
Result There is no peak found outside any 100 kHz bandwidth of the operating frequency band in the three transmit frequency. All three transmit frequency modes comply with the limit stated in subclause 15.247(c). For test protocols refer to Appendix 1, page 9-10.		

Subclause 15.247 (c) – Spurious Conducted Emissions		Pass			
Test Specification : FCC Part 15 Subpart A – Subclause 15.31 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet Port of testing : Temporary antenna port Detector : Peak RBW/VBW : 100 kHz / 300 kHz Supply voltage : 3.7VDC from DC power supply Temperature : 23 °C Humidity : 50 %					
Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.				
Result There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency. All three transmit frequency modes comply with the limit stated in subclause 15.247(c). For test protocols refer to Appendix 1, page 11-15 .					
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	No peak found	-	-	-	Pass
2441	No peak found	-	-	-	Pass
2480	No peak found	-	-	-	Pass

Subclause 15.247 (c) – Spurious Radiated Emissions		Pass	
Test Specification : ANSI C63.4 - 2003 Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : internal batteries has been activated Temperature : 23°C Humidity : 50%			
Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.		
Result			
All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found under the frequency below 30MHz.			
Tx frequency 2402MHz		Vertical Polarization	
Freq (MHz)	Level (dBuV/m)	Limit/ Detector (dBuV/m)	Delta to Limit (dB)
86.2400	7.00	43.5 / QP	36.50
433.3400	32.60	43.5 / QP	10.90
736.1600	29.70	43.5 / QP	13.80
4803.8000	50.76	74.0 / P	23.24
4803.9800	45.15	54.0 / A	8.85
Tx frequency 2402MHz		Horizontal Polarization	
Freq (MHz)	Level (dBuV/m)	Limit/ Detector (dBuV/m)	Delta to Limit (dB)
438.0800	38.70	43.5 / QP	4.80
707.8400	34.90	43.5 / QP	8.60
1601.9000	43.94	74.0 / P	30.06
1601.9800	42.76	54.0 / A	11.24
Tx frequency 2441MHz		Vertical Polarization	
Freq (MHz)	Level (dBuV/m)	Limit/ Detector (dBuV/m)	Delta to Limit (dB)
88.5200	7.10	43.5 / QP	36.40
435.3200	39.10	43.5 / QP	4.40
4881.8800	52.17	74.0 / P	21.83
4881.9800	48.70	54.0 / A	5.30

Tx frequency 2441MHz Horizontal Polarization			
Freq (MHz)	Level (dBuV/m)	Limit/ Detector (dBuV/m)	Delta to Limit (dB)
434.9000	39.30	43.5 / QP	4.20
753.2000	36.70	43.5 / QP	6.80
1627.9400	43.31	74.0 / P	30.69
1627.9400	42.00	54.0 / A	12.00
Tx frequency 2480MHz Vertical Polarization			
Freq (MHz)	Level (dBuV/m)	Limit/ Detector (dBuV/m)	Delta to Limit (dB)
86.4200	7.10	43.5 / QP	36.40
434.0600	32.50	43.5 / QP	11.00
4959.9600	52.77	74.0 / P	21.23
4959.9600	49.53	54.0 / A	4.47
Tx frequency 2480MHz Horizontal Polarization			
Freq (MHz)	Level (dBuV/m)	Limit/ Detector (dBuV/m)	Delta to Limit (dB)
431.0000	37.70	43.5 / QP	5.80
680.0000	30.50	43.5 / QP	13.00
1653.9000	43.43	74.0 / P	30.57
1654.0200	42.22	54.0 / A	11.78