

## **BAND EDGE COMPLIANCE**

**Standard:** FCC part 15.247

**Test procedure:** Public Notice DA 00-705, Delta Marker method.

### **Test equipment used:**

<b>TYPE</b>	<b>MANUFACTURER</b>	<b>EMITECH NUMBER</b>
Spectrum analyzer FSP 40	Rohde & Schwarz	4088
Antenna RGA-60	Electrometrics	1204
Variac R213	Dereix	1419

### **Measured condition:**

Requirements: Emissions that fall in the restricted bands (part 15.205). These emissions must be less than or equal to 500  $\mu\text{V/m}$  (54  $\text{dB}\mu\text{V/m}$ ). Part 15.35b applies in the restricted bands.

Test procedure: An in band field strength measurement of the fundamental Emission using the RBw and detector function required by C63.4-2003 and FCC Rules.

### **Test operating condition of the equipment:**

The equipment is locked in frequency hopping mode

### **Results:**

Lower Band Edge: from 2310 MHz to 2390 MHz (curve n°1)

Upper Band Edge: from 2483.5 MHz to 2500 MHz (curve n°2)

#### Sample n° 1:

Fundamental Frequency (MHz)	Field Strength Level of fundamental ( $\text{dB}\mu\text{V/m}$ )	Peak Or Average	Frequency of maximum Band-edges Emission (MHz)	Delta Marker (dB)*	Calculated Max Out of Band Emission Level ( $\text{dB}\mu\text{V/m}$ **)	Limit ( $\text{dB}\mu\text{V/m}$ )	Margin (dB)
2402	96.41	Peak	2389.2	47.22	49.19 <sup>(1)</sup>	74	24.81
2480	96	Peak	2485.96	47.47	48.53 <sup>(1)</sup>	74	25.47


\* According to step 2 of Marker-Delta Method DA 00-705

\*\* According to step 3 of Marker-Delta Method:

Calculated Emission Level = Field Strength Level – Delta Marker Level

(1) The level is below the average limit (54  $\text{dB}\mu\text{V/m}$ )

**Test conclusion: RESPECTED PUBLIC NOTICE**




Date: 3.OCT.2006 16:27:46

RA-06-24111-2

Band edge compliance

Curve n°1



Date: 3.OCT.2006 16:31:18

RA-06-2411-2

Band edge compliance

Curve n° 2