

RF EXPOSURE REPORT

REPORT NO.: SA131121C21

MODEL NO.: U3

FCC ID: RLS-STAVL1321

RECEIVED: Nov. 21, 2013

ISSUED: Dec. 05, 2013

APPLICANT: SYSTEMS & TECHNOLOGY CORP.

ADDRESS: 18-5F, No.79, Hsin Tai Wu Road, Sec. 1, Hsichih District, New Taipei City, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. RF EXPOSURE	5
2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	5
2.2 MPE CALCULATION FORMULA	5
2.3 CLASSIFICATION	5
2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA131121C21	Original release	Dec. 05, 2013

1. CERTIFICATION

PRODUCT: GPS Vehicle Tracking Device

MODEL: U3

BRAND: CAREU

APPLICANT: SYSTEMS & TECHNOLOGY CORP.

TEST SAMPLE: PRODUCTION UNIT

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Gina Liu , **DATE** : Dec. 05, 2013

Gina Liu / Specialist

APPROVED BY : Roy Wu , **DATE** : Dec. 05, 2013

Roy Wu / Manager

2. RF EXPOSURE

2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

Band	Operating Mode	Maximum Conducted (dBm)		Permitted Maximum Antenna Gain (dBi)	E.I.R.P. (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
		Burst Avg. Power	Time Avg. Power				
GSM850	GPRS12	29.50	26.50	7.8	2691.53	0.54	0.55
GSM1900	GPRS12	26.34	23.34	13.6	4943.11	0.98	1.0
GSM850	EDGE33	29.16	26.16	8.2	2728.98	0.54	0.55
GSM1900	EDGE12	26.26	23.26	13.7	4965.92	0.99	1.0

Band	Maximum Conducted (dBm)	Permitted Maximum Antenna Gain (dBi)	E.I.R.P. (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA II	21.41	15.5	4909.08	0.98	1.0
WCDMA V	22.20	12.1	2691.53	0.54	0.55
WCDMA IV	22.39	14.5	4886.52	0.97	1.0