FCC ID: RLVAUDIOPILLAR

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculated.

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up power(dBm)	Result calculation	1-g SAR
2.402	GFSK	4.880	5±1	6	0.9535	3.00
2.441	GFSK	4.797	5±1	6	0.9430	3.00
2.480	GFSK	4.260	5±1	6	0.8400	3.00
2.402	π/4-DQPSK	4.001	3.5 ± 1	4.5	0.7788	3.00
2.441	π/4-DQPSK	3.792	3.5±1	4.5	0.7482	3.00
2.480	π/4-DQPSK	2.945	3.5±1	4.5	0.6205	3.00
2.402	8-DPSK	4.182	4±1	5	0.8119	3.00
2.441	8-DPSK	4.074	4±1	5	0.7984	3.00
2.480	8-DPSK	3.286	4±1	5	0.6712	3.00

Maximum measured transmitter power:

Conclusion:

For the max result $0.9535 \le 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Sincerely,

Signature Company Name: SHENZHEN EMTEK CO., LTD. Address: Bldg 69, Majialong Industry Zone, NanshanDistrict, Shenzhen, China. David Lee/ Manager