Letter of Undertaking

CUSTOMER:	Dongguan Hailutong Industrial Co., Ltd		
CUST P/N:	303030-00034		
FINE P/N:			
DESC:	Φ43.5MMX5.3MMX0.8MM Slotting 0.08*48P*10TS-6.5UH Line length45MM		
DATE:	2023.12.20		
Version:	A1.0		

PREPARED BY	CHECKED BY	APPROVED BY	CUSTOMER APPROVE
HU YUE	TIAN JIA	YAN KAI	

Version Change History

Rev.	Before Chang	After Change	Change Date	Approved By
A1.0	Newly issued		20231211	YAN KAI

DESC		© 43.5MMX5.3MMX0.8MM CUST:			Hailutong
	Slotting 0.08*48P*10TS-6.5UH Lir length45MM	Rev: A.0	CUST P/N:		303030-00034
-, DIMENSI				А	43.5 ± 0.5
				В	20.5 \pm 0.5
				С	0.8 ± 0.1
				D	45 ± 1
	FIC DIAGRAM:			Е	3±1
S		F		F	2.5 ± 1
•		0	-	G	2.0 Max
		G		3.2. The size is inner ho the thic 0.1mm. 4.3. Tap high-ten paper, t thickness magnetic 2.0mmMax of dippi 5. Paste	oss out wire; e magnetic disc 43.5 ± 0.5 mm, the ole is 5.3mm, and ekness is $0.8\pm$ e the coil with 3mm mperature adhesive the overall ss of the coil and e sheet is a, and the length ng tin is 2.5 ± 1 mm 42.5mm adhesive on a and 42.5 mm black

SPECIFICATION

film on the front

\equiv Winding Specification:

NO.	TERMIN	RMINAL WIRE		ERMINAL WIRE Turns Winding Direct		Winding Direction
1	S	F	Silk-covered wire 0.8*48P	10Ts	CCW	

四、ELECTRICAL CHARACTERISTICS:

TEMPERATURE:25±10°C, RELATIVE HUMIDITY:65±20%

NO.	ITEM	TERMINAL	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS
1	IND.	S-F	6.5uH $\pm 10\%$ Add Magnetic	100KHz/1.0V	EUCOL U2832
			disc		
2	DCR	S-F	80m Ω	100KHz/1.0V	EUCOL U2832
3	Q	S-F	40MAX	100KHz/1.0V	EUCOL U2832
			•	•	·

五、PACKAGE

包装图片 Packing pictures:

The packaging shall be based on the existing packaging tray as the reference standard, and the actual shipment packaging shall prevail. If there are special requirements, customization can be made.