

Page : 1 of 9
Issued date : 2022/3/22
FCC ID : RLY21GMD01

Maximum Permissible Exposure Report

Product : ALPHA Dongle

Model Name : ALPHAMD-BKBWW

FCC ID : RLY21GMD01

Test Regulation : 47 CFR FCC Part 2.1093

Received Date : 2022/2/24

Test Date : 2022/3/8~ 2022/3/15

Issued Date : 2022/3/22

Applicant: ADATA Technology Co., Ltd.

2F., No.258, Lian Cheng Rd., Chung Ho Dist., New Taipei

City 235, Taiwan (R.O.C.)

Issued By : Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd.,

Zhudong Township, Hsinchu County, Taiwan





The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



Page : 2 of 9
Issued date : 2022/3/22
FCC ID : RLY21GMD01

REVISION HISTORY

Original Test Report No.: 4790323504B-US-R1-V0

Rev.	Tost var out No	Date	Page revised	Contents
Original	Test report No. 4790323504B-US-R1-V0	2022/3/22	- Page revised	Initial issue
Original	4/90323304B-US-R1-V0	2022/3/22	-	Initial issue
-				
	I.	l		I.



Doc No: 17-EM-F0864 / 5.0

Page : 3 of 9
Issued date : 2022/3/22
FCC ID : RLY21GMD01

Table of Contents

1.	Attestation of Test Results	4
2.	Test Methodology and Reference Procedures	5
3.	Facilities and Accreditation	5
4.	Equipment Under Test	6
4	4.1. Description of EUT	6
5.	Requirement	8
6.	Radio Frequency SAR Test Exclusion Thresholds	9



Page : 4 of 9
Issued date : 2022/3/22
FCC ID : RLY21GMD01

1. Attestation of Test Results

APPLICANT: ADATA Technology Co., Ltd.

2F., No.258, Lian Cheng Rd., Chung Ho Dist., New Taipei City 235,

Taiwan (R.O.C.)

EUT DESCRIPTION: ALPHA Dongle

BRAND: XPG

MODEL: ALPHAMD-BKBWW

SAMPLE STAGE: Engineering Verification Test sample

APPLICABLE STANDARDS

STANDARD

Test Results

47 CFR FCC PART 2.1093

PASS

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:

Approved and Authorized By:

Sally Lu Project Handler

Date: 2022/3/22

Kent Liu

Date: 2022/3/22

Senior Project Engineer

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



Page : 5 of 9
Issued date : 2022/3/22
FCC ID : RLY21GMD01

2. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

3. Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.	
Address	Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan	
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398.	



Page : 6 of 9
Issued date : 2022/3/22
FCC ID : RLY21GMD01

4. Equipment Under Test

4.1. Description of EUT

Product Name	ALPHA Dongle		
Brand Name	XPG		
Model Name	ALPHAMD-BKBWW		
Operating Frequency	SRD 2403MHz ~ 2475MHz		
Modulation	SRD GFSK		
Number of Channel	SRD	5	
Normal Voltage	5Vdc from USB		
Sample ID	4737134		

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual.



Page : 7 of 9
Issued date : 2022/3/22
FCC ID : RLY21GMD01

4.2. Description of Available Antennas

nt. Vo.	Transmitter Circuit	Brand Name	Model Name	Ant. Type	Maximum Gain (dBi)
1	Chain (0)	WoodStone	2.4GHZ ANTENNA	PCB	-2.68

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual.



Page : 8 of 9
Issued date : 2022/3/22
FCC ID : RLY21GMD01

5. Requirement

Following FCC KDB 447498 D01 "General SAR test exclusion guidance"

The corresponding SAR Exclusion Threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- ► f(GHz) is the RF channel transmit frequency in GHz.
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.
- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:
 - a) [Threshold at 50 mm in step 1) + (test separation distance 50mm)·(f(MHz)/150)] mW, at 100MHz to 1500 MHz
 - b) [Threshold at 50 mm in step 1) + (test separation distance 50 mm) \cdot 10] mW at > 1500 MHz and \leq 6 GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
 - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(MHz))]$ for test separation distances > 50 mm and < 200 mm.
 - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances ≤ 50 mm.
 - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

Facsimile (FAX) :+886-3-583-7948 Doc No: 17-EM-F0864 / 5.0



Page : 9 of 9
Issued date : 2022/3/22
FCC ID : RLY21GMD01

6. Radio Frequency SAR Test Exclusion Thresholds

Operating Mode	Evaluation Frequency	Max. Average power	Antenna Gain	Min. test separation distance	SAR test exclusion calculation	10-g SAR test exclusion	Result
	(MHz)	(mW)	(dBi)	(mm)	value	thresholds	
SRD	2475	2.559	-2.68	5	0.805	7.5	PASS

Note:

Conclusion:

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.

END OF REPORT

^{1.} Calculate SAR test exclusion thresholds from section 5.1 formulas.