

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM170300160502

Page: 1 of 8

RF Exposure Evaluation Report

Application No.: SZEM1703001605CR

Applicant: ADATA Technology Co., Ltd Manufacturer: ADATA Technology Co., Ltd

Factory Nanjing Skyworth Institute of Information Technology Co., Ltd

Product Name: HDMI Streaming Media Adapter

Model No.(EUT): MV100

Trade mark: ADATA

FCC ID: RLYMV100

Standards: 47 CFR Part 1.1307 (2016)

47 CFR Part 1.1310 (2016)

Date of Receipt: 2017-03-08

Date of Test: 2017-04-17 to 2017-07-19

Date of Issue: 2017-07-20

Test Result : PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM170300160502

Page: 2 of 8

2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
01		2017-07-20		Original	

Authorized for issue by:		
	Peter Gene	
	Peter Geng /Project Engineer	
	Eric Fu	
	Eric Fu /Reviewer	



Report No.: SZEM170300160502

Page: 3 of 8

3 Contents

		Pa	ige
1	С	COVER PAGE	1
2	٧	/ERSION	2
3	С	CONTENTS	3
4	G	GENERAL INFORMATION	4
	4.1		
	4.2		4
	4.3	TEST LOCATION	
	4.4	TEST FACILITY	
	4.5	DEVIATION FROM STANDARDS	6
	4.6	ABNORMALITIES FROM STANDARD CONDITIONS	6
	4.7	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
5	R	RF EXPOSURE EVALUATION	7
	5.1	RF Exposure Compliance Requirement	7
		5.1.1 Limits	
	5	5.1.2 Test Procedure	7
	4.1.3	3 EUT RF Exposure Evaluation	8



Report No.: SZEM170300160502

Page: 4 of 8

4 General Information

4.1 Client Information

Applicant:	ADATA Technology Co., Ltd
Address of Applicant:	2F, NO.258, Lian Cheng RD., Chung Ho Dist., New Taipei City, Taiwan
Manufacturer:	ADATA Technology Co., Ltd
Address of Manufacturer:	2F, NO.258, Lian Cheng RD., Chung Ho Dist., New Taipei City, Taiwan
Factory:	Nanjing Skyworth Institute of Information Technology Co., Ltd
Address of Factory:	1036, 10th. Floor, No.28 of Ningshuang Rd., Yuhuatai District, Nanjing, Jingsu Pro., PRC

4.2 General Description of EUT

Product Name:	HDMI Streaming Media Adapter		
Model No.:	MV100		
Trade Mark:	ADATA		
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz		
	IEEE 802.11n(HT40): 2422MHz to 2452MHz		
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels		
	IEEE 802.11n HT40: 7 Channels		
Channel Separation:	5MHz		
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK)		
	IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK)		
	IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM,		
	QPSK,BPSK)		
Antenna Type:	PIFA		
Antenna Gain:	2dBi		
Power supply:	DC 5V from USB port		
Test voltage	AC 120V/60Hz		
Cable:	USB cable:60cm unshielded		



Report No.: SZEM170300160502

Page: 5 of 8

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

· CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC

Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



Report No.: SZEM170300160502

Page: 6 of 8

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None

4.7 Other Information Requested by the Customer

None.



Report No.: SZEM170300160502

Page: 7 of 8

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30 30			

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*Pi*R2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Report No.: SZEM170300160502

Page: 8 of 8

4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 2dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.58 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Test Mode	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
11B	2462	14.02	25.23	0.0079	1	PASS
11G	2462	16.8	47.86	0.0151	1	PASS
11N20SISO	2462	17	50.12	0.0158	1	PASS
11N40SISO	2452	15.42	34.83	0.0110	1	PASS

Note: Refer to report No. SZEM1703001605001 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.