



Engineering Solutions & Electromagnetic Compatibility Services

**FCC Part 15.247 & Industry Canada RSS-210
Certification Application Report**

Test Lab: Rhein Tech Laboratories, Inc. Tel: 703-689-0368 360 Herndon Parkway Fax: 703-689-2056 Suite 1400 www.rheintech.com Herndon, VA 20170 E-Mail: atcbinfo@rheintech.com		Applicant: TMI-USA, Inc. 11491 Sunset Hills Road; Suite 310 Reston, VA 20190 (USA) Contact: Guillaume Favre guillaume.favre@tmigi.com	
FCC/IC ID	RMK-RECZIGB1/ 10839A-RECZIGB1	Test Report Date	January 31, 2013
Platform	N/A	RTL Work Order #	2013024
Model #	ZIGBEEBASE1	RTL Quote #	QRTL13-024
American National Standard Institute	ANSI C63.4-2003: Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz		
FCC Classification	DTS – Part 15 Digital Transmission System		
FCC Rule Part(s)/ Guidance	FCC Rules Part 15.247: Operation within the bands 920-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz Direct Sequence System November 1, 2012, 558074 D01 DTS Meas Guidance v01		
Industry Canada	RSS-210 Issue 8: Low Power License-Exempt Communications Devices RSS-Gen Issue 3 2010: General Requirements and Information for the Certification of Radio Apparatus		
Digital Interface Information	Digital Interface was found to be compliant		
Frequency Range (MHz)	Output Power (W)	Frequency Tolerance	Emission Designator
2405 – 2475	0.003	N/A	1M68FXD

I, the undersigned, hereby declare that the equipment tested and referenced in this report conforms to the identified standard(s) as described in this test report. No modifications were made to the equipment during testing in order to achieve compliance with these standards. Furthermore, there was no deviation from, additions to, or exclusions from, the applicable parts of FCC Part 2, FCC Part 15, IC RSS-210, IC RSS-Gen and ANSI C63.4.

Signature: 

Date: January 31, 2013

Typed/Printed Name: Desmond A. Fraser

Position: President

This report may not be reproduced, except in full, without the written approval of Rhein Tech Laboratories, Inc. and TMI-USA, Inc. The test results relate only to the item(s) tested.

These tests are accredited and meet the requirements of ISO/IEC 17025 as verified by ANSI-ASQ National Accreditation Board/ACLASS. Refer to certificate and scope of accreditation AT-1445.

Table of Contents

1	General Information	5
1.1	Scope	5
1.2	Description of EUT	5
1.3	Test Facility	5
1.4	Related Submittal(s)/Grant(s)	5
1.5	Modifications	5
2	Test Information	6
2.1	Description of Test Modes	6
2.2	Exercising the EUT	6
2.3	Test Result Summary.....	6
2.4	Test System Details	7
2.5	Configuration of Tested System.....	7
3	Peak Output Power – FCC §15.247(b)(1); RSS-210 §A8.4(4).....	8
3.1	Power Output Test Procedure.....	8
3.2	Power Output Test Data.....	8
4	Compliance with the Band Edge – FCC §15.247(d); RSS-210 §2.2.....	9
4.1	Band Edge Test Procedure.....	9
4.2	Restricted Band Edge Test Results	10
4.2.1	Calculation of Lower Band Edge.....	10
4.2.2	Calculation of Upper Band Edge – 802.11b.....	11
5	Antenna Conducted Spurious Emissions – FCC §15.247(d); RSS-Gen.....	12
5.1	Antenna Conducted Spurious Emissions Test Procedure.....	12
5.2	Antenna Conducted Spurious Emissions Test Results	13
6	Power Spectral Density – FCC §15.247(e); RSS-210 §A8.2	16
6.1	Power Spectral Density Test Procedure	16
6.2	Power Spectral Density Test Data	16
7	Radiated Emissions – FCC §15.209, RSS-210 §A8.5	20
7.1	Limits of Radiated Emissions Measurement.....	20
7.2	Radiated Emissions Measurement Test Procedure.....	20
7.3	Radiated Emissions Harmonics/Spurious Test Data	22
8	AC Conducted Emissions - FCC §15.207; RSS-Gen §7.2.4: Conducted Limits.....	24
8.1	Test Methodology for Conducted Line Emissions Measurements.....	24
8.2	Conducted Line Emission Test Procedure.....	24
8.3	Conducted Line Emissions Test Data	25
9	6 dB Bandwidth – FCC §15.247(a)(2); RSS-210 §A8.2	27
9.1	6 dB Bandwidth Test Procedure – Minimum 6 dB Bandwidth.....	27
9.2	6 dB Modulated Bandwidth Test Data	27
10	Conclusion	31

Figure Index

Figure 2-1: Configuration of System Under Test.....	7
---	---

Table Index

Table 2-1: Channels Tested	6
Table 2-2: Test Result Summary – FCC Part 15, Subpart C (Section 15.247).....	6
Table 2-3: Equipment Under Test	7
Table 3-1: Power Output Test Equipment.....	8
Table 3-2: Power Output Test Data.....	8
Table 4-1: Band Edge Test Equipment	9
Table 5-1: Antenna Conducted Spurious Emissions Test Equipment	12
Table 6-1: Power Spectral Density Test Equipment	16
Table 6-2: Power Spectral Density Test Data – 802.11b	16
Table 7-1: Radiated Emissions Test Equipment	21
Table 7-2: Radiated Emissions Harmonics/Spurious - 2405 MHz – Peak Detector	22
Table 7-3: Radiated Emissions Harmonics/Spurious - 2405 MHz – Average Detector	22
Table 7-4: Radiated Emissions Harmonics/Spurious - 2440 MHz – Peak Detector	22
Table 7-5: Radiated Emissions Harmonics/Spurious - 2440 MHz – Average Detector	22
Table 7-6: Radiated Emissions Harmonics/Spurious - 2475 MHz – Peak Detector	23
Table 7-7: Radiated Emissions Harmonics/Spurious - 2475 MHz – Average Detector	23
Table 8-1: Conducted Line Emissions Test Equipment	24
Table 8-2: Accessory Test Equipment List.....	25
Table 9-1: 6 dB Bandwidth Test Equipment.....	27
Table 9-2: 6 db Bandwidth Test Data – 802.11b.....	27

Plot Index

Plot 4-1: Lower Band Edge - 2405 MHz	10
Plot 4-2: Upper Band Edge - 2475 MHz.....	11
Plot 5-1: Antenna Conducted Spurious Emissions - 2405 MHz.....	13
Plot 5-2: Antenna Conducted Spurious Emissions - 2440 MHz.....	14
Plot 5-3: Antenna Conducted Spurious Emissions - 2475 MHz.....	15
Plot 6-1: Power Spectral Density - 2405 MHz	17
Plot 6-2: Power Spectral Density - 2440 MHz	18
Plot 6-3: Power Spectral Density - 2475 MHz	19
Plot 8-1: Conducted Emissions (Phase Side); Mode: Transmit AC Adapter.....	25
Plot 8-2: Conducted Emissions (Neutral Side); Mode: Transmit AC Adapter	25
Plot 8-3: Conducted Emissions (Phase Side); Mode: Transmit USB Power.....	26
Plot 8-4: Conducted Emissions (Neutral Side); Mode: Transmit USB Power	26
Plot 9-1: 6 dB Bandwidth - 2405 MHz	28
Plot 9-2: 6 dB Bandwidth - 2440 MHz	29
Plot 9-3: 6 dB Bandwidth - 2475 MHz	30

Appendix Index

Appendix A:	FCC Part 1.1307, 1.1310, 2.1091, 2.1093; IC RSS-Gen: RF Exposure.....	32
Appendix B:	Agency Authorization Letter	33
Appendix C:	FCC Confidentiality Request Letter.....	34
Appendix D:	IC Letters	35
Appendix E:	Canadian Based Representative Attestation Letter	36
Appendix F:	IC Confidentiality Request Letter	37
Appendix G:	ID Label and Label Location.....	38
Appendix H:	Technical Operational Description	39
Appendix I:	Schematics.....	40
Appendix J:	Block Diagram.....	41
Appendix K:	Manual.....	42
Appendix L:	Test Photographs	43
Appendix M:	External Photographs.....	49
Appendix N:	Internal Photographs.....	50

Photograph Index

Photograph 1:	Radiated Testing – Front View.....	43
Photograph 2:	Radiated Testing – Rear View	44
Photograph 3:	AC Conducted Testing – Front View – USB Powered.....	45
Photograph 4:	AC Conducted Testing – Rear View – USB Powered.....	46
Photograph 5:	AC Conducted Testing – Front View – AC Adapter.....	47
Photograph 6:	AC Conducted Testing – Rear View – AC Adapter.....	48

1 General Information

1.1 Scope

This is an original certification application request for the TMI-USA, Inc. ZigBeeBase 2.4 GHz, Model # ZIGBEEBASE1.

Applicable Standards:

- FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz.
- Industry Canada RSS-210: Low Power License-Exempt Communications Devices

1.2 Description of EUT

Equipment Under Test	Receiver
Model/Model #	ZigBeeBase 2.4 GHz/ZIGBEEBASE1
Power Supply	5VDC from USB connection or 9VDC or 12VDC 400 mA AC Adapter
Modulation Type	DSSS
Frequency Range	2405 – 2475 MHz
Antenna Connector Type	Reverse polarity SMA
Antenna Type	External Duck

1.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report and approved by the Federal Communications Commission to perform AC line conducted and radiated emissions testing (ANSI C63.4-2003).

1.4 Related Submittal(s)/Grant(s)

This is an original certification application for TMI-USA, Inc., ZigBeeBase 2.4 GHz, Model # ZIGBEEBASE1, FCC ID: RMK-RECZIGB1, IC: 10839A-RECZIGB1.

1.5 Modifications

No modifications were made to the equipment during testing in order to achieve compliance with these standards.

2 Test Information

2.1 Description of Test Modes

In accordance with FCC 15.31(m), and because the EUT utilizes an operating band greater than 10 MHz, the following frequencies were tested:

Table 2-1: Channels Tested

Channel	Frequency
Low (11)	2405
Middle (18)	2440
High (25)	2475

2.2 Exercising the EUT

The EUT was supplied with test firmware programmed with a high, mid, and low channel for testing. The EUT was tested in all three orthogonal planes in order to determine worst-case emissions. The EUT was provided with software to continuously transmit during testing. The carrier was also checked to verify that information was being transmitted.

2.3 Test Result Summary

Table 2-2: Test Result Summary – FCC Part 15, Subpart C (Section 15.247)

Standard	Test	Pass/Fail or N/A
FCC 15.207	AC Power Conducted Emissions	Pass
FCC 15.209	Radiated Emissions	Pass
FCC 15.247(a)(2)	6 dB Bandwidth	Pass
FCC 15.247(b)	Maximum Peak Power Output	Pass
FCC 15.247(d)	Antenna Conducted Spurious Emissions	Pass
FCC 15.247(e)	Power Spectral Density	Pass
FCC 15.247(d)	Band Edge Measurement	Pass

2.4 Test System Details

The test samples were received on January 16, 2013. The FCC identifiers for all applicable equipment, plus descriptions of all cables used in the tested system, are identified in the following table.

Table 2-3: Equipment Under Test

Part	Manufacturer	Model #	Serial Number	FCC ID	Cable Description	RTL Bar Code
Receiver	TMI-USA, Inc.	ZIGBEEBASE1	RZV5NYQC	RMK-RECZIGB1	N/A	20972
AC Adapter	MW	MW7812T-1GS	N/A	N/A	6'unshielded	N/A

2.5 Configuration of Tested System




Figure 2-1: Configuration of System Under Test

3 Peak Output Power – FCC §15.247(b)(1); RSS-210 §A8.4(4)

3.1 Power Output Test Procedure

A conducted power measurement of the EUT was taken using a Rhode & Schwarz FSU Spectrum Analyzer.

Table 3-1: Power Output Test Equipment


RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	1166.1660.50	Spectrum Analyzer	2001006	6/3/13

3.2 Power Output Test Data

Table 3-2: Power Output Test Data

Channel	Frequency (MHz)	Peak Power Conducted Output (dBm)
11	2405	4.2
18	2440	4.0
25	2475	3.7

Test Personnel:

Daniel W. Baltzell Test Engineer	 Signature	January 26-28, 2013 Dates of Test
-------------------------------------	--	--------------------------------------

4 Compliance with the Band Edge – FCC §15.247(d); RSS-210 §2.2

4.1 Band Edge Test Procedure

The transmitter output was connected to its appropriate antenna. Peak and average radiated measurements were taken with a suitable span to encompass the peak of the fundamental. A delta measurement was performed from the highest peak in the restricted band to the peak of the fundamental, and subtracted from the field strength; the result was compared to the limit in the restricted band (54 dBuV/m).

Table 4-1: Band Edge Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	1166.1660.50	Spectrum Analyzer	2001006	6/3/13
900878	Rhein Tech Laboratories	AM3-1197-0005	3 meter antenna mast, polarizing	Outdoor Range 1	Not Required
901242	Rhein Tech Laboratories	WRT-000-0003	Wood rotating table	N/A	Not Required
900772	EMCO	3161-02	Horn Antenna (2-4 GHz)	9804-1044	4/19/14

4.2 Restricted Band Edge Test Results


4.2.1 Calculation of Lower Band Edge

101.9 dBuV/m is the field strength measurement, from which the delta measurement of 56.2 dB is subtracted (reference plots), resulting in a level of 45.7 dBuV/m. This level has a margin of 8.3 dB below the limit of 54 dBuV/m.

Calculation: $101.9 \text{ dBuV/m} - 56.2 \text{ dB} - 54 \text{ dBuV/m} = -8.3 \text{ dB}$

Peak Field Strength of Lower Band Edge (1 MHz RBW/3 MHz VBW, Pk Det.) = 102.1 dBuV/m
 Average Field Strength of Lower Band Edge (1 MHz RBW/3 MHz VBW, Av Det.) = 101.9 dBuV/m
 Delta measurement = 56.2 dB

Plot 4-1: Lower Band Edge - 2405 MHz




4.2.2 Calculation of Upper Band Edge – 802.11b

101.2 dBuV/m is the field strength measurement, from which the delta measurement of 53.3 dB is subtracted (reference plots), resulting in a level of 47.9 dBuV/m. This level has a margin of 6.1 dB below the limit of 54 dBuV/m.


Calculation: $101.2 \text{ dBuV/m} - 53.3 \text{ dB} - 54 \text{ dBuV/m} = -6.1 \text{ dB}$

Peak Field Strength of Upper Band Edge (1 MHz RBW/3 MHz VBW, Pk. Det.) = 102.3 dBuV/m
Average Field Strength of Upper Band Edge (1 MHz RBW/3 MHz VBW, Av Det.) = 101.2 dBuV/m
Delta measurement = 53.3 dB

Plot 4-2: Upper Band Edge - 2475 MHz



Test Personnel:

Daniel W. Baltzell Test Engineer	 Signature	January 26-28, 2013 Dates of Test
-------------------------------------	--	--------------------------------------

5 Antenna Conducted Spurious Emissions – FCC §15.247(d); RSS-Gen

5.1 Antenna Conducted Spurious Emissions Test Procedure


Antenna spurious emissions per FCC 15.247(d) were measured from the EUT antenna port using a 50-ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at 300 kHz. The modulated carrier was identified at the following frequencies: 2405 MHz, 2440 MHz and 2475 MHz.

Table 5-1: Antenna Conducted Spurious Emissions Test Equipment


RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	1166.1660.50	Spectrum Analyzer	2001006	6/3/13

5.2 Antenna Conducted Spurious Emissions Test Results


Plot 5-1: Antenna Conducted Spurious Emissions - 2405 MHz



Plot 5-2: Antenna Conducted Spurious Emissions - 2440 MHz



Plot 5-3: Antenna Conducted Spurious Emissions - 2475 MHz



Test Personnel:

Daniel W. Baltzell
Test Engineer

Daniel W. Baltzell
Signature

January 28-30, 2013
Dates of Test

6 Power Spectral Density – FCC §15.247(e); RSS-210 §A8.2

6.1 Power Spectral Density Test Procedure

The power spectral density per FCC 15.247(e) was measured using a 50-ohm spectrum analyzer with the resolution bandwidth set at 3 kHz, the video bandwidth set at equal to or greater than 10 times the RBW, and the sweep time set at 500 seconds. The spectral lines were resolved for the modulated carriers at 2405 MHz, 2440 MHz, and 2475 MHz respectively. These levels are below the +8 dBm limit. See the power spectral density table and plots.

Table 6-1: Power Spectral Density Test Equipment


RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	1166.1660.50	Spectrum Analyzer	2001006	6/3/13

6.2 Power Spectral Density Test Data


Table 6-2: Power Spectral Density Test Data – 802.11b

Channel	Frequency (MHz)	RF Power Level (dBm)	Maximum Limit +8dBm	Pass/Fail
11	2405	-9.5	8	Pass
18	2440	-10.0	8	Pass
26	2475	-10.4	8	Pass


Plot 6-1: Power Spectral Density - 2405 MHz



Plot 6-2: Power Spectral Density - 2440 MHz



Plot 6-3: Power Spectral Density - 2475 MHz



Test Personnel:

Daniel W. Baltzell
Test Engineer

Signature

January 28, 2013
Date of Test

7 Radiated Emissions – FCC §15.209, RSS-210 §A8.5

7.1 Limits of Radiated Emissions Measurement

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009-0.490	2400/f (kHz)	300
0.490-1.705	2400/f (kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any circumstances of modulation.

7.2 Radiated Emissions Measurement Test Procedure

Before final measurements of radiated emissions were made on the open-field three/ten meter range, the EUT was scanned indoors at one and three meter distances. This was done in order to determine its emissions spectrum signature. The physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. This process was repeated during final radiated emissions measurements on the open-field range, at each frequency, in order to ensure that maximum emission amplitudes were attained.

Final radiated emissions measurements were made on the three/ten-meter, open-field test site. The EUT was placed on a nonconductive turntable 0.8 meters above the ground plane. The spectrum was examined from 9 kHz to the 10th harmonic of the highest fundamental transmitter frequency (24.8 GHz).

At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the emission's maximum level. Measurements were taken using both horizontal and vertical antenna polarizations. For frequencies between 30 and 1000 MHz, the spectrum analyzer's 6 dB bandwidth was set to 120 kHz, and the analyzer was operated in the CISPR quasi-peak detection mode. For emissions above 1000 MHz, emissions are measured using the average detector function with a minimum resolution bandwidth of 1 MHz. No video filter less than 10 times the resolution bandwidth was used. The highest emission amplitudes relative to the appropriate limit were measured and recorded in this report.

Table 7-1: Radiated Emissions Test Equipment

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
900932	Hewlett Packard	8449B OPT H02	Preamplifier (1-26.5 GHz)z	3008A00505	7/14/13
900772	EMCO	3161-02	Horn Antenna (2-4 GHz)	9804-1044	4/19/14
900321	EMCO	3161-03	Horn Antenna (4.0-8.2 GHz)	9508-1020	4/19/14
900323	EMCO	3160-07	Horn Antenna (8.2-12.4 GHz)	9605-1054	4/19/14
900356	EMCO	3160-08	Horn Antenna (12.4-18 GHz)	9607-1044	4/19/14
900325	EMCO	3160-9	Horn Antenna (18-26.5 GHz)	9605-1051	4/19/14
900151	Rohde and Schwarz	HFH2-Z2	Loop Antenna (9 kHz-30 MHz)	827525/019	10/1/13
901595	Mini-Circuits	ZHL-4240V	Amplifier	H090293-5	2/17/13
900878	Rhein Tech Laboratories	AM3-1197-0005	3 meter antenna mast, polarizing	Outdoor Range 1	Not Required
901242	Rhein Tech Laboratories	WRT-000-0003	Wood rotating table	N/A	Not Required
901581	Rohde & Schwarz	1166.1660.50	Spectrum Analyzer	2001006	6/3/13
900791	Chase	CBL6111B	Bilog Antenna (30 MHz-2000 MHz)	N/A	1/31/13
901592	Insulated Wire Inc.	KPS-1503-3600-KPR	SMK RF Cables 20'	NA	8/16/13
901593	Insulated Wire Inc.	KPS-1503-360-KPR	SMK RF Cables 36"	NA	8/16/13

7.3 Radiated Emissions Harmonics/Spurious Test Data

Table 7-2: Radiated Emissions Harmonics/Spurious - 2405 MHz – Peak Detector

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV/m) (1 MHz RBW/VBW)	Site Correction Factor (dB/m)	Peak Corrected (dBuV/m)	Peak Limit (dBuV/m)	Peak Margin (dB)
4810.0	53.8	-5.0	48.8	74.0	-25.2
12025.0	27.6	2.7	30.3	74.0	-43.7
19240.0	24.5	12.2	36.7	74.0	-37.3

Table 7-3: Radiated Emissions Harmonics/Spurious - 2405 MHz – Average Detector

Emission Frequency (MHz)	Average Analyzer Reading (dBuV/m) (1 MHz RBW/VBW)	Site Correction Factor (dB/m)	Average Corrected (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4810.0	50.7	-5.0	45.7	54.0	-8.3
12025.0	20.1	2.7	22.8	54.0	-31.2
19240.0	16.5	12.2	28.7	54.0	-25.3

Table 7-4: Radiated Emissions Harmonics/Spurious - 2440 MHz – Peak Detector

Emission Frequency (MHz)	Peak Analyzer Reading (dBuV/m) (1 MHz RBW/VBW)	Site Correction Factor (dB/m)	Peak Corrected (dBuV/m)	Peak Limit (dBuV/m)	Peak Margin (dB)
4880.0	51.9	-5.0	46.9	74.0	-27.1
7320.0	47.6	-3.1	44.5	74.0	-29.5
12200.0	38.8	3.4	42.2	74.0	-31.8
19520.0	24.5	11.6	36.1	74.0	-37.9

Table 7-5: Radiated Emissions Harmonics/Spurious - 2440 MHz – Average Detector

Emission Frequency (MHz)	Average Analyzer Reading (dBuV/m) (1 MHz RBW/VBW)	Site Correction Factor (dB/m)	Average Corrected (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4880.0	47.6	-5.0	42.6	54.0	-11.4
7320.0	40.9	-3.1	37.8	54.0	-16.2
12200.0	35.0	3.4	38.4	54.0	-15.6
19520.0	16.8	11.6	28.4	54.0	-25.6

Table 7-6: Radiated Emissions Harmonics/Spurious - 2475 MHz – Peak Detector


Emission Frequency (MHz)	Peak Analyzer Reading (dBuV/m) (1 MHz RBW/VBW)	Site Correction Factor (dB/m)	Peak Corrected (dBuV/m)	Peak Limit (dBuV/m)	Peak Margin (dB)
4950.0	54.1	-5.8	48.3	74.0	-25.7
7425.0	44.3	-3.5	40.8	74.0	-33.2
12375.0	30.3	3.1	33.4	74.0	-40.6
19800.0	35.0	11.4	46.4	74.0	-27.6
22275.0	35.1	12.7	47.8	74.0	-26.2

Table 7-7: Radiated Emissions Harmonics/Spurious - 2475 MHz – Average Detector

Emission Frequency (MHz)	Average Analyzer Reading (dBuV/m) (1 MHz RBW/VBW)	Site Correction Factor (dB/m)	Average Corrected (dBuV/m)	Average Limit (dBuV/m)	Average Margin (dB)
4950.0	47.7	-5.8	41.9	54.0	-12.1
7425.0	39.0	-3.5	35.5	54.0	-18.5
12375.0	23.6	3.1	26.7	54.0	-27.3
19800.0	24.5	11.4	35.9	54.0	-18.1
22275.0	23.7	12.7	36.4	54.0	-17.6

Test Personnel:

Daniel W. Baltzell
 Test Engineer



Signature

January 26-28, 2013
 Dates of Test

8 AC Conducted Emissions - FCC §15.207; RSS-Gen §7.2.4: Conducted Limits

8.1 Test Methodology for Conducted Line Emissions Measurements

The power line conducted emission measurements were performed in a Series 81 type shielded enclosure manufactured by Rayproof. The EUT was assembled on a wooden table 80 centimeters high. Power was fed to the EUT through a 50 ohm / 50 microhenry Line Impedance Stabilization Network (EUT LISN). The EUT LISN was fed power through an A.C. filter box on the outside of the shielded enclosure. The filter box and EUT LISN housing are bonded to the ground plane of the shielded enclosure. A second LISN, the peripheral LISN, provides isolation for the EUT test peripherals. This peripheral LISN was also fed A.C. power. A metal power outlet box, which is bonded to the ground plane and electrically connected to the peripheral LISN, powers the EUT host peripherals.

The spectrum analyzer was connected to the A.C. line through an isolation transformer. The 50-ohm output of the EUT LISN was connected to the spectrum analyzer input through a Solar high-pass filter. The filter is used to prevent overload of the spectrum analyzer from noise below 100 kHz. Conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode if applicable). The analyzer's 6 dB bandwidth was set to 9 kHz. No video filter less than 10 times the resolution bandwidth was used. Average measurements are performed in linear mode using a 10 kHz resolution bandwidth, a 1 Hz video bandwidth, and by increasing the sweep time in order to obtain a calibrated measurement. The emission spectrum was scanned from 150 kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in this report.

8.2 Conducted Line Emission Test Procedure

The conducted test was performed with the EUT exercise program loaded, and the emissions were scanned between 150 kHz to 30 MHz on the NEUTRAL SIDE and PHASE SIDE.

Table 8-1: Conducted Line Emissions Test Equipment


RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901083	AFJ international	LS16	16A LISN	16010020080	4/18/13
900968	Hewlett Packard	8567A	Spectrum Analyzer (10 kHz-1.5 GHz)	2602A00160	2/7/14
900339	Hewlett Packard	85650A	Quasi-Peak Adapter (30 Hz-1 GHz)	2521A00743	2/7/14
900970	Hewlett Packard	85662A	Spectrum Analyzer Display	2542A11239	2/7/14

Table 8-2: Accessory Test Equipment List


Manufacturer	Model	Part Type	Serial Number	Cable Type
Westell, Inc.	B90-36R515-01	DSL Modem (used as termination device)	00BH05367678	Unshielded RJ-11 (6'), RJ-45 (7')
Sony	VPCEB23FM	Laptop	27524532 3D42604	N/A
Sony	VGP-AC19V48	AC Adapter	1489078110477658	Unshielded 14'

8.3 Conducted Line Emissions Test Data


Plot 8-1: Conducted Emissions (Phase Side); Mode: Transmit AC Adapter




Plot 8-2: Conducted Emissions (Neutral Side); Mode: Transmit AC Adapter



Plot 8-3: Conducted Emissions (Phase Side); Mode: Transmit USB Power



Plot 8-4: Conducted Emissions (Neutral Side); Mode: Transmit USB Power



Test Personnel:

Dan Baltzell
 Test Engineer

Signature

January 30, 2013
 Date of Test

9 6 dB Bandwidth – FCC §15.247(a)(2); RSS-210 §A8.2

9.1 6 db Bandwidth Test Procedure – Minimum 6 dB Bandwidth

The minimum 6 dB bandwidths per FCC 15.247(a)(2) were measured using a 50-ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at 300 kHz. The device was modulated. The minimum 6 dB bandwidths are presented below.

Table 9-1: 6 dB Bandwidth Test Equipment


RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	1166.1660.50	Spectrum Analyzer	2001006	6/3/13

9.2 6 dB Modulated Bandwidth Test Data


Table 9-2: 6 db Bandwidth Test Data – 802.11b

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass/Fail
11	2405	1.68	500	Pass
18	2440	1.64	500	Pass
25	2475	1.66	500	Pass


Plot 9-1: 6 dB Bandwidth - 2405 MHz



Plot 9-2: 6 dB Bandwidth - 2440 MHz



Plot 9-3: 6 dB Bandwidth - 2475 MHz



Test Personnel:

Daniel W. Baltzell
 Test Engineer

Signature

January 26-28, 2013
 Dates of Test

10 Conclusion

The data in this measurement report shows that the EUT as tested, TMI-USA, Inc. ZigBeeBase 2.4 GHz, Model # ZIGBEEBASE1, FCC ID: RMK-RECZIGB1, IC: 10839A-RECZIGB1, complies with all the applicable requirements of Parts 2 and 15 of the FCC Rules and Regulations, and IC RSS-210 and RSS-Gen.