

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

17.4 TEST DATA


Below 1GHz

[TestMode: TX]; [Polarity: Horizontal]



Test Result: Pass

[TestMode: TX]; [Polarity: Vertical]



Site
Limit: FCC Part15 Class B
EUT: Loudbox
M/N: Mini Charge
Mode: TX mode
Note:

Polarization: **Vertical**
Power:


Temperature: (C)
Humidity: %RH

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	33.2112	0.32	22.78	23.10	40.00	-16.90	QP	P	
2	50.2324	2.56	23.15	25.71	40.00	-14.29	QP	P	
3	160.3456	6.30	23.17	29.47	43.50	-14.03	QP	P	
4	246.8149	1.43	21.36	22.79	46.00	-23.21	QP	P	
5	490.7447	2.76	27.93	30.69	46.00	-15.31	QP	P	
6 *	818.8341	1.55	33.91	35.46	46.00	-10.54	QP	P	

Test Result: Pass

Above 1GHz

[TestMode: TX lowest channel]; [Polarity: Horizontal]




Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Loudbox		
M/N: Mini Charge		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over					
							MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4807.000	42.58	4.07	46.65	74.00	-27.35				peak	
2		7326.000	37.83	8.21	46.04	74.00	-27.96				peak	
3		8907.750	39.71	9.31	49.02	74.00	-24.98				peak	
4		9648.000	37.63	11.01	48.64	74.00	-25.36				peak	
5	*	11293.000	39.35	13.58	52.93	74.00	-21.07				peak	

Test Result: Pass

[TestMode:TX lowest channel]; [Polarity: Vertical]




Site	Polarization: Vertical	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Loudbox		
M/N: Mini Charge		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB/m	dBuV/m	dB	Detector
1		4807.000	44.45	4.07	48.52	74.00	-25.48			peak	
2		6040.750	43.45	4.07	47.52	74.00	-26.48			peak	
3		7326.000	38.61	8.21	46.82	74.00	-27.18			peak	
4		8261.500	40.81	9.02	49.83	74.00	-24.17			peak	
5		9648.000	38.71	11.01	49.72	74.00	-24.28			peak	
6	*	11316.500	39.71	13.59	53.30	74.00	-20.70			peak	

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]




Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Loudbox		
M/N: Mini Charge		
Mode: TX-M		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over					
							MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4874.000	42.14	4.32	46.46	74.00	-27.54				peak	
2		5829.250	39.99	6.78	46.77	74.00	-27.23				peak	
3		7311.000	38.40	8.18	46.58	74.00	-27.42				peak	
4		8026.500	41.41	8.91	50.32	74.00	-23.68				peak	
5		9748.000	37.62	11.26	48.88	74.00	-25.12				peak	
6	*	11798.250	38.97	13.81	52.78	74.00	-21.22				peak	

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Vertical]




Site	Polarization: Vertical	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Loudbox		
M/N: Mini Charge		
Mode: TX-M		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB/m	dBuV/m	dB	Detector
1		4877.500	45.56	4.35	49.91	74.00	-24.09			peak	
2		5876.250	39.72	6.81	46.53	74.00	-27.47			peak	
3		7311.000	38.12	8.18	46.30	74.00	-27.70			peak	
4		8672.750	39.75	9.21	48.96	74.00	-25.04			peak	
5		9748.000	38.03	11.26	49.29	74.00	-24.71			peak	
6	*	11751.250	38.57	13.79	52.36	74.00	-21.64			peak	

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Horizontal]




Site	Polarization: <i>Horizontal</i>	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Loudbox		
M/N: Mini Charge		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB/m	dBuV/m	dB	Detector
1		4090.250	42.50	2.63	45.13	74.00	-28.87			peak	
2		4959.750	43.25	5.42	48.67	74.00	-25.33			peak	
3		7386.000	38.88	8.36	47.24	74.00	-26.76			peak	
4		7709.250	43.12	8.74	51.86	74.00	-22.14			peak	
5		9848.000	36.39	11.52	47.91	74.00	-26.09			peak	
6	*	11387.000	38.89	13.63	52.52	74.00	-21.48			peak	

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Vertical]



Site	Polarization: Vertical	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Loudbox		
M/N: Mini Charge		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB/m	dBuV/m	dB	Detector
1		4959.750	44.51	5.42	49.93	74.00	-24.07			peak	
2		6005.500	42.27	3.92	46.19	74.00	-27.81			peak	
3		7386.000	38.41	8.36	46.77	74.00	-27.23			peak	
4		8473.000	39.11	9.12	48.23	74.00	-25.77			peak	
5		9848.000	36.70	11.52	48.22	74.00	-25.78			peak	
6	*	11833.500	38.69	13.82	52.51	74.00	-21.49			peak	

Test Result: Pass

18 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25 °C
Humidity	60%

18.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

18.2 BLOCK DIAGRAM OF TEST SETUP



18.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

18.4 TEST DATA

[TestMode: TX lowest channel]; [Polarity: Horizontal]




Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Loudbox
M/N: Mini Charge
Mode: TX-L
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over					
							MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		2310.000	43.03	-4.27	38.76	74.00	-35.24		peak			
2	*	2390.000	48.23	-3.82	44.41	74.00	-29.59		peak			

Test Result: Pass

[TestMode: TX lowest channel]; [Polarity: Vertical]




Site	Polarization: <i>Vertical</i>	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Loudbox		
M/N: Mini Charge		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB/m	dBuV/m	dB	Detector
1		2310.000	44.28	-4.27	40.01	74.00	-33.99	peak			
2	*	2390.000	47.50	-3.82	43.68	74.00	-30.32	peak			

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Horizontal]




Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Loudbox		
M/N: Mini Charge		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over					
							MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	2483.500	43.47	-3.96	39.51	74.00	-34.49	peak				
2		2500.000	43.14	-4.00	39.14	74.00	-34.86	peak				

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Loudbox
M/N: Mini Charge
Mode: TX-H
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment		Limit	Over	
					dB/m	dBuV/m		dB	Detector
1	*	2483.500	43.69	-3.96	39.73	74.00	-34.27	peak	
2		2500.000	43.32	-4.00	39.32	74.00	-34.68	peak	

Test Result: Pass

19 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


19.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2dBi.




20 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25 °C
Humidity	60%

20.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

20.2 BLOCK DIAGRAM OF TEST SETUP



20.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


21 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25 °C
Humidity	60%

21.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

21.2 BLOCK DIAGRAM OF TEST SETUP



21.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


22 APPENDIX

Appendix1


22.1 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	Ant1	1.256	21	Pass
NVNT	1-DH1	2441	Ant1	0.764	21	Pass
NVNT	1-DH1	2480	Ant1	0.236	21	Pass
NVNT	2-DH1	2402	Ant1	3.317	21	Pass
NVNT	2-DH1	2441	Ant1	2.892	21	Pass
NVNT	2-DH1	2480	Ant1	2.361	21	Pass
NVNT	3-DH1	2402	Ant1	3.862	21	Pass
NVNT	3-DH1	2441	Ant1	3.348	21	Pass
NVNT	3-DH1	2480	Ant1	2.963	21	Pass


Power NVNT 1-DH1 2402MHz Ant1




Power NVNT 1-DH1 2441MHz Ant1




Power NVNT 1-DH1 2480MHz Ant1




Power NVNT 2-DH1 2402MHz Ant1




Power NVNT 2-DH1 2441MHz Ant1



Power NVNT 2-DH1 2480MHz Ant1



Power NVNT 3-DH1 2402MHz Ant1



Power NVNT 3-DH1 2441MHz Ant1