

849 NW STATE ROAD 45  
NEWBERRY, FL 32669 USA

PHONE: 888.472.2424 OR 352.472.5500

EMAIL: [INFO@TIMCOENGR.COM](mailto:INFO@TIMCOENGR.COM)

WEB: [HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)



# RF Exposure Evaluation Report

APPLICANT	NiCOM USA, INC
ADDRESS	1690 CACTUS ROAD SAN DIEGO CA. 92154 USA
FCC ID	RMYTSL910
MODEL NUMBER	Tsl910
PRODUCT DESCRIPTION	FM BROADCAST TRANSMITTER
DATE SAMPLE RECEIVED	12/31/2018
FINAL TEST DATE	1/14/2018
PREPARED BY	Tim Royer
TEST RESULTS	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

Report Number	Report Version	Description	Issue Date
2249UT18 MPE_TestReport_	Rev1	Initial Issue	10/15/2019

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT THE  
WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**

## TABLE OF CONTENTS

<b>GENERAL REMARKS .....</b>	<b>2</b>
<b>GENERAL INFORMATION .....</b>	<b>3</b>
<b>ANTENNA INFORMATION .....</b>	<b>3</b>
<b>MPE CALCULATION .....</b>	<b>3</b>
<b>MPE TABLE .....</b>	<b>5</b>
<b>GENERAL UNCONTROLLED EXPOSURE .....</b>	<b>5</b>
<b>GENERAL CONTROLLED EXPOSURE .....</b>	<b>6</b>

## GENERAL REMARKS

### Summary

The device under test does:

- Fulfill the general approval requirements as identified in this test report and was selected by the customer.
- Not fulfill the general approval requirements as identified in this test report

### Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.

I attest that the necessary measurements were made at:

**Timco Engineering Inc.**  
**849 NW State Road 45**  
**Newberry, FL 32669**  
**Designation #: US1070**

### Prepared by:



<b>Name and Title</b>	Tim Royer, Project Manager / EMC Testing Engineer
<b>Date</b>	10/15/2019

## GENERAL INFORMATION

<b>EUT Description</b>	FM BROADCAST TRANSMITTER		
<b>Model Number</b>	Tsl910		
<b>EUT Power Source</b>	<input checked="" type="checkbox"/> 110–120Vac, 50–60Hz	<input type="checkbox"/> DC Power	<input type="checkbox"/> Battery Operated
<b>Test Item</b>	<input type="checkbox"/> Engineering Prototype	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Production
<b>Type of Equipment</b>	<input checked="" type="checkbox"/> Fixed	<input type="checkbox"/> Mobile	<input type="checkbox"/> Portable
<b>Antenna Connector</b>	external N Type		
<b>Test Conditions</b>	The temperature was 26°C Relative humidity of 50%.		
<b>Modification to the EUT</b>	No Modification to EUT.		
<b>Applicable Standards</b>	FCC CFR 47 Part 2.1091		
<b>Test Facility</b>	Timco Engineering Inc. at 849 NW State Road 45 Newberry, FL 32669 USA. Designation #: US1070		

## ANTENNA INFORMATION

Manufacturer Provides Antenna	Type	Max Gain (dBi)
No	Unspecified	0 dBi

## POWER OUTPUT OF EUT

Frequency (MHz)	Rated Output Power (W)
950.4	20

## MPE CALCULATION

The minimum separation distance is calculated as follows:


$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

## MPE LIMITS

*Figure 1. FCC Limits for Maximum Permissible Exposure (MPE)*

*Plane-wave Equivalent Power Density*




## MPE Table

### General Uncontrolled Exposure

The limit for General Uncontrolled Exposure Environment is calculated as shown in FCC Pt. 1.1310, Table B:

Variable	Value
Max Power	20 W
Frequency Range	944 - 952 MHz
Duty Cycle (at full power)	100%
Max Antenna Gain	0 dB
Coax Loss	0 dB
Power Density	0.6336 mW/cm <sup>2</sup>
Minimum Separation Distance	50.12 cm



## General Controlled Exposure

The limit for General Controlled Exposure Environment is calculated as shown in FCC Pt. 1.1310, Table A:

Variable	Value
Max Power	20 W
Frequency Range	944 - 952 MHz
Duty Cycle (at full power)	100%
Max Antenna Gain	0 dBi
Coax Loss	0 dB
Power Density	3.168 mW/cm <sup>2</sup>
Minimum Separation Distance	22.41 cm

