

FCC Radio TEST Report

FCC ID: RNE75110R

This report concerns (check one) : Original Grant Class I Change

Issued Date : Jun. 25, 2008

Project No. : 0805C078

Equipment : Full Weather Station

Model Name : 75110 RHT

Applicant : Chaney Instrument Co.

Address : Rm 1102-3, Enterprise Square One, Tower
3, No.9, Sheung Yuet Road, Kowloon
Bay, Kowloon, Hong Kong, China

Tested by:

Neutron Engineering Inc. EMC Laboratory

Date of Test:

May. 14, 2008 ~ Jun. 24, 2008

Testing Engineer : Tendy Huang
(Tendy Huang)

Technical Manager : Vic Chiu
(Vic Chiu)

Authorized Signatory : Steven Lu
(Steven Lu)

NEUTRON ENGINEERING INC.

No. 132-1, Lane 329, Sec. 2, Palain Rd.,
Shijr City, Taipei, Taiwan
TEL : (02) 2646-5426 FAX : (02) 2646-6815



Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

| Table of Contents | Page |
|--|-------------|
| 1 . CERTIFICATION | 5 |
| 2 . SUMMARY OF TEST RESULTS | 6 |
| 2.1 TEST FACILITY | 7 |
| 2.2 MEASUREMENT UNCERTAINTY | 7 |
| 3 . GENERAL INFORMATION | 8 |
| 3.1 GENERAL DESCRIPTION OF EUT | 8 |
| 3.2 DESCRIPTION OF TEST MODES | 9 |
| 3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 10 |
| 3.4 DESCRIPTION OF SUPPORT UNITS | 11 |
| 4 . EMC EMISSION TEST | 12 |
| 4.1 CONDUCTED EMISSION MEASUREMENT | 12 |
| 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS | 12 |
| 4.1.2 MEASUREMENT INSTRUMENTS LIST | 12 |
| 4.1.3 TEST PROCEDURE | 13 |
| 4.1.4 DEVIATION FROM TEST STANDARD | 13 |
| 4.1.5 TEST SETUP | 13 |
| 4.1.6 EUT OPERATING CONDITIONS | 13 |
| 4.1.7 TEST RESULTS | 14 |
| 4.2 RADIATED EMISSION MEASUREMENT | 15 |
| 4.2.1. FIELD STRENGTH OF FUNDAMENTAL EMISSIONS MEASUREMENT LIMIT | 15 |
| 4.2.2. MEASURING INSTRUMENTS AND SETTING (FIELD STRENGTH OF FUNDAMENTAL EMISSIONS) | 15 |
| 4.2.3 RADIATED EMISSIONS MEASUREMENT | 16 |
| 4.2.4. DWELL TIME OF PERIODIC OPERATION MEASUREMENT | 18 |
| 4.2.5. MEASUREMENT INSTRUMENTS LIST | 20 |
| 4.2.6. TEST PROCEDURE | 20 |
| 4.2.7. DEVIATION FROM TEST STANDARD | 20 |
| 4.2.8. TEST SETUP | 21 |
| 4.2.9. EUT OPERATING CONDITIONS | 21 |
| 4.3. TEST RESULTS (BETWEEN 30 – 1000 MHz) | 22 |
| 4.4 TEST RESULTS (ABOVE 1000 MHz) | 26 |
| 5. 20dB SPECTRUM BANDWIDTH MEASUREMENT | 30 |
| 5.1.MEASURING INSTRUMENTS AND SETTING | 30 |
| 5.2.TEST PROCEDURES | 30 |
| 5.3. TEST SETUP LAYOUT | 30 |

| Table of Contents | Page |
|--|-------------|
| 5.4. TEST DEVIATION | 30 |
| 5.5. EUT OPERATION DURING TEST | 30 |
| 5.6. TEST RESULT | 31 |
| 6. TIMING TESTING | 32 |
| 6.1. MEASURING INSTRUMENTS AND SETTING | 32 |
| 6.2. TEST PROCEDURES | 32 |
| 6.3. TEST SETUP LAYOUT | 32 |
| 6.4. TEST DEVIATION | 32 |
| 6.5. EUT OPERATION DURING TEST | 32 |
| 6.6. TEST RESULT | 33 |
| 7. EUT TEST PHOTO | 34 |

1. CERTIFICATION

Equipment: Full Weather Station
Trade Name : ACURITE
Model Name.: 75110 RHT
Applicant: Chaney Instrument Co.
Date of Test: May. 14, 2008 ~ Jun. 24, 2008
Test Item: ENGINEERING SAMPLE
Standards: FCC Part15, Subpart C(15.231)/ ANCI C63.4 : 2003

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-0805C078) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15, Subpart C (15.231) | | | |
|--------------------------------|-------------------------------------|----------|---------|
| Standard Section | Test Item | Judgment | Remark |
| 15.207 | Conducted Emission | - | Note(1) |
| 15.209 & 15.231(e) | Radiated Spurious Emission | PASS | |
| 15.231(c) | 20dB Occupied Bandwidth Measurement | PASS | |

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **C01/OS02** at the location of No.132-1, Lane 329, Sec. 2, Palain Road, Shijr City, Taipei, Taiwan.
Neutron's test firm number is 95335

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95 %**.

A. Conducted Measurement :

| Test Site | Method | Measurement Frequency Range | U , (dB) | NOTE |
|-----------|--------|-----------------------------|----------|------|
| C01 | ANSI | 150 KHz ~ 30MHz | 1.94 | |

B. Radiated Measurement :

| Test Site | Method | Measurement Frequency Range | Ant. H / V | U , (dB) | NOTE |
|-----------|--------|-----------------------------|------------|----------|------|
| OS-01 | ANSI | 30MHz ~ 200MHz | V | 3.82 | |
| | | 30MHz ~ 200MHz | H | 3.60 | |
| | | 200MHz ~ 1,000MHz | V | 3.86 | |
| | | 200MHz ~ 1,000MHz | H | 3.94 | |
| OS-02 | ANSI | 30MHz ~ 200MHz | V | 2.48 | |
| | | 30MHz ~ 200MHz | H | 2.16 | |
| | | 200MHz ~ 1,000MHz | V | 2.50 | |
| | | 200MHz ~ 1,000MHz | H | 2.66 | |

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | | |
|--|---|--------------------------------|
| Equipment | Full Weather Station | |
| Trade Name | ACURITE | |
| Model Name. | 75110 RHT | |
| OEM Brand/Model Name | N/A | |
| Model Difference | N/A | |
| Product Description | The EUT is a Full Weather Station. | |
| | Product Type | Low Power Communication Device |
| | Operation Frequency: | 433.92 MHz |
| | Modulation Type: | OOK(ASK) |
| | Number Of Channel | 1CH |
| | Antenna Designation: | Printed antenna |
| | Output Power: | 71.04 dBuV/m (AV Max.) |
| Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual. | | |
| Channel List | Please refer to the Note 2. | |
| Power Source | DC Voltage supplied from 2*AA size Battery(TX Sample) | |
| Power Rating | DC 3.0V (TX Sample) | |
| Connecting I/O Port(s) | Please refer to the User's Manual | |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

- 2.

| Frequency Band | Channel No. | Frequency |
|----------------|-------------|------------|
| | 1 | 433.92 MHz |

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description |
|--------------|-----------------|
| Mode 1 | TX CH 433.92MHz |


| For Conducted Test | |
|--------------------|---|
| Final Test Mode | Description |
| | " N/A" denotes test is not applicable in this Test Report |

| For Radiated Test | |
|-------------------|-----------------|
| Final Test Mode | Description |
| Mode 1 | TX CH 433.92MHz |

Note:

- (1) The test sample used the new battery

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | FCC ID | Series No. | Note |
|------|----------------------|-----------|----------------|-----------|------------|------|
| E-1 | Full Weather Station | ACURITE | 75110 RHT | RNE75110R | N/A | EUT |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|--------|------|
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

| FREQUENCY (MHz) | Class A (dBuV) | | Class B (dBuV) | | Standard |
|-----------------|----------------|---------|----------------|-----------|----------|
| | Quasi-peak | Average | Quasi-peak | Average | |
| 0.15 -0.5 | 79.00 | 66.00 | 66 - 56 * | 56 - 46 * | CISPR |
| 0.50 -5.0 | 73.00 | 60.00 | 56.00 | 46.00 | CISPR |
| 5.0 -30.0 | 73.00 | 60.00 | 60.00 | 50.00 | CISPR |

| | | | | | |
|-----------|-------|-------|-----------|-----------|-----|
| 0.15 -0.5 | 79.00 | 66.00 | 66 - 56 * | 56 - 46 * | FCC |
| 0.50 -5.0 | 73.00 | 60.00 | 56.00 | 46.00 | FCC |
| 5.0 -30.0 | 73.00 | 60.00 | 60.00 | 50.00 | FCC |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 MEASUREMENT INSTRUMENTS LIST

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|-----------------|----------|------------|------------------|
| 1 | LISN | EMCO | 3816/2 | 00042991 | Jan. 24, 2009 |
| 2 | LISN | EMCO | 3816/2 | 00042990 | Jan. 24, 2009 |
| 3 | Pulse Limiter | Electro-Metrics | EM-7600 | 112644 | Nov. 27, 2008 |
| 4 | 50Ω Terminator | N/A | N/A | N/A | May.13, 2009 |
| 5 | Test Cable | N/A | C01 | N/A | Nov. 27, 2008 |
| 6 | EMI Test Receiver | R&S | ESCI | 100082 | Mar. 07, 2009 |

Remark: " N/A" denotes No Model Name. , Serial No. or No Calibration specified.

The following table is the setting of the receiver

| Receiver Parameters | Setting |
|---------------------|----------|
| Attenuation | 10 dB |
| Start Frequency | 0.15 MHz |
| Stop Frequency | 30 MHz |
| IF Bandwidth | 9 kHz |


4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.7 TEST RESULTS

| | | | |
|---------------|---|---------------------|-----------|
| EUT : | Full Weather Station | Model Name. : | 75110 RHT |
| Temperature : | 26 °C | Relative Humidity : | 58 % |
| Pressure : | 1010 hPa | Test Power : | DC 3.0V |
| Test Mode : | " N/A" denotes test is not applicable in this Test Report | | |

Remark

- (1) All readings are QP Mode value unless otherwise stated AVG in column of Note. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a " * " marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.
- (3) " N/A" denotes test is not applicable in this Test Report

4.2 RADIATED EMISSION MEASUREMENT

4.2.1. FIELD STRENGTH OF FUNDAMENTAL EMISSIONS MEASUREMENT LIMIT

| Frequency Band (MHz) | Fundamental Emissions Limit (uV/m) at 3m |
|----------------------|--|
| 40.66-40.70 | 1000 |
| 70-130 | 500 |
| 130-174 | 500-1500(**) |
| 174-260 | 1500 |
| 260-470 | 1500-5000(**) |
| Above 470 | 5000 |

**1. Linear interpolations, the formulas for calculating the maximum permitted fundamental field strengths are as follows:

- (1) for the band 130 - 174 MHz, $\mu\text{V/m}$ at 3 meters = $22.72727 \times (\text{operating frequency, MHz}) - 2454.545$;
- (2) for the band 260 - 470 MHz, $\mu\text{V/m}$ at 3 meters = $16.6667 \times (\text{operating frequency, MHz}) - 2833.3333$.

So the field strength of emission limits have been calculated in below table.

| Carrier Frequency (MHz) | Fundamental Emissions Limit (dBuV/m) at 3m |
|-------------------------|--|
| 433.92 MHz | 72.87 (Average) |
| 433.92 MHz | 92.87 (Peak) |

4.2.2. MEASURING INSTRUMENTS AND SETTING (FIELD STRENGTH OF FUNDAMENTAL EMISSIONS)

| Receiver Parameter | Setting |
|--------------------|-----------------------|
| Attenuation | Auto |
| Center Frequency | Fundamental Frequency |
| RBW | 120 kHz |
| Detector | Peak / Average |

4.2.3 RADIATED EMISSIONS MEASUREMENT

Devices complying with 47 CFR FCC part 15 subpart C, section 15.231(e). The field strength of emissions from intentional radiators at 3 meters operated under this Section shall not exceed the following:

| Frequency Band (MHz) | Spurious Emissions Limit (uV/m) at 3m |
|----------------------|---------------------------------------|
| 40.66-40.70 | 100 |
| 70-130 | 50 |
| 130-174 | 50-150(**) |
| 174-260 | 150 |
| 260-470 | 150-500(**) |
| Above 470 | 500 |

**1. Linear interpolations, the formulas for calculating the maximum permitted fundamental field strengths are as follows:

(1) for the band 130 - 174 MHz, $\mu\text{V/m}$ at 3 meters = $22.72727 \times (\text{operating frequency, MHz}) - 2454.545$;

(2) for the band 260 - 470 MHz, $\mu\text{V/m}$ at 3 meters = $16.6667 \times (\text{operating frequency, MHz}) - 2833.3333$.

(3) The maximum permitted unwanted emissions level is 20 dB below the maximum permitted fundamental level. In addition field strength of any emissions which appear inside of the restriction band shall not exceed the general radiated emissions limits in Section 15.209(a).

| Frequencies (MHz) | Field Strength (microrvolts/meter) | Measurement Distance (meters) |
|-------------------|------------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

| Receiver Parameter | Setting |
|------------------------|----------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |

| Spectrum Parameter | Setting |
|---------------------------------------|---|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10th carrier harmonic |
| RB / VB (emission in restricted band) | 1MHz / 1MHz for Peak, AV Mode with Dwell time |
| RB / VB (other emission) | 100KHz / 100KHz for peak |

Dwell time=ON/ON+OFF

ON:(0.36ms*24)+(0.54ms*34)+ (0.81ms*4)



ON+OFF:(total time):99.72ms



Dwell time:30.32%

AV=PK+20 log(Dwell time)

AV=PK-10.36

4.2.4. DWELL TIME OF PERIODIC OPERATION MEASUREMENT





4.2.5. MEASUREMENT INSTRUMENTS LIST

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------------|------------------|--------------|------------|------------------|
| 1 | Log-Bicon Antenna | Schwarzbeck | VULB 9160 | 3058 | Nov. 27, 2008 |
| 2 | Test Cable | N/A | 10M_OS02 | N/A | Nov. 27, 2008 |
| 3 | Test Cable | N/A | OS02-1/-2/-3 | N/A | Nov. 27, 2008 |
| 4 | Pre-Amplifier | Anritsu | MH648A | M09961 | Nov. 27, 2008 |
| 5 | EMI Test Receiver | R&S | ESCI | 100082 | Jan. 30, 2009 |
| 6 | Antenna Mast | Chance Most | CMTB-1.5 | N/A | N/A |
| 7 | Turn Table | Chance Most | CMTB-1.5 | N/A | N/A |
| 8 | Spectrum Analyzer | R&S | FSP_40 | 100129 | Jan. 07, 2009 |
| 9 | Horn Antenna | Schwarzbeck | BBHA9120D | 9120D-325 | Oct. 24, 2008 |
| 10 | Horn Antenna | Schwarzbeck | BBHA9170 | 9170187 | Oct. 24, 2008 |
| 11 | Microwave Pre_amplifier | Agilent | 8449B | 3008A01714 | Mar. 09, 2009 |
| 12 | Microflex Cable | United Microwave | 57793 | 1m | Mar. 09, 2009 |
| 13 | Microflex Cable | United Microwave | A30A30-5006 | 10M | Jul. 07, 2008 |

Remark: " N/A" denotes No Model Name. / Serial No. and No Calibration specified.

4.2.6. TEST PROCEDURE


- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.7. DEVIATION FROM TEST STANDARD


No deviation

4.2.8. TEST SETUP

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



4.2.9. EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

4.3. TEST RESULTS (BETWEEN 30 – 1000 MHz)



| | | | |
|--|---------------------------------|---------------------|-----------|
| EUT : | Full Weather Station | Model Name. : | 75110 RHT |
| Temperature : | 26 °C | Relative Humidity : | 60 % |
| Pressure : | 1010hPa | Test Power : | DC 3.0V |
| Test Mode : | TX Mode(Fundamental & Spurious) | | |
| About the duty cycle correction factor calculated, please refer to the page 17~19 | | | |

| Freq. (MHz) | Ant.Pol. H/V | Reading | | Ant./CF CF(dB) | Act. | | Limit | | Result |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
| | | Peak (dBuV) | AV (dBuV) | | Peak (dBuV/m) | AV (dBuV/m) | Peak (dBuV/m) | AV (dBuV/m) | |
| 434.01 | V | 69.12 | 52.56 | 18.48 | 87.60 | 71.04 | 92.87 | 72.87 | X/F |
| 867.99 | V | 38.79 | 28.43 | -4.29 | 34.50 | 24.14 | 46.00 | 46.00 | X/F |

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『 Note 』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; " H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode or QP detector mode of the emission .
- (4) Data of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle)

Orthogonal Axis : X
TX 433.92 MHz (Fundamental frequency, Vertical)





| | | | |
|--|---------------------------------|---------------------|-----------|
| EUT : | Full Weather Station | Model Name. : | 75110 RHT |
| Temperature : | 26 °C | Relative Humidity : | 60 % |
| Pressure : | 1010hPa | Test Power : | DC 3.0V |
| Test Mode : | TX Mode(Fundamental & Spurious) | | |
| About the duty cycle correction factor calculated, please refer to the page 17~19 | | | |

| Freq. (MHz) | Ant.Pol. H/V | Reading | | Ant./CF CF(dB) | Act. | | Limit | | Result |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
| | | Peak (dBuV) | AV (dBuV) | | Peak (dBuV/m) | AV (dBuV/m) | Peak (dBuV/m) | AV (dBuV/m) | |
| 434.01 | H | 59.12 | 48.76 | 18.48 | 77.60 | 67.24 | 92.87 | 72.87 | X/F |
| 868.00 | H | 35.70 | 25.34 | -4.29 | 31.41 | 21.05 | 46.00 | 46.00 | X/F |

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『 Note 』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; " H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode or QP detector mode of the emission .
- (4) Data of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle)

Orthogonal Axis : X
TX 433.92 MHz (Fundamental frequency,Horizontal)




4.4 TEST RESULTS (ABOVE 1000 MHz)

| | | | |
|--|----------------------|---------------------|-----------|
| EUT : | Full Weather Station | Model Name. : | 75110 RHT |
| Temperature : | 26 °C | Relative Humidity : | 60 % |
| Pressure : | 1010hPa | Test Power : | DC 3.0V |
| Test Mode : | TX CH 433.92 MHz | | |
| About the duty cycle correction factor calculated, please refer to the page 17~19 | | | |

| Freq. (MHz) | Ant.Pol. H/V | Reading | | Ant./CF CF(dB) | Act. | | Limit | | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
| | | Peak (dBuV) | AV (dBuV) | | Peak (dBuV/m) | AV (dBuV/m) | Peak (dBuV/m) | AV (dBuV/m) | |
| 1302.01 | V | 54.89 | 44.53 | -8.05 | 46.84 | 36.48 | 74.00 | 54.00 | X/H |
| 1735.96 | V | 58.48 | 48.12 | -5.73 | 52.75 | 42.39 | 74.00 | 54.00 | X/H |
| 2169.91 | V | 52.97 | 42.61 | -3.76 | 49.21 | 38.85 | 74.00 | 54.00 | X/H |
| 2604.03 | V | 46.23 | 35.87 | -2.52 | 43.71 | 33.35 | 74.00 | 54.00 | X/H |
| 3038.10 | V | 43.9 | 33.54 | -0.98 | 42.92 | 32.56 | 74.00 | 54.00 | X/H |
| 4340.12 | V | 41.56 | 31.20 | 2.48 | 44.04 | 33.68 | 74.00 | 54.00 | X/H |

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『 Note 』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle)
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (8) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna




| | | | |
|---------------|----------------------|---------------------|-----------|
| EUT : | Full Weather Station | Model Name. : | 75110 RHT |
| Temperature : | 26 °C | Relative Humidity : | 60 % |
| Pressure : | 1010hPa | Test Power : | DC 3.0V |
| Test Mode : | TX CH 433.92 MHz | | |

About the duty cycle correction factor calculated, please refer to the page 17~19

| Freq. (MHz) | Ant.Pol. H/V | Reading | | Ant./CF CF(dB) | Act. | | Limit | | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
| | | Peak (dBuV) | AV (dBuV) | | Peak (dBuV/m) | AV (dBuV/m) | Peak (dBuV/m) | AV (dBuV/m) | |
| 1735.96 | H | 62.68 | 52.32 | -5.73 | 56.95 | 46.59 | 74.00 | 54.00 | X/H |
| 2169.66 | H | 53.04 | 42.68 | -3.76 | 49.28 | 38.92 | 74.00 | 54.00 | X/H |
| 2603.94 | H | 49.28 | 38.92 | -2.53 | 46.75 | 36.39 | 74.00 | 54.00 | X/H |
| 3038.12 | H | 53.12 | 42.76 | -0.98 | 52.14 | 41.78 | 74.00 | 54.00 | X/H |
| 3905.92 | H | 43.89 | 33.53 | 1.86 | 45.75 | 35.39 | 74.00 | 54.00 | X/H |
| 4339.98 | H | 41.24 | 30.88 | 2.47 | 43.71 | 33.35 | 74.00 | 54.00 | X/H |

Remark :

- (1) All readings are Peak unless otherwise stated QP in column of 『 Note 』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency . "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle)
- (5) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (7) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (8) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



5. 20dB SPECTRUM BANDWIDTH MEASUREMENT

Limit

The bandwidth of the emissions shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. So the emission bandwidth limits have been calculated in below table.

| Fundamental Frequency | 20dB Bandwidth Limits (kHz) |
|-----------------------|-----------------------------|
| 433.92 MHz | 108.48 |

5.1.MEASURING INSTRUMENTS AND SETTING


Please refer to section 5 in this report. The following table is the setting of the Spectrum Analyzer.

| Spectrum Parameters | Setting |
|---------------------|------------------|
| Attenuation | Auto |
| Span Frequency | > 20dB Bandwidth |
| RB | 10 kHz |
| VB | 10 kHz |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | Auto |

5.2.TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 10 kHz and the video bandwidth of 10 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.

5.3. TEST SETUP LAYOUT



5.4. TEST DEVIATION

There is no deviation with the original standard.


5.5. EUT OPERATION DURING TEST

The EUT was programmed to be in continuously transmitting mode.

5.6. TEST RESULT

| | | | |
|---------------|----------------------|---------------------|-----------|
| EUT : | Full Weather Station | Model Name. : | 75110 RHT |
| Temperature : | 26°C | Relative Humidity : | 60 % |
| Pressure : | 1020 hPa | Test Power : | DC 3.0V |
| Test Mode : | TX CH 01 | | |

| Test Channel | Frequency (MHz) | 20 dBc Bandwidth (KHz) | 99% occupied Bandwidth(KHz) | Result |
|--------------|-----------------|------------------------|-----------------------------|--------|
| CH01 | 433.92 | 48.00 | 323.00 | PASS |



6. TIMING TESTING

Limit

In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

6.1. MEASURING INSTRUMENTS AND SETTING


Please refer to section 6 in this report. The following table is the setting of the Spectrum Analyzer.

| Spectrum Parameters | Setting |
|---------------------|------------|
| Attenuation | Auto |
| Span Frequency | Zero Span |
| RB | 10 kHz |
| VB | 10 kHz |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | 20 seconds |

6.2. TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 10 kHz and the video bandwidth of 10 kHz were used.

6.3. TEST SETUP LAYOUT



6.4. TEST DEVIATION

There is no deviation with the original standard.



6.5. EUT OPERATION DURING TEST

The EUT was programmed to be in normal mode.

6.6. TEST RESULT

| | | | |
|---------------|----------------------|---------------------|-----------|
| EUT : | Full Weather Station | Model Name. : | 75110 RHT |
| Temperature : | 26°C | Relative Humidity : | 60 % |
| Pressure : | 1020 hPa | Test Power : | DC 3.0V |
| Test Mode : | TX CH 01 | | |

| Test Channel | Frequency (MHz) | Transmission time (msec) | Silent period (seconds) | Result |
|--------------|-----------------|--------------------------|-------------------------|--------|
| CH01 | 433.92 | 108 | > 10 | PASS |



7. EUT TEST PHOTO

**Radiated Measurement Photos
TX Mode**

