



FCC/IC Radio Test Report

FCC ID: RNE875TX

IC: 6608A-875TX

This report concerns (check one): Original Class I Change

Issued Date: Dec. 27, 2010

Project No.: 1012C141

Equipment: Rain Gauge

Model Name : 00875TX

Applicant : Chaney Instrument Co.

Address : Rm 1102-3, Enterprise Square One, Tower 3,
No.9, Sheung Yuet Road, Kowloon bay, Kowloon,
Hong Kong, China

Tested by:

Neutron Engineering Inc. EMC Laboratory

Date of Receipt: Dec. 18, 2010

Date of Test:

Dec. 18, 2010 ~ Dec. 22, 2010

Testing Engineer :

(Ivan Cao)

Technical Manager :

(Leo Hung)

Authorized Signatory :

(Steven Lu)

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang
Town, Dong Guan, China.

TEL : (0769) 8318-3000 FAX : (0769) 8319-6000



Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.



| Table of Contents | Page |
|---|-------------|
| 1 . CERTIFICATION | 5 |
| 2 . SUMMARY OF TEST RESULTS | 6 |
| 2.1 TEST FACILITY | 7 |
| 2.2 MEASUREMENT UNCERTAINTY | 7 |
| 3 . GENERAL INFORMATION | 8 |
| 3.1 GENERAL DESCRIPTION OF EUT | 8 |
| 3.2 DESCRIPTION OF TEST MODES | 9 |
| 3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 10 |
| 3.4 DESCRIPTION OF SUPPORT UNITS | 10 |
| 4 . EMC EMISSION TEST | 11 |
| 4.1 CONDUCTED EMISSION MEASUREMENT | 11 |
| 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS | 11 |
| 4.1.2 MEASUREMENT INSTRUMENTS LIST | 11 |
| 4.1.3 TEST PROCEDURE | 12 |
| 4.1.4 DEVIATION FROM TEST STANDARD | 12 |
| 4.1.5 TEST SETUP | 12 |
| 4.1.6 EUT OPERATING CONDITIONS | 12 |
| 4.1.7 TEST RESULTS | 13 |
| 4.2 RADIATED EMISSION MEASUREMENT | 14 |
| 4.2.1. FIELD STRENGTH OF FUNDAMENTAL EMISSIONS MEASUREMENT LIMIT | 14 |
| 4.2.2. MEASURING INSTRUMENTS AND SETTING (FIELD STRENGTH OF FUNDAMENTAL EMISSIONS) | 14 |
| 4.2.3 RADIATED EMISSIONS MEASUREMENT | 15 |
| 4.2.4. DWELL TIME OF PERIODIC OPERATION MEASUREMENT | 17 |
| 4.2.5. MEASUREMENT INSTRUMENTS LIST | 18 |
| 4.2.6. TEST PROCEDURE | 18 |
| 4.2.7. DEVIATION FROM TEST STANDARD | 18 |
| 4.2.8. TEST SETUP | 19 |
| 4.2.9. EUT OPERATING CONDITIONS | 19 |
| 4.3. TEST RESULTS (9KHz-30MHz) | 19 |
| 4.3.1 TEST RESULTS(BETWEEN 30 – 1000 MHz) | 20 |
| 4.3.2 TEST RESULTS (ABOVE 1000 MHz) | 24 |
| 5. 20dB SPECTRUM BANDWIDTH MEASUREMENT | 28 |
| 5.1.MEASURING INSTRUMENTS AND SETTING | 28 |



| Table of Contents | Page |
|--|-------------|
| 5.2. TEST PROCEDURES | 28 |
| 5.3. TEST SETUP LAYOUT | 28 |
| 5.4. TEST DEVIATION | 28 |
| 5.5. EUT OPERATION DURING TEST | 28 |
| 5.6. TEST RESULT | 29 |
| 6. TIMING TESTING | 30 |
| 6.1. MEASURING INSTRUMENTS AND SETTING | 30 |
| 6.2. TEST PROCEDURES | 30 |
| 6.3. TEST SETUP LAYOUT | 30 |
| 6.4. TEST DEVIATION | 30 |
| 6.5. EUT OPERATION DURING TEST | 30 |
| 6.6. TEST RESULT | 31 |
| 7. EUT TEST PHOTO | 33 |



1. CERTIFICATION

Equipment : Rain Gauge

Trade Name : ACURITE

Model Name. : 00875TX

Applicant : Chaney Instrument Co.

Date of Test : Dec. 18, 2010 ~ Dec. 22, 2010

Test Item : ENGINEERING SAMPLE

Standards : FCC Part15, Subpart C(15.231)/ ANSI C63.4 : 2003; Canada RSS-210:2010

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FICP-1-1012C141) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Test result included in this report is only for the 00875TX-TX Sample part of the product.



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15, Subpart C (15.231) /RSS-210:2010 | | | | |
|--|-----------------------|--|----------|-------------|
| Standard Section | | Test Item | Judgment | Remark |
| | 15.207 | Conducted Emission | - | Note(1)/(2) |
| RSS210 2.5 | 15.209 & 15.231(e) | Radiated Spurious Emission | PASS | |
| RSS-210 A1.1.3 | 15.231(c) | 20dB Occupied Bandwidth Measurement | PASS | |

Remark:

- (1) "N/A" denotes test is not applicable in this Test Report
- (2) The EUT is used new battery.



2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-CB03** at the location of No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792

Neutron's test firm number for FCC 319330

Neutron's test firm number for IC 4428B-1

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95 %**.

A. Conducted Measurement :

| Test Site | Method | Measurement Frequency Range | U , (dB) | NOTE |
|-----------|--------|-----------------------------|----------|------|
| DG-C02 | CISPR | 150 KHz ~ 30MHz | 1.94 | |

B. Radiated Measurement :

| Test Site | Method | Measurement Frequency Range | Ant. H / V | U , (dB) | NOTE |
|-----------|--------|-----------------------------|------------|----------|------|
| DG-CB03 | CISPR | 30MHz ~ 200MHz | V | 3.82 | |
| | | 30MHz ~ 200MHz | H | 3.60 | |
| | | 200MHz ~ 1,000MHz | V | 3.86 | |
| | | 200MHz ~ 1,000MHz | H | 3.94 | |



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | | | | | | | | | | | | | |
|--|---|--------------------------------|--------------------------------|----------------------|------------|------------------|-----|-------------------|-----|----------------------|------------------|---------------|------------------------|
| Equipment | Rain Gauge | | | | | | | | | | | | |
| Trade Name | ACURITE | | | | | | | | | | | | |
| Model Name. | 00875TX | | | | | | | | | | | | |
| OEM Brand/Model Name | N/A | | | | | | | | | | | | |
| Model Difference | N/A | | | | | | | | | | | | |
| Product Description | The EUT is a Rain Gauge. | | | | | | | | | | | | |
| | <table border="1"> <tr> <td>Product Type</td> <td>Low Power Communication Device</td> </tr> <tr> <td>Operation Frequency:</td> <td>433.92 MHz</td> </tr> <tr> <td>Modulation Type:</td> <td>ASK</td> </tr> <tr> <td>Number Of Channel</td> <td>1CH</td> </tr> <tr> <td>Antenna Designation:</td> <td>Integral antenna</td> </tr> <tr> <td>Output Power:</td> <td>62.78 dBuV/m (AV Max.)</td> </tr> </table> | Product Type | Low Power Communication Device | Operation Frequency: | 433.92 MHz | Modulation Type: | ASK | Number Of Channel | 1CH | Antenna Designation: | Integral antenna | Output Power: | 62.78 dBuV/m (AV Max.) |
| | Product Type | Low Power Communication Device | | | | | | | | | | | |
| | Operation Frequency: | 433.92 MHz | | | | | | | | | | | |
| | Modulation Type: | ASK | | | | | | | | | | | |
| | Number Of Channel | 1CH | | | | | | | | | | | |
| | Antenna Designation: | Integral antenna | | | | | | | | | | | |
| Output Power: | 62.78 dBuV/m (AV Max.) | | | | | | | | | | | | |
| More details of EUT technical specification please refer to the User's Manual. | | | | | | | | | | | | | |
| Channel List | Please refer to the Note 2. | | | | | | | | | | | | |
| Power Source | DC Voltage supplied from Battery(TX Sample) | | | | | | | | | | | | |
| Power Rating | DC 3.0V (TX Sample) | | | | | | | | | | | | |
| Connecting I/O Port(s) | Please refer to the User's Manual | | | | | | | | | | | | |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

| Frequency Band | Channel No. | Frequency |
|----------------|-------------|------------|
| | 1 | 433.92 MHz |



3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description |
|--------------|-----------------|
| Mode 1 | TX CH 433.92MHz |

| For Conducted Test | |
|--------------------|--|
| Final Test Mode | Description |
| - | " N/A " denotes test is not applicable in this Test Report |


| For Radiated Test | |
|-------------------|-----------------|
| Final Test Mode | Description |
| Mode 1 | TX CH 433.92MHz |

Note:

- (1) The test sample used the new battery
- (2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis. The worst case was found positioned on Z-plane (TX Sample). Therefore only the test data of this Z-plane (TX Sample) was used for radiated emission measurement test.



3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | FCC ID/IC | Series No. | Note |
|------|------------|-----------|----------------|-------------------------|------------|------|
| E-1 | Rain Gauge | ACURITE | 00875TX | RNE875TX 6608A-875TX | N/A | EUT |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|--------|------|
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in m in 『Length』 column.



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

| FREQUENCY (MHz) | Class A (dBuV) | | Class B (dBuV) | | Standard |
|-----------------|----------------|---------|----------------|-----------|----------|
| | Quasi-peak | Average | Quasi-peak | Average | |
| 0.15 -0.5 | 79.00 | 66.00 | 66 - 56 * | 56 - 46 * | CISPR |
| 0.50 -5.0 | 73.00 | 60.00 | 56.00 | 46.00 | CISPR |
| 5.0 -30.0 | 73.00 | 60.00 | 60.00 | 50.00 | CISPR |

| | | | | | |
|-----------|-------|-------|-----------|-----------|-----|
| 0.15 -0.5 | 79.00 | 66.00 | 66 - 56 * | 56 - 46 * | FCC |
| 0.50 -5.0 | 73.00 | 60.00 | 56.00 | 46.00 | FCC |
| 5.0 -30.0 | 73.00 | 60.00 | 60.00 | 50.00 | FCC |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 MEASUREMENT INSTRUMENTS LIST

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|-----------|------------|------------------|
| 1 | LISN | EMCO | 3816/2 | 00052765 | May.26.2011 |
| 2 | LISN | Rolf Heine | NNB-2-16Z | 99044 | May.26.2011 |
| 3 | 50Ω Terminator | SHX | TF2-3G-A | 08122901 | May.26.2011 |
| 4 | Transient Limiter | Agilent | 11947A | 3107A03668 | May.26.2011 |
| 5 | Test Cable | N/A | C-06_C03 | N/A | Mar.31.2011 |
| 6 | EMI TEST RECEIVER | R&S | ESCS30 | 8333641017 | May.27.2011 |

Remark: " N/A" denotes No Model Name. , Serial No. or No Calibration specified.

The following table is the setting of the receiver

| Receiver Parameters | Setting |
|---------------------|----------|
| Attenuation | 10 dB |
| Start Frequency | 0.15 MHz |
| Stop Frequency | 30 MHz |
| IF Bandwidth | 9 kHz |


4.1.3 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The EUT operating condition is continue Transmitter.



4.1.7 TEST RESULTS

| | | | |
|---------------|---|---------------------|---------|
| EUT : | Rain Gauge | Model Name. : | 00875TX |
| Temperature : | -- | Relative Humidity : | -- |
| Pressure : | -- | Test Power : | -- |
| Test Mode : | " N/A" denotes test is not applicable in this Test Report | | |

Remark

- (1) All readings are QP Mode value unless otherwise stated AVG in column of 『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a " * " marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.
- (3) " N/A" denotes test is not applicable in this Test Report



4.2 RADIATED EMISSION MEASUREMENT

4.2.1. FIELD STRENGTH OF FUNDAMENTAL EMISSIONS MEASUREMENT LIMIT

| Frequency Band (MHz) | Fundamental Emissions Limit (uV/m) at 3m |
|-----------------------------|---|
| 40.66-40.70 | 1000 |
| 70-130 | 500 |
| 130-174 | 500-1500(**) |
| 174-260 | 1500 |
| 260-470 | 1500-5000(**) |
| Above 470 | 5000 |

**1. Linear interpolations, the formulas for calculating the maximum permitted fundamental field strengths are as follows:

- (1) for the band 130 - 174 MHz, $\mu\text{V/m}$ at 3 meters = $22.72727 \times (\text{operating frequency, MHz}) - 2454.545$;
- (2) for the band 260 - 470 MHz, $\mu\text{V/m}$ at 3 meters = $16.6667 \times (\text{operating frequency, MHz}) - 2833.3333$.

So the field strength of emission limits have been calculated in below table.

| Carrier Frequency (MHz) | Fundamental Emissions Limit (dBuV/m) at 3m |
|--------------------------------|---|
| 433.92 MHz | 72.86 (Average) |
| 433.92 MHz | 92.86 (Peak) |

4.2.2. MEASURING INSTRUMENTS AND SETTING (FIELD STRENGTH OF FUNDAMENTAL EMISSIONS)

| Receiver Parameter | Setting |
|---------------------------|-----------------------|
| Attenuation | Auto |
| Center Frequency | Fundamental Frequency |
| RBW | > 99% OBW |
| Detector | Peak / Average |



4.2.3 RADIATED EMISSIONS MEASUREMENT

Devices complying with 47 CFR FCC part 15 subpart C, section 15.231(e). The field strength of emissions from intentional radiators at 3 meters operated under this Section shall not exceed the following:

| Frequency Band (MHz) | Spurious Emissions Limit (uV/m) at 3m |
|----------------------|---------------------------------------|
| 40.66-40.70 | 100 |
| 70-130 | 50 |
| 130-174 | 50-150(**) |
| 174-260 | 150 |
| 260-470 | 150-500(**) |
| Above 470 | 500 |

**1. Linear interpolations, the formulas for calculating the maximum permitted fundamental field strengths are as follows:

(1) for the band 130 - 174 MHz, $\mu\text{V/m}$ at 3 meters = $22.72727 \times (\text{operating frequency, MHz}) - 2454.545$;

(2) for the band 260 - 470 MHz, $\mu\text{V/m}$ at 3 meters = $16.6667 \times (\text{operating frequency, MHz}) - 2833.3333$.

(3) The maximum permitted unwanted emissions level is 20 dB below the maximum permitted fundamental level. In addition field strength of any emissions which appear inside of the restriction band shall not exceed the general radiated emissions limits in Section 15.209(a).

| Frequencies (MHz) | Field Strength (microrvolts/meter) | Measurement Distance (meters) |
|-------------------|------------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

| Receiver Parameter | Setting |
|------------------------|----------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |



| Spectrum Parameter | Setting |
|---------------------------------------|--|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10th carrier harmonic |
| RB / VB (emission in restricted band) | 1MHz / 1MHz for Peak, AV Mode with Dwell time Use 100mS for calculation |
| RB / VB (other emission) | 1MHz / 1MHz for peak |

In order to determine possible Maximum Modulation percentage, alternations are made to the EUT.

We measured:


$$\text{Duty Cycle} = (N1*L1+N2*L2+...+Nn-1*Ln-1+Nn*Ln)/100 \text{ or } T$$

$$\text{Duty Cycle} = \{(0.8\text{ms}*75)+1.6\text{ms}+2.8\text{ms}\}/100\text{msec}=0.644\%$$

For duty cycle refer to plot #1



$$\text{Average Reading} = \text{Peak Reading (dBuV/m)} + 20\log(\text{Duty cycle})$$

$$\text{Average Reading} = \text{Peak value} + 20\log(\text{Duty cycle}) , AV=PK-3.82$$





4.2.4. DWELL TIME OF PERIODIC OPERATION MEASUREMENT





4.2.5. MEASUREMENT INSTRUMENTS LIST

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|---------------------|--------------|---------------|------------|------------------|
| 1 | Antenna | ETS | 3115 | 00075789 | May.27.2011 |
| 2 | Amplifier | Agilent | 8449B | 3008A02274 | May.26.2011 |
| 3 | Spectrum | Agilent | E4408B | US39240143 | Nov.15.2011 |
| 4 | Test Cable | HUBER+SUHNER | CB03 High Fre | N/A | May.03.2011 |
| 5 | Antenna | Schwarbeck | VULB9160 | 9160-3232 | Jun.30.2011 |
| 6 | Amplifier | HP | 8447D | 2944A09673 | May.26.2011 |
| 7 | Test Receiver | R&S | ESCI | 100895 | May.26.2011 |
| 8 | Test Cable | N/A | C-01_CB03 | N/A | Jul.05.2011 |
| 9 | Triple Loop Antenna | R&S | HFH2-Z2 | 830749/020 | Jun.30.2011 |

Remark: " N/A" denotes No Model Name. / Serial No. and No Calibration specified.

4.2.6. TEST PROCEDURE


- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.7. DEVIATION FROM TEST STANDARD


No deviation

4.2.8. TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



4.2.9. EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

4.3. TEST RESULTS (9KHz-30MHz)

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.



4.3.1 TEST RESULTS(BETWEEN 30 – 1000 MHz)

| | | | |
|--|------------|---------------------|---------|
| EUT : | Rain Gauge | Model Name. : | 00875TX |
| Temperature : | 23 °C | Relative Humidity : | 58% |
| Pressure : | 1008 hPa | Test Power : | DC 3.0V |
| Test Mode : | TX Mode | | |
| About the duty cycle correction factor calculated, please refer to the page 16~17 | | | |



| Freq. (MHz) | Ant.Pol. H/V | Reading | | Ant./CF CF(dB) | Act. | | Limit | | Result |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------------|
| | | Peak (dBuV) | AV (dBuV) | | Peak (dBuV/m) | AV (dBuV/m) | Peak (dBuV/m) | AV (dBuV/m) | |
| 433.70 | V | 75.02 | 71.20 | -8.42 | 66.60 | 62.78 | 92.87 | 72.87 | Z/F |
| 866.99 | V | 32.16 | 28.34 | -0.61 | 31.55 | 27.73 | 72.87 | 52.87 | Z/H |

Remark :

- (1) EUT Orthogonal Axis:
 "X" - denotes Laid on Table: "Y" - denotes Vertical Stand: "Z" - denotes Side Stand.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency ◦ "F" denotes fundamental frequency; " H" denotes spurious frequency. "E" denotes band edge frequency.
- (4) Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode or QP detector mode of the emission ◦
- (5) Data of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) The average value of fundamental frequency is:
 Average = Peak value + 20log(Duty cycle) ◦ Final AV=PK-3.82



Orthogonal Axis : Z
TX 433.92 MHz (Fundamental frequency, Vertical)





| | | | |
|---------------|------------|---------------------|---------|
| EUT : | Rain Gauge | Model Name. : | 00875TX |
| Temperature : | 23 °C | Relative Humidity : | 58% |
| Pressure : | 1008 hPa | Test Power : | DC 3.0V |
| Test Mode : | TX Mode | | |

About the duty cycle correction factor calculated, please refer to the page 16~17



| Freq. (MHz) | Ant.Pol. H/V | Reading | | Ant./CF CF(dB) | Act. | | Limit | | Result |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|--------|
| | | Peak (dBuV) | AV (dBuV) | | Peak (dBuV/m) | AV (dBuV/m) | Peak (dBuV/m) | AV (dBuV/m) | |
| 433.69 | H | 64.13 | 60.31 | -8.42 | 55.71 | 51.89 | 92.87 | 72.87 | Z/F |
| 867.04 | H | 34.58 | 30.76 | -0.61 | 33.97 | 30.15 | 72.87 | 52.87 | Z/F |

Remark :

- (1) EUT Orthogonal Axis:
 "X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency ◦ "F" denotes fundamental frequency; " H" denotes spurious frequency. "E" denotes band edge frequency.
- (4) Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Peak detector mode or QP detector mode of the emission ◦
- (5) Data of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (6) The average value of fundamental frequency is:
 Average = Peak value + 20log(Duty cycle) ◦ Final AV=PK-3.82



Orthogonal Axis : Z
TX 433.92 MHz (Fundamental frequency,Horizontal)





4.3.2 TEST RESULTS (ABOVE 1000 MHz)


| | | | |
|---------------|------------|---------------------|---------|
| EUT : | Rain Gauge | Model Name. : | 00875TX |
| Temperature : | 23 °C | Relative Humidity : | 51% |
| Pressure : | 1008 hPa | Test Power : | DC 3.0V |
| Test Mode : | TX Mode | | |

About the duty cycle correction factor calculated, please refer to the page 16~17

| Freq. (MHz) | Ant.Pol. H/V | Reading | | Ant./CF CF(dB) | Act. | | Limit | | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
| | | Peak (dBuV) | AV (dBuV) | | Peak (dBuV/m) | AV (dBuV/m) | Peak (dBuV/m) | AV (dBuV/m) | |
| 1302.83 | V | 42.34 | 38.52 | -6.93 | 35.41 | 31.59 | 74.00 | 54.00 | Z/H |

Remark :

- (1) EUT Orthogonal Axis:
"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode of the emission.
- (5) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle) , Final AV=PK-3.82
- (6) Data of measurement within this frequency range shown "*" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (7) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (8) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (9) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna






| | | | |
|---------------|------------|---------------------|---------|
| EUT : | Rain Gauge | Model Name. : | 00875TX |
| Temperature : | 23 °C | Relative Humidity : | 51% |
| Pressure : | 1008 hPa | Test Power : | DC 3.0V |
| Test Mode : | TX Mode | | |

About the duty cycle correction factor calculated, please refer to the page 16~17

| Freq. (MHz) | Ant.Pol. H/V | Reading | | Ant./CF CF(dB) | Act. | | Limit | | Note |
|----------------|-----------------|----------------|--------------|-------------------|------------------|----------------|------------------|----------------|------|
| | | Peak (dBuV) | AV (dBuV) | | Peak (dBuV/m) | AV (dBuV/m) | Peak (dBuV/m) | AV (dBuV/m) | |
| 1302.16 | H | 43.64 | 39.82 | -6.93 | 36.71 | 32.89 | 74.00 | 54.00 | Z/H |

Remark :

- (1) EUT Orthogonal Axis:
"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (4) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode of the emission.
- (5) The average value of fundamental frequency is:
Average = Peak value + 20log(Duty cycle) ∴ Final AV=PK-3.82
- (6) Data of measurement within this frequency range shown "*" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (7) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (8) EUT Orthogonal Axis :
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (9) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna



5. 20dB SPECTRUM BANDWIDTH MEASUREMENT

Limit

The bandwidth of the emissions shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. So the emission bandwidth limits have been calculated in below table.

| Fundamental Frequency | 20dB Bandwidth Limits (MHz) |
|-----------------------|-----------------------------|
| 433.92 MHz | 1.0848 |

5.1. MEASURING INSTRUMENTS AND SETTING


Please refer to section 5 in this report. The following table is the setting of the Spectrum Analyzer.

| Spectrum Parameters | Setting |
|---------------------|------------------|
| Attenuation | Auto |
| Span Frequency | > 20dB Bandwidth |
| RB | 10 kHz |
| VB | 10 kHz |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | Auto |

5.2. TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 10 kHz and the video bandwidth of 10 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.

5.3. TEST SETUP LAYOUT



5.4. TEST DEVIATION

There is no deviation with the original standard.

5.5. EUT OPERATION DURING TEST


The EUT was programmed to be in continuously transmitting mode.



5.6. TEST RESULT

| | | | |
|---------------|------------|---------------------|---------|
| EUT : | Rain Gauge | Model Name. : | 00875TX |
| Temperature : | 20°C | Relative Humidity : | 63 % |
| Pressure : | 1020 hPa | Test Power : | DC 3.0V |
| Test Mode : | TX CH 01 | | |

| Test Channel | Frequency (MHz) | 20 dBc Bandwidth (KHz) | 99% OBW (KHz) | Result |
|--------------|-----------------|------------------------|---------------|--------|
| CH01 | 433.92 | 46.00 | 76.80 | PASS |



6. TIMING TESTING

Limit

In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

6.1. MEASURING INSTRUMENTS AND SETTING


Please refer to section 6 in this report. The following table is the setting of the Spectrum Analyzer.

| Spectrum Parameters | Setting |
|---------------------|------------|
| Attenuation | Auto |
| Span Frequency | Zero Span |
| RB | 1000KHz |
| VB | 1000KHz |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | 50 seconds |

6.2. TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 1000KHz and the video bandwidth of 1000KHz were used.

6.3. TEST SETUP LAYOUT



6.4. TEST DEVIATION

There is no deviation with the original standard.

6.5. EUT OPERATION DURING TEST


The EUT was programmed to be in normal mode.




6.6. TEST RESULT

| | | | |
|---------------|------------|---------------------|---------|
| EUT : | Rain Gauge | Model Name. : | 00875TX |
| Temperature : | 23 °C | Relative Humidity : | 51 % |
| Pressure : | 1008 hPa | Test Power : | DC 3.0V |
| Test Mode : | TX CH 01 | | |

| Test Channel | Frequency (MHz) | Transmission time (sec) | Silent period (seconds) | Result |
|--------------|-----------------|-------------------------|-------------------------|--------|
| CH01 | 433.92 | 60.4 | > 10 | PASS |







7. EUT TEST PHOTO

Radiated Measurement Photos

