

No.3 of Assembly Instructions.

RF and Optical  
s and enjoyment of  
IC from Agilent  
power deplete with  
800DPI that allow  
to readjustment is  
the current is below

**Power Saving:**

The circuit is embedded with an automatic sleeping power-saving function. If the mouse is not moved or touched for 4 minutes, the brightness from LED will be lowered and after another 30 seconds, all other current except for waking-up feature will be off automatically. After 8 minutes more, it will enter into full-sleeping state and the power-usage is almost near zero.

**Voltage-Protection:**

When the current voltage is decreased to a minimum level, the mouse will be powered off automatically and the new batteries must be replaced.

**Wake-up Feeler: two ways.**

- 1. touch mode: Grasp the mouse
- 2. press mode: Click any key

**Features of receiver:**

- Frequency: 27MHz
- Interface: PS/2, USB & Combo available
- Current: +5V DC

kinds of branded  
XP and Windows

please refer to the

**Assembly In**

- 1. Connect  
Connect the  
PS/2 Interface m  
USB connector
- 2. Battery I  
Open the b  
brand new batte  
the right side or

**WARNING**

*Different k  
batteries) mixe*

- 3. Adjustin  
Before usin  
interfered, for ex  
distances, the II  
the mouse, Thus  
be pressed first
- 4. Usage  
The receive  
Mouse can be u  
on any white or  
saved.)

