

No	component name	model	quartity	remark
1	PCB	1.6×67×33mm	1	2101-A TX
2	IC	A2051 DIP16pin	1	U3
3	IC	MA6221-s7K SSOP28pin	1	U2
4	IC	RH5RH501A-T1 SOT-89	1	U1
5	LED	HLMP-ED80-KP000	1	D4
6	LENS	HDNS-2100	1	
7	SWITCH	MTS2-70	2	R, L
8	SWITCH	DSD-ST	1	M
9	ID SWITCH	TS60-43PSM160	1	ID
10	encoder	H=7mm	1	EN
11	DIODE	MA729 0805	2	D1, D2
12	DIODE	1N5817 1206	1	D3
13	LED	3mm red	1	D5
14	crystal frequency genrator	27.042MHZ 16pF SMD	1	X1
15	crystal frequency genrator	76.8KHZ DIP	1	X2
16	crystal frequency genrator	18.00MHz DIP	1	X4
17	inductance	1.8uH 1210	1	L3
18	inductance	220uH RL0406-221K	2	L1, L2
19	resistance	4.7M 0603	1	R1
20	resistance	91K 0603	1	R2
21	resistance	220K 0603	1	R3
22	resistance	680K 0603	1	R4
23	resistance	1M6 0603	1	R5
24	resistance	15K 0603	1	R6
25	resistance	560R 0603	1	R7
26	capacitance	220uF/ 6v Btype (1210)	2	C2, C7
27	capacitance	20pF 0603	1	C3

ET TECH

# BOM

MODEL: 2101-A

ver : A0

date: 2004-07-31

№: ET-04210101

28		capacitance	30pF	0603	1	C5
29		capacitance	104	0603	3	C6, C8, C12
30		capacitance	22pF	0603	2	C9, C10
31		capacitance	33pF	0603	1	C11
32		capacitance	75pF	0603	1	C13
33		capacitance	10uF	1206	1	C14
34		capacitance	47pF	0603	1	C15
35		capacitance	22pF	0603	1	C16