

FCC PART 15.227
EMI MEASUREMENT AND TEST REPORT

For

EASTERN TIMES TECHNOLOGY CO.,LTD

BUILDING 5,PENGHUA INDUSTRY PARK, HEPING ROAD (W), LONGHUA TOWN, SHENZHEN

| |
|---------------------------|
| FCC ID: RNKDS-2118 |
|---------------------------|

January 24, 2005

| | |
|---|--|
| This Report Concerns: <input checked="" type="checkbox"/> Original Report | Equipment Type: Transmitter, WIRELESS OPTICAL MOUSE |
| Test Engineer: Lisa Zhu <i>Lisa Zhu</i> | |
| Report No.: RSZ04123104 | |
| Test Date: January 1, 2005-January 19, 2005 | |
| Reviewed By: William Chan <i>William. Chan</i> | |
| Prepared By: Bay Area Compliance Lab Corp. (ShenZhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, ShenZhen, Guangdong 518038, P.R.China Tel: +86-755-33320018 Fax: +86-755-33320008 | |

Note: The test report is specially limited to the above company and the product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

GENERAL INFORMATION.....3
 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)3
 OBJECTIVE3
 RELATED SUBMITTAL(S)/GRANT(S).....3
 TEST METHODOLOGY3
 TEST FACILITY3

SYSTEM TEST CONFIGURATION.....4
 JUSTIFICATION4
 SCHEMATICS AND BLOCK DIAGRAM.....4
 EQUIPMENT MODIFICATIONS4
 TEST SETUP CONFIGURATION4

SUMMARY OF TEST RESULTS5

§15.203 - ANTENNA REQUIREMENT.....6
 STANDARD APPLICABLE6

§15.205, §15.209, §15.227(A) - RADIATED EMISSIONS TEST7
 MEASUREMENT UNCERTAINTY7
 EUT SETUP.....7
 EMI TEST RECEIVER SETUP7
 TEST EQUIPMENT LIST AND DETAILS.....8
 CORRECTED AMPLITUDE & MARGIN CALCULATION8
 TEST DATA9

§15.227(B) - OUT OF BAND EMISSION10

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *EASTERN TIMES TECHNOLOGY CO.,LTD*'s product, model number: DS-2118 or the "EUT" as referred to in this report is a WIRELESS OPTICAL MOUSE Transmitter. The EUT is measured approximately 8.5" L x 5.1" W x 3.0" H. rated input voltage: DC 3V battery.

** The test data gathered are from production sample, serial number: 0412038, provided by the manufacturer.*

Objective

This Type approval report is prepared on behalf of *EASTERN TIMES TECHNOLOGY CO.,LTD* in accordance with Part 2, Subpart J, and Part 15, Subparts A , B and C of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules, sec 15.203, 15.205, 15.209 and sec 15.227.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to ANSI C63.4-2003.

Schematics and Block Diagram

Please refer to Appendix D.

Equipment Modifications

No modifications were made to the EUT.

Test Setup Configuration



Mouse Transmitter

SUMMARY OF TEST RESULTS

Results reported relate only to the product tested, serial number:0412038.

| FCC RULES | DESCRIPTION OF TEST | RESULT |
|------------|------------------------------|--------|
| §15.203 | Antenna requirement | Pass |
| §15.205 | Restricted Band of operation | Pass |
| §15.209 | Radiated Emission Limit | Pass |
| §15.227(a) | Field Strength | Pass |
| §15.227(b) | Band Edge | Pass |

§15.203 - ANTENNA REQUIREMENT

Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a permanent antenna, fulfill the requirement of this section.

Test Result: Pass

§15.205, §15.209, §15.227(a) - RADIATED EMISSIONS TEST

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BAEL is ± 4.0 dB.

The fundamental data was recorded in average detection mode: set the VBW AVE on, then record the data.

EUT Setup

The radiated emission tests were performed in the open area 3-meter chamber, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC Part 15 Subpart C limits.

EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated from 27 to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

| <u><i>Frequency Range</i></u> | <u><i>RBW</i></u> | <u><i>Video B/W</i></u> |
|-------------------------------|-------------------|-------------------------|
| Below 30 MHz | 10 kHz | 10 kHz |
| 30 – 1000 MHz | 100 kHz | 100 kHz |
| Above 1000 MHz | 1 MHz | 1 MHz |

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|---------------------|---------|---------------|------------------|----------------------|
| Sunol Sciences | Antenna | JBI | A040904-1 | 2004-4-19 | 2005-4-18 |
| HP | Amplifier | HP844TK | 2944A09295 | 2004-4-5 | 2005-4-4 |
| THERMAX | Coaxial Cable | RGS-142 | EC002 | 2004-11-20 | 2005-11-19 |
| Rohde & Schwarz | EMI Test Receiver | ESCS30 | 830245/006 | 2004-11-20 | 2005-11-19 |
| Fluke | True RMS Multimeter | 187 | 78540402 | 2004-3-23 | 2005-3-22 |

* **Statement of Traceability:** BACL attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

Test Data

| INDICATED | | TABLE | ANTENNA | | CORRECTION FACTOR | | | CORRECTED AMPLITUDE | FCC PART 15.227 | | |
|---------------|--------------------|--------------|--------------|------------|-------------------|----------|---------|--------------------------|--------------------|-----------|-----------|
| Frequency MHz | Ampl. dB μ V/m | Angle Degree | Height Meter | Polar H/ V | Antenna dB/m | Cable dB | Amp. dB | Corr. Ampl. dB μ V/m | Limit dB μ V/m | Margin dB | Remark |
| 54.000 | 40.86 | 60 | 3.0 | h | 8.5 | 0.7 | 28.7 | 21.4 | 40 | -18.7 | Harmonic |
| 138.640 | 46.53 | 61 | 3.1 | h | 14.2 | 1.1 | 28.5 | 33.3 | 43.5 | -10.2 | Harmonic |
| 284.140 | 45.43 | 154 | 3.1 | h | 13.8 | 1.5 | 27.6 | 33.1 | 46 | -12.9 | Harmonic |
| 303.540 | 45.50 | 45 | 1.0 | h | 13.9 | 1.6 | 27.7 | 33.3 | 46 | -12.7 | Harmonic |
| 355.920 | 50.07 | 60 | 1.2 | h | 15.0 | 1.8 | 27.6 | 39.3 | 46 | -6.7 | Harmonic |
| 480.080 | 51.02 | 270 | 1.0 | h | 17.9 | 2.3 | 28.5 | 42.7 | 46 | -3.3 | Harmonic |
| 495.600 | 52.47 | 45 | 1.2 | h | 18.2 | 2.4 | 28.5 | 44.6 | 46 | -1.4 | Harmonic |
| 54.000 | 45.83 | 45 | 1.2 | v | 8.5 | 0.7 | 28.7 | 26.3 | 40 | -13.7 | Harmonic |
| 145.750 | 44.71 | 180 | 1.0 | v | 13.4 | 1.1 | 28.5 | 30.7 | 43.5 | -12.8 | Harmonic |
| 471.200 | 49.40 | 90 | 1.2 | v | 17.6 | 2.3 | 28.4 | 40.9 | 46 | -5.1 | Harmonic |
| 483.850 | 51.32 | 90 | 1.2 | v | 17.9 | 2.3 | 28.5 | 43.0 | 46 | -3.0 | Harmonic |
| 502.250 | 49.93 | 90 | 1.2 | v | 18.0 | 2.4 | 28.6 | 41.7 | 46 | -4.3 | Harmonic |
| 514.900 | 50.09 | 90 | 1.2 | v | 18.0 | 2.4 | 28.6 | 41.9 | 46 | -4.1 | Harmonic |
| 27.0459 | 64.50 | 60 | 3.0 | h | 24.1 | 0.6 | 28.8 | 60.4 | 100 | -39.6 | FUND (PK) |
| 27.045 | 62.80 | 90 | 1.2 | v | 24.1 | 0.6 | 28.8 | 58.7 | 100 | -41.3 | FUND (PK) |
| 27.045 | 62.40 | 60 | 3.0 | h | 24.1 | 0.6 | 28.8 | 58.3 | 80 | -21.7 | FUND (AV) |
| 27.045 | 61.41 | 90 | 1.2 | v | 24.1 | 0.6 | 28.8 | 57.3 | 80 | -22.7 | FUND (AV) |


Test Result: Pass

§15.227(b) - Out of Band Emission


The result has been complied with the 15.227(b), see the following plot:

| Frequency MHz | Emission dB μ V/m | Limit dB μ V/m |
|------------------|--------------------------|-----------------------|
| 27.28 | 18.99 | 40 |
| 26.96 | 20.95 | 40 |

Test Result: Pass



Date: 11.JAN.2005 21:31:14



Date: 11.JAN.2005 21:31:33