

Annex D



This test report annex is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report annex authorized:

Thomas Vogler
Lab Manager
Radio Communications & EMC


1 Table of contents

1	Table of contents.....	2
2	Measurement results, FCC Part 87 and FCC Part 25	3
3	Measurement results, Spurious emissions 30MHz - 18 GHz	273
4	Measurement results, FCC Part 15B	276
5	Document history	277

2 Measurement results, FCC Part 87 and FCC Part 25

This chapter consists of 240 pages including this page.

Plot No. 1



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R5T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 14:00:44
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.626575 GHz
Stop frequency: 1.626675 GHz
Center frequency: 1.626625 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 38 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 2



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R20T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 14:02:55
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.626575 GHz
Stop frequency: 1.626675 GHz
Center frequency: 1.626625 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 37 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 3



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R20T1QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 14:05:16
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.626575 GHz
Stop frequency: 1.626675 GHz
Center frequency: 1.626625 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 37 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 4



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R5T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 14:13:34
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 5



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R20T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 14:16:11
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 6



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R5T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 14:18:51
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 7



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R20T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 14:22:47
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 8



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R5T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:12:18
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 9



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R20T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:14:11
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 10



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R5T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:21:08
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 11



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fl, R20T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:22:43
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 12



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, R20T0.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:25:28
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6265875 GHz
Stop frequency: 1.6266375 GHz
Center frequency: 1.6266125 GHz
Frequency span: 50 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 19 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 13



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R5T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed

Environment condition:
Date & Time: Fri 15/May/2020 14:25:44
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz


Setup of measurement equipment:
Start frequency: 1.626575 GHz
Stop frequency: 1.626675 GHz
Center frequency: 1.626625 GHz
Frequency span: 100 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:

Directional coupler	+ 0.0 dB
Coaxial cable (C220)	+ 0.9 dB
DUT-Antenna (on-axis)	+ 0.0 dB
Test antenna	+ 0.0 dB
BW correction factor	+ 0.0 dB
Atten. between HPA and feedhorn	+ 0.0 dB
20 dB attenuator (U312)	+ 19.5 dB
10 dB attenuator(U311)	+ 9.7 dB
Power splitter	+ 6.7 dB
TOTAL CORRECTION:	+ 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 39 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 14



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R20T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:40:35
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.626575 GHz
Stop frequency: 1.626675 GHz
Center frequency: 1.626625 GHz
Frequency span: 100 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 38 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 15



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R20T1QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:42:18
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.626575 GHz
Stop frequency: 1.626675 GHz
Center frequency: 1.626625 GHz
Frequency span: 100 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 38 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 16



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R5T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:45:08
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 17



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R20T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:46:46
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 18



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R5T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:48:36
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 19



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R20T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:54:08
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 20



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R5T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:57:13
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 21



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R20T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:59:27
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 22



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R5T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:04:01
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 23



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, R20T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:05:53
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 24



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl R20T0.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, R001

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 05/Jun/2020 12:56:47
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6265875 GHz
Stop frequency: 1.6266375 GHz
Center frequency: 1.6266125 GHz
Frequency span: 50 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 19 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 25



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, FR80T2.5X16

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:11:08
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 88 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 26



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, FR80T2.5X32

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:13:12
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 88 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 27



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, FR80T2.5X64

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:15:21
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.62655 GHz
Stop frequency: 1.62675 GHz
Center frequency: 1.62665 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 88 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 28



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, FR80T5X16

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:17:26
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 174 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 29



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, FR80T5X32

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:18:38
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 174 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 30



Subclause: -/- Function test
Modulated rf-carrier at the lower edge of the band (fl)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fl, FR80T5X64

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:20:03
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6266 GHz
Stop frequency: 1.627 GHz
Center frequency: 1.6268 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fl:
The measured value is about 174 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 31



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R5T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, R001, U312, U311, Power Splitter

Remark:

Test result: Test passed

Environment condition:
Date & Time: Thu 14/May/2020 11:53:45
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz


Setup of measurement equipment:
Start frequency: 1.64345 GHz
Stop frequency: 1.64355 GHz
Center frequency: 1.6435 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:

Directional coupler	+ 0.0 dB
Coaxial cable (C220)	+ 0.9 dB
DUT-Antenna	+ 0.0 dBi
Test antenna	+ 0.0 dB
BW correction factor (1k -> 3k)	+ 4.8 dB
Atten. between HPA and feedhorn	- 0.0 dB
20 dB attenuator (U312)	+ 19.5 dB
10 dB attenuator(U311)	+ 9.7 dB
Power splitter	+ 6.7 dB
TOTAL CORRECTION:	+ 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 38 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 32



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R20T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 11:59:27
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.64345 GHz
Stop frequency: 1.64355 GHz
Center frequency: 1.6435 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 37 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 33



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R20T1QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 12:03:53
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.64345 GHz
Stop frequency: 1.64355 GHz
Center frequency: 1.6435 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 37 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 34



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R5T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 12:11:49
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 35



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R20T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 12:16:39
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 36



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R20T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 12:25:06
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 37



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R2T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 12:28:39
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 38



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R5T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 13:38:26
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 39



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R20T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 13:43:32
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 166 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 40



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R5T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 13:48:20
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 166 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 41



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R20T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 13:52:03
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 166 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 42



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fm, R20T0.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 13:55:27
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.643475 GHz
Stop frequency: 1.643525 GHz
Center frequency: 1.6435 GHz
Frequency span: 50 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 19 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 43



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R5T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed

Environment condition:
Date & Time: Fri 15/May/2020 13:19:43
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz


Setup of measurement equipment:
Start frequency: 1.64345 GHz
Stop frequency: 1.64355 GHz
Center frequency: 1.6435 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:

Directional coupler	+ 0.0 dB
Coaxial cable (C220)	+ 0.9 dB
DUT-Antenna	+ 0.0 dBi
Test antenna	+ 0.0 dB
BW correction factor (1k -> 3k)	+ 4.8 dB
Atten. between HPA and feedhorn	- 0.0 dB
20 dB attenuator (U312)	+ 19.5 dB
10 dB attenuator(U311)	+ 9.7 dB
Power splitter	+ 6.7 dB
TOTAL CORRECTION:	+ 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 38 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 44



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R20T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:22:26
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.64345 GHz
Stop frequency: 1.64355 GHz
Center frequency: 1.6435 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 37 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 45



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R20T1QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:24:43
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.64345 GHz
Stop frequency: 1.64355 GHz
Center frequency: 1.6435 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 37 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 46



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R5T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:28:53
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 47



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R20T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:32:03
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 48



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R5T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:35:51
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 49



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R20T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:38:17
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 50



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R20T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:44:35
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 51



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R5T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:48:20
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 52



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R20T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:53:18
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 53



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R5T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:55:32
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 54



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, R20T0.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 13:57:59
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.643475 GHz
Stop frequency: 1.643525 GHz
Center frequency: 1.6435 GHz
Frequency span: 50 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 19 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 55



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, FR80T2.5X16

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:06:37
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 87 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 56



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, FR80T2.5X32

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:09:00
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 87 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 57



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, FR80T2.5X64

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:10:55
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6434 GHz
Stop frequency: 1.6436 GHz
Center frequency: 1.6435 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 87 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 58



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, FR80T5X16

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:13:40
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 174 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 59



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, FR80T5X32

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:15:54
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 173 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 60



Subclause: -/- Function test
Modulated rf-carrier in the middle of the band (fm)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fm, FR80T5X64

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 14:18:47
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6433 GHz
Stop frequency: 1.6437 GHz
Center frequency: 1.6435 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna + 0.0 dBi
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn - 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 173 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 61



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R5T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:36:20
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660425 GHz
Stop frequency: 1.660525 GHz
Center frequency: 1.660475 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 38 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 62



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R20T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:39:12
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660425 GHz
Stop frequency: 1.660525 GHz
Center frequency: 1.660475 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 38 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 63



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R20T1QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:43:17
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660425 GHz
Stop frequency: 1.660525 GHz
Center frequency: 1.660475 GHz
Frequency span: 100 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 38 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 64



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R5T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:49:27
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 65



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R20T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:53:33
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 66



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R5T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 16:58:34
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 67



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R20T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 17:01:34
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 74 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 68



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R5T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 17:05:28
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 69



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R20T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 17:07:47
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 166 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 70



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R5T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 17:11:22
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 71



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R20T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 17:23:19
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 72



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 ACD, fh R20T0.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Thu 14/May/2020 17:16:38
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.6604625 GHz
Stop frequency: 1.6605125 GHz
Center frequency: 1.6604875 GHz
Frequency span: 50 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor (1k -> 3k) + 4.8 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 41.6 dB

Remarks:
Determination of the 'occupied bandwidth' at fm:
The measured value is about 19 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 73



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R5T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:23:33
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660425 GHz
Stop frequency: 1.660525 GHz
Center frequency: 1.660475 GHz
Frequency span: 100 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 39 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 74



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R20T1XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:25:01
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660425 GHz
Stop frequency: 1.660525 GHz
Center frequency: 1.660475 GHz
Frequency span: 100 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 39 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 75



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R20T1QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed

Environment condition:
Date & Time: Fri 15/May/2020 15:37:55
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz


Setup of measurement equipment:
Start frequency: 1.660425 GHz
Stop frequency: 1.660525 GHz
Center frequency: 1.660475 GHz
Frequency span: 100 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:

Directional coupler	+ 0.0 dB
Coaxial cable (C220)	+ 0.9 dB
DUT-Antenna (on-axis)	+ 0.0 dB
Test antenna	+ 0.0 dB
BW correction factor	+ 0.0 dB
Atten. between HPA and feedhorn	+ 0.0 dB
20 dB attenuator (U312)	+ 19.5 dB
10 dB attenuator(U311)	+ 9.7 dB
Power splitter	+ 6.7 dB
TOTAL CORRECTION:	+ 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 38 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 76



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R5T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed

Environment condition:
Date & Time: Fri 15/May/2020 15:40:02
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz


Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:

Directional coupler	+ 0.0 dB
Coaxial cable (C220)	+ 0.9 dB
DUT-Antenna (on-axis)	+ 0.0 dB
Test antenna	+ 0.0 dB
BW correction factor	+ 0.0 dB
Atten. between HPA and feedhorn	+ 0.0 dB
20 dB attenuator (U312)	+ 19.5 dB
10 dB attenuator(U311)	+ 9.7 dB
Power splitter	+ 6.7 dB
TOTAL CORRECTION:	+ 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 77



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R20T2XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:42:00
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 78



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R5T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:44:26
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 79



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R20T2QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:45:40
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 75 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 80



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R5T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:48:25
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 81



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R20T4.5XD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:50:51
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 82



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R5T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:53:51
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 83



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, R20T4.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 15:56:35
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 167 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 84



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh R20T0.5QD

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed

Environment condition:
Date & Time: Fri 05/Jun/2020 13:03:55
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz


Setup of measurement equipment:
Start frequency: 1.6604625 GHz
Stop frequency: 1.6605125 GHz
Center frequency: 1.6604875 GHz
Frequency span: 50 kHz
Resolution-BW: 1 kHz
Video-BW: 3 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:

Directional coupler	+ 0.0 dB
Coaxial cable (C220)	+ 0.9 dB
DUT-Antenna (on-axis)	+ 0.0 dB
Test antenna	+ 0.0 dB
BW correction factor	+ 0.0 dB
Atten. between HPA and feedhorn	+ 0.0 dB
20 dB attenuator (U312)	+ 19.5 dB
10 dB attenuator(U311)	+ 9.7 dB
Power splitter	+ 6.7 dB
TOTAL CORRECTION:	+ 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 19kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 85



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, FR80T2.5X16

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 16:02:04
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 88 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 86



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, FR80T2.5X32

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 16:03:25
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 88 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 87



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, FR80T2.5X64

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 16:04:16
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.66035 GHz
Stop frequency: 1.66055 GHz
Center frequency: 1.66045 GHz
Frequency span: 200 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 88 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 88



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, FR80T5X16

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 16:06:45
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 174 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 89



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, FR80T5X32

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed


Environment condition:
Date & Time: Fri 15/May/2020 16:09:54
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 174 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.

Plot No. 90



Subclause: -/- Function test
Modulated rf-carrier at the upper edge of the band (fh)
Determination of the 'occupied bandwidth'

Limit:
The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission. (see §2.1049).

Test results:
see plot (an explicit table was not generated)

Operating condition of DUT:
operating condition 1, see test report chapter 5.4
A700S Class 6 HDR PIESD, fh, FR80T5X64

Test setup:
see test report chapter 7.2 setup 1.1hgj

Test equipment:
see test report chapter 7.2: C220, Power Splitter, R001, U311, U312

Remark:
Determination of occupied bandwidth

Test result: Test passed

Environment condition:
Date & Time: Fri 15/May/2020 16:12:21
Location: CTC advanced GmbH, Laboratory RC-SYS
Temperature: 22 °C
Humidity: 55 %
Voltage: 115 Vac / 400 Hz

Setup of measurement equipment:
Start frequency: 1.660175 GHz
Stop frequency: 1.660575 GHz
Center frequency: 1.660375 GHz
Frequency span: 400 kHz
Resolution-BW: 3 kHz
Video-BW: 10 kHz
Input attenuation: 40 dB
Trace-Mode: Max-Hold
Detector-Mode: Pos Peak

Correction:
Directional coupler + 0.0 dB
Coaxial cable (C220) + 0.9 dB
DUT-Antenna (on-axis) + 0.0 dB
Test antenna + 0.0 dB
BW correction factor + 0.0 dB
Atten. between HPA and feedhorn + 0.0 dB
20 dB attenuator (U312) + 19.5 dB
10 dB attenuator(U311) + 9.7 dB
Power splitter + 6.7 dB
TOTAL CORRECTION: + 36.8 dB

Remarks:
Determination of the 'occupied bandwidth' at fh:
The measured value is about 174 kHz (delta marker)
Measurement with 3 kHz resolution filter and noise averaging.