

# FCC TEST REPORT

For

**Tablet**

**Model Number: 800P31C, 800P\*\*A, 800P\*\*B, 800P\*\*C**

**FCC ID: ROU00005**

**Report Number : WT138003996**

Test Laboratory	:	Shenzhen Academy of Metrology and Quality Inspection
		National Digital Electronic Product Testing Center
Site Location	:	No.4 Tongfa Road, Xili Town, Nanshan District, Shenzhen, Guangdong, China
Tel	:	0086-755-86928965
Fax	:	0086-755-86009898-31396
Web	:	<a href="http://www.smq.com.cn">www.smq.com.cn</a>

## TEST REPORT DECLARATION




Applicant : : Shenzhen KTC Technology Co., Ltd.  
Address : : The workshop No#1 , Northern Wuhe  
Road,Gangtou,Buji,Longgang,Shenzhen,China  
Manufacturer : : Shenzhen KTC Technology Co., Ltd.  
Address : : The workshop No#1 , Northern Wuhe  
Road,Gangtou,Buji,Longgang,Shenzhen,China  
EUT Description : : Tablet  
Model No : : 800P31C, 800P\*\*A, 800P\*\*B, 800P\*\*C  
Trade mark : : /  
Serial Number : : /  
FCC ID : : ROU00005

Test Standards:

**FCC Part 15 Subpart B 15.107, 15.109 (2012)**

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Project Engineer:	 (Liu Zheng)	Date:	Jan.26.2014
Checked by:	 (Yang Dong Ping)	Date:	Jan.26.2014
Approved by:	 (Lin Bin)	Date:	Jan.26.2014

## TABLE OF CONTENTS

<b>TEST REPORT DECLARATION.....</b>	<b>2</b>
<b>1. TEST RESULTS SUMMARY.....</b>	<b>4</b>
<b>2. GENERAL INFORMATION.....</b>	<b>5</b>
2.1. Report information.....	5
2.2. Laboratory Accreditation and Relationship to Customer .....	5
2.3. Measurement Uncertainty.....	5
<b>3. PRODUCT DESCRIPTION.....</b>	<b>6</b>
3.1. EUT Description .....	6
3.2. Block Diagram of EUT Configuration .....	7
3.3. Operating Condition of EUT .....	7
3.4. Support Equipment List.....	7
3.5. Test Conditions.....	7
3.6. Modifications .....	7
<b>4. TEST EQUIPMENT USED.....</b>	<b>8</b>
4.1. Test Equipment Used to Measure Conducted Disturbance.....	8
4.2. Test Equipment Used to Measure Radiated Disturbance.....	8
<b>5. CONDUCTED DISTURBANCE TEST .....</b>	<b>9</b>
5.1. Test Standard and Limit.....	9
5.2. Test Procedure .....	9
5.3. Test Arrangement .....	9
5.4. Test Data .....	9
<b>6. RADIATION DISTURBANCE TEST.....</b>	<b>12</b>
6.1. Test Standard and Limit.....	12
6.2. Test Procedure .....	12
6.3. Test Arrangement .....	12
6.4. Test Data .....	12

## 1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	FCC Rules	Test Results
Conducted Disturbance	15.107	Pass
Radiation Emission	15.109	Pass

Remark: "N/A" means "Not applicable."

## **2. GENERAL INFORMATION**

### **2.1. Report information**

- 2.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.
- 2.1.2. The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 2.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

### **2.2. Laboratory Accreditation and Relationship to Customer**

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at Bldg. of Metrology & Quality Inspection, Longzhu Road, Nanshan District, Shenzhen, Guangdong, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Committee for Laboratories (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is L0579.

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number are 446246 806614 994606(semi anechoic chamber).

The Laboratory is registered to perform emission tests with Industry Canada (IC), and the registration number is IC4174.

TUV Rhineland accredits the Laboratory for conformance to IEC and EN standards, the registration number is E2024086Z02.

Measurement Uncertainty

### **2.3. Measurement Uncertainty**

Conducted Emission

9kHz~30MHz 3.5dB

Radiated Emission

30MHz~1000MHz 4.5dB

1GHz~18GHz 4.6dB

### 3. PRODUCT DESCRIPTION

#### 3.1.EUT Description


Table 2 Specification of the Equipment under Test

Product Type:	800P31C, 800P**A, 800P**B, 800P**C
Hardware Version:	QP78C_MAIN PCB V1.1
Software Version :	0502HP77_QP78C_800P31CB15MX8E
FCC-ID:	ROU00005
Frequency:	GSM850/PCS1900MHz/WCDMA850MHz Wifi:2412MHz-2462MHz; Bluetooth: 2402MHz-2480MHz BLE: 2402MHz-2480MHz
Type(s) of Modulation :	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth: GFSK, pi/4DQPSK, 8DPSK BLE: GFSK
Antenna Type:	Built in type
Operating voltage:	3.7V-4.2V

Remark:

800P\*\*A , 800P\*\*B , 800P\*\*C ( 1st\* could be 0-99 or A-Z, means different client code; 2nd\* could be 0-99 or A-Z or blank, stands for the shape or color of enclosure,no impact on Products safety and EMC characteristics ) ; &&800\*\*\*\*\* ( & could be “ A-Z ” or “ a-z ” , \* could be “ 0-99 ” 、 “ A-Z ” 、 “ a-z ” 、 “ - ” 、 “ / ” or blank, means different client code,no impact on Products safety and EMC characteristics ) : 5VDC 2A

### 3.2. Block Diagram of EUT Configuration



Test mode 1

### 3.3. Operating Condition of EUT

Test mode 1: data transmitter with PC by USB port

The Radiated emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission (X plane).

### 3.4. Support Equipment List

Name	Model No	S/N	Manufacturer	FCC
Computer	9439	L3BDF2K	Lenovo	DOC
Keyboard (USB)	SK-8825 (L)	02553778	Lenovo	DOC
Mouse (USB)	MO28UOL	4418011108	Lenovo	DOC
Monitor	9227-AE1	V1TDB38	Lenovo	DOC
Printer	BJC-265SP	EVX81604	CANON	DOC
Adaptor for Printer	AD-300	---	CANON	DOC

### 3.5. Test Conditions

Date of test : Dec 21-Dec 29, 2013

Date of EUT Receive : Dec 18, 2013

Temperature: 22-24 °C

Relative Humidity: 53-57%

### 3.6. Modifications

No modification was made.

## 4. TEST EQUIPMENT USED

### 4.1. Test Equipment Used to Measure Conducted Disturbance

Table 2 Conducted Disturbance Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB3319	EMI Test Receiver	R&S	ESCS30	Jan.21,2013	1 Year
SB4357	AMN	R&S	ENV216	Jan.21,2013	1 Year

### 4.2. Test Equipment Used to Measure Radiated Disturbance

Table 3 Radiated Disturbance Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB3436	EMI Test Receiver	Rohde & Schwarz	ESI26	Jan.21,2013	1 Year
SB5472/02	Bilog Antenna	SCHWARZBECK	VULB9163	Jan.21,2013	1 Year
SB9422/16	Horn Antenna	Rohde & Schwarz	HF907	May.13.2013	1Year



## 5. CONDUCTED DISTURBANCE TEST

### 5.1. Test Standard and Limit

#### 5.1.1. Test Standard

FCC Part 15: Section 15.107

#### 5.1.2. Test Limit

Table 4 Conducted Disturbance Test Limit (Class B)

Frequency	Power Port limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15MHz ~ 0.5MHz	66~56*	56~46*
0.5MHz ~ 5 MHz	56	46
5 MHz ~ 30MHz	60	50

\* Decreasing linearly with logarithm of the frequency

### 5.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions form both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

### 5.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

### 5.4. Test Data

The emissions don' t show in following result tables are more than 20dB below the limits, the test curves are shown in the next page.

Table 5 Conducted Disturbance Test Data at mains Port

Model No.: 800P31C								
Test mode: data transmitter with PC by USB port								
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average		
			Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)
Line	0.170	9.7	37.9	47.6	65.0	22.4	32.1	55.0
	0.186	9.7	33.0	42.7	64.2	23.9	33.6	54.2
	0.394	9.7	26.6	36.3	58.0	20.7	30.4	48.0
	0.922	9.8	32.0	41.8	56	11.6	21.4	46
	1.315	9.8	27.3	37.1	56	10.3	20.1	46
	16.560	9.9	30.2	40.1	60	25.3	35.2	50
Neutral	0.222	9.7	26.7	36.4	62.7	15.0	24.7	52.7
	0.390	9.7	26.8	36.5	58.1	17.9	27.6	48.1
	2.230	9.9	20.5	30.4	56	13.3	23.2	46
	2.690	9.9	21.4	31.3	56	14.3	24.2	46
	3.460	9.9	20.5	30.4	56	13.0	22.9	46
	16.460	9.9	33.0	42.9	60	31.1	41.0	50


REMARKS: 1. Emission level(dBuV)=Read Value(dBuV) + Correction Factor(dB)

2. Correction Factor(dB) =LISN Factor (dB) + Cable Factor (dB)+Limiter Factor(dB)

3. The other emission levels were are more than 20dB below the limits.


### Conducted Disturbance

EUT: 800P31C  
 On Cond: Connect to PC  
 Test Spec: L  
 Comment: AC 120V60Hz  
 File name: 123456.SPC



## Conducted Disturbance

EUT: 800P31C  
Op Cond: Connect to PC  
Test Spec: N  
Comment: AC 120V60Hz  
File name: 123456.SPC



## 6. RADIATION DISTURBANCE TEST

### 6.1. Test Standard and Limit

#### 6.1.1. Test Standard

FCC Part 15: Section 15.109

#### 6.1.2. Test Limit

Table 6 Radiation Disturbance Test Limit for FCC (Class B)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

\* The lower limit shall apply at the transition frequency.

\* The test distance is 3m.

### 6.2. Test Procedure

The EUT is placed on a turntable, which is 0.8 meter above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set **3 meters** away from the receiving antenna, which is mounted on an antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna is used as a receiving antenna. Both horizontal and vertical polarization of the antenna is set on test. Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Detector function = peak; Set RBW = 1 MHz, VBW= 3MHz for  $f > 1$  GHz for peak measurement.

### 6.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

### 6.4. Test Data

The emissions don't show in following result tables are more than 20dB below the limits, the test curves are shown in the next page.

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Table 7 Radiated Disturbance Test Data

Frequency MHz	Cable Loss +pre amp(dB)	Antenna Factor(d B)	Readings(d B $\mu$ V/m)	Level(dB $\mu$ V/m)	Polarity(H/V )	Turntable Angle(de g)	Antenna Height(m )	Limits( dB $\mu$ V/m)	Margin(d B)
44.938	0.7	13.6	5.4	19.7	H	0	100	40.0	20.3
98.288	1.0	12.8	10.3	24.1	H	330	100	43.5	19.4
196.646	1.7	10.6	24.9	37.2	H	260	100	43.5	6.3
299.854	2.1	12.7	9.8	24.6	H	0	200	46.0	21.4
336.035	2.1	13.3	10.1	25.5	H	0	200	46.0	20.5
366.881	2.2	14.3	9.2	25.7	H	60	100	46.0	20.3
51.243	0.8	13.3	8.5	22.6	V	0	100	40.0	17.4
196.646	1.7	10.6	20.7	33.0	V	0	200	43.5	10.5
232.633	1.8	11.2	7.9	20.9	V	0	100	46.0	25.1
299.951	2.1	12.7	6.2	21.0	V	90	100	46.0	25.0
366.008	2.2	14.3	5.2	21.7	V	330	100	46.0	24.3
434.005	2.5	15.5	4.3	22.3	V	0	100	46.0	23.7
PK									
1067.500	-41.1	24.4	54.8	38.1	H	30	100	74	35.9
1159.000	-41.0	24.4	57.5	40.9	H	150	100	74	33.1
1339.500	-40.8	24.3	57.7	41.2	H	80	100	74	32.8
1499.500	-40.8	25.1	65.5	49.8	H	190	100	74	24.2
2099.000	-40.4	28.6	54.6	42.8	H	180	100	74	31.2
4482.500	-39.4	33.7	50.8	45.1	H	330	100	74	28.9
1069.500	-41.1	24.4	53.2	36.5	V	260	100	74	37.5
1159.000	-41.0	24.4	53.9	37.3	V	0	100	74	36.7
1349.500	-40.7	24.3	58.6	42.2	V	30	100	74	31.8
1499.500	-40.8	25.1	61.5	45.8	V	190	100	74	28.2
2665.500	-39.6	29.6	49.8	39.8	V	210	100	74	34.2
4446.500	-39.2	33.7	51.2	45.7	V	90	100	74	28.3
AV									
1067.500	-41.1	24.4	40.3	23.6	H	30	100	54	30.4
1159.000	-41.0	24.4	40.1	23.5	H	150	100	54	26.5
1339.500	-40.8	24.3	37.3	20.8	H	80	100	54	29.2
1499.500	-40.8	25.1	60.3	44.6	H	190	100	54	5.4
2099.000	-40.4	28.6	49.7	37.9	H	180	100	54	12.1
4482.500	-39.4	33.7	37.1	31.4	H	330	100	54	22.6
1069.500	-41.1	24.4	37.4	20.7	V	260	100	54	29.3
1159.000	-41.0	24.4	34.8	18.2	V	0	100	54	31.8
1349.500	-40.7	24.3	51.8	35.4	V	30	100	54	14.6
1499.500	-40.8	25.1	55.8	40.1	V	190	100	54	9.9
2665.500	-39.6	29.6	34.8	24.8	V	210	100	54	25.2
4446.500	-39.2	33.7	37.1	31.6	V	90	100	54	22.4

# Radiated Emission


## EUT Information

EUT Model name: 800P31C  
Operator Mode: Connect to PC  
Comment:

## Common Information

Test Description: SMQ NETC EMC Lab.3m Chamber  
Customer  
Antenna Position: Horizontal  
Operator Name:  
Comment1: AC 1120V/60Hz  
Comment2:

Field strength 30M-1GHz 1F 3m chamber



# Radiated Emission


## EUT Information

EUT Model name: 800P31C  
Operator Mode: Connect to PC  
Comment:

## Common Information

Test Description: SMQ NETC EMC Lab.3m Chamber  
Customer:  
Antenna Position: Vertical  
Operator Name:  
Comment1: AC 120V/60Hz  
Comment2:

Field strength 30M-1GHz 1F 3m chamber



# Radiated Emission


## EUT Information

EUT Model name: 800P31C  
Operator Mode: Connect to PC  
Comment:

## Common Information

Test Description: SMQ NETC EMC Lab.3m Chamber  
Customer  
Antenna Position: Horizontal  
Operator Name:  
Comment1: AC 120V/60Hz  
Comment2:

Field strength 1-6GHz 1F 3m chamber





# Radiated Emission

## EUT Information

EUT Model name: 800P31C  
Operator Mode: Connect to PC  
Comment:

## Common Information

Test Description: SMQ NETC EMC Lab.3m Chamber  
Customer:  
Antenna Position: Vertical  
Operator Name:  
Comment1: AC 120V/60Hz  
Comment2:

Field strength 1-6GHz 1F 3m chamber

