

FCC §15.247 (i), §2.1091 - RF Exposure

FCC ID: ROW-61821CE

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: *f* is frequency in MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

^{* =} Power density limit is applicable at frequencies greater than 100 MHz

^{* =} Plane-wave equivalent power density



MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna, R=0.2m

TEST RESULTS

MIMO Mode

	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenn a (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2	Result
8DPSK (BDR+EDR)	2±1	3	2.0	1.25 (0.97dBi)	0.000498	1	Pass
GFSK (BLE)	0±1	1	1.26	1.25 (0.97dBi)	0.000313	1	Pass
802.11b (2.4G Hz WIFI)	15±1	16	39.81	1.69 (2.27dBi)	0.013389	1	Pass
802.11a20 (U-NII-1)	15±1	16	39.81	1.79 (2.53dBi)	0.014181	1	Pass
802.11n20 (U-NII-2A)	11±1	12	15.85	1.29 (1.11dBi)	0.004069	1	Pass
802.11a20 (U-NII-3)	13±1	14	25.12	1.59 (2.01dBi)	0.007948	1	Pass



For the Max simultaneous transmission:

	Power Density (S) (mW/ cm2)	Total Power Density (S)	Limit	Result	
2.4GHz WIFI	0.013389	0.02757	4	Pass	
5GHz WIFI	0.014181	0.02757	_	rass	