



FCC §15.247 (i), §2.1091 – RF Exposure

# FCC ID: ROW-CDW61822CE

**Applied procedures / limit**

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

**Limits for Occupational / Controlled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

**Limits for General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

\* = Plane-wave equivalent power density



## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=0.2m

## TEST RESULTS

	max possible output power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
8DPSK (BDR+EDR)	7±1	8	6.31	1.585 (2dBi)	0.00199	1	Pass
GFSK (BLE)	6±1	7	5.01	1.585 (2dBi)	0.00158	1	Pass
802.11b (2.4G Hz WIFI) ANT A	15±1	16	39.81	1.585 (2dBi)	0.01255	1	Pass
802.11n20 (2.4G Hz WIFI) MIMO	12±1	13	19.95	3.170 (5.01dBi)	0.01258	1	Pass
802.11a20 (U-NII-1) ANT A	15±1	16	39.81	1.585 (2dBi)	0.01255	1	Pass
802.11n20 (U-NII-1) MIMO	14±1	15	31.62	3.170 (5.01dBi)	0.01994	1	Pass
802.11a20 (U-NII-3) ANT A	15±1	16	39.81	1.585 (2dBi)	0.01255	1	Pass
802.11n20 (U-NII-3) MIMO	14±1	15	31.62	3.170 (5.01dBi)	0.01994	1	Pass

**For the Max simultaneous transmission:**

	Power Density (S) (mW/ cm <sup>2</sup> )	Total Power Density (S)	Limit	Result
BDR+EDR	0.00199	0.01454	1	Pass
802.11a20 (U-NII-3) ANT A	0.01255			