











CHENZHEN



















CO.LTD







CHENZHEN















CO., LTD.





13. Duty Cycle Of Test Signal

13.1 Standard Requirement

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle. All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

13.2 Formula

$$\text{Duty Cycle} = \text{Ton} / (\text{Ton} + \text{Toff})$$



13.3 Test Procedure

1. Set span = Zero
2. RBW = 8MHz
3. VBW = 8MHz,
4. Detector = Peak


13.4 Test Result




Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (Hz)
NVNT	b	2412	100	0	10
NVNT	b	2437	100	0	10
NVNT	b	2462	100	0	10
NVNT	g	2412	100	0	10
NVNT	g	2437	100	0	10
NVNT	g	2462	100	0	10
NVNT	n20	2412	100	0	10
NVNT	n20	2437	100	0	10
NVNT	n20	2462	100	0	10
NVNT	n40	2422	100	0	10
NVNT	n40	2437	100	0	10
NVNT	n40	2452	100	0	10
NVNT	ax20	2412	100	0	10
NVNT	ax20	2437	100	0	10
NVNT	ax20	2462	100	0	10









TEST
 TO
 OVER
 検査












CO., LTD.





SHENZHEN








BCTC
 BCTC
 PPR
 本測



検査
 OVER
 TO
 TEST






14. Antenna Requirement

14.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


14.2 Test Result

The EUT antenna is PCB antenna, fulfill the requirement of this section.




15. EUT Photographs

EUT Photo



NOTE: Appendix-Photographs Of EUT Constructional Details





16. EUT Test Setup Photographs


Conducted Emissions Photo





Radiated Measurement Photos



C T
CT
PRO
测检



Above 1GHz



STATEMENT

1. The equipment lists are traceable to the national reference standards.
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The test report without CMA mark is only used for scientific research, teaching, enterprise product development and internal quality control purposes.
8. The quality system of our laboratory is in accordance with ISO/IEC17025.
9. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

E-Mail: bctc@bctc-lab.com.cn

***** **END** *****

