

Request for Modular Approval FCC ID: ROW+CDZ-N2EFR3200 ; IC: 23734+N2EFR32

| Item | Requirements   | EUT  |
|------|--|--|
| 1    | Have its own RF shielding  | Device is equipped with metal shielding to cover RF section. Refer to external photos.                   |
| 2    | Have buffered modulation/data inputs (if such inputs are provided)   | All inputs to the modules are buffered through logic and microprocessor inputs.                          |
| 3    | Have its own power supply regulation   | Module chipset incorporates voltage regulation to transceiver circuitry                                  |
| 4    | Meet the antenna requirements of section 15.203  | The device has a ceramic antenna and a dedicated antenna.  |
| 5    | Demonstrate compliance in a stand-alone configuration  | Device is tested in a test fixture in a standalone configuration   |
| 6    | The licensed module must have a FCC ID label on the module itself. That FCC ID label must be visible through a window on the final device or it must be visible when an access panel, door or cover is easily removed. If not, a second label must be placed on the outside of the final device that contains the following text: Contains "FCC ID: ROW+CDZ-N2EFR3200" | FCC ID label format will be included in the filling. Host ID label will be displayed on the host system. |
| 7    | The module must comply with all specific rules applicable to the transmitter. The grantee must provide comprehensive instructions to explain compliance requirements.  | Please refer to "User Manual" Exhibit  |
| 8    | The module must comply with RF exposure requirements. See FCC Rules. Spread Spectrum transmitters must comply with RF exposure limits in 15.247.   | RF exposure evaluation is exempted because of low output power.  |

Thank you for your attention to this matter.

Yours Sincerely,



Ivy Zhu, Certification Manager