

Standalone SAR test exclusion considerations

RF feature	Mode	Transmitting Frequency(MHz)	Test separation distance (mm)	ANT Gain (dBi)	Max. power with tune-up tolerance (dBm) ^{Note1}	Max. power with tune-up tolerance (mW)	Power thresholds	SAR test exclusion thresholds
Bluetooth(BDR)	1 Mbps	2 480.00	5.0	2.0	1.5	1.412 5	0.44	3.00
Bluetooth LE	1 Mbps	2 480.00	5.0	2.0	2.5	1.778 3	0.56	3.00

Note1. Please refet to the operation description for Max Tune-up power.

KDB 447498 D01 clause 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances \leq 50 mm

$[\text{max. power of channel, including tune-up tolerance, mW}] / [\text{min. test separation distance, mm}] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1g SAR and ≤ 7.5 for 10g extremity SAR

Sample Calculation

$$= [(1.4125 \text{mW} / 5 \text{mm})] \times [\sqrt{2.48 \text{GHz}}] = 0.44$$

Note. The calculation result was rounded to two decimal place for comparison.

Conclusion : SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required