

FCC Part 15

EMI TEST REPORT

of

E.U.T. : SEEFreeKit

MODEL : SFK306

FCC ID. : RPR3060101

for

APPLICANT : SEECODE Co., Ltd.

ADDRESS : 3rd Floor, Amin Bldg., 110-1, Yangjae-dong, Seocho-gu,
Seoul 137-891, Korea

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN
NO. 8 LANE 29, WENMIMG ROAD,
LOSHAN TSUN, KWEISHAN HSIANG,
TAOYUAN, TAIWAN, R.O.C.

Tel:(03)3280026#570~576
Fax:(03)3276188

Report Number : ET92S-12-142

TEST REPORT CERTIFICATION

Applicant : SEECODE Co., Ltd.
3rd Floor, Amin Bldg., 110-1, Yangjae-dong, Seocho-gu, Seoul 137-891, Korea

Manufacturer : SEECODE Co., Ltd.
3rd Floor, Amin Bldg., 110-1, Yangjae-dong, Seocho-gu, Seoul 137-891, Korea

Description of EUT :

- a) Type of EUT : SEEFreeKit
- b) Trade Name : SEEFreeKit
- c) Model No. : SFK306
- d) Power Supply : 10/12/24VDC

Regulation Applied : FCC Rules and Regulations Part 15 Subpart B & C (2003)

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note: 1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced except in full, without the written approval of ETC.

Issued Date : Dec. 25, 2003

Test Engineer : Anderson

Approve & Authorized Signer : Win-Po Tsai

Signature

Win-Po Tsai

Manager of EMC Testing Department
Electronics Testing Center, Taiwan

Table of Contents	Page
1 GENERAL INFORMATION	1
1.1 Product Description	1
1.2 Characteristics of Device	1
1.3 Test Methodology	1
1.4 Modification List of EUT	1
1.5 Test Facility	1
2 PROVISIONS APPLICABLE.....	2
2.1 Definition	2
2.2 Requirement for Compliance	3
2.3 Restricted Bands of Operation	5
2.4 Labeling Requirement.....	5
2.5 User Information	6
3. SYSTEM TEST CONFIGURATION	7
3.1 Justification.....	7
3.2 Devices for Tested System.....	7
4 RADIATED EMISSION MEASUREMENT	8
4.1 Applicable Standard.....	8
4.2 Measurement Procedure	8
4.3 Measuring Instrument	10
4.4 Radiated Emission Data.....	11
4.4.1 RF Portion.....	11
4.4.2 Other Emission	14
4.5 Field Strength Calculation	14
4.6 Photos of Radiation Measuring Setup	19
5 CONDUCTED EMISSION MEASUREMENT	20
6 ANTENNA REQUIREMENT	21
6.1 Standard Applicable.....	21
6.2 Antenna Construction and Directional Gain.....	21
7 20dB EMISSION BANDWIDTH MEASUREMENT	22
7.1 Standard Applicable.....	22
7.2 Measurement Procedure	22
7.3 Measurement Equipment	22
7.4 Measurement Data	23
8 OUTPUT POWER MEASUREMENT	27
8.1 Standard Applicable.....	27

8.2 Measurement Procedure	27
8.3 Measurement Equipment	27
8.4 Measurement Data	28
9 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT	32
9.1 Standard Applicable.....	32
9.2 Measurement Procedure	32
9.3 Measurement Equipment	32
9.4 Measurement Data	33
10 RADIATED MEASUREMENT AT BANDEDGE WITH FUNDAMENTAL FREQUENCIES ...	39
10.1 Standard Applicable.....	39
10.2 Measurement Procedure	39
10.3 Measuring Instrument	40
10.4 Radiated Emission Data.....	41
11 NUMBER OF HOPPING CHANNELS.....	42
11.1 Standard Applicable.....	42
11.2 Measurement Procedure	42
11.3 Measurement Equipment	42
11.4 Measurement Data	42
12 CHANNEL CARRIER FREQUENCIES SEPERATION	44
12.1 Standard Applicable.....	44
12.2 Measurement Procedure	44
12.3 Measurement Equipment	44
12.4 Measurement Data	45
13 POWER SPECTRAL DENSITY.....	49
13.1 Standard Applicable.....	49
13.2 Measurement Procedure	49
13.3 Measurement Equipment	49
13.4 Measurement Data	50
14 DWELL TIME	54
14.1 Standard Applicable.....	54
14.2 Measurement Procedure	54
14.3 Measurement Equipment	54
14.4 Measurement Data	54

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : SEEFreeKit
- b) Trade Name : SEEFreeKit
- c) Model No. : SFK306
- d) Power Supply : 10/12/24VDC

1.2 Characteristics of Device

Bluetooth enabled car hands-free system which is installed in cigar jack of the car

1.3 Test Methodology

The SEEFreeKit designed with a transmitting method of Frequency Hopping spread spectrum, which operates at 2.4 GHz ISM band. The rated output power is 0.33dBm (1.079 mW).

1.4 Modification List of EUT

No modifications were required. (That is the EUT complied with the requirements as tested.)

1.5 Test Facility

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C.

This site has been accreditation as a FCC filing site.

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business or industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following:

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

*Decreases with the logarithm of the frequency.

For intentional device, according to § 15.207(a) Line Conducted Emission Limits is same as above table.

(2) Radiated Emission Requirement

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

(4) 20dB Bandwidth Requirement

For frequency hopping systems, according to 15.247(a)(1), hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(5) Output Power Requirement

For frequency hopping systems, according to 15.247(1), operating in the 2400-2483.5MHz band employing at least 75 hopping channels. The maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in § 15.209(a), whichever results in the lesser attenuation.

(7) Number of Hopping Channels

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels.

(8) Channel Carrier Frequencies Separation

According to 15.247(a)(1)(iii), the frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(9) Dwell Time

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

(10) RF Exposure Evaluation

According to 15.247(b)(5), system operating under the provisions of this section(15.247) shall operate in a manner that ensures that the public is not exposed to radio frequency levels in excess of the commission guidelines, 1.1307(b)(1)

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

3. SYSTEM TEST CONFIGURATION


3.1 Justification

For the purposes of this test report ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT during the test. Notebook PC was used to control the RF channel under the highest, middle and lowest frequency and transmit the maximum RF power. Customer would not use it. But nevertheless ancillary equipment can influence the test results..

3.2 Devices for Tested System

Device	Manufacture	Model	Cable Description
* SEEFreeKit	SEECODE Co., Ltd.	SFK306	1.8m, Unshielded RS232 cable
Notebook PC	ASUS	L7245	1.8m, Unshielded Power Line (Adaptor)
DC power supply	GW	GW3030D	1.8m, Unshielded Power Line
Test Jig	----	----	0.01m, Unshielded Control Line

Remark “*” means equipment under test.



4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with § 15.109(a).

For intentional radiators, according to § 15.247 (a), operation under this provision is limited to frequency hopping and frequency hopping spread spectrum, and the out band emission shall be comply with § 15.247 (c)

4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
2. For emission frequencies measured below 1 GHz, it is performed in a semi-anechoic chamber to determine the accurate frequencies of higher emissions. For emission frequencies measured above 1 GHz, a pre-scan be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.

Note : A band pass filter was used to avoid pre-amplifier saturated when measure TX operation mode in frequency band above 1 GHz.

5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the datarate, placement of ANT. cables associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.	Next Cal. Due
EMI Test Receiver	Hewlett-Packard	8546A	08/27/2004
Horn Antenna	EMCO	3115	06/05/2004
LogBicone Antenna	Schwarzbeck	9160	10/28/2004
Horn Antenna	EMCO	3116	06/28/2004
Preamplifier	Hewlett-Packard	8449B	09/04/2004
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2004

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	300 kHz
	Spectrum Analyzer	Peak	120 kHz	300 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

4.4 Radiated Emission Data

4.4.1 RF Portion

a) Channel 1

Operation Mode : Transmitting/Receiving

Fundamental Frequency : 2402 MHz

Test Date : Dec. 25, 2003

Temperature : 18

Humidity : 60%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave	(H/V Max.)		
4804.000	---	---	---	---	2.5	---	---	74.0	54.0	---	---	---
12010.000	---	---	---	---	9.2	---	---	74.0	54.0	---	---	---
16216.000	---	---	---	---	8.9	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.
5. The estimated measurement uncertainty of the result measurement is:

±4.1dB(1GHz f 18GHz)

±4.4dB(18GHz< f 40GHz)

b) Channel 40

Operation Mode : Transmitting/Receiving

Fundamental Frequency : 2441 MHz

Test Date : Dec. 25, 2003 Temperature : 18 Humidity : 60%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave	(H/V Max.)		
4882.000	---	---	---	---	2.7	---	---	74.0	54.0	---	---	---
7323.000	---	---	---	---	5.9	---	---	74.0	54.0	---	---	---
12205.000	---	---	---	---	9.3	---	---	74.0	54.0	---	---	---
19528.000	---	---	---	---	8.5	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.
5. The estimated measurement uncertainty of the result measurement is:

 $\pm 4.1 \text{ dB}$ (1GHz \leq f \leq 18GHz) $\pm 4.4 \text{ dB}$ (18GHz < f \leq 40GHz)

c) Channel 79

Operation Mode : Transmitting/Receiving

Fundamental Frequency : 2480 MHz

Test Date : Dec. 25, 2003

Temperature : 18

Humidity : 60%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave	(H/V Max.)		
4960.000	---	---	---	---	2.8	---	---	74.0	54.0	---	---	---
7440.000	---	---	---	---	6.1	---	---	74.0	54.0	---	---	---
12400.000	---	---	---	---	9.4	---	---	74.0	54.0	---	---	---
19840.000	---	---	---	---	8.6	---	---	74.0	54.0	---	---	---
22320.000	---	---	---	---	10.1	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.
5. The estimated measurement uncertainty of the result measurement is:

 $\pm 4.1 \text{dB}(1\text{GHz} \leq f \leq 18\text{GHz})$ $\pm 4.4 \text{dB}(18\text{GHz} < f \leq 40\text{GHz})$

4.4.2 Other Emission

A.below 1GHz

Operation Mode: Transmitting/ Receiving Mode

Test Date : Dec. 25, 2003 Temperature : 18 Humidity : 60%

Emission Frequency (MHz)	Meter Reading (dBuV)		CORR'd Factor (dB)	Results (dBuV/m)		Limit (3m) (dBuV/m)	Margins (dB)	Table Degree (deg)		Ant. High (m)	
	HOR.	VERT.		HOR.	VERT.			HOR.	VERT.	HOR.	VERT.
62.980	***	20.2	8.4	***	28.6	40.0	-11.4	***	270	***	1.0
196.840	15.5	9.5	12.7	28.2	22.2	43.5	-15.3	120	273	1.2	1.0
206.540	***	14.7	12.7	***	27.4	43.5	-16.1	***	275	***	1.1
213.330	17.2	8.7	13.4	30.6	22.1	43.5	-12.9	118	223	1.4	1.0
227.880	15.9	***	13.4	29.3	***	46.0	-16.7	122	***	1.0	***
247.280	19.8	***	14.5	34.3	***	46.0	-11.7	145	***	1.0	***
288.990	***	16.3	16.5	***	32.8	46.0	-13.2	***	190	***	1.0
349.130	12.5	***	19.0	31.5	***	46.0	-14.5	223	***	1.1	***
465.530	***	9.4	21.3	***	30.7	46.0	-15.3	***	273	***	1.1
502.390	9.3	***	22.3	31.6	***	46.0	-14.4	120	***	1.2	***
521.790	19.5	***	22.3	41.8	***	46.0	-4.2	118	***	1.0	***
523.730	***	15.1	22.3	***	37.4	46.0	-8.6	***	27.3	***	1.0

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “***” means that the emissions level is too low to be measured.
3. Remark “#“ means the noise was low, so record the peak value.
4. Item “Margin” referred to Q.P. limit while there is only peak result.
5. The estimated measurement uncertainty of the result measurement is:

±4.6dB(30MHz f 300MHz)

±4.4dB(300MHz f 1GHz)

B.above 1GHz

The emission level is too low to be measured. Please see next pages for plotted data.

4.5 Field Strength Calculation


The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

where


Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss - Amplifier Gain

Horizontal




START 1.00GHz
*RBW 1.0MHz *VBW 1.0MHz
STOP 18.00GHz
SWP 340ms

Vertical




START 18.000GHz
*RBW 1.0MHz *VBW 1.0MHz STOP 25.000GHz
*RBW 1.0MHz *VBW 1.0MHz SWP 140ms

Horizontal




START 1.00GHz
RBW 1.0MHz *VBW 1.0MHz STOP 18.00GHz
*SWP 340ms

Vertical



START 18.000GHz
*RBW 1.0MHz *VBW 1.0MHz STOP 25.000GHz
SWP 140ms

4.6 Photos of Radiation Measuring Setup



5 CONDUCTED EMISSION MEASUREMENT

This EUT is excused from investigation of conducted emission, for it is powered by battery only. According to § 15.027 (d), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to § 15.247 (b), if Receiving antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.2 Antenna Construction and Directional Gain

Highly efficient special antennas fix on the PCB. The directional gain of antenna used for Receiving is typical 0dBi.

7 20dB EMISSION BANDWIDTH MEASUREMENT


7.1 Standard Applicable

According to 15.247(a)(1), for frequency hopping systems, hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Figure 4: Emission bandwidth measurement configuration.



7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Plotter	Hewlett-Packard	7550A	N/A
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2004

7.4 Measurement Data

Test Date : Dec. 25, 2003

Temperature : 18

Humidity: 60%


- a) Channel 01 : 20 dB Emission Bandwidth is 820 KHz
- b) Channel 40 : 20 dB Emission Bandwidth is 820 KHz
- c) Channel 79 : 20 dB Emission Bandwidth is 820 KHz


Note:


1. The estimated measurement uncertainty of the result measurement is:

: $\pm 1.5 \text{ dB}$ (1GHz f 18GHz)

2. Please see next pages for plotted data







8 OUTPUT POWER MEASUREMENT


8.1 Standard Applicable

For frequency hopping system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If Receiving antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz and VBW to 3 MHz.
4. Measure the highest amplitude appearing on spectral display and record the level to calculate result data.
5. Repeat above procedures until all frequencies measured were complete.

Figure 5: Output power and measurement configuration.



8.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Plotter	Hewlett-Packard	7550A	N/A
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2004

8.4 Measurement Data

Test Date : Dec. 25, 2003Temperature : 18Humidity: 60%

- a) Channel 01 : Output Peak Power is -0.83dBm or 0.826 mW
- b) Channel 40 : Output Peak Power is 0.33 dBm or 1.079 mW
- c) Channel 79 : Output Peak Power is 0 dBm or 1.000 mW


Note:


1. *The estimated measurement uncertainty of the result measurement is:*

:±1.5dB(1GHz f 18GHz)

2. *Please see next pages for plotted data*







9 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT

9.1 Standard Applicable

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in § 15.209(a), whichever results in the lesser attenuation.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Plotter	Hewlett-Packard	7550A	N/A
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2004

9.4 Measurement Data

Test Date : Dec. 25, 2003


Temperature : 18


Humidity: 60%


- a) Lower Band Edge : maximum value is -46.33 dBm that is attenuated more than 20dB
- b) Upper Band Edge : maximum value is -43.83 dBm that is attenuated more than 20dB


Note:


1. *The estimated measurement uncertainty of the result measurement is:
:±1.5dB(1GHz f 18GHz)*
2. *Please see next pages for plotted data*











10 RADIATED MEASUREMENT AT BANDEDGE WITH FUNDAMENTAL FREQUENCIES

10.1 Standard Applicable

According to 15.247(c), radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

10.2 Measurement Procedure

1. Setup the configuration per figure 2 for 2.39GHz and 2.4835GHz measured.
2. Set the spectrum analyzer on 1MHz resolution bandwidth for each frequency measured.
3. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
4. Repeat step 3 until all frequencies need to be measured were complete.
5. Repeat step 4 with search antenna in vertical polarized orientations.
6. Measurement applied to channel 1、40、79, recorded the result.

10.3 Measuring Instrument

The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.	Next Cal. Due
EMI Test Receiver	Hewlett-Packard	8546A	08/27/2004
Horn Antenna	EMCO	3115	06/05/2004
LogBicone Antenna	Schwarzbeck	9160	10/28/2004
Horn Antenna	EMCO	3116	06/28/2004
Preamplifier	Hewlett-Packard	8449B	09/04/2004
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2004

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
2390 & 2483.5	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

10.4 Radiated Emission Data

a) Channel 1

Operation Mode : Transmitting / Receiving

Fundamental Frequency : 2402 MHz

Test Date : Dec. 25, 2003

Temperature : 18

Humidity: 60%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave	(H/V Max.)		
2390.000	29.8	---	29.6	---	29.0	58.8	---	74.0	54.0	-15.2	120	1.1
2483.500	29.5	---	30.2	---	29.1	59.3	---	74.0	54.0	-14.7	270	1.0

b) Channel 40

Operation Mode : Transmitting / Receiving

Fundamental Frequency : 2441MHz

Test Date : Dec. 25, 2003

Temperature : 18

Humidity: 60%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave	(H/V Max.)		
2390.000	29.6	---	29.6	---	29.0	58.6	---	74.0	54.0	-15.4	120	1.0
2483.500	29.5	---	30.1	---	29.1	59.2	---	74.0	54.0	-14.8	272	1.0

c) Channel 79

Operation Mode : Transmitting / Receiving

Fundamental Frequency : 2480 MHz

Test Date : Dec. 25, 2003

Temperature : 18

Humidity: 60%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave	(H/V Max.)		
2390.500	29.6	---	29.6	---	29.0	58.6	---	74.0	54.0	-15.4	118	1.0
2483.500	29.6	---	30.8	---	29.1	59.9	---	74.0	54.0	-14.1	273	1.0

Note:

The estimated measurement uncertainty of the result measurement is:

$\pm 4.1 \text{ dB}$ (1GHz f 18GHz)

11 Number of Hopping Channels

11.1 Standard Applicable

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels

11.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set EUT to hopping operating mode and set spectrum analyzer maximum to measure the number of hopping channels.

11.3 Measurement Equipment


Equipment	Manufacturer	Model No.	Next Cal. Due
Plotter	Hewlett-Packard	7440A	N/A
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2004

11.4 Measurement Data

Test Date : Dec. 25, 2003 Temperature : 18 Humidity: 60%

Number of hopping channels = 79 channels

Note: Please see next pages for plotted data



12 Channel Carrier Frequencies Separation

12.1 Standard Applicable

According to 15.247(a)(1), the frequency hopping system shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

12.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measurement frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set spectrum analyzer maximum hold to measure channel carrier frequency , then adjust channel carrier frequency to adjacent channel.
4. Repeat above procedure until all measured frequencies were complete.

12.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Plotter	Hewlett-Packard	7550A	N/A
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2004

12.4 Measurement Data

Test Date : Dec. 25, 2003Temperature : 18Humidity: 60% %


- a) 2402MHz channel separation is 1.0MHz
- b) 2441MHz channel separation is 1.0MHz
- c) 2480MHz channel separation is 1.0MHz


Note:


1. *The estimated measurement uncertainty of the result measurement is:*

:±1.5dB(1GHz f 18GHz)

2. *Please see next pages for plotted data*







13 POWER SPECTRAL DENSITY


13.1 Standard Applicable

For frequency hopping system, according to 15.247(d), for digitally modulated, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

13.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 3kHz, VBW to 30 kHz, sweep 300kHz and sweep time 100 sec.
4. Measure the highest amplitude appearing on spectral display and record the level to calculate result data.
5. Repeat above procedures until all frequencies measured were complete.

Figure 5: Output power and measurement configuration.



13.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Plotter	Hewlett-Packard	7550A	N/A
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2004


13.4 Measurement Data


Test Date : Dec. 25, 2003Temperature : 18Humidity: 60%


- a) Channel 01 : Power Spectral Density is -12.83 dBm
- b) Channel 40 : Power Spectral Density is -12.00 dBm
- c) Channel 79 : Power Spectral Density is -12.67 dBm

Note:

1. *The estimated measurement uncertainty of the result measurement is:
:±1.0dB(1GHz f 18GHz)*
2. *Please see next pages for plotted datas*







14 Dwell Time

14.1 Standard Applicable

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

14.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5.

14.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Plotter	Hewlett-Packard	7550A	N/A
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2004

14.4 Measurement Data

Test Date : Dec. 25, 2003 Temperature : 18 Humidity: 60%

Test period=0.4(second/channel)×79 channel=31.6sec

- a) 2402MHz dwell time= $0.4233\text{ms} \times \frac{800}{79} \times 31.6 = 135.456\text{ms}$
- b) 2441MHz dwell time= $0.4233\text{ms} \times \frac{800}{79} \times 31.6 = 135.456\text{ms}$
- c) 2480MHz dwell time= $0.4233\text{ms} \times \frac{800}{79} \times 31.6 = 135.456\text{ms}$

Note: Please see next pages for plotted data

