

FCC TEST REPORT

The Reputation of LG Defense Industry Continues with NEX1 Future.

Locations & Offices

NEX1 GUMI

133 Gongdan-dong, Gumi, Gyongsangbuk-do,
730-030, Korea

Tel : +82-54-469-8213
Fax : +82-54-469-8065



Network Navigation

• SEOUL
• YONGIN
• GUMI

February 24, 2006

NEX 1 Future Co., Ltd.

TEST REPORT CERTIFICATION

Applicant : SEECODE Co., Ltd.

Adderss : 3rd Floor, Amin Bldg., 110-1 Yangjae-dong, Seocho-gu, Seoul,
Korea

EUT Name : Slim Headset

Model No. : VSH-511

Serial No. : Engineering Sample

FCCID : RPRVSH511

Testing location : Nex1 Future Co., Ltd.
133, Kongdan-Dong, Gumi-City, Kyeongsangbuk-Do, 730-030, R.O.K

Applied specification : FCC Part 15


Test result : The above mentioned test item passed.

Test Date February 24, 2006 **Review Date** February 24, 2006

Tested by Hyo-Jeung, Cho **Reviewed by** Jeong-Hi, Jin

Title Engineer **Title** EMC Manager

Signature


조효중

Signature


진경희

I HEREBY CERTIFY THAT the data shown in this report were made in accordance with the procedures given in the applied specification and I assume full responsibility for accuracy and completeness of these data.

Note : This test report relates to the a. m. test item. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products.

Contents

1. GENERAL INFORMATION.....	5
1.1 PRODUCT DESCRIPTION	5
1.2 PROJECT DATA.....	5
1.3 APPLICANT	5
1.4 MANUFACTURER	5
2. EUT INFORMATION.....	6
2.1 GENERAL EUT INFORMATION.....	6
2.2 CENTER FREQUENCY OF TESTED CHANNEL.....	6
2.3 TEST ENVIRONMENT	6
2.4 ACCESSORIES AND ANCILLARY EQUIPMENT	6
3. TESTING FACILITIES.....	7
4. EUT DESCRIPTION AND OPERATIONAL DESCRIPTION.....	7
5. TEST SET-UP.....	8
5.1 PRINCIPLE OF CONFIGURATION	8
5.2 OPERATIONAL MODES	8
5.3 APPLIED SPECIFICATION	8
6. TEST REPORT SUMMARY	9
7. TEST RESULTS	10
7.1 ANTENNA CONNECTOR REQUIREMENTS	10
7.2 AC CONNECTED EMISSION	11
7.3 CARRIER FREQUENCY SEPARATION.....	12
7.4 TIME OF OCCUPANCY(DWELL TIME)	14
7.5 20dB BANDWIDTH.....	16
7.6 NUMBER OF HOPPING FREQUENCIES REQUIREMENTS	20
7.7 PSEUDORANDOM FHS AND EQUAL HOPPING FREQUENCY USE REQUIREMENTS.....	22
7.8 RECEIVER INPUT BANDWIDTH REQUIREMENTS.....	23

7.9 PEAK OUTPUT POWER.....	24
7.10 BAND-EDGE COMPLIANCE.....	28
7.11 SPURIOUS CONDUCTED EMISSIONS	32
7.12 SPURIOUS RADIATED EMISSIONS	43
8. LIST OF TEST AND MEASUREMENT INSTRUMENTS	46

1. General Information

1.1 Product Description

Product Name : Slim Headset
Product ID : VSH-511
Serial No. : Prototype
FCC ID : RPRVSH511

1.2 Project data

Receipt of EUT : February 17, 2006
Date of Test : February 24, 2006
Data of report : February 24, 2006

1.3 Applicant

Company Name : SEECODE Co., Ltd.
Address : 3rd Floor, Amin Building, 110-1, Yangjae-dong, Seocho-gu,
Seoul 137-891, Korea
Contact Person : Mr. Knag Chi-jung

1.4 Manufacturer

Company Name : SEECODE Co., Ltd.
Address : 3rd Floor, Amin Building, 110-1, Yangjae-dong, Seocho-gu,
Seoul 137-891, Korea
Contact Person : Mr. Knag Chi-jung

2. EUT Information

2.1 General EUT Information

Type	Transmitter	Receiver
FCC Classification	FHSS Sequence Spread Spectrum (FHSS)	FHSS Sequence Spread Spectrum (FHSS)
Operating frequency range	2402 – 2480 MHz	2402 – 2480 MHz
Bands of operation	2.400 – 2.4835 GHz	2.400 – 2.4835 GHz
Number of Channels	79	79
Channel Separation	1MHz	1MHz
Type of Antenna	Dielectric Chip Antenna	Dielectric Chip Antenna
Power Supply	DC 3.7 V Lithium Ion	DC 3.7 V Lithium Ion

2.2 Center Frequency of Tested Channel

Frequency	Tx (MHz)	Rx (MHz)
Lowest	2402	2402
Middle	2441	2441
Highest	2480	2480

2.3 Test Environment

Temperature	25°C
Relative Humidity	30 ~ 60%
Voltage	DC 3.7V

2.4 Accessories and Ancillary Equipment

Equipment	Model No.	Serial Number	Maker
Laptop PC	PS428L-OE142	30014068J	Toshiba

3. Testing Facilities

Nex1 Future Co., Ltd.

133, Kongdan-Dong, Gumi-City, Kyeongsangbuk-Do, 730-030, R.O.K

4. EUT Description and Operational Description

VSH511 is a mobile phone headset with Bluetooth Wireless Technology.

It has excellent operating time which is over 5 hours talking, and startling 12 hours in waiting mode. It also features very good looking design so that if a customer ever lays his/her eyes on it a single moment, he/she would not be able to drop the thoughts of buying it.

This product has following specification :

Item	Description
Bluetooth Specification	V1.2
Supported Profile	Headset profile
Rx. Sensitivity	Typ. -70 dBm
Battery	3.7V, 125mAh Li-ion Polymer
Speaker	32Ω / 11Ø
MIC	-44dB / Omnidirectional
Low Power Current (Sniff Mode)	≤ 1 mA (Avg.)
Talking Current	23±3 mA (Avg.)
Standby Time (Sniff Mode)	≥ 120 Hr
Talking Time	≥ 5 Hr
Full Charging Time	≤ 2 Hr
Operating Temperature	-10℃ ~ 60℃
Operating Humidity	5% ~ 85% RH
Storage Temperature	-20℃ ~ 60℃
Storage Humidity	85% RH

5. Test Set-up

5.1 Principle of configuration

Conducted : The equipment under test (EUT) was configured with a temporary SMA Connector and EUT transmits the related packet type with PRBS 9 as payload.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes and test settings were adapted accordingly in reference to the instructions for use.

For details, please refer to the Operation mode in chapter 7.

5.2 Operational Modes

Page Scan,

Inquiry Scan

Hopping Mode

Fixed mode (2402Mhz, 2441Mhz and 2480Mhz)

5.3 Applied Specification

FCC Part 15

6. Test Report Summary

Related Clause	Test Cases	FCC Part Sections	Result (Note1)
7.1	Antenna Connector Requirements	15.203 15.204	C
7.2	AC Connected Emission	15.207	N/A
7.3	Carrier Frequency Separation	15.247	Pass
7.4	Time of Occupancy(Dwell time)	15.247	Pass
7.5	20dB Bandwidth	15.247	Pass
7.6	Number of Hopping Frequencies Requirements	15.247	C
7.7	Pseudorandom Frequency Hopping Sequence and Equal Hopping Frequency use Requirements	15.247	C
7.8	Receiver Input Bandwidth Requirements	15.247	C
7.9	Peak Output Power	15.247	Pass
7.10	Band-edge Compliance	15.247	Pass
7.11	Spurious Conducted emissions	15.247	Pass
7.12	Spurious Radiated emissions	15.247	Pass

* Note1: C: Complies, Pass: Passed, Fail : Failed and NA : Not Applicable

7. Test Results

7.1 Antenna Connector Requirements

Requirements

Subclause 15.203 and 15.204(c)

According to the Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to the Part 15.204(c), only the antenna with which an intentional radiator is authorized may be used with the intentional radiator.

Test results

RESULT:

Complies

The antenna is permanently attached on the PCB.

The EUT has a Dielectric Chip Antenna.

For more information on the antenna:

Antenna gain : 0 dBi

Manufacturer : AMOTECH Co., Ltd.

Model No. : AMAN542012SC01

Type : Dielectric Chip Antenna

7.2 AC Connected Emission

Test Mode and conditions

The power is supplied by a DC 3.7 V Lithium Ion and it does not operate during the charging.

Requirements

Subclause15.207(a)

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency of Emission (M Hz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test results

N/A

7.3 Carrier Frequency Separation

Test Mode and conditions

Mode of operation : Tx mode (hopping on), DH1 packet with PRBS9 payload
Measurement Method : Conducted
Detector : PK
Trace : Max hold
RBW/VBW : 100kHz/300kHz

Requirements


Subclause 15.247(a)(1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

Test results

Reference frequency (MHz)	Channel Separation (kHz)	Limit	Results
2441.000	990	Minimum of 25kHz or the 20dB bandwidth	Pass

Carrier Frequency Separation Plot



Date: 20.FEB.2006 09:18:17

7.4 Time of Occupancy(Dwell time)

Test Mode and conditions

Mode of operation : Tx mode(2441MHz), DH5 packet with PRBS9 payload
Measurement Method : Conducted
Detector : PK
Trace : Max hold
RBW/VBW : 1MHz/3MHz

Requirements

Subclause 15.247(a)(1)(iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 75 hopping frequencies. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

Test results

The system makes 1600 hops per second or has a length of 625us.


Let take DH5 packet in worst case. A DH5 packet has 5 slots for transmitting and 1 slot for receiving. It means it can have maximum 266.67 ($=1600/6$) hops per second.

Therefore it has 3.38 hops($=266.67/79$) per second for each channel.

And it has 106.81hops appearance for 31.6 seconds ($= 0.4 \times 79 \text{ channels}$).

Length per slot(L)	Number slots (N)	Dwell Time (=L*N)	Limit	Results
2.960 ms	106.81	316.1576 ms	0.4 seconds	Pass

Time of Occupancy Plot



Date: 20.FEB.2006 09:32:05

7.5 20dB Bandwidth**Test Mode and conditions**

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz),
DH5 packet with PRBS9 payload
Measurement Method : Conducted
Detector : PK
Trace : Max hold
RBW/VBW : 30kHz/100kHz

Requirements**Subclause 15.247(a)(1)**

It is mentioned implicitly as the maximum 20dB bandwidth of the hopping channel is 1Mhz.

Test results

Operating frequency (MHz)	20dB Bandwidth (MHz)	Limit	Results
2402	0.796	< 1 Mhz	Pass
2441	0.796	< 1 Mhz	Pass
2480	0.788	< 1 Mhz	Pass

20dB Bandwidth Plot – 2402Mhz



Date: 20.FEB.2006 09:39:30

20dB Bandwidth Plot – 2441Mhz



Date: 20.FEB.2006 09:41:50

20dB Bandwidth Plot – 2480Mhz



Date: 20.FEB.2006 09:44:43

7.6 Number of Hopping Frequencies Requirements

Test Mode and conditions

Mode of operation : Hopping, DH1 with PRBS9 payload
Measurement Method : Conducted
Detector : PK
Trace : Max hold
RBW/VBW : 100kHz/300kHz

Requirements


15.247(b)(1)

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels,

Test results

Operating frequency (MHz)	Number of Hopping	Limit	Results
2402~2480	79	≥ 15	Pass

Number of Hopping Frequencies Plot



Date: 20.FEB.2006 09:50:53

7.7 Pseudorandom FHS and Equal Hopping Frequency use Requirements

Requirements

Subclause 15.247 (a)(1)


The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter.

RESULT

Complies

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master. For details, refer to the figure 1. The X input determines the phase in the 32-hop segment, whereas Y1 and Y2 selects between master-to-slave and slave-to-master transmission. The inputs A to D determine the ordering within the segment, the inputs E and F determine the mapping onto the hop frequencies.

The algorithm in the Bluetooth specifications shows that each of its hopping channels is used equally on average also.



< Figure 1 : Block diagram of hop selection kernel for 79 hop system >

7.8 Receiver Input Bandwidth Requirements

Requirements

Subclause 15.247 (a)(1)

The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in the synchronization with the transmitted signals.

RESULT

Complies

The receiver bandwidth is equal to the receiver bandwidth in the 79 hopping channel mode, which is 1 MHz. The receiver bandwidth is indirectly verified during Bluetooth RF conformance testing.

7.9 Peak Output Power

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz),
DH1 packet with PRBS 9 payload
Measurement Method : Conducted
Detector : PK
Trace : Max hold
RBW/VBW : 1MHz/3MHz

Requirements


Subclause 15.247(b)(1)

For frequency hopping systems operating in the 2400~2483.5 Mhz band employing at least 75hopping channels, the maximum output power of the intentional radiator shall not exceeded 1 watt.

Test results


Operating Frequency (MHz)	Reading (dBm)	Cable attenuation (dB)	Actual Value (W)	Limit (W)	Results
2402	-0.83	1.80	0.001250259	<1.0	Pass
2441	-0.58	1.83	0.001333500	<1.0	Pass
2480	-1.02	1.85	0.001210598	<1.0	Pass

Peak Output Power Plot - 2402




Date: 20.FEB.2006 09:53:34

Peak Output Power Plot – 2441



Date: 20.FEB.2006 09:54:45

Peak Output Power Plot – 2480



Date: 20.FEB.2006 09:10:37

7.10 Band-edge Compliance

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet
Measurement Method : Conducted
Detector : PK
Trace : Max hold
RBW/VBW : 300kHz/1.0MHz

Requirements

Subclause 15.247(d)


In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Test results

There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency.


Tx Frequency (MHz)	RF power outside 100kHz BW (MHz)	Limit	Results
2402	No peak above 20dB	20dB below	Pass
2441	No peak above 20dB	20dB below	Pass
2480	No peak above 20dB	20dB below	Pass

Band-edge Compliance Plot - 2402




Date: 20.FEB.2006 10:00:45

Band-edge Compliance Plot – 2441



Date: 20.FEB.2006 10:03:54

Band-edge Compliance Plot – 2480



Date: 20.FEB.2006 10:06:23

7.11 Spurious Conducted emissions

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet
 Measurement Method : Conducted
 Detector : PK
 Trace : Max hold
 RBW/VBW : 100kHz/300kHz

Requirements

Subclause 15.247(d)

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.


Test results

Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
<i>Operating frequency : 2402MHz</i>					
9621.14	-53.01	3.4	-49.61	-20.830	28.78
17960	-51.70	6.7	-45.00	-20.830	24.17
20000	-48.21	6.7	-41.51	-20.830	20.68

Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
<i>Operating frequency : 2441MHz</i>					
9780.66	-49.99	3.4	-46.59	-20.580	26.01
13680	-52.02	6.7	-45.32	-20.580	24.74
20050	-48.21	6.7	-41.51	-20.580	20.93


Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
<i>Operating frequency : 2480MHz</i>					
9920.24	-51.10	3.4	-47.70	-21.020	26.68
13620	-51.60	6.0	-45.60	-21.020	24.58
20000	-47.32	6.7	-40.62	-21.020	19.60

Spurious Conducted emissions plot- 2402 (30MHz~10GHz)




Date: 20.FEB.2006 11:13:00

Spurious Conducted emissions plot- 2402 (10GHz~20GHz)




Date: 20.FEB.2006 10:19:04

Spurious Conducted emissions plot- 2402 (20GHz~25GHz)




Date: 20.FEB.2006 10:21:49

Spurious Conducted emissions plot- 2441 (30MHz~10GHz)




Date: 20.FEB.2006 10:26:14

Spurious Conducted emissions plot- 2441 (10GHz~20GHz)




Date: 20.FEB.2006 10:29:02

Spurious Conducted emissions plot- 2441 (20GHz~25GHz)




Date: 20.FEB.2006 10:31:35

Spurious Conducted emissions plot- 2480 (30MHz~10GHz)




Date: 20.FEB.2006 10:34:41

Spurious Conducted emissions plot- 2480 (10GHz~20GHz)



Date: 20.FEB.2006 10:37:24

Spurious Conducted emissions plot- 2480 (20GHz~25GHz)



Date: 20.FEB.2006 10:42:44

7.12 Spurious Radiated emissions

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz),
DH1 packet
Detector : PK
Trace : Max hold
Measurement Method : Radiated- Enclosure
Measurement Distance : 3m
Measurement BW : 1 MHz for $f \geq 1$ GHz, 100kHz for $f < 1$ GHz

Requirements

Subclause 15.247(d)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to Section 15.209(a) , except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Field strength (dB μ V/m)	Measurement distance (meters)
30-88	100**	$20 \cdot \log(100) = 40.0$	3
88-216	150**	$20 \cdot \log(150) = 43.5$	3
216-960	200	$20 \cdot \log(200) = 46.0$	3
960-2500	500	$20 \cdot \log(500) = 54.0$	3

** Except as provided in paragraph(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72Mhz, 76-88Mhz, 174-216Mhz or 470-806Mhz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

According to section 15.35(b), on any frequency or frequencies above 1000 MHz the radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission

measurements are specified in this part, including emission measurements below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated

Test results

Frequency (MHz)	Polariz- ation (H/V)	Corr. Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)		Table Angle (Deg.)	Ant. Height (m)
			A	P	A	P	A	P		
Operating frequency : 2402Mhz										
4804	V	16.3	42.9	54.3	54	74	11.1	19.7	40	1.5
9605	V	23.6	42.4	54.5	54	74	11.6	19.5	40	1.5
4804	H	16.3	38.7	50.4	54	74	15.3	23.6	120	1.5

Frequency (MHz)	Polariz- ation (H/V)	Corr. Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)		Table Angle (Deg.)	Ant. Height (m)
			A	P	A	P	A	P		
Operating frequency : 2441Mhz										
4882	V	16.4	42.5	54.0	54	74	11.5	20.0	40	1.5
9760	V	23.8	41.0	56.6	54	74	13.0	17.4	40	1.5
4882	H	16.4	36.9	49.6	54	74	17.1	24.4	120	1.5

Frequency (MHz)	Polarization (H/V)	Corr. Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)		Table Angle (Deg.)	Ant. Height (m)
			A	P	A	P	A	P		
Operating frequency : 2480Mhz										
4960	V	16.4	38.0	50.5	54	74	16.0	23.5	40	1.5
7440	V	20.4	41.0	51.5	54	74	13.0	22.5	40	1.5
4960	H	16.4	36.0	48.9	54	74	18.0	25.1	120	1.5
7440	H	20.4	37.9	50.2	54	74	16.1	23.8	120	1.5

* Note :

1. Remark "*" means that the emission frequency is produced by local oscillator.
2. Remark "- -" means that the emission level is too low to be measured.
3. The measurement uncertainty of the radiated emission test is $\pm 3\text{dB}$
4. "A" and "P" mean average and peak measurement respectively.
5. There are no spurious emissions found between the lowest internal oscillating frequency and 30 MHz.

8. List of Test and Measurement Instruments

	Kind of Equipment	Type	Manufacturer	S/N
☒	EMI Test Receiver	ESI26	R/S	8340.0010.02
☒	Spectrum Analyzer	FSP30	R/S	1093.4495.30
☐	Tracking Generator	ESMI-B1	R/S	1033.3240.52
☐	Spectrum Analyzer	8566B	HP	3638A0857E
☐	Spectrum Analyzer	E4407B	HP	MY41310181
☒	Wave Dipole Antenna	HZ-12	R/S	842006/0012
☒	Wave Dipole Antenna	HZ-12	R/S	846556/0004
☒	Biconical Antenna	3104C	EMCO	9408-4667
☐	Biconical Antenna	3109	EMCO	9405-2812
☒	Log-Periodic Antenna	3146A	EMCO	1064
☒	Biconilog Antenna	HLP2603	EMC Automaion	080100
☐	V-Network	ESH3-Z5	R/S	847265/030
☐	V-Network	ESH3-Z6	R/S	847250/016
☐	T-Network	E-Z10	R/S	84480/011
☐	LISN	3825/2	EMCO	9502-2334
☒	Turn Table	2081	EMCO	
☒	Antenna Tower	1072-5	EMCO	9202-1651
☒	Positioning Controller	1090	EMCO	
☐	Printer	C4569A	HP	SG78K1H1FS
☒	Absorbing Clamp	MDS 21	R/S	847905/005
☐	Signal Generator	2023	MARCONI	112246067
☐	Swept Signal Generator	83620B	HP	3722A00549
☐	10dB Attenuator	23-10-34	Weinschel co	BD4316
☐	10dB Attenuator	33-10-34	Weinschel co	BB9784
☒	Antenna	3142	EMCO	9710-1220
☒	Antenna	3115	EMCO	9202-3820
☒	Antenna	3160-08	EMCO	1168

☒	Antenna	3160-09	EMCO	1304
☒	Amplifier	HP8447F	HP	3113A06911
☒	Amplifier	HP83006	HP	3104A00611
☒	Amplifier	HP8449B	HP	3008A00859
☒	EMI test receiver	ESCS30	R&S	839809/003
☒	Artificial mains network	ESH2-Z5	R&S	829991/009
☒	Artificial hand	FCC-AH-1	Fischer custom communications Inc.	2008