



# FCC TEST REPORT

**REPORT NO.:** RF920605H05C

**MODEL NO.:** GW21W-MAXI

**RECEIVED:** Nov. 27, 2003

**TESTED:** Nov. 27 to Dec. 16, 2003

**APPLICANT:** ATOP TECHNOLOGIES, INC.

**ADDRESS:** 3F, No.8, Prosperity Rd.II, Science-Based  
Industrial Park, Hsinchu, Taiwan, R.O.C

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien,  
Taiwan, R.O.C.

This test report consists of 45 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample.



0536  
ILAC MRA



## Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS .....	5
3	GENERAL INFORMATION .....	6
3.1	GENERAL DESCRIPTION OF EUT .....	6
3.2	DESCRIPTION OF TEST MODES .....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS.....	7
3.4	DESCRIPTION OF SUPPORT UNITS .....	8
4	TEST TYPES AND RESULTS .....	9
4.1	CONDUCTED EMISSION MEASUREMENT.....	9
4.1.1	TEST INSTRUMENTS.....	9
4.1.2	TEST PROCEDURES .....	10
4.1.3	DEVIATION FROM TEST STANDARD .....	10
4.1.4	TEST SETUP.....	11
4.1.5	EUT OPERATING CONDITIONS.....	12
4.1.6	TEST RESULTS .....	13
4.2	RADIATED EMISSION MEASUREMENT .....	15
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	15
4.2.2	TEST INSTRUMENTS.....	16
4.2.3	TEST PROCEDURES .....	17
4.2.4	DEVIATION FROM TEST STANDARD .....	17
4.2.5	TEST SETUP.....	18
4.2.6	EUT OPERATING CONDITIONS.....	18
4.2.7	TEST RESULTS .....	19
4.3	6dB BANDWIDTH MEASUREMENT .....	23
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	23
4.3.2	TEST INSTRUMENTS.....	23
4.3.3	TEST PROCEDURE.....	24
4.3.4	DEVIATION FROM TEST STANDARD .....	24
4.3.5	TEST SETUP.....	24
4.3.6	EUT OPERATING CONDITIONS.....	24
4.3.7	TEST RESULTS .....	25
4.4	MAXIMUM PEAK OUTPUT POWER.....	29
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	29
4.4.2	INSTRUMENTS.....	29
4.4.3	TEST PROCEDURES .....	30
4.4.4	TEST SETUP.....	30
4.4.5	EUT OPERATING CONDITIONS.....	30
4.4.6	TEST RESULTS .....	31



4.4.7	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT.....	32
4.4.8	TEST INSTRUMENTS.....	32
4.4.9	TEST PROCEDURE.....	33
4.4.10	DEVIATION FROM TEST STANDARD .....	33
4.4.11	TEST SETUP.....	33
4.4.12	EUT OPERATING CONDITION.....	33
4.4.13	TEST RESULTS .....	34
4.5	BAND EDGES MEASUREMENT .....	38
4.5.1	LIMITS OF BAND EDGES MEASUREMENT.....	38
4.5.2	TEST INSTRUMENTS.....	38
4.5.3	TEST PROCEDURE.....	38
4.5.4	DEVIATION FROM TEST STANDARD .....	38
4.5.5	EUT OPERATING CONDITION.....	39
4.5.6	TEST RESULTS .....	39
4.6	ANTENNA REQUIREMENT .....	42
4.6.1	STANDARD APPLICABLE.....	42
4.6.2	ANTENNA CONNECTED CONSTRUCTION.....	42
5	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	43
6	INFORMATION ON THE TESTING LABORATORIES.....	45



# 1 CERTIFICATION

**PRODUCT :** Wireless Serial Server  
**MODEL NO. :** GW21W-MAXI  
**BRAND :** ATOP  
**APPLICANT :** ATOP TECHNOLOGIES, INC.  
**STANDARDS :** 47 CFR Part 15, Subpart C (Section 15.247)  
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Nov. 27 to Dec. 16, 2003. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

**PREPARED BY:** Midoli Peng , **DATE:** Mar. 18, 2004  
( Midoli Peng )

**APPROVED BY:** Eric Lin , **DATE:** Mar. 18, 2004  
( Eric Lin, Manager )



## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: 47 CFR Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>REMARK</b>
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -15.02dBuV at 0.244MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -1.50dBuV at 600.05MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Wireless Serial Server
<b>MODEL NO.</b>	GW21W-MAXI
<b>POWER SUPPLY</b>	24VDC from AC Adapter
<b>MODULATION TYPE</b>	DBPSK for 1Mbps DQPSK for 2Mbps CCK for 5.5/11Mbps
<b>RADIO TECHNOLOGY</b>	DSSS, CCK
<b>TRANSFER RATE</b>	1/2/5.5/11Mbps
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>OUTPUT POWER</b>	14.50dBm
<b>DATA CABLE</b>	NA
<b>ANTENNA TYPE</b>	Dipole Antenna
<b>I/O PORTS</b>	2 ComPorts
<b>ASSOCIATED DEVICES</b>	Please see note 2

1. The EUT was powered by the following power adapter ( Just for test but not for sale):

<b>Brand:</b>	DEER
<b>Model No.:</b>	AD1524C
<b>Input power:</b>	AC100-240V, 0.5A, 50/60Hz
<b>Output power:</b>	DC24V, 0.6A DC Output Cable: 1.8m/nonshielded/without core

2. The EUT could be assembled with following module as defined by the client:

<b>Brand:</b>	ATOP
<b>Product name</b>	Wireless Serial Server Module
<b>Model No.:</b>	GW21SW-MAXI(C)

3. For more detailed features description, please refer to the manufacturer's specifications or User's Manual.



### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

**NOTE:**

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an Wireless Serial Server . According to the specifications of the manufacturer, it must comply with therequirements of the following standards:

**47 CFR Part 15, Subpart C. (15.247)**


**ANSI C63.4 : 1992**

All tests have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral. It has been verified to comply with the requirements of 47 CFR Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



### 3.4 DESCRIPTION OF SUPPORT UNITS



**NOTE:** 1 Please refer to the photos of test configuration in Item 5 also.





## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	CONDUCTED LIMIT (DB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

- NOTES:**
- (1) The lower limit shall apply at the transition frequencies.
  - (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
  - (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.1 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	847124/029	Nov. 17, 2004
ROHDE & SCHWARZ LISN (for EUT)	ESHS-Z5	848773/004	Nov. 13, 2004
KYORITSU LISN (for peripheral)	KNW-407	8/1395/12	Jul. 23, 2004
RF Cable (JETBAO)	RG233/U	Cable_CA_01	Jul. 03, 2004
Terminator(for KYORITSU)	50	3	Apr. 11, 2004
Software	Cond-V2e	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in ADT Shielded Room No. A.
  3. The VCCI Con A Registration No. is C-817.




#### 4.1.2 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



#### 4.1.5 EUT OPERATING CONDITIONS

- a. Turned on the power of EUT.
- b. EUT was set up under full load condition.




4.1.6 TEST RESULTS

<b>EUT</b>	Wireless Serial Server	<b>MODEL</b>	GW21W-MAXI
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 50%RH, 982 hPa	<b>TESTED BY</b>	Eric Lee

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.240	0.20	44.61	-	44.81	-	62.10	52.10	-17.29	-
2	0.364	0.20	38.26	-	38.46	-	58.64	48.64	-20.18	-
3	0.487	0.21	36.15	-	36.36	-	56.23	46.23	-19.86	-
4	0.974	0.30	36.51	-	36.81	-	56.00	46.00	-19.19	-
5	2.302	0.32	31.54	-	31.86	-	56.00	46.00	-24.14	-
6	23.129	1.23	19.31	-	20.54	-	60.00	50.00	-39.46	-

- NOTES:** (1) "\*\*": Undetectable  
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.  
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.  
 (4) The emission levels of other frequencies were very low against the limit.  
 (5) Correction Factor = Insertion loss + Cable loss  
 (6) Margin value = Emission level - Limit value






<b>EUT</b>	Wireless Serial Server	<b>MODEL</b>	GW21W-MAXI
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 50%RH, 982 hPa	<b>TESTED BY</b>	Eric Lee

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.244	0.20	46.75	-	46.95	-	61.97	51.97	-15.02	-
2	0.366	0.20	40.61	-	40.81	-	58.59	48.59	-17.78	-
3	0.498	0.22	35.37	-	35.59	-	56.04	46.04	-20.45	-
4	0.611	0.24	36.08	-	36.32	-	56.00	46.00	-19.68	-
5	2.322	0.32	31.50	-	31.82	-	56.00	46.00	-24.18	-
6	22.141	1.09	22.53	-	23.62	-	60.00	50.00	-36.38	-

- NOTES:** (1) "\*\*": Undetectable  
 (2) Q.P. and AV. are abbreviations of quasi-peak and average.  
 (3) "-": The Quasi-peak reading value also meets an average limit, thus measurement with the average detector is unnecessary.  
 (4) The emission levels of other frequencies were very low against the limit.  
 (5) Correction Factor = Insertion loss + Cable loss  
 (6) Margin value = Emission level - Limit value





## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
HP Spectrum Analyzer	8594ER	3829U04676	Jul. 14, 2004
ADVANTEST Spectrum Analyzer	R3271A	85060311	May 21, 2004
CHASE RF Pre_Amplifier	CPA9232	1057	Apr. 24, 2004
HP Pre_Amplifier	8449B	3008A01281	June 27, 2004
ROHDE & SCHWARZ Test Receiver	ESVS 10	849231 /019	Nov. 03, 2004
CHASE Broadband Antenna	CBL6111c	2730	Jul 17, 2004
Schwarzbeck Horn_Antenna	3115	5619	Jul. 17, 2004
SCHWARZBECK Tunable Dipole Antenna	UHAP	897	Mar. 07, 2005
SCHWARZBECK Tunable Dipole Antenna	VHAP	880	Mar. 07, 2005
RF Switches (ARNITSU)	CS-201	1565157	Dec. 01, 2004
RF CABLE (Chaintek) 1GHz-20GHz	SF102	22054-2	Feb. 10. 2004
RF Cable(RICHTEC)	9913-30M	STCCAB-30M- 1GHz-021	Nov. 5, 2004
Software	AS60P8	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
CHANCE MOST Turn Table	TT-100	0203	NA

Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Tunable Dipole Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.

2. \* = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. C.
5. The FCC Site Registration No. is 656396.
6. The VCCI Site Registration No. is R-1626.
7. The CANADA Site Registration No. is IC 3789-C.





#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6



4.2.7 TEST RESULTS

<b>EUT</b>	Wireless Serial Server	<b>MODEL</b>	GW21W-MAXI
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 65%RH, 982 hPa	<b>TESTED BY</b>	Mitch Jen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	36.05	32.00 QP	40.00	-8.00	1.00 H	122	15.40	16.60
2	200.00	25.00 QP	43.50	-18.50	1.32 H	278	14.90	10.10
3	300.04	36.90 QP	46.00	-9.10	1.01 H	303	21.50	15.40
4	310.81	31.40 QP	46.00	-14.60	1.01 H	29	15.70	15.70
5	400.02	34.10 QP	46.00	-11.90	1.12 H	116	15.50	18.70
6	500.06	38.00 QP	46.00	-8.00	1.27 H	258	16.40	21.60
7	600.09	34.50 QP	46.00	-11.50	1.59 H	220	11.70	22.90
8	700.06	35.20 QP	46.00	-10.80	1.61 H	271	10.50	24.70
9	800.06	35.70 QP	46.00	-10.30	1.80 H	333	9.70	26.00
10	900.10	37.50 QP	46.00	-8.50	1.77 H	226	9.70	27.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	48.28	33.60 QP	40.00	-6.40	1.00 V	243	23.70	10.00
2	132.00	33.30 QP	43.50	-10.20	1.37 V	91	20.60	12.70
3	199.99	29.70 QP	43.50	-13.80	1.49 V	299	19.60	10.10
4	265.50	35.00 QP	46.00	-11.00	1.39 V	193	19.70	15.30
5	300.03	34.70 QP	46.00	-11.30	1.36 V	338	19.30	15.40
6	400.03	37.40 QP	46.00	-8.60	1.54 V	198	18.70	18.70
7	500.06	37.00 QP	46.00	-9.00	1.95 V	40	15.30	21.60
<b>8</b>	<b>600.05</b>	<b>44.50 QP</b>	<b>46.00</b>	<b>-1.50</b>	<b>1.02 V</b>	<b>68</b>	<b>21.60</b>	<b>22.90</b>
9	700.08	40.40 QP	46.00	-5.60	1.07 V	235	15.70	24.70
10	800.09	39.50 QP	46.00	-6.50	1.55 V	204	13.50	26.00

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



<b>EUT</b>	Wireless Serial Server	<b>MODEL</b>	GW21W-MAXI
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	1000 ~ 25000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 57%RH, 982 hPa	<b>TESTED BY</b>	Tony Chen

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2038.00	43.30 PK	74.00	-30.70	1.12 H	28	13.90	29.30
2	2390.00	43.30 PK	74.00	-30.70	1.27 H	247	12.90	30.40
3	*2412.00	100.40 PK			1.16 H	8	69.80	30.50
3	*2412.00	93.50 AV			1.16 H	8	63.00	30.50
4	4076.00	43.30 PK	74.00	-30.70	1.76 H	15	9.30	34.00
5	4824.00	41.40 PK	74.00	-32.60	1.58 H	192	5.20	36.20
6	7236.00	47.00 PK	74.00	-27.00	1.31 H	136	5.30	41.70

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2038.00	47.20 PK	74.00	-26.80	1.08 V	225	17.80	29.30
2	2390.00	48.40 PK	74.00	-25.60	1.04 V	257	18.00	30.40
3	*2412.00	105.30 PK			1.33 V	5	74.80	30.50
3	*2412.00	98.00 AV			1.33 V	5	67.40	30.50
4	4076.00	44.60 PK	74.00	-29.40	1.44 V	182	10.60	34.00
5	4824.00	45.40 PK	74.00	-28.60	1.24 V	43	9.20	36.20
6	7236.00	45.90 PK	74.00	-28.10	1.12 V	124	4.20	41.70

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



<b>EUT</b>	Wireless Serial Server	<b>MODEL</b>	GW21W-MAXI
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	1000 ~ 25000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 57%RH, 982 hPa	<b>TESTED BY</b>	Tony Chen

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2063.00	42.30 PK	74.00	-31.70	1.18 H	21	12.90	29.40
2	*2437.00	100.80 PK			1.15 H	0	70.10	30.70
2	*2437.00	94.00 AV			1.15 H	0	63.30	30.70
3	4125.00	44.90 PK	74.00	-29.10	1.16 H	58	10.80	34.10
4	4874.00	42.10 PK	74.00	-31.90	1.50 H	46	5.60	36.50
5	7311.00	47.30 PK	74.00	-26.70	1.33 H	70	5.60	41.80

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2063.00	46.70 PK	74.00	-27.30	1.13 V	46	17.30	29.40
2	2370.00	39.50 PK	74.00	-34.50	1.13 V	5	9.20	30.40
3	*2437.00	106.20 PK			1.06 V	4	75.60	30.70
3	*2437.00	99.80 AV			1.06 V	4	69.10	30.70
4	4125.00	48.50 PK	74.00	-25.50	1.00 V	61	14.40	34.10
5	4874.00	45.20 PK	74.00	-28.80	1.15 V	197	8.80	36.50
6	7311.00	48.20 PK	74.00	-25.80	1.09 V	15	6.40	41.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



<b>EUT</b>	Wireless Serial Server	<b>MODEL</b>	GW21W-MAXI
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	1000 ~ 25000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 57%RH, 982 hPa	<b>TESTED BY</b>	Tony Chen

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2088.00	45.60 PK	74.00	-28.40	1.12 H	24	16.10	29.50
2	*2462.00	100.00 PK			1.15 H	360	69.20	30.80
2	*2462.00	93.70 AV			1.15 H	360	62.90	30.80
3	2483.50	42.10 PK	74.00	-31.90	1.04 H	301	11.20	31.00
4	4175.00	45.50 PK	74.00	-28.50	1.26 H	34	11.30	34.20
5	4924.00	41.80 PK	74.00	-32.20	1.26 H	56	5.10	36.70
6	7386.00	46.40 PK	74.00	-27.60	1.08 H	75	4.60	41.80

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2088.00	47.80 PK	74.00	-26.20	1.10 V	181	18.30	29.50
2	*2462.00	105.00 PK			1.14 V	4	74.20	30.80
2	*2462.00	98.30 AV			1.14 V	4	67.40	30.80
3	2483.50	48.70 PK	74.00	-25.30	1.24 V	239	17.70	31.00
4	4176.00	47.60 PK	74.00	-26.40	1.25 V	194	13.40	34.20
5	4924.00	40.20 PK	74.00	-33.80	1.15 V	114	3.50	36.70
6	7386.00	46.60 PK	74.00	-27.40	1.41 V	124	4.80	41.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP	1093.4495.30	Dec. 19, 2004

**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP



#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.






## 4.3.7 TEST RESULTS

<b>EUT</b>	Wireless Serial Server	<b>MODEL</b>	GW21W-MAXI
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	24deg. C, 58%RH, 982 hPa
<b>TEST BY</b>	Tony Chen		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6 dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	11.30	0.5	PASS
6	2437	9.60	0.5	PASS
11	2462	11.30	0.5	PASS




CH1






CH6





CH11





#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP30	100019	Dec. 19, 2004
R&S SIGNAL GENERATOR	SMP04	100011	May 28, 2004
TEKTRONIX OSCILLOSCOPE	TDS 220	B048470	Mar. 05, 2004
NARDA DETECTOR	4503A	FSCM99899	NA

**NOTE:**


The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.



#### 4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the peak response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

#### 4.4.4 TEST SETUP



#### 4.4.5 EUT OPERATING CONDITIONS

Same as Item 4.3.6



## 4.4.6 TEST RESULTS

<b>EUT</b>	Wireless Serial Server	<b>MODEL</b>	GW21W-MAXI
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	27 deg.C, 57 %RH, 982 hPa
<b>TEST BY</b>	Tony Chen		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	14.20	30	PASS
6	2437	14.50	30	PASS
11	2462	13.25	30	PASS



#### 4.4.7 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

#### 4.4.8 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP	1093.4495.30	Dec. 19, 2004

**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.



#### 4.4.9 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time = span/3 kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3 kHz for a full response of the mixer in the spectrum analyzer.

#### 4.4.10 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.11 TEST SETUP



#### 4.4.12 EUT OPERATING CONDITION

Same as Item 4.3.6




## 4.4.13 TEST RESULTS

<b>EUT</b>	Wireless Serial Server	<b>MODEL</b>	GW21W-MAXI
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	24deg. C, 58%RH, 982 hPa
<b>TEST BY</b>	Tony Chen		

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 kHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-11.77	8	PASS
6	2437	-10.13	8	PASS
11	2462	-12.06	8	PASS




CH1






CH6





CH11





## 4.5 BAND EDGES MEASUREMENT

### 4.5.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP	1093.4495.30	Dec. 19, 2004

**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation



#### 4.5.5 EUT OPERATING CONDITION


Same as Item 4.3.6

#### 4.5.6 TEST RESULTS


The spectrum plots are attached on the following 2 pages. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

**NOTE (1):** The band edge emission plot on the following first page shows 59.28dB delta between carrier maximum power and local maximum emission in restrict band (2.3874GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 98.0dBuV/m, so the maximum field strength in restrict band is  $98.0 - 59.28 = 38.72$  dBuV/m which is under 54 dBuV/m limit.

**NOTE (2):** The band edge emission plot on the following second page shows 60.05dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 98.30dBuV/m, so the maximum field strength in restrict band is  $98.30 - 60.05 = 38.25$  dBuV/m which is under 54 dBuV/m limit.









## **4.6 ANTENNA REQUIREMENT**


### **4.6.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **4.6.2 ANTENNA CONNECTED CONSTRUCTION**

The antenna used in this product is Dipole antenna with SMA Reversed Connector. The maximum Gain of the antenna is 2dBi.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



### RADIATED EMISSION TEST





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP, UL
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA , CSA
<b>R.O.C.</b>	CNLA, BSMI, DGT
<b>Netherlands</b>	Telefication
<b>Singapore</b>	PSB , GOST-ASIA(MOU)
<b>Russia</b>	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180  
Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Lab:**

Tel: 886-3-3183232  
Fax: 886-3-3185050

**Linko RF & Telecom Lab.**

Tel: 886-3-3270910  
Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.