



# MEASUREMENT REPORT

## FCC PART 15.247 Bluetooth

---

**FCC ID** : RQ9N18  
**APPLICANT** : Yanfeng Visteon Automotive Electronics Co.,Ltd  
**Application Type** : Certification  
**Product** : Car Radio With Bluetooth  
**Model No.** : N18  
**FCC Classification** : FCC Part 15 Spread Spectrum Transmitter(DSS)  
**FCC Rule Part(s)** : Part 15 Subpart C (Section 15.247)  
**Test Procedure(s)** : ANSI C63.10-2013  
**Test Date** : April 09 ~ 17, 2018

Reviewed By :   
( Kevin Guo )

Approved By :   
( Marlin Chen )



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and DA 00-705. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

### Revision History

Report No.	Version	Description	Issue Date	Note
1803WSU008-U1	Rev. 01	Initial report	05-17-2018	Valid

---

## CONTENTS

Description	Page
<b>1. INTRODUCTION .....</b>	<b>7</b>
1.1. Scope .....	7
1.2. MRT Test Location .....	7
<b>2. PRODUCT INFORMATION .....</b>	<b>8</b>
2.1. Equipment Description.....	8
2.2. Product Specification Subjective to this Standard .....	8
2.3. Working Frequencies for this report .....	9
2.4. Pseudorandom Frequency Hopping Sequence.....	10
2.5. Test Mode .....	10
2.6. Test Software .....	10
2.7. Device Capabilities .....	10
2.8. Test Configuration .....	11
2.9. EMI Suppression Device(s)/Modifications.....	11
2.10. Labeling Requirements.....	11
<b>3. DESCRIPTION of TEST .....</b>	<b>12</b>
3.1. Evaluation Procedure .....	12
3.2. AC Line Conducted Emissions .....	12
3.3. Radiated Emissions.....	13
<b>4. ANTENNA REQUIREMENTS .....</b>	<b>14</b>
<b>5. TEST EQUIPMENT CALIBRATION DATE .....</b>	<b>15</b>
<b>6. MEASUREMENT UNCERTAINTY.....</b>	<b>16</b>
<b>7. TEST RESULT .....</b>	<b>17</b>
7.1. Summary .....	17
7.2. 20dB Bandwidth Measurement.....	18
7.2.1. Test Limit .....	18
7.2.2. Test Procedure used.....	18
7.2.3. Test Setting.....	18
7.2.4. Test Setup.....	18
7.2.5. Test Result.....	19
7.3. Output Power Measurement.....	23
7.3.1. Test Limit .....	23
7.3.2. Test Procedure Used .....	23
7.3.3. Test Setting.....	23

---

7.3.4.	Test Setup.....	23
7.3.5.	Test Result.....	24
7.4.	Carrier Frequency Separation Measurement.....	28
7.4.1.	Test Limit.....	28
7.4.2.	Test Procedure Used.....	28
7.4.3.	Test Setting.....	28
7.4.4.	Test Setup.....	28
7.4.5.	Test Result.....	29
7.5.	Number of Hopping Channels Measurement.....	33
7.5.1.	Test Limit.....	33
7.5.2.	Test Procedure Used.....	33
7.5.3.	Test Setting.....	33
7.5.4.	Test Setup.....	33
7.5.5.	Test Result.....	34
7.6.	Time of Occupancy Measurement.....	37
7.6.1.	Test Limit.....	37
7.6.2.	Test Procedure Used.....	37
7.6.3.	Test Setting.....	37
7.6.4.	Test Setup.....	38
7.6.5.	Test Result.....	39
7.7.	Band-edge Compliance Measurement.....	41
7.7.1.	Test Limit.....	41
7.7.2.	Test Procedure Used.....	41
7.7.3.	Test Setting.....	41
7.7.4.	Test Setup.....	42
7.7.5.	Test Result.....	43
7.8.	Conducted Spurious Emissions Measurement.....	46
7.8.1.	Test Limit.....	46
7.8.2.	Test Procedure Used.....	46
7.8.3.	Test Setting.....	46
7.8.4.	Test Setup.....	47
7.8.5.	Test Result.....	48
7.9.	Radiated Spurious Emission Measurement.....	52
7.9.1.	Test Limit.....	52
7.9.2.	Test Procedure Used.....	52
7.9.3.	Test Setting.....	52
7.9.4.	Test Setup.....	54
7.9.5.	Test Result.....	56

- 7.10. Radiated Restricted Band Edge Measurement ..... 76
  - 7.10.1. Test Result..... 76
- 7.11. AC Conducted Emissions Measurement..... 124
  - 7.11.1. Test Limit ..... 124
  - 7.11.2. Test Setup..... 124
  - 7.11.3. Test Result..... 124
- 8. CONCLUSION..... 125**

## §2.1033 General Information

<b>Applicant:</b>	Yanfeng Visteon Automotive Electronics Co.,Ltd
<b>Applicant Address:</b>	300 Minolta Road Songjiang County Shanghai, China
<b>Manufacturer:</b>	Yanfeng Visteon Automotive Electronics Co.,Ltd
<b>Manufacturer Address:</b>	300 Minolta Road Songjiang County Shanghai, China
<b>Test Site:</b>	MRT Technology (Suzhou) Co., Ltd
<b>Test Site Address:</b>	D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
<b>FCC Registration No.:</b>	893164
<b>Test Device Serial No.:</b>	N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering
<b>FCC Classification:</b>	Spread Spectrum Transmitter(DSS)

### Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 893164) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-20025, G-20034, C-20020, T-20020) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications and Radio testing for FCC, Industry Canada, EU and TELEC Rules.



## 1. INTRODUCTION

### 1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.



## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

Product Name	Car Radio With Bluetooth
Model No.	N18
Bluetooth Spec	Bluetooth Classic mode

### 2.2. Product Specification Subjective to this Standard

Operating Frequency	2402 ~ 2480MHz
Type of modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)
Antenna Type	PCB Antenna
Antenna Gain	0 dBi

Note: For other features of this EUT, test report will be issued separately.

The equipment under test (EUT) is the **Car Radio With Bluetooth**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.




### 2.3. Working Frequencies for this report

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz
03	2405 MHz	04	2406 MHz	05	2407 MHz
06	2408 MHz	07	2409 MHz	08	2410 MHz
09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz
15	2417 MHz	16	2418 MHz	17	2419 MHz
18	2420 MHz	19	2421 MHz	20	2422 MHz
21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz
27	2429 MHz	28	2430 MHz	29	2431 MHz
30	2432 MHz	31	2433 MHz	32	2434 MHz
33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz
39	2441 MHz	40	2442 MHz	41	2443 MHz
42	2444 MHz	43	2445 MHz	44	2446 MHz
45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz
51	2453 MHz	52	2454 MHz	53	2455 MHz
54	2456 MHz	55	2457 MHz	56	2458 MHz
57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz
63	2465 MHz	64	2466 MHz	65	2467 MHz
66	2468 MHz	67	2469 MHz	68	2470 MHz
69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz
75	2477 MHz	76	2478 MHz	77	2479 MHz
78	2480 MHz	N/A	N/A	N/A	N/A

## 2.4. Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

## 2.5. Test Mode

Test Mode	Mode 1: Transmit by DH5
	Mode 2: Transmit by 2DH5
	Mode 3: Transmit by 3DH5

Note: There are two test samples, DAB and Non-DAB. They have the same Bluetooth module and RF parameters, so it's performed the diffident Radiated test, but the same conducted test in this report.

## 2.6. Test Software

The test utility software used during testing was "Blue Test3", and the version was "2.5.0.93".

## 2.7. Device Capabilities

This device contains the following capabilities:

Bluetooth Classic mode

## **2.8. Test Configuration**

The device was tested per the guidance of ANSI C63.10-2013 and DA 00-705. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

## **2.9. EMI Suppression Device(s)/Modifications**

No EMI suppression device(s) were added and/or no modifications were made during testing.

## **2.10. Labeling Requirements**

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

### 3. DESCRIPTION of TEST

#### 3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the “Filing” was used in the measurement of the device.

**Deviation from measurement procedure.....None**

#### 3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions were used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

### 3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

## 4. ANTENNA REQUIREMENTS

### **Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

### **Conclusion:**

The device unit complies with the requirement of §15.203.

## 5. TEST EQUIPMENT CALIBRATION DATE

### Conducted Emissions - SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2018/08/18
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2018/06/21
Two-Line V-Network	R&S	ENV216	MRTSUE06003	1 year	2018/06/21
Thermohygrometer	Testo	608-H1	MRTSUE06404	1 year	2018/08/14
Shielding Anechoic Chamber	Mikebang	Chamber-SR2	MRTSUE06214	1 year	2019/05/10

### Radiated Emissions - AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
PXA Signal Analyzer	Keysight	9030B	MRTSUE06395	1 year	2018/09/13
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2018/08/18
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2018/11/20
EXA Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2019/04/20
Microwave System Amplifier	Agilent	83017A	MRTSUE06076	1 year	2018/11/17
Bilog Period Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2018/11/18
Broad Band Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06023	1 year	2018/10/21
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06024	1 year	2018/12/14
Amplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2018/06/14
Thermohygrometer	Testo	608-H1	MRTSUE06403	1 year	2018/08/14
Anechoic Chamber	TDK	Chamber-AC1	MRTSUE06212	1 year	2019/04/30

### Conducted Test Equipment - TR3

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2019/04/20
Power Meter	Agilent	U2021XA	MRTSUE06030	1 year	2018/12/06
Thermohygrometer	Testo	608-H1	MRTSUE06401	1 year	2018/08/14

Software	Version	Function
e3	V 8.3.5	EMI Test Software

## 6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

<b>AC Conducted Emission Measurement - SR2</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 150kHz~30MHz: 3.46dB
<b>Radiated Emission Measurement - AC1</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 9kHz ~ 1GHz: 4.18dB 1GHz ~ 25GHz: 4.76dB
<b>Spurious Emissions, Conducted - TR3</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.78dB
<b>Output Power - TR3</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.13dB
<b>Power Spectrum Density - TR3</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.15dB
<b>Occupied Bandwidth - TR3</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.28%



## 7. TEST RESULT

### 7.1. Summary

Company Name: Yanfeng Visteon Automotive Electronics Co.,Ltd

FCC ID: RQ9N18

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(1)	20dB Bandwidth	Refer to 7.2.1	Conducted	PASS	Section 7.2
15.247(b)(1)	Peak Transmitter Output Power	Refer to 7.3.1		PASS	Section 7.3
15.247(a)(1)	Channel Separation	Refer to 7.4.1		PASS	Section 7.4
15.247(a)(1)(iii)	Number of Channels	Refer to 7.5.1		PASS	Section 7.5
15.247(a)(1)(iii)	Time of Occupancy	Refer to 7.6.1		PASS	Section 7.6
15.247(d)	Band Edge / out- of-Band Emissions	Refer to 7.7.1 & 7.8.1		PASS	Section 7.7 Section 7.8
15.205, 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Refer to 7.9.1 & 7.10.1	Radiated	PASS	Section 7.9 Section 7.10
15.207	AC Conducted Emissions 150kHz - 30MHz	Refer to 7.11.1	Line Conducted	N/A	Section 7.11

#### Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.

## 7.2. 20dB Bandwidth Measurement

### 7.2.1. Test Limit

N/A


### 7.2.2. Test Procedure used

ANSI C63.10-2013 - Section 6.9.2

### 7.2.3. Test Setting

1. Set RBW = 1% to 5% of the 20dB bandwidth
2. VBW = approximately three times RBW
3. Span = approximately 2 to 5 times the 20dB bandwidth
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace to stabilize

### 7.2.4. Test Setup




**7.2.5. Test Result**

Product	Car Radio With Bluetooth	Temperature	25°C
Test Engineer	Hunk Li	Relative Humidity	52%
Test Site	TR3	Test Date	2018/04/11 ~ 2018/04/17


Test Mode	Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	Result
DH5	00	2402	924.1	Pass
DH5	39	2441	924.5	Pass
DH5	78	2480	925.1	Pass
2DH5	00	2402	1316.0	Pass
2DH5	39	2441	1316.0	Pass
2DH5	78	2480	1315.0	Pass
3DH5	00	2402	1273.0	Pass
3DH5	39	2441	1273.0	Pass
3DH5	78	2480	1277.0	Pass

DH5 20dB Bandwidth


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




2DH5 20dB Bandwidth


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)



3DH5 20dB Bandwidth


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



### 7.3. Output Power Measurement

#### 7.3.1. Test Limit

The maximum out power permissible output power is 1 Watt for all other frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.


#### 7.3.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.5

#### 7.3.3. Test Setting

1. RBW > 20 dB bandwidth of the emission being measured.
2. VBW  $\geq$  RBW
3. Span = Approximately five times the 20dB bandwidth, centered on a hopping channel
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto
7. Allow the trace to stabilize, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

#### 7.3.4. Test Setup



**7.3.5. Test Result**

Product	Car Radio With Bluetooth	Temperature	25°C
Test Engineer	Hunk Li	Relative Humidity	53%
Test Site	TR3	Test Date	2018/04/11 ~ 2018/04/17

Test Mode	Channel No.	Frequency (MHz)	Peak Power (dBm)	Peak Power Limit (dBm)
DH5	00	2402	4.72	< 30
DH5	39	2441	7.23	< 30
DH5	78	2480	8.37	< 30
2DH5	00	2402	2.68	< 30
2DH5	39	2441	6.10	< 30
2DH5	78	2480	7.57	< 30
3DH5	00	2402	3.06	< 30
3DH5	39	2441	6.36	< 30
3DH5	78	2480	7.73	< 30



### DH5 Output Power

#### Channel 00 (2402MHz)



#### Channel 39 (2441MHz)



#### Channel 78 (2480MHz)



Frequency

Auto Tune

Center Freq 2.48000000 GHz

Start Freq 2.477500000 GHz

Stop Freq 2.482500000 GHz


CF Step 500.000 kHz

Auto

Freq Offset 0 Hz

2DH5 Output Power


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)



### 3DH5 Output Power


#### Channel 00 (2402MHz)



#### Channel 39 (2441MHz)



#### Channel 78 (2480MHz)



## 7.4. Carrier Frequency Separation Measurement

### 7.4.1. Test Limit

The minimum permissible channel separation for this system is  $2/3$  the value of the 20dB BW.


### 7.4.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.2

### 7.4.3. Test Setting

1. Span: Wide enough to capture the peaks of two adjacent channels.
2. RBW: Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
3. VBW  $\geq$  RBW
4. Detector = Peak
5. Sweep time = Auto
6. Trace mode = Max hold
7. Trace was allowed to stabilize

### 7.4.4. Test Setup



**7.4.5. Test Result**


Product	Car Radio With Bluetooth	Temperature	25°C
Test Engineer	Hunk Li	Relative Humidity	53%
Test Site	TR3	Test Date	2018/04/17

Test Mode	Channel No.	Frequency (MHz)	Limit (kHz)	Result
DH5	00	2402	≥ 616.1	Pass
DH5	39	2441	≥ 616.3	Pass
DH5	78	2480	≥ 616.7	Pass
2DH5	00	2402	≥ 877.3	Pass
2DH5	39	2441	≥ 877.3	Pass
2DH5	78	2480	≥ 876.7	Pass
3DH5	00	2402	≥ 848.7	Pass
3DH5	39	2441	≥ 848.7	Pass
3DH5	78	2480	≥ 851.3	Pass

Note: The Limit is 2/3 the value of the 20dB BW.

### DH5 Carrier Frequency Separation


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)



### 2DH5 Carrier Frequency Separation

Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)



### 3DH5 Carrier Frequency Separation

Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)





## 7.5. Number of Hopping Channels Measurement

### 7.5.1. Test Limit

This frequency hopping system must employ a minimum of 15 hopping channels.


### 7.5.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.3

### 7.5.3. Test Setting

1. Span = the frequency band of operation.
2. RBW < 30 % of the channel spacing or the 20 dB bandwidth, whichever is smaller.
3. VBW  $\geq$  RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep time = Auto
7. The trace was allowed to stabilize

### 7.5.4. Test Setup



**7.5.5. Test Result**


Product	Car Radio With Bluetooth	Temperature	25°C
Test Engineer	Hunk Li	Relative Humidity	52%
Test Site	TR3	Test Date	2018/04/11 ~ 2018/04/17

Test Mode (Hopping)	Channel Numbers	Frequency (MHz)	Limit (Hopping Channels)	Result
DH5	79	2402~2480	≥ 15	Pass
2DH5	79	2402~2480	≥ 15	Pass
3DH5	79	2402~2480	≥ 15	Pass




## 2DH5 Number of Hopping Channels


2402 ~ 2421MHz




2422 ~ 2441MHz



2442 ~ 2461MHz




2462 ~ 2480MHz




## 3DH5 Number of Hopping Channels


2402 ~ 2421MHz




2422 ~ 2441MHz



2442 ~ 2461MHz



2462 ~ 2480MHz



## 7.6. Time of Occupancy Measurement

### 7.6.1. Test Limit

The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.

### 7.6.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.4

### 7.6.3. Test Setting

1. Span = zero span, centered on a hopping channel.
2.  $RBW \leq$  channel spacing and where possible should be set  $\gg 1 / T$ , where T is the expected dwell time per channel.
3.  $VBW \geq RBW$
4. Sweep time = as necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
5. Detector = Peak
6. Trace mode = max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:


(Number of hops in the period specified in the requirements) =

(Number of hops on spectrum analyzer) × (period specified in the requirements / analyzer sweep time)

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.


#### 7.6.4. Test Setup



7.6.5. Test Result

Product	Car Radio With Bluetooth	Temperature	25°C
Test Engineer	Hunk Li	Relative Humidity	52%
Test Site	TR3	Test Date	2018/04/11

Test Mode	Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
3DH1	39	2441	128.0	< 400	Pass
3DH3	39	2441	258.2	< 400	Pass
3DH5	39	2441	305.0	< 400	Pass



Note 1: According to the Bluetooth Standard Specification, the nominal hop rate is 1600 hops/s. All Bluetooth units participating in the piconet are time and hop synchronized to the channel.

Hops Over Occupancy Time in 31.6s for 3DH1 =  $1600 / 2 / 79 * 31.6 = 320$ .

Hops Over Occupancy Time in 31.6s for 3DH3 =  $1600 / 4 / 79 * 31.6 = 160$ .

Hops Over Occupancy Time in 31.6s for 3DH5 =  $1600 / 6 / 79 * 31.6 = 107$ .

Note 2: Time of Occupancy = Packet Transfer Time \* Hops Over Occupancy Time in 31.6s.



## **7.7. Band-edge Compliance Measurement**

### **7.7.1. Test Limit**

The maximum permissible emission level is 20dBc. Any emissions were lying outside of the emission bandwidth and in authorized band edges to a field strength limit specified in Section 15.209 of the Title 47 CFR.

### **7.7.2. Test Procedure Used**

ANSI C63.10-2013 - Section 6.10.4


### **7.7.3. Test Setting**

1. Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = Peak
5. Sweep time = Coupled
6. Trace mode = max hold
7. Trace was allowed to stabilize

Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.

Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.

### 7.7.4. Test Setup



**7.7.5. Test Result**

Product	Car Radio With Bluetooth	Temperature	25°C
Test Engineer	Hunk Li	Relative Humidity	52%
Test Site	TR3	Test Date	2018/04/11

Test Mode	Channel No.	Frequency (MHz)	Limit	Result
DH5	00	2402	20dBc	Pass
DH5	78	2480	20dBc	Pass
2DH5	00	2402	20dBc	Pass
2DH5	78	2480	20dBc	Pass
3DH5	00	2402	20dBc	Pass
3DH5	78	2480	20dBc	Pass

### DH5 Band-edge Compliance

#### Channel 00 (2402MHz)




#### Channel 78 (2480MHz)



### 2DH5 Band-edge Compliance

#### Channel 00 (2402MHz)




#### Channel 78 (2480MHz)




### 3DH5 Band-edge Compliance

#### Channel 00 (2402MHz)




#### Channel 78 (2480MHz)




### DH5 Operation Frequency Range of 20dB Bandwidth within Hopping Mode

Channel 00 (2402MHz)




Channel 78 (2480MHz)




### 2DH5 Operation Frequency Range of 20dB Bandwidth within Hopping Mode

Channel 00 (2402MHz)




Channel 78 (2480MHz)




### 3DH5 Operation Frequency Range of 20dB Bandwidth within Hopping Mode

Channel 00 (2402MHz)



Channel 78 (2480MHz)



## **7.8. Conducted Spurious Emissions Measurement**

### **7.8.1. Test Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### **7.8.2. Test Procedure Used**


ANSI C63.10-2013 - Section 7.8.8

### **7.8.3. Test Setting**

1. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10<sup>th</sup> harmonic. Typically, several plots are required to cover this entire span.
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

### 7.8.4. Test Setup



**7.8.5. Test Result**


Product	Car Radio With Bluetooth	Temperature	25°C
Test Engineer	Hunk Li	Relative Humidity	52%
Test Site	TR3	Test Date	2018/04/11

Test Mode	Channel No.	Frequency (MHz)	Limit (MHz)	Result
DH5	00	2402	20dBc	Pass
DH5	39	2441	20dBc	Pass
DH5	78	2480	20dBc	Pass
2DH5	00	2402	20dBc	Pass
2DH5	39	2441	20dBc	Pass
2DH5	78	2480	20dBc	Pass
3DH5	00	2402	20dBc	Pass
3DH5	39	2441	20dBc	Pass
3DH5	78	2480	20dBc	Pass



DH5 Conducted Spurious Emissions

Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)



2DH5 Conducted Spurious Emissions


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)



### 3DH5 Conducted Spurious Emissions


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



## 7.9. Radiated Spurious Emission Measurement

### 7.9.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 – 30	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

### 7.9.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.12.1

### 7.9.3. Test Setting

#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = 3 \* RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

**Table 1 - RBW as a function of frequency**


Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

**Average Field Strength Measurements**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW  $\geq 1/T$
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

### 7.9.4. Test Setup


#### 9kHz ~ 30MHz Test Setup:



#### 30MHz ~ 1GHz Test Setup:



1GHz ~ 25GHz Test Setup:



### 7.9.5. Test Result

#### For EUT with Non- DAB

Test Mode:	DH5	Test Site:	AC1
Test Channel:	00	Test Engineer:	Will Yan
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4799.5	45.7	5.8	51.5	74.0	-22.5	Peak	Horizontal
	7460.0	37.1	12.9	50.0	74.0	-24.0	Peak	Horizontal
*	8871.0	36.2	13.2	49.4	79.8	-30.4	Peak	Horizontal
*	10401.0	37.1	17.3	54.4	79.8	-25.4	Peak	Horizontal
	4808.0	45.1	5.9	51.0	74.0	-23.0	Peak	Vertical
	7409.0	36.8	12.6	49.4	74.0	-24.6	Peak	Vertical
*	8820.0	36.0	13.3	49.3	79.8	-30.5	Peak	Vertical
*	10333.0	35.6	17.3	52.9	79.8	-26.9	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (99.8dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)



Test Mode:	DH5	Test Site:	AC1
Test channel:	39	Test Engineer:	Will Yan
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4884.5	43.5	6.0	49.5	74.0	-24.5	Peak	Horizontal
	7468.5	36.2	12.9	49.1	74.0	-24.9	Peak	Horizontal
*	8607.5	37.8	12.9	50.7	78.5	-27.8	Peak	Horizontal
*	9942.0	34.7	16.8	51.5	78.5	-27.0	Peak	Horizontal
	4884.5	45.1	6.0	51.1	74.0	-22.9	Peak	Vertical
	7528.0	37.2	12.8	50.0	74.0	-24.0	Peak	Vertical
*	8811.5	34.4	13.3	47.7	78.5	-30.8	Peak	Vertical
*	9721.0	34.7	15.7	50.4	78.5	-28.1	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (98.5dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	DH5	Test Site:	AC1
Test channel:	78	Test Engineer:	Will Yan
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4961.0	48.6	6.1	54.7	74.0	-19.3	Peak	Horizontal
	4961.0	47.1	6.1	53.2	54.0	-0.8	Average	Horizontal
	7443.0	40.2	12.9	53.1	74.0	-20.9	Peak	Horizontal
	7443.0	38.3	12.9	51.2	54.0	-2.8	Average	Horizontal
*	8854.0	35.5	13.4	48.9	77.6	-28.7	Peak	Horizontal
*	10214.0	35.2	17.1	52.3	77.6	-25.3	Peak	Horizontal
	4960.0	48.3	6.1	54.4	74.0	-19.6	Peak	Vertical
	4960.0	47.5	6.1	53.6	54.0	-0.4	Average	Vertical
	7443.0	38.8	12.9	51.7	74.0	-22.3	Peak	Vertical
*	8684.0	36.3	13.1	49.4	77.6	-28.2	Peak	Vertical
*	10265.0	35.9	17.2	53.1	77.6	-24.5	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (99.6dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	2DH5	Test Site:	AC1
Test channel:	00	Test Engineer:	Will Yan
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4808.0	41.5	5.9	47.4	74.0	-26.6	Peak	Horizontal
	7468.5	36.5	12.9	49.4	74.0	-24.6	Peak	Horizontal
*	8709.5	36.1	13.0	49.1	77.4	-28.3	Peak	Horizontal
*	9967.5	35.3	16.7	52.0	77.4	-25.4	Peak	Horizontal
	4808.0	41.3	5.9	47.2	74.0	-26.8	Peak	Vertical
	8301.5	35.9	12.6	48.5	74.0	-25.5	Peak	Vertical
*	9721.0	34.5	15.7	50.2	77.4	-27.2	Peak	Vertical
*	10341.5	35.7	17.3	53.0	77.4	-24.4	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (97.4dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	2DH5	Test Site:	AC1
Test channel:	39	Test Engineer:	Will Yan
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4876.0	44.1	6.0	50.1	74.0	-23.9	Peak	Horizontal
	7485.5	36.7	12.8	49.5	74.0	-24.5	Peak	Horizontal
*	8692.5	35.8	13.0	48.8	76.8	-28.0	Peak	Horizontal
*	10205.5	35.3	17.1	52.4	76.8	-24.4	Peak	Horizontal
	4876.0	44.2	6.0	50.2	74.0	-23.8	Peak	Vertical
	7485.5	36.5	12.8	49.3	74.0	-24.7	Peak	Vertical
*	8624.5	36.1	12.9	49.0	76.8	-27.8	Peak	Vertical
*	10358.5	35.2	17.4	52.6	76.8	-24.2	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (96.8dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	2DH5	Test Site:	AC1
Test channel:	78	Test Engineer:	Will Yan
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4961.0	44.8	6.1	50.9	74.0	-23.1	Peak	Horizontal
	7468.5	36.8	12.9	49.7	74.0	-24.3	Peak	Horizontal
*	8862.5	36.4	13.3	49.7	75.8	-26.1	Peak	Horizontal
*	10086.5	33.5	16.9	50.4	75.8	-25.4	Peak	Horizontal
	4961.0	45.1	6.1	51.2	74.0	-22.8	Peak	Vertical
	7383.5	37.0	12.6	49.6	74.0	-24.4	Peak	Vertical
*	8760.5	36.3	13.2	49.5	75.8	-26.3	Peak	Vertical
*	10035.5	35.8	16.7	52.5	75.8	-23.3	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (95.8dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	3DH5	Test Site:	AC1
Test channel:	00	Test Engineer:	Will Yan
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4808.0	41.5	5.9	47.4	74.0	-26.6	Peak	Horizontal
	7570.5	35.3	12.9	48.2	74.0	-25.8	Peak	Horizontal
*	8786.0	35.4	13.3	48.7	77.8	-29.1	Peak	Horizontal
*	9831.5	34.7	16.6	51.3	77.8	-26.5	Peak	Horizontal
	4808.0	41.1	5.9	47.0	74.0	-27.0	Peak	Vertical
	7451.5	36.3	12.9	49.2	74.0	-24.8	Peak	Vertical
*	8735.0	34.7	13.0	47.7	77.8	-30.1	Peak	Vertical
*	9874.0	35.6	16.8	52.4	77.8	-25.4	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (97.8dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	3DH5	Test Site:	AC1
Test channel:	39	Test Engineer:	Will Yan
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4884.5	44.0	6.0	50.0	74.0	-24.0	Peak	Horizontal
	7545.0	35.1	13.0	48.1	74.0	-25.9	Peak	Horizontal
*	8624.5	36.4	12.9	49.3	76.7	-27.4	Peak	Horizontal
*	10375.5	35.4	17.4	52.8	76.7	-23.9	Peak	Horizontal
	4884.5	44.1	6.0	50.1	74.0	-23.9	Peak	Vertical
	7426.0	36.5	12.8	49.3	74.0	-24.7	Peak	Vertical
*	8862.5	36.9	13.3	50.2	76.7	-26.5	Peak	Vertical
*	10367.0	35.2	17.4	52.6	76.7	-24.1	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (96.7dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	3DH5	Test Site:	AC1
Test channel:	78	Test Engineer:	Will Yan
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4961.0	44.6	6.1	50.7	74.0	-23.3	Peak	Horizontal
	7460.0	36.6	12.9	49.5	74.0	-24.5	Peak	Horizontal
*	8684.0	35.8	13.1	48.9	75.9	-27.0	Peak	Horizontal
*	9823.0	35.0	16.5	51.5	75.9	-24.4	Peak	Horizontal
	4961.0	45.4	6.1	51.5	74.0	-22.5	Peak	Vertical
	7443.0	36.8	12.9	49.7	74.0	-24.3	Peak	Vertical
*	8845.5	35.9	13.3	49.2	75.9	-26.7	Peak	Vertical
*	9882.5	35.2	16.7	51.9	75.9	-24.0	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (95.9dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)



**For EUT with DAB**

Test Mode:	DH5	Test Site:	AC1
Test Channel:	00	Test Engineer:	Will Yan
Remark:	3. Average measurement was not performed if peak level lower than average limit. 4. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4808.0	44.6	5.9	50.5	74.0	-23.5	Peak	Horizontal
	7468.5	36.9	12.9	49.8	74.0	-24.2	Peak	Horizontal
*	8692.5	37.4	13.0	50.4	80.9	-30.5	Peak	Horizontal
*	9755.0	36.9	16.2	53.1	80.9	-27.8	Peak	Horizontal
	4808.0	43.8	5.9	49.7	74.0	-24.3	Peak	Vertical
	7451.5	36.2	12.9	49.1	74.0	-24.9	Peak	Vertical
*	8896.5	36.9	13.2	50.1	80.9	-30.8	Peak	Vertical
*	10239.5	35.0	17.2	52.2	80.9	-28.7	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (100.9dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	DH5	Test Site:	AC1
Test channel:	39	Test Engineer:	Will Yan
Remark:	3. Average measurement was not performed if peak level lower than average limit. 4. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4884.5	44.4	6.0	50.4	74.0	-23.6	Peak	Horizontal
	7664.0	37.6	12.8	50.4	74.0	-23.6	Peak	Horizontal
*	8862.5	37.5	13.3	50.8	81.2	-30.4	Peak	Horizontal
*	10324.5	35.8	17.3	53.1	81.2	-28.1	Peak	Horizontal
	4882.0	47.8	6.0	53.8	74.0	-20.2	Peak	Vertical
	4882.0	46.5	6.0	52.5	54.0	-1.5	Average	Vertical
	7477.0	36.3	12.9	49.2	74.0	-24.8	Peak	Vertical
*	8760.5	36.5	13.2	49.7	81.2	-31.5	Peak	Vertical
*	9840.0	35.0	16.7	51.7	81.2	-29.5	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (101.2dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	DH5	Test Site:	AC1
Test channel:	78	Test Engineer:	Will Yan
Remark:	3. Average measurement was not performed if peak level lower than average limit. 4. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4960.0	47.0	6.1	53.1	74.0	-20.9	Peak	Horizontal
	4960.0	45.7	6.1	51.8	54.0	-2.2	Average	Horizontal
	7443.0	39.1	12.9	52.0	74.0	-22.0	Peak	Horizontal
*	8777.5	36.5	13.2	49.7	81.7	-32.0	Peak	Horizontal
*	9840.0	34.7	16.7	51.4	81.7	-30.3	Peak	Horizontal
	4960.0	47.4	6.1	53.5	74.0	-20.5	Peak	Vertical
	4960.0	46.4	6.1	52.5	54.0	-1.5	Average	Vertical
	7443.0	38.6	12.9	51.5	74.0	-22.5	Peak	Vertical
*	8743.5	35.6	13.1	48.7	81.7	-33.0	Peak	Vertical
*	9865.5	35.2	16.7	51.9	81.7	-29.8	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (101.7dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	2DH5	Test Site:	AC1
Test channel:	00	Test Engineer:	Will Yan
Remark:	3. Average measurement was not performed if peak level lower than average limit. 4. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4799.5	40.3	5.8	46.1	74.0	-27.9	Peak	Horizontal
	5411.5	36.4	6.6	43.0	74.0	-31.0	Peak	Horizontal
*	7239.0	37.0	12.7	49.7	78.2	-28.5	Peak	Horizontal
*	9755.0	35.4	16.2	51.6	78.2	-26.6	Peak	Horizontal
	4808.0	40.1	5.9	46.0	74.0	-28.0	Peak	Vertical
	7417.5	35.7	12.7	48.4	74.0	-25.6	Peak	Vertical
*	8633.0	36.7	12.9	49.6	78.2	-28.6	Peak	Vertical
*	10035.5	34.8	16.7	51.5	78.2	-26.7	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (98.2dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	2DH5	Test Site:	AC1
Test channel:	39	Test Engineer:	Will Yan
Remark:	3. Average measurement was not performed if peak level lower than average limit. 4. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4884.5	42.1	6.0	48.1	74.0	-25.9	Peak	Horizontal
	7502.5	36.8	12.7	49.5	74.0	-24.5	Peak	Horizontal
*	8837.0	35.6	13.2	48.8	79.8	-31.0	Peak	Horizontal
*	9704.0	34.7	15.5	50.2	79.8	-29.6	Peak	Horizontal
	4884.5	44.5	6.0	50.5	74.0	-23.5	Peak	Vertical
	7536.5	37.3	12.9	50.2	74.0	-23.8	Peak	Vertical
*	8820.0	36.8	13.3	50.1	79.8	-29.7	Peak	Vertical
*	9857.0	34.6	16.7	51.3	79.8	-28.5	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (99.8dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	2DH5	Test Site:	AC1
Test channel:	78	Test Engineer:	Will Yan
Remark:	3. Average measurement was not performed if peak level lower than average limit. 4. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4961.0	43.8	6.1	49.9	74.0	-24.1	Peak	Horizontal
	7426.0	37.3	12.8	50.1	74.0	-23.9	Peak	Horizontal
*	8794.5	35.5	13.3	48.8	80.2	-31.4	Peak	Horizontal
*	10129.0	34.6	16.9	51.5	80.2	-28.7	Peak	Horizontal
	4961.0	44.0	6.1	50.1	74.0	-23.9	Peak	Vertical
	7681.0	37.5	12.8	50.3	74.0	-23.7	Peak	Vertical
*	8811.5	36.1	13.3	49.4	80.2	-30.8	Peak	Vertical
*	9831.5	34.4	16.6	51.0	80.2	-29.2	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (100.2dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	3DH5	Test Site:	AC1
Test channel:	00	Test Engineer:	Will Yan
Remark:	3. Average measurement was not performed if peak level lower than average limit. 4. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	4799.5	38.5	5.8	44.3	74.0	-29.7	Peak	Horizontal
	7426.0	36.5	12.8	49.3	74.0	-24.7	Peak	Horizontal
*	8735.0	35.8	13.0	48.8	78.8	-30.0	Peak	Horizontal
*	10086.5	35.0	16.9	51.9	78.8	-26.9	Peak	Horizontal
	4808.0	41.4	5.9	47.3	74.0	-26.7	Peak	Vertical
	7502.5	36.3	12.7	49.0	74.0	-25.0	Peak	Vertical
*	8896.5	37.1	13.2	50.3	78.8	-28.5	Peak	Vertical
*	10137.5	36.2	17.0	53.2	78.8	-25.6	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (98.8dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Mode:	3DH5	Test Site:	AC1
Test channel:	39	Test Engineer:	Will Yan
Remark:	3. Average measurement was not performed if peak level lower than average limit. 4. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4884.5	42.3	6.0	48.3	74.0	-25.7	Peak	Horizontal
	7494.0	36.5	12.7	49.2	74.0	-24.8	Peak	Horizontal
*	8896.5	36.5	13.2	49.7	79.5	-29.8	Peak	Horizontal
*	10384.0	35.4	17.4	52.8	79.5	-26.7	Peak	Horizontal
	4884.5	44.1	6.0	50.1	74.0	-23.9	Peak	Vertical
	7460.0	37.2	12.9	50.1	74.0	-23.9	Peak	Vertical
*	8692.5	35.1	13.0	48.1	79.5	-31.4	Peak	Vertical
*	10375.5	35.2	17.4	52.6	79.5	-26.9	Peak	Vertical

Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (99.5dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)



Test Mode:	3DH5	Test Site:	AC1
Test channel:	78	Test Engineer:	Will Yan
Remark:	3. Average measurement was not performed if peak level lower than average limit. 4. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
	4799.5	39.1	5.8	44.9	74.0	-29.1	Peak	Horizontal
	7443.0	35.8	12.9	48.7	74.0	-25.3	Peak	Horizontal
*	8701.0	36.5	13.0	49.5	80.2	-30.7	Peak	Horizontal
*	10205.5	35.5	17.1	52.6	80.2	-27.6	Peak	Horizontal
	4799.5	38.7	5.8	44.5	74.0	-29.5	Peak	Vertical
	5445.5	36.0	6.7	42.7	74.0	-31.3	Peak	Vertical
*	7944.5	36.5	13.5	50.0	80.2	-30.2	Peak	Vertical
*	10180.0	35.2	17.1	52.3	80.2	-27.9	Peak	Vertical


Note 1: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (100.2dB $\mu$ V/m) or 15.209 which is higher.

Note 2: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

**The worst case of Radiated Emission below 1GHz:**

Site: AC1	Time: 2018/04/17 - 18:57
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: VULB9168_20-2000MHz	Polarity: Horizontal
EUT: Car Radio With Bluetooth	Power: DC 12V
<b>Worst Case Mode:</b> Transmit at Channel 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		95.960	15.545	4.783	-27.955	43.500	10.762	QP
2	*	170.160	36.744	22.400	-6.756	43.500	14.344	QP
3		191.020	24.928	13.252	-18.572	43.500	11.676	QP
4		221.575	23.247	11.146	-22.753	46.000	12.101	QP
5		324.880	32.108	17.023	-13.892	46.000	15.085	QP
6		846.740	28.776	5.042	-17.224	46.000	23.734	QP

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

Site: AC1	Time: 2018/04/17 - 19:05
Limit: FCC_Part15.209_RE(3m)	Engineer: Snake Ni
Probe: VULB9168_20-2000MHz	Polarity: Vertical
EUT: Car Radio With Bluetooth	Power: DC 12V
<b>Worst Case Mode:</b> Transmit at Channel 2402MHz by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		38.730	18.986	4.507	-21.014	40.000	14.479	QP
2	*	161.435	30.718	15.541	-12.782	43.500	15.177	QP
3		191.505	20.392	8.743	-23.108	43.500	11.649	QP
4		202.660	21.125	9.875	-22.375	43.500	11.249	QP
5		324.880	25.220	10.135	-20.780	46.000	15.085	QP
6		856.925	25.247	1.417	-20.753	46.000	23.830	QP

Note 1: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)


Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

## 7.10. Radiated Restricted Band Edge Measurement

### 7.10.1. Test Result

#### For Car Radio With Bluetooth with Non-DAB

Site: AC1	Time: 2018/04/09 - 10:23
Limit: FCC_Part15.209_RE(3m)	Engineer: Alex Ma
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Car Radio With Bluetooth	Power: DC 12V
Test Mode: Transmit by DH5 at channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2379.302	59.483	27.142	-14.517	74.000	32.342	PK
2			2390.000	56.705	24.378	-17.295	74.000	32.327	PK
3		*	2402.150	95.488	63.184	N/A	N/A	32.304	PK

Note: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2018/04/09 - 10:29
Limit: FCC_Part15.209_RE(3m)	Engineer: Alex Ma
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Car Radio With Bluetooth	Power: DC 12V
Test Mode: Transmit by DH5 at channel 2402MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2377.403	40.642	8.298	-13.358	54.000	32.344	AV
2			2390.000	39.284	6.957	-14.716	54.000	32.327	AV
3		*	2402.055	94.842	62.538	N/A	N/A	32.304	AV

Note: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)