

FCC REPORT

Applicant: Hyundai Corporation

Address of Applicant: 140-2, Kye-dong, Chongro-ku, Seoul, South Korea

Equipment Under Test (EUT)

Product Name: Smart Watch

Model No.: PULSE

Trade mark: HYUNDAI

FCC ID: RQQHLT-D24KWM

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 21 Mar., 2016

Date of Test: 21 Mar., to 21 Apr., 2016

Date of report issued: 22 Apr., 2016

Test Result: Pass *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	22 Apr., 2016	Original

Tested by: YT Yang **Date:** 22 Apr., 2016
Test Engineer

Reviewed by: Carrey Chen **Date:** 22 Apr., 2016
Project Engineer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE.....	5
5.4 DESCRIPTION OF SUPPORT UNITS	6
5.5 LABORATORY FACILITY	6
5.6 LABORATORY LOCATION	6
5.7 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	8
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION	11
7 TEST SETUP PHOTO	17
8 EUT CONSTRUCTIONAL DETAILS	18

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Hyundai Corporation
Address of Applicant:	140-2, Kye-dong, Chongro-ku, Seoul, South Korea
Manufacturer/Factory:	Shenzhen Kingwear Intelligent Technology Co.,Ltd.
Address of Manufacturer/Factory:	Building C, Block 9, Baoneng HiTech industrial Park, Qingxiang Road, Qinghu, Longhua, shenzhen, China

5.2 General Description of E.U.T.

Product Name:	Smart Watch
Model No.:	PULSE
Power supply:	Rechargeable Li-ion Battery DC3.7V-300mAh

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
NAKAMICHI	Bluetooth earphone	T8	N/A	FCC ID

5.5 Laboratory Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> FCC - Registration No.: 817957 Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012. IC - Registration No.: 10106A-1 The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1. CNAS - Registration No.: CNAS L6048 Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

<p>Shenzhen Zhongjian Nanfang Testing Co., Ltd. Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755-23118282 Fax: +86-755-23116366</p>
--

5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m SAC	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK	VULB9163	CCIS0005	03-25-2016	03-25-2017
3	Horn Antenna	SCHWARZBECK	BBHA9120D	CCIS0006	03-25-2016	03-25-2017
4	Pre-amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	04-01-2016	03-31-2017
5	Pre-amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	04-01-2016	03-31-2017
6	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP30	CCIS0023	03-30-2016	03-30-2017
7	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	03-24-2016	03-24-2017
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	08-23-2014	08-22-2017
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	03-24-2016	03-24-2017
3	LISN	CHASE	MN2050D	CCIS0074	03-26-2016	03-26-2017
4	Coaxial Cable	CCIS	N/A	CCIS0086	04-01-2016	03-31-2017
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107														
Test Method:	ANSI C63.4:2009														
Test Frequency Range:	150kHz to 30MHz														
Class / Severity:	Class B														
Receiver setup:	RBW=9kHz, VBW=30kHz														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>0.5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dB μ V)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	0.5-30	60	50
	Frequency range (MHz)		Limit (dB μ V)												
		Quasi-peak	Average												
	0.15-0.5	66 to 56*	56 to 46*												
	0.5-5	56	46												
0.5-30	60	50													
* Decreases with the logarithm of the frequency.															
Test setup:	<p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test procedure	<ol style="list-style-type: none"> The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2009 on conducted measurement. 														
Test environment:	Temp.: 23 °C Humid.: 56% Press.: 101kPa														
Measurement Record:	Uncertainty: ± 3.28 dB														
Test Instruments:	Refer to section 5.7 for details														
Test mode:	Refer to section 5.3 for details														
Test results:	Pass														

Measurement data:

Line:




Trace: 15

Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 EUT : Smart Watch
 Model : PULSE
 Test Mode : PC mode
 Power Rating : AC120/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: YI
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	27.76	0.26	10.78	38.80	65.78	-26.98	QP
2	0.154	22.90	0.26	10.78	33.94	55.78	-21.84	Average
3	0.258	14.45	0.26	10.75	25.46	51.51	-26.05	Average
4	0.299	19.00	0.26	10.74	30.00	60.28	-30.28	QP
5	0.299	12.67	0.26	10.74	23.67	50.28	-26.61	Average
6	0.697	21.64	0.28	10.77	32.69	56.00	-23.31	QP
7	0.697	13.59	0.28	10.77	24.64	46.00	-21.36	Average
8	1.032	15.69	0.29	10.87	26.85	56.00	-29.15	QP
9	18.820	23.10	0.89	10.92	34.91	60.00	-25.09	QP
10	18.920	21.23	0.89	10.92	33.04	50.00	-16.96	Average
11	22.655	24.10	1.30	10.89	36.29	50.00	-13.71	Average
12	22.896	26.74	1.36	10.89	38.99	60.00	-21.01	QP

Neutral:



Trace: 13

Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN NEUTRAL
 EUT : Smart Watch
 Model : PULSE
 Test Mode : PC mode
 Power Rating : AC120/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: YT
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	28.18	0.17	10.78	39.13	65.78	-26.65	QP
2	0.154	22.81	0.17	10.78	33.76	55.78	-22.02	Average
3	0.170	26.49	0.17	10.77	37.43	64.94	-27.51	QP
4	0.174	20.30	0.17	10.77	31.24	54.77	-23.53	Average
5	0.258	19.52	0.16	10.75	30.43	61.51	-31.08	QP
6	0.258	13.88	0.16	10.75	24.59	51.51	-26.92	Average
7	0.697	11.89	0.17	10.77	22.83	46.00	-23.17	Average
8	0.720	19.41	0.17	10.78	30.36	56.00	-25.64	QP
9	17.109	22.16	0.60	10.91	33.67	60.00	-26.33	QP
10	17.291	21.12	0.60	10.91	32.63	50.00	-17.37	Average
11	22.655	23.09	0.95	10.89	34.93	50.00	-15.07	Average
12	23.018	26.24	1.00	10.89	38.13	60.00	-21.87	QP

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

6.2 Radiated Emission


Test Requirement:	FCC Part 15 B Section 15.109				
Test Method:	ANSI C63.4:2009				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency	Limit (dBuV/m @3m)			Remark
	30MHz-88MHz	40.0			Quasi-peak Value
	88MHz-216MHz	43.5			Quasi-peak Value
	216MHz-960MHz	46.0			Quasi-peak Value
	960MHz-1GHz	54.0			Quasi-peak Value
	Above 1GHz	54.0			Average Value
		74.0			Peak Value
Test setup:	Below 1GHz				
	Above 1GHz				

Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test environment:	Temp.: 25 °C Humid.: 55% Press.: 1 01kPa
Measurement Record:	Uncertainty: ±4.88dB
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Below 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) HORIZONTAL
 EUT : Smart Watch
 Model : PULSE
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: YT
 REMARK :

	ReadAntenna	Cable Preamp	Limit	Over				
Freq	Level Factor	Loss Factor	Level	Line	Limit	Remark		
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	55.027	44.92	12.65	1.36	29.80	29.13	40.00	-10.87 QP
2	128.563	53.61	12.24	2.27	29.34	38.78	43.50	-4.72 QP
3	140.342	53.97	11.70	2.41	29.27	38.81	43.50	-4.69 QP
4	216.024	52.20	11.18	2.85	28.73	37.50	46.00	-8.50 QP
5	245.090	51.87	11.85	2.82	28.57	37.97	46.00	-8.03 QP
6	625.078	42.55	18.64	3.90	28.86	36.23	46.00	-9.77 QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) VERTICAL
 EUT : Smart Watch
 Model : PULSE
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: YI
 REMARK :

	Read	Antenna	Cable	Preamp		Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
-----	-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	46.503	47.27	16.96	1.28	29.85	35.66	40.00	-4.34 QP
2	53.693	44.75	13.24	1.32	29.81	29.50	40.00	-10.50 QP
3	121.549	46.07	11.89	2.19	29.38	30.77	43.50	-12.73 QP
4	132.685	47.90	12.12	2.32	29.31	33.03	43.50	-10.47 QP
5	233.349	46.74	11.66	2.83	28.63	32.60	46.00	-13.40 QP
6	517.248	46.77	17.23	3.71	29.00	38.71	46.00	-7.29 QP

Above 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Smart Watch
 Model : PULSE
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: YT
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	3591.116	45.19	28.66	8.94	40.21	42.58	74.00	-31.42	Peak
2	3591.116	35.69	28.66	8.94	40.21	33.08	54.00	-20.92	Average
3	4187.860	41.97	33.18	9.86	40.96	44.05	74.00	-29.95	Peak
4	4187.860	31.68	33.18	9.86	40.96	33.76	54.00	-20.24	Average
5	5018.643	39.20	36.83	10.80	39.99	46.84	74.00	-27.16	Peak
6	5018.643	30.41	36.83	10.80	39.99	38.05	54.00	-15.95	Average

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Smart Watch
 Model : PULSE
 Test mode : PC Mode
 Power Rating : AC120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: YT
 REMARK :

	Read	Antenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	3407.311	41.82	27.43	8.61	38.96	38.90	74.00 -35.10 Peak
2	3407.311	31.64	27.43	8.61	38.96	28.72	54.00 -25.28 Average
3	4187.860	40.68	33.18	9.86	40.96	42.76	74.00 -31.24 Peak
4	4187.860	30.24	33.18	9.86	40.96	32.32	54.00 -21.68 Average
5	5289.370	41.03	35.63	11.12	40.14	47.64	74.00 -26.36 Peak
6	5289.370	31.48	35.63	11.12	40.14	38.09	54.00 -15.91 Average