

FCC Part 24E & 27 Measurement and Test Report

For

Hyundai Corporation

25, Yulgok-ro 2-Gil, Jongno-gu, Seoul, South Korea

FCC ID: RQQHLT-FSL500B

FCC Rules: FCC Part 24E, FCC Part 27

Product Description: 4G Smart Phone

Tested Model: L500C

Report No.: STR16108015I-2

Tested Date: 2016-10-09 to 2016-10-24

Issued Date: 2016-10-25

Tested By: Iven Guo / Engineer *Iven Guo*

Reviewed By: Silin Chen / EMC Manager *Silin Chen*

Approved & Authorized By: Jandy So / PSQ Manager *Jandy So*

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

TABLE OF CONTENTS

| | |
|---|-----------|
| 1. GENERAL INFORMATION..... | 3 |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3 |
| 1.2 TEST STANDARDS..... | 4 |
| 1.3 TEST METHODOLOGY..... | 4 |
| 1.4 TEST FACILITY..... | 4 |
| 1.5 EUT SETUP AND TEST MODE..... | 5 |
| 1.6 MEASUREMENT UNCERTAINTY..... | 6 |
| 1.7 TEST EQUIPMENT LIST AND DETAILS..... | 6 |
| 2. SUMMARY OF TEST RESULTS..... | 7 |
| 3. RF EXPOSURE..... | 8 |
| 3.1 STANDARD APPLICABLE..... | 8 |
| 3.2 TEST RESULT..... | 8 |
| 4. RF OUTPUT POWER..... | 9 |
| 4.1 STANDARD APPLICABLE..... | 9 |
| 4.2 TEST PROCEDURE..... | 9 |
| 4.3 ENVIRONMENTAL CONDITIONS..... | 9 |
| 4.4 SUMMARY OF TEST RESULTS/PLOTS..... | 10 |
| 5. PEAK-TO-AVERAGE RATIO (PAR) OF TRANSMITTER..... | 13 |
| 5.1 STANDARD APPLICABLE..... | 13 |
| 5.2 TEST PROCEDURE..... | 13 |
| 5.3 ENVIRONMENTAL CONDITIONS..... | 13 |
| 5.4 SUMMARY OF TEST RESULTS..... | 13 |
| 6. EMISSION BANDWIDTH..... | 14 |
| 6.1 STANDARD APPLICABLE..... | 14 |
| 6.2 TEST PROCEDURE..... | 14 |
| 6.3 ENVIRONMENTAL CONDITIONS..... | 14 |
| 6.4 SUMMARY OF TEST RESULTS/PLOTS..... | 14 |
| 7. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL..... | 15 |
| 7.1 STANDARD APPLICABLE..... | 15 |
| 7.2 TEST PROCEDURE..... | 15 |
| 7.3 ENVIRONMENTAL CONDITIONS..... | 15 |
| 7.4 SUMMARY OF TEST RESULTS/PLOTS..... | 16 |
| 8. SPURIOUS RADIATED EMISSIONS..... | 17 |
| 8.1 STANDARD APPLICABLE..... | 17 |
| 8.2 TEST PROCEDURE..... | 17 |
| 8.3 ENVIRONMENTAL CONDITIONS..... | 17 |
| 8.4 SUMMARY OF TEST RESULTS/PLOTS..... | 17 |
| 9. FREQUENCY STABILITY..... | 23 |
| 9.1 STANDARD APPLICABLE..... | 23 |
| 9.2 TEST PROCEDURE..... | 23 |
| 9.3 ENVIRONMENTAL CONDITIONS..... | 24 |
| 9.4 SUMMARY OF TEST RESULTS/PLOTS..... | 24 |

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Hyundai Corporation
 Address of applicant: 25, Yulgok-ro 2-Gil, Jongno-gu, Seoul, South Korea

Manufacturer: Shenzhen Fortuneship Technology Co., Ltd.
 Address of manufacturer: Room 701-716, 7th Floor, Kanghesheng Building, No.1
 ChuangSheng Road, Nanshan District, Shenzhen,
 Guangdong, P. R. China

| General Description of EUT: | |
|---|-----------------|
| Product Name: | 4G Smart Phone |
| Brand Name: | / |
| Model No.: | L500C |
| Hardware version: | WW816 V0.6 |
| Software version: | Android 6.0 |
| Rated Voltage: | DC 3.7V |
| Battery Capacity: | 2200mAh |
| Device Category: | Portable Device |
| <i>Note: The test data is gathered from a production sample provided by the manufacturer.</i> | |

| Technical Characteristics of EUT: Main board | |
|--|---|
| 4G | |
| Support Networks: | FDD-LTE |
| Support Band: | FDD-LTE Band 2, 7 |
| Uplink Frequency: | FDD-LTE Band 2: Tx: 1850-1910MHz, FDD-LTE Band 7: Tx: 2500-2570MHz |
| Downlink Frequency: | FDD-LTE Band 2: Rx: 1930-1990MHz, FDD-LTE Band 7: Rx: 2620-2690MHz |
| RF Output Power: | FDD-LTE Band 2: 24.02dBm, FDD-LTE Band 7: 24.07dBm, |
| Type of Emission: | FDD-LTE Band 2: 17M9G7D, 17M9W7D FDD-LTE Band 7: 17M9G7D, 17M9W7D |
| Type of Modulation: | QPSK, 16QAM |
| Antenna Type: | Integral Antenna |
| Antenna Gain: | FDD-LTE Band 2: -1.6dBi FDD-LTE Band 7: -1.0dBi |

1.2 Test Standards

The following report is prepared on behalf of the Hyundai Corporation in accordance with FCC Part 22 subpart H, FCC Part 24 subpart E and FCC Part 27 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 22 subpart H, FCC Part 24 subpart E and FCC Part 27 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI/TIA-603-D: 2010 and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 971168 D01 Power Meas License Digital Systems v02r02 shall be performed also.

1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

| Test Mode List | | |
|-----------------------|----------------|----------------------------|
| Test Mode | Description | Remark |
| TM1 | FDD-LTE Band 2 | Low, Middle, High Channels |
| TM2 | FDD-LTE Band 7 | Low, Middle, High Channels |

EUT Cable List and Details

| Cable Description | Length (M) | Shielded/Unshielded | With Core/Without Core |
|-------------------|------------|---------------------|------------------------|
| USB Cable | 1.0 | Shielded | Without Ferrite |
| Earphone | 1.2 | Unshielded | Without Ferrite |

Auxiliary Equipment List and Details

| Description | Manufacturer | Model | Serial Number |
|-------------|--------------|-------|---------------|
| Notebook | Lenovo | E10 | LR-63C8R |

Special Cable List and Details

| Cable Description | Length (M) | Shielded/Unshielded | With Core/Without Core |
|-------------------|------------|---------------------|------------------------|
| / | / | / | / |

1.6 Measurement Uncertainty

| Measurement uncertainty | | |
|--------------------------------|------------|---------------------|
| Parameter | Conditions | Uncertainty |
| RF Output Power | Conducted | $\pm 0.42\text{dB}$ |
| Occupied Bandwidth | Conducted | $\pm 1.5\%$ |
| Frequency Stability | Conducted | 2.3% |
| Transmitter Spurious Emissions | Radiated | $\pm 5.1\text{dB}$ |
| Transmitter Spurious Emissions | Conducted | $\pm 0.42\text{dB}$ |

1.7 Test Equipment List and Details

| No. | Description | Manufacturer | Model | Serial No. | Cal Date | Due. Date |
|-----------|-------------------------|-----------------|-------------|-------------|------------|------------|
| SEMT-1075 | Communication Tester | Rohde & Schwarz | CMW500 | 148650 | 2016-06-04 | 2017-06-03 |
| SEMT-1034 | GSM Tester | Rohde & Schwarz | CMU200 | 104036 | 2016-06-04 | 2017-06-03 |
| SEMT-1072 | Spectrum Analyzer | Agilent | E4407B | MY41440400 | 2016-06-04 | 2017-06-03 |
| SEMT-1079 | Spectrum Analyzer | Agilent | N9020A | US47140102 | 2016-06-04 | 2017-06-03 |
| SEMT-1080 | Signal Generator | Agilent | 83752A | 3610A01453 | 2016-06-04 | 2017-06-03 |
| SEMT-1081 | Vector Signal Generator | Agilent | N5182A | MY47070202 | 2016-06-04 | 2017-06-03 |
| SEMT-1028 | Power Divider | Weinschel | 1506A | PM204 | 2016-06-04 | 2017-06-03 |
| SEMT-1082 | Power Divider | RF-Lambda | RFLT4W5M18G | 14110400027 | 2016-06-04 | 2017-06-03 |
| SEMT-1031 | Spectrum Analyzer | Rohde & Schwarz | FSP30 | 836079/035 | 2016-06-04 | 2017-06-03 |
| SEMT-1007 | EMI Test Receiver | Rohde & Schwarz | ESVB | 825471/005 | 2016-06-04 | 2017-06-03 |
| SEMT-1008 | Amplifier | Agilent | 8447F | 3113A06717 | 2016-06-04 | 2017-06-03 |
| SEMT-1043 | Amplifier | C&D | PAP-1G18 | 2002 | 2016-06-04 | 2017-06-03 |
| SEMT-1069 | Loop Antenna | Schwarz beck | FMZB 1516 | 9773 | 2016-06-04 | 2017-06-03 |
| SEMT-1068 | Broadband Antenna | Schwarz beck | VULB9163 | 9163-333 | 2016-06-04 | 2017-06-03 |
| SEMT-1042 | Horn Antenna | ETS | 3117 | 00086197 | 2016-06-04 | 2017-06-03 |
| SEMT-1121 | Horn Antenna | ETS | 3116B | 00088203 | 2016-06-04 | 2017-06-03 |

2. SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test Item | Result |
|------------------------|--|-----------|
| § 1.1307, § 2.1093 | RF Exposure | Compliant |
| § 24.232 (c), §27.50 | RF Output Power | Compliant |
| § 24.51, § 27.50 | Peak-to-average Ratio (PAR) of Transmitter | Compliant |
| § 24.238 (b), § 27.53 | Emission Bandwidth | Compliant |
| § 24.238 (a), § 27.53 | Spurious Emissions at Antenna Terminal | Compliant |
| § 24.238 (a) , § 27.53 | Spurious Radiation Emissions | Compliant |
| § 24.238 (a) , § 27.53 | Out of Band Emissions | Compliant |
| § 24.235, § 27.54 | Frequency Stability | Compliant |

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR report.

4. RF Output Power

4.1 Standard Applicable

According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d)(4), Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

According to §27.50(c)(10), Portable stations (hand-held devices) in the 698-746 MHz band are limited to 3 watts ERP.

4.2 Test Procedure

Conducted output power test method:



Radiated power test method:

- 1.The setup of EUT is according with per ANSI/TIA Standard 603D and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

4.3 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 24 °C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

4.4 Summary of Test Results/Plots

Max. Radiated Power:

FDD-LTE Band 2

| Channel Bandwidth: 1.4 MHz | | | |
|----------------------------|---------|---------------|---------|
| Modulation | Channel | E.i.r.p [dBm] | Verdict |
| QPSK | LCH | 22.09 | PASS |
| | MCH | 22.86 | PASS |
| | HCH | 21.05 | PASS |
| 16QAM | LCH | 22.64 | PASS |
| | MCH | 21.72 | PASS |
| | HCH | 21.89 | PASS |
| Channel Bandwidth: 3 MHz | | | |
| Modulation | Channel | E.i.r.p [dBm] | Verdict |
| QPSK | LCH | 21.72 | PASS |
| | MCH | 21.54 | PASS |
| | HCH | 22.25 | PASS |
| 16QAM | LCH | 21.82 | PASS |
| | MCH | 22.05 | PASS |
| | HCH | 22.17 | PASS |
| Channel Bandwidth: 5 MHz | | | |
| Modulation | Channel | E.i.r.p [dBm] | Verdict |
| QPSK | LCH | 22.69 | PASS |
| | MCH | 21.16 | PASS |
| | HCH | 21.91 | PASS |
| 16QAM | LCH | 21.82 | PASS |
| | MCH | 21.39 | PASS |
| | HCH | 21.91 | PASS |
| Channel Bandwidth: 10 MHz | | | |
| Modulation | Channel | E.i.r.p [dBm] | Verdict |
| QPSK | LCH | 22.13 | PASS |
| | MCH | 21.81 | PASS |
| | HCH | 22.69 | PASS |
| 16QAM | LCH | 21.99 | PASS |
| | MCH | 21.45 | PASS |
| | HCH | 21.16 | PASS |

| Channel Bandwidth: 15 MHz | | | |
|---------------------------|---------|---------------|---------|
| Modulation | Channel | E.i.r.p [dBm] | Verdict |
| QPSK | LCH | 22.27 | PASS |
| | MCH | 21.74 | PASS |
| | HCH | 21.57 | PASS |
| 16QAM | LCH | 21.57 | PASS |
| | MCH | 22.36 | PASS |
| | HCH | 21.51 | PASS |
| Channel Bandwidth: 20 MHz | | | |
| Modulation | Channel | E.i.r.p [dBm] | Verdict |
| QPSK | LCH | 21.67 | PASS |
| | MCH | 22.28 | PASS |
| | HCH | 21.74 | PASS |
| 16QAM | LCH | 21.67 | PASS |
| | MCH | 22.19 | PASS |
| | HCH | 22.41 | PASS |

FDD-LTE Band 7

| Channel Bandwidth: 5 MHz | | | |
|---------------------------|---------|---------------|---------|
| Modulation | Channel | E.i.r.p [dBm] | Verdict |
| QPSK | LCH | 21.16 | PASS |
| | MCH | 21.04 | PASS |
| | HCH | 22.29 | PASS |
| 16QAM | LCH | 21.28 | PASS |
| | MCH | 22.34 | PASS |
| | HCH | 21.57 | PASS |
| Channel Bandwidth: 10 MHz | | | |
| Modulation | Channel | E.i.r.p [dBm] | Verdict |
| QPSK | LCH | 21.47 | PASS |
| | MCH | 22.52 | PASS |
| | HCH | 22.47 | PASS |
| 16QAM | LCH | 22.43 | PASS |
| | MCH | 21.98 | PASS |
| | HCH | 22.28 | PASS |
| Channel Bandwidth: 15 MHz | | | |
| Modulation | Channel | E.i.r.p [dBm] | Verdict |

| QPSK | LCH | 22.03 | PASS |
|---------------------------|---------|---------------|---------|
| | MCH | 21.91 | PASS |
| | HCH | 22.21 | PASS |
| 16QAM | LCH | 21.37 | PASS |
| | MCH | 22.68 | PASS |
| | HCH | 21.93 | PASS |
| Channel Bandwidth: 20 MHz | | | |
| Modulation | Channel | E.i.r.p [dBm] | Verdict |
| QPSK | LCH | 21.91 | PASS |
| | MCH | 21.43 | PASS |
| | HCH | 21.97 | PASS |
| 16QAM | LCH | 21.85 | PASS |
| | MCH | 22.33 | PASS |
| | HCH | 21.78 | PASS |

Max. Conducted Output Power

Please refer to Appendix A: Average Power Output Data

Test result: Pass

5. Peak-to-average Ratio (PAR) of Transmitter

5.1 Standard Applicable


According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

According to §27.50(B), the peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

5.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded. Record the maximum PAPR level associated with a probability of 0.1%.

Test Configuration for the emission bandwidth testing:



5.3 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

5.4 Summary of Test Results

Please refer to Appendix B: Peak-to-Average Ratio

Test result: Pass

6. Emission Bandwidth

6.1 Standard Applicable


According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §27.53, The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

6.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



6.3 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

6.4 Summary of Test Results/Plots

Please refer to Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test result: Pass

7. Out of Band Emissions at Antenna Terminal

7.1 Standard Applicable

According to §24.238(a), The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.


According to §27.53 (g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB.

According to §27.53 (m)(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz.

7.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10th harmonic.

Test Configuration for the out of band emissions testing:



7.3 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 53% |
| ATM Pressure: | 1018 mbar |

7.4 Summary of Test Results/Plots

Please refer to Appendix D & E: Band Edge & Conducted Spurious Emission

Test result: Pass

8. Spurious Radiated Emissions

8.1 Standard Applicable

According to §24.238(a), The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

According to §27.53 (g) the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB.

8.2 Test Procedure

1. The setup of EUT is according with per ANSI/TIA-603-D: 2010 and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB = $43 + 10 \log_{10}(\text{power out in Watts})$

8.3 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52% |
| ATM Pressure: | 1012 mbar |

8.4 Summary of Test Results/Plots

According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:


Note: 1. this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

2. All test modes (different bandwidth and different modulation) are performed, but only the worst case is recorded in this report.

Spurious Emission From 30MHz to 1GHz


For FDD_LTE Band 2 Mode

Horizontal:



| No. | Frequency (MHz) | Reading (dBm) | Correct (dB) | Result (dBm) | Limit (dBm) | Margin (dB) | Remark |
|-----|-----------------|---------------|--------------|--------------|-------------|-------------|--------|
| 1 | 57.3923 | -69.24 | 4.99 | -64.25 | -13.00 | -51.25 | ERP |
| 2 | 102.3597 | -69.53 | 4.91 | -64.62 | -13.00 | -51.62 | ERP |
| 3 | 251.1804 | -70.02 | 9.36 | -60.66 | -13.00 | -47.66 | ERP |
| 4 | 321.0608 | -69.05 | 11.92 | -57.13 | -13.00 | -44.13 | ERP |
| 5 | 404.6665 | -69.15 | 12.50 | -56.65 | -13.00 | -43.65 | ERP |
| 6 | 675.2080 | -70.00 | 18.42 | -51.58 | -13.00 | -38.58 | ERP |


Vertical:



| No. | Frequency (MHz) | Reading (dBm) | Correct (dB) | Result (dBm) | Limit (dBm) | Margin (dB) | Remark |
|-----|-----------------|---------------|--------------|--------------|-------------|-------------|--------|
| 1 | 38.8879 | -68.96 | 4.76 | -64.20 | -13.00 | -51.20 | ERP |
| 2 | 52.2079 | -69.48 | 5.04 | -64.44 | -13.00 | -51.44 | ERP |
| 3 | 99.5281 | -70.05 | 4.86 | -65.19 | -13.00 | -52.19 | ERP |
| 4 | 304.6100 | -69.10 | 11.94 | -57.16 | -13.00 | -44.16 | ERP |
| 5 | 394.8545 | -68.91 | 12.46 | -56.45 | -13.00 | -43.45 | ERP |
| 6 | 620.7096 | -69.30 | 17.38 | -51.92 | -13.00 | -38.92 | ERP |


For FDD_LTE Band 7 Mode

Horizontal:



| No. | Frequency (MHz) | Reading (dBm) | Correct (dB) | Result (dBm) | Limit (dBm) | Margin (dB) | Remark |
|-----|-----------------|---------------|--------------|--------------|-------------|-------------|--------|
| 1 | 44.4308 | -68.51 | 4.95 | -63.56 | -13.00 | -50.56 | ERP |
| 2 | 56.3948 | -68.96 | 5.00 | -63.96 | -13.00 | -50.96 | ERP |
| 3 | 123.6985 | -69.28 | 4.52 | -64.76 | -13.00 | -51.76 | ERP |
| 4 | 221.3921 | -69.04 | 7.76 | -61.28 | -13.00 | -48.28 | ERP |
| 5 | 404.6665 | -69.15 | 12.50 | -56.65 | -13.00 | -43.65 | ERP |
| 6 | 763.3757 | -69.38 | 17.95 | -51.43 | -13.00 | -38.43 | ERP |

Vertical:



| No. | Frequency (MHz) | Reading (dBm) | Correct (dB) | Result (dBm) | Limit (dBm) | Margin (dB) | Remark |
|-----|-----------------|---------------|--------------|--------------|-------------|-------------|--------|
| 1 | 40.1347 | -69.85 | 4.93 | -64.92 | -13.00 | -51.92 | ERP |
| 2 | 55.8047 | -69.48 | 5.02 | -64.46 | -13.00 | -51.46 | ERP |
| 3 | 106.7587 | -69.74 | 4.88 | -64.86 | -13.00 | -51.86 | ERP |
| 4 | 315.4808 | -68.83 | 11.95 | -56.88 | -13.00 | -43.88 | ERP |
| 5 | 392.0951 | -68.58 | 12.33 | -56.25 | -13.00 | -43.25 | ERP |
| 6 | 668.1423 | -69.80 | 18.03 | -51.77 | -13.00 | -38.77 | ERP |

Note: Margin= (Reading+ Correct)- Limit

Spurious Emissions Above 1GHz
For FDD_LTE Band 2 Mode

| Frequency | Reading | Correct | Result | Limit | Margin | Polar |
|----------------------------|---------|---------|--------|-------|--------|-------|
| (MHz) | (dBm) | dB | (dBm) | (dBm) | (dB) | H/V |
| Low Channel (1852.4MHz) | | | | | | |
| 3704.80 | -34.94 | 9.92 | -25.02 | -13 | -12.02 | H |
| 5557.20 | -34.41 | 13.47 | -20.94 | -13 | -7.94 | H |
| 3704.80 | -32.78 | 9.92 | -22.86 | -13 | -9.86 | V |
| 5557.20 | -33 | 13.47 | -19.53 | -13 | -6.53 | V |
| Middle Channel (1880.0MHz) | | | | | | |
| 3760.00 | -35.98 | 10.08 | -25.9 | -13 | -12.90 | H |
| 5640.00 | -32.23 | 13.53 | -18.7 | -13 | -5.70 | H |
| 3760.00 | -32.7 | 10.08 | -22.62 | -13 | -9.62 | V |
| 5640.00 | -36.4 | 13.53 | -22.87 | -13 | -9.87 | V |
| High Channel (1907.6MHz) | | | | | | |
| 3815.20 | -36.99 | 9.92 | -27.07 | -13 | -14.07 | H |
| 5722.80 | -31.96 | 13.47 | -18.49 | -13 | -5.49 | H |
| 3815.20 | -37.97 | 9.92 | -28.05 | -13 | -15.05 | V |
| 5722.80 | -34.81 | 13.47 | -21.34 | -13 | -8.34 | V |

For FDD_LTE Band 7 Mode

| Frequency | Reading | Correct | Result | Limit | Margin | Polar |
|--------------------------|---------|---------|--------|-------|--------|-------|
| (MHz) | (dBm) | dB | (dBm) | (dBm) | (dB) | H/V |
| Low Channel (2500.0MHz) | | | | | | |
| 5000.00 | -36.51 | 11.66 | -24.85 | -13 | -11.85 | H |
| 7500.00 | -31.61 | 15.09 | -16.52 | -13 | -3.52 | H |
| 5000.00 | -33.94 | 11.66 | -22.28 | -13 | -9.28 | V |
| 7500.00 | -34.72 | 15.09 | -19.63 | -13 | -6.63 | V |
| Middle Channel (2535MHz) | | | | | | |
| 5070.00 | -34.85 | 11.78 | -23.07 | -13 | -10.07 | H |
| 7605.00 | -36.65 | 15.21 | -21.44 | -13 | -8.44 | H |
| 5070.00 | -33.18 | 11.78 | -21.4 | -13 | -8.40 | V |
| 7605.00 | -36.6 | 15.21 | -21.39 | -13 | -8.39 | V |
| High Channel (2570MHz) | | | | | | |
| 5140.00 | -31.95 | 11.89 | -20.06 | -13 | -7.06 | H |
| 7710.00 | -34.83 | 15.32 | -19.51 | -13 | -6.51 | H |
| 5140.00 | -34.57 | 11.89 | -22.68 | -13 | -9.68 | V |
| 7710.00 | -35.79 | 15.32 | -20.47 | -13 | -7.47 | V |

Note: Result=Reading+ Correct, Margin= Result- Limit

Testing is carried out with frequency rang 9kHz to 20GHz, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so the data is not display.

9. Frequency Stability

9.1 Standard Applicable

According to §24.235, The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

According to §27.54 The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

| Temperature: | Supply Voltage |
|----------------|--------------------------------------|
| 20°C | DC 3.3-4.2V declared by manufacturer |
| -30°C to +50°C | Normal |

9.3 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 20°C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

9.4 Summary of Test Results/Plots

Please refer to Appendix F: Frequency Stability

Test result: Pass

******* END OF REPORT *******