

RF EXPOSURE REPORT

REPORT NO.: SA121205E03A

MODEL NO.: WMC-AC01

FCC ID: RRK2012060056-1

RECEIVED: Jan. 13, 2013

TESTED: Jan. 29, 2013

ISSUED: Apr. 26, 2013

APPLICANT: Alpha Networks Inc.

ADDRESS: No.8 Li-shing 7th Rd., Science-based

Industrial Park, Hsinchu, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,

Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,

R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Reference No.: 130117E13

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Report No.: SA121205E03A 1 of 6 Report Format Version 5.0.0



TABLE OF CONTENTS

RE	LEASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE LIMIT	5
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA121205E03A	Original release	Apr. 26, 2013

Report No.: SA121205E03A 3 of 6 Report Format Version 5.0.0

Reference No.: 130117E13



1. CERTIFICATION

PRODUCT: Wireless AC Module

BRAND NAME: Alpha

MODEL NO.: WMC-AC01

TEST SAMPLE: R&D SAMPLE

APPLICANT: Alpha Networks Inc.

TESTED DATE: Jan. 29, 2013

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment (Model: WMC-AC01) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : ______, DATE: _Apr. 26, 2013

(Lori Chung, Specialist()

APPROVED BY: _____, DATE: Apr. 26, 2013



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY ELECTRIC FIELD STRENGTH (V/m)		MAGNETIC FIELD STRENGTH (A/m)	_	AVERAGE TIME (minutes)					
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE									
300-1500		F/1500		30					
1500-100,000			1.0	30					

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm²)	LIMIT (mW/cm²)
5260-5320 5500-5580 & 5660-5700	240.954	3.82	20	0.11552	1

--- END ---