

RF Exposure Evaluation

FCC ID: *RRPZM-HPS10BT*

1. Client Information

Applicant : Zalman Tech Co., Ltd.
Address : 14th Fl, Partners Tower 1, 345-13, Gasan-dong, Gumchun-gu, Seoul, 153-802 Korea
Manufacturer : Zalman Tech Co., Ltd.
Address : 14th Fl, Partners Tower 1, 345-13, Gasan-dong, Gumchun-gu, Seoul, 153-802 Korea

2. General Description of EUT

EUT Name	:	Bluetooth Headphone	
Models No.	:	ZM-HPS10BT	
Model Difference	:	N/A	
Product Description	:	Operation Frequency:2402MHz~2480MHz	
	:	Number of Channel:	79Channels see note (2)
	:	Out Power:	GFSK:4.159mW Conducted Power 8DPSK:4.150mW Conducted Power
	:	Antenna Gain:	3.44 dBi PCB Antenna
	:	Modulation Type:	GFSK 1Mbps(1 Mbps) π /4-DQPSK(2 Mbps) 8-DPSK(3 Mbps)
Power Supply	:	DC Voltage supplied from Host System by USB cable DC Voltage supplied by Li-ion battery.	
Power Rating	:	DC 5.0V from USB DC 3.7V from Li-ion battery	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note

For a more detailed features description, please refer to the RF Test Report.

MPE Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies V05.

Appendix A: SAR Test Thresholds for 100MHz~6GHz and ≤ 50 mm.

SAR can be exempted if the output power is less than the SAR exclusion threshold: For F=2450, and Distance=10mm, the output power is less than 19mW (12.79 dBm).

Please see the follow table:

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

2. Calculation:

$$\text{EIRP} = \text{P} + \text{G}$$

Where P=Conducted Output Power (dBm)

G=Power Gain of the Antenna (dBi)

So

Bluetooth				
Test Mode	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)
GFSK(1Mbps)	6.19	3.44	9.63	9.183
8-DPSK(3 Mbps)	6.18	3.44	9.62	9.162

3. Conclusion:

No SAR Evaluation required since Transmitter output power is bellow FCC threshold.