
Find a Location for Lynx and Mount It


Mount method or the Vent Mount method. For the Vent Mount, wait until after you have connected all the cables to the Vehicle Dock before you attach it to the mount.

IMPORTANT: The air temperature needs to be at least 60° F to install the Dash Mount. If needed, turn on the heater in your


- 3. Select a flat surface for the Dash Mount with ample room for the Vehicle Dock and Radio. Avoid mounting on leather surfaces.
- Orient the adhesive foot so that the Vehicle Dock and Radio are easily accessible. Loosen the knob, adjust the adhesive foot, and then

Knob Adhesive Foot





to the PowerConnect Vehicle Dock using the provided screws.






• Once the surface is dry, remove the adhesive liner. Press and hold the Dash Mount in place for 30






You can adjust the dock mounting plate tilting it in your preferred direction





 Push until hooked on the rear PUSH ====> of the vent louver. Rest the foot against the bottom of the vent.






Install the Magnetic Mount Antenna and PowerConnect Power Adapter















NOTE: Steps **d** through **f** describe the antenna cable routing for a sedan or coupe where the antenna is mounted above the front windshield. The Lynx User Guide has detailed antenna cable routing instructions for all types of vehicles, online at www.siriusxm.com

Tuck the antenna cable under the windshield rubber molding and run it to


Route the cable out of the molding and into the rubber weather stripping around the door opening. Lift the weather stripping, tuck and run the cable inside




TIP: Include enough slack in your cable routing to accommodate open doors or the hood lid. Coil any excess cable in a hidden location and keep it away from any vehicle the audio so you can hear it in your vehicle. pedals or controls.

Signal found!

Run the cable under the dash, or under a floor mat, bringing it out at the Radio location.






Place Lynx into the Vehicle Dock and press



you connect the Vehicle Dock to the Vent Mount.



Be sure the vehicle is parked in a safe place outside.

with a clear view of the sky, and tap Continue

If Lynx displays Signal Found, tap Continue and proceed with connecting the audio in the next

If Lynx displays No Signal/Check Antenna. reposition the vehicle so that nothing is blocking the antenna's clear view of the sky, and tap and then **Continue** to try again.

You'll need to decide how you will connect Aux In Cable (or Cassette Adapter) Audio Setup: dio Quality GOOD BETTER E

Aux In Cable (AUX)

recommended for the FMDA.

How will you connect your audio?

If your vehicle radio has an AUX jack, the Aux In Cable connects Lynx to your vehicle radio for the audio. If your vehicle has a cassette player, you can also use an optional Cassette Adapter (sold separately) for the audio.





Bluetooth Stereo Audio Setup:



PowerConnect Audio Setup: You should now be hearing the SiriusXM audio. Connect the Vehicle Dock to

the Vent Mount if you are using the Vent Mount. PowerConnect plays the audio through your vehicle's FM radio, when Lynx and your vehicle's Proceed to the **Subscribe** section on the opposite side of this Quick Start

Should you should decide to change your type of audio connection at a later time can adjust the settings by tapping **Home** (a), tap (b), tap **Settings** (b), tap **Mode**,

Connect the Audio

connection option.

playing, tap No.

and tap Continue.

The chart to the right shows the

possible audio connection options an

their quality. Also consult the three

The Audio check screen should be

audio setup. Tap Continue.

information about each type of audio

displayed. If you cannot hear the audio

You will be prompted to continue with the

At the **How will you connect your audio?**

Continue to follow the on-screen instruction

until you reach the **Activation** screen










For mounting the *Power*Connect™ Vehicle Dock, you can select either the **Dash**


Dash Mount Method:




- tighten it again.




FM Channel Select

















Vent Mount Method:

Vehicle Dock.

Some vents have

Select a vent with ample


room for the Radio and


recessed louvers. If yours


are recessed, remove the


regular vent clamps and















Install the Vent Mount onto the





ADJUSTMENT



Subscribe

Lock Tab vehicle parked where it has a clear view of the sky throughout the activation process. Follow the instructions on the screen to subscribe. Dock. Push back to release

- a. To subscribe to SiriusXM satellite radio, you will need the Radio ID which can be found:
- on the Activation screen
- by tuning to channel 0
- on a label on the bottom of the gift box
- on the label inside the rear cover of Lynx The Radio ID does not use the letters I, C
- Lynx should be displaying the **Activation** screen. To subscribe:
- Online: Go to www.siriusxm.com/ activatenow



Radio remain on and in the Vehicle Dock until subscribed. Once subscribed you'll be able to tune to the channels in your subscription plan.

Internet radio, Lynx will prompt you to set up Internet radio. Follow the

as the plan you choose, on the subscription package you choose (which may differ from the package which arrived with the radio) until you call us at 1-866-635-2349 to cancel. See our Customer Agreement for complete terms at www.siriusxm.com. Activation fee of \$15, other fees and taxes apply. All fees and programming are subject to change

PowerConnect Vehicle Dock Controls & Connectors Remote Control Button Functions and Battery Copyrights and Trademarks

Front View When at the **Now Playing** two seconds to display

satellite or Internet browsing mode, and scro

Lvnx from the dock.



Knob to select a channe

ANT (Silver)

provided screws

AMPS Mounts Mounting Point AUDIO

In Cable or optional Cassette Adapter (so

FM preset at the bottom

< 88.7 >


Tap + at the bottom of

the screen to save the FM

channel as a new preset.

preset to replace it with a

new FM channel.



FM channel frequency.

FM OUT (Blue)

Internet radio service, including MLB® play-by-play.

cancer and birth defects or other reproductive harm.

Press for 5 seconds to turn Radio On; press and hold to

Tune Up/Down Channels

the city you have selected.

which you had previously

down the channels.

Toggles through the FM presets. If no FM presets have been set, opens the **FM Settings** screen.

battery cover.

Operating Temperature: PowerConnect Vehicle Dock

Battery Antenna Connector Battery Cover Remote Control

annels are limited to 1 rewind and up to 5 skip forwards per hour (other channels may have same Weight:

What's in the Box?









1.0 V_{rms} (max)

4.4 in (width) x 3.4 in (height) x 1.6 in (depth) 112 mm (width) x 87 mm (height) x 41 mm (depth)

Specifications

55 mm (width) x 105 mm (height) x 10 mm (depth)

9-16 V DC, 1.5 A (max) -4°F to +140°F (-20°C to +60°C)

1/8 in (3.5 mm) female





Dash Mount

Extended Vent

















do not cover the installation, removal, or reinstallation of any product.



Vehicle Kit LV1 QUICK START GUIDE

Listen to your Lynx Radio through your vehicle's stereo

siriusxm.com

Lvnx VK QSG 110921a

Sirius XM Radio Inc.

New York, NY 10020

© 2011 Sirius XM Radio Inc

1.866.635.2349

1221 Avenue of the Americas

