



1 APPENDIX I radio frequency exposure

LIMIT

According to §15.407(f), U-NII devices are subject to the radio frequency radiation exposure requirements specified in §§ 1.1307(b), 2.1091 and 2.1093 of this chapter, as appropriate. All equipment shall be considered to operate in a "general population/uncontrolled" environment. Applications for equipment authorization of devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request.

EUT Specification

| | |
|-----------------------------------|---|
| EUT | Mini BHS ADSL2+ |
| Frequency band (Operating) | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> Others: _____ |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others: _____ |
| Exposure classification | General Population/Uncontrolled exposure ($S=1mW/cm^2$) |
| Antenna diversity | <input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity |
| Max. output power | IEEE 802.11b: 18.19dBm (65.917mW) IEEE 802.11g: 14.15dBm (26.002mW) draft 802.11n Standard-20 MHz Channel mode:16.06dBm (40.365mW) draft 802.11n Wide-40 MHz Channel mode:15.64dBm (36.644mW) |
| Antenna gain (Max) | PIFA antenna(internal antenna): 3.5 dBi gain (Max) (Numeric gain: 2.239) |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation* <input type="checkbox"/> N/A |

Remark:

1. The maximum output power is 18.19 dBm (65.917mW) at 2412MHz (with 2.239 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is $1.0 mW/cm^2$ even if the calculation indicates that the power density would be larger.
4. All two antennas are completely uncorrelated with each other.

TEST RESULTS

No non-compliance noted.



Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter
 P = Power in Watts
 G = Numeric antenna gain
 d = Distance in meters
 S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$
$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm
 P = Power in mW
 G = Numeric antenna gain
 S = Power density in mW / cm²

Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²



Compliance Certification Services Inc.

Report No: C131228R01-RPW

FCC ID: RS3TA04GTF1

Date of Issue :January 13, 2014

| Modulation Mode | Frequency band (MHz) | Max. Conducted output power(dBm) | Antenna gain (dBi) | Distance (cm) | Power density (mW/cm ²) | Limit (mW/cm ²) |
|-----------------|----------------------|----------------------------------|--------------------|---------------|-------------------------------------|-----------------------------|
| 802.11b | 2412-2462 | 18.19 | 3.5 | 20 | 0.0294 | 1 |
| 802.11g | | 14.15 | 3.5 | 20 | 0.0116 | 1 |
| 802.11 n(20MHz) | | 16.06 | 3.5 | 20 | 0.0180 | 1 |
| 802.11 n(40MHz) | 2422-2452 | 15.64 | 3.5 | 20 | 0.0163 | 1 |

Note:

Both of the WLAN 2.4G can transmit simultaneously, the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.)

END OF REPORT