

Analysis Report

The Equipment Under Test (EUT) is a NER Laser Ops Alphapoint with Bluetooth 4.0 BLE only function. The Bluetooth module in the EUT is operating in the frequency range from 2402MHz to 2480MHz (40 channels with 2MHz channel spacing). The EUT can be connected with an iPhone so that it can control the DUT via the Apps. The DUT can fire in the Apps and some sound effect.

The EUT is powered by 4 x 1.5V AA batteries power supply.

The Model: E2281 is the same as the Model: E2280 in hardware aspect. The difference in model number serves as marketing strategy.
The models are different in model number only.

Antenna Type: Internal antenna

Antenna Gain: 0dBi

Nominal rated field strength is 95.3 dB μ V/m at 3m

Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 98.3dB μ V/m at 3m in frequency 2.480GHz, thus;

The EIRP = $[(FS * D)^2 * 1000 / 30] = 2.03mW$

Conducted power = Radiated Power (EIRP) – Antenna Gain
So;

Conducted Power = 2.03mW.

The SAR Exclusion Threshold Level:

= $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

= $3.0 * 5 / \text{sqrt}(2.480) \text{ mW}$

= 9.53 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.