



Hasbro Far East Limited

Application
For
Permissive Change
Two Way Radio with FRS and Messaging

(FCC ID: RS4HB001)

July 7, 2005

0513582
TL/ Ann Choy
July 7, 2005

- The test results reported in this report shall refer only to the sample actually tested and shall not refer or be deemed a refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2371 0521 Website: www.hk.intertek-etlsemko.com

INTERTEK TESTING SERVICES

SUMMARY OF CONTENTS

LIST OF EXHIBITS

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Spurious Emission
<i>EXHIBIT 4:</i>	Technical Specifications
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Photographs
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Part List
<i>EXHIBIT 9:</i>	RF Exposure Info
<i>EXHIBIT 10:</i>	Confidentiality Request

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

Application : Hasbro Far East Limited
Trade Name/Model No : Hasbro/ 75071 (Chat Now single pack - Flip)
Hasbro/ 75028 (Chat Now Communicator 2pk Assortment)
Hasbro/ 72970 (Chat Now Communicator single pk Assortment)
Hasbro/ 74855 (Chat Now 2pk - Flip)
Date : July 7, 2005

This report concerns (check one:) Original Grant _____ Class II Change X

Equipment Type: FRF – Part 95 Family Radio Face Held Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes _____ No X

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Report prepared by:

Tommy Leung
Intertek Testing Services
2/F., Garment Centre,
576 Castle Peak Road,
Kowloon, Hong Kong.
Phone: 852-2173-8536
Fax: 852-2741-1693

INTERTEK TESTING SERVICES

Table of Contents

1.0 <u>General Description</u>	2
1.1 Product Description	2
1.2 Purpose of Application	3
1.3 Test Methodology.....	3
1.4 Test Facility	3
2.0 <u>System Test Configuration</u>	5
2.1 Justification	5
2.2 EUT Exercising Software	6
2.3 Special Accessories	6
2.4 Measurement Uncertainty.....	6
2.5 Equipment Modification	6
2.6 Support Equipment.....	6
3.0 <u>Spurious Emission (Section 95.635(b))</u>	8
3.1 Field Strength of Spurious Radiation.....	9
4.0 <u>Technical Specifications</u>	15
5.0 <u>Product Labelling</u>	19
6.0 <u>Equipment Photographs</u>	22
7.0 <u>Instruction Manual</u>	24
8.0 <u>Part List</u>	26
9.0 <u>RF Exposure Info</u>	28
10.0 <u>Confidentiality Request</u>	30

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	Filename
Cover Page	Confidentiality Request	request.pdf
Cover Page	Purpose of Application	purpose of change.pdf
Test Report	Spurious Emission	spurious.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	config photos.doc
Internal Photo	Internal Photo	internal photos.doc
External Photo	External Photo	external photos.doc
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Test Report	Part List	partlist.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment Under Test (EUT) is a Two Way Radio with FRS operating between 462.5625MHz and 467.7125MHz. The EUT can conduct two-way voice communication with another person on the same channel (1-14). Also, the EUT can send a brief text message to another specific person on the pre-set channel. The EUT is powered by 6V (4 x "AAA" size 1.5V alkaline batteries).

Transmitter Portion

- (i) Type of Emission : FRS - 10K5F3E, 5K50F2D
- (ii) Frequency Range : FRS - 462.5625MHz to 462.7125MHz (7 Channels)
FRS - 467.5625MHz to 467.7125MHz (7 Channels)
- (iii) Maximum Power Rating : FRS (Channel 1-7) - 0.08W ERP
FRS (Channel 8-14) - 0.06W ERP
- (iv) Antenna Type : Integral

The flip type communicator in the Model: Hasbro 75028 (Chat Now Communicator 2pk Assortment), Hasbro 72970 (Chat Now Communicator single pk Assortment), and the Model: Hasbro 74855 (Chat Now 2pk - Flip) are same as the Model: Hasbro 75071 (Chat Now single pack - Flip) in hardware aspect. The model numbers are difference in package. The model numbers are identical in electrical, mechanical, and physical design. The difference in model number serves as marketing strategy.

INTERTEK TESTING SERVICES

1.2 Purpose of Application

The purpose of application is saved with filename: purpose of change.pdf.

As the RF module remained unchanged, only the spurious emission results were included in this report.

1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2001) and ANSI/TIA-603-B-2002. All measurement were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. For each scan, the procedure of maximizing emissions in Appendices D and E were followed. All Radiated tests were performed at an antenna the EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the emission data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. The test facility and site measurement data have been fully placed on file with the FCC.

INTERTEK TESTING SERVICES

EXHIBIT 2

SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

2.0 **System Test Configuration**

2.1 Justification

The device was configured for testing in a typical fashion (as a customer would normally use it). The device was placed on a turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes. When the radiated emissions are measured.

The device was powered by 4 new "AAA" size 1.5V alkaline batteries.

The frequency range from 30 MHz to 4.69 GHz was searched for spurious emissions from the device. Only those emissions reported were detected. All other emissions were at least 20 dB below the applicable limits.

INTERTEK TESTING SERVICES

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered on, a signal is transmitted.

2.3 Special Accessories

No special accessory is needed for compliance of this device.

2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.5 Equipment Modification

Any modification installed previous to testing by Hasbro Far East Limited will be incorporated in each production model sold/leased in the United States.


No modification were installed by Intertek Testing Services.

2.6 Support Equipment

A headset with 1.2m unshielded cable. (Supplied by Client)

Confirmed by:

*Tommy Leung
Assistant Manager
Intertek Testing Services
Agent for Hasbro Far East Limited*

 Signature

July 7, 2005 Date

INTERTEK TESTING SERVICES

EXHIBIT 3

SPURIOUS EMISSION

INTERTEK TESTING SERVICES

3.0 **Spurious Emission (Section 95.635)**

In order to satisfy the 95.635 requirement, the spurious emission from the EUT are measured and shown in the Exhibit 3.1.

INTERTEK TESTING SERVICES

3.1 Field Strength of Spurious Radiation (Section 95.635)

A. Test Equipment

Equipment	Brand Name	Model No.
Antenna	EMCO	A100, 3148, 3104C, 3115
Spectrum Analyzer	ADVANTEST	R3271
Test receiver	Rohde & Schwarz	ESVS30
RF Filter	Trilithic	3VF500/1000-5-50-CC

B. Testing Procedure

Radiated emission measurements were performed according to the procedures in ANSI C63.4(2001). All measurements were performed in Open Area Test Sites located at Roof Top of Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.

INTERTEK TESTING SERVICES

C. Radiated Emission Configuration Photograph

Worst Case Radiated Emission

For electronic filing, the radiated emission configurations photograph is saved with filename: config photos.doc

INTERTEK TESTING SERVICES

C. Test Result

**Hasbro Far East Limited
Hasbro/ 75071 (Chat Now single pack - Flip)**

Table 1(a)

1) Unwanted emission from CARRIER $\pm 6.25\text{kHz}$ to CARRIER $\pm 31.25\text{kHz}$

(Refer to the plots which is saved with filename: spurious.pdf)

Region	Unwanted emission	
	Channel 4	Channel 11
CARRIER $\pm 6.25\text{kHz}$ to $\pm 12.5\text{kHz}$	<25dB	<25dB
CARRIER $\pm 12.5\text{kHz}$ to $\pm 31.25\text{kHz}$	<35dB	<35dB

INTERTEK TESTING SERVICES

Table 1(b): Channel 4

Frequency (MHz)	Effective Radiated Power (dBm)	Transmission Power (dBm)	Attenuation (dBc)	Limit (dB)	Margin (dB)
925.275	-34.8	18.9	53.7	31.9	-21.8
1387.913	-27.3	18.9	46.2	31.9	-14.3
1850.550	-47.1	18.9	66.0	31.9	-34.1
2313.188	-42.2	18.9	61.1	31.9	-29.2
2775.825	-48.7	18.9	67.6	31.9	-35.7
3238.463	-49.9	18.9	68.8	31.9	-36.9
3701.100	-45.0	18.9	63.9	31.9	-32.0
4163.738	-40.6	18.9	59.5	31.9	-27.6
4626.375	-47.7	18.9	66.6	31.9	-34.7

- Remark: 1. Transmission power is 18.9 dBm or -11.1 dB(W).
2. According to Section 95.635(b7), the unwanted emission should be attenuated below TP by at least $43 + 10 \log_{10} (TP)$ dB or 31.9 dB.
3. The test is performed according to ANSI/TIA-603-B-2002.

Test Engineer: Kenneth C. C. Lam

Date of Test: June 23-28, 2005

INTERTEK TESTING SERVICES

Table 1(b): Channel 11

Frequency (MHz)	Effective Radiated Power (dBm)	Transmission Power (dBm)	Attenuation (dBc)	Limit (dB)	Margin (dB)
935.275	-35.0	17.9	52.9	30.9	-22.0
1402.912	-27.9	17.9	45.8	30.9	-14.9
1870.549	-46.7	17.9	64.6	30.9	-33.7
2338.186	-41.6	17.9	59.5	30.9	-28.6
2805.824	-48.3	17.9	66.2	30.9	-35.3
3273.461	-49.8	17.9	67.7	30.9	-36.8
3741.098	-45.3	17.9	63.2	30.9	-32.3
4208.736	-40.3	17.9	58.2	30.9	-27.3
4676.373	-48.5	17.9	66.4	30.9	-35.5

- Remark: 1. Transmission power is 17.9 dBm or -12.1 dB(W).
2. According to Section 95.635(b7), the unwanted emission should be attenuated below TP by at least $43 + 10 \log_{10} (TP)$ dB or 30.9 dB.
3. The test is performed according to ANSI/TIA-603-B-2002.

Test Engineer: Kenneth C. C. Lam

Date of Test: June 23-28, 2005

INTERTEK TESTING SERVICES

EXHIBIT 4

TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

4.0 Technical Specifications

INTERTEK TESTING SERVICES

4.1 Block Diagram

For electronic filing, the block diagram of the transceiver is saved with filename: block.pdf

Figure 4.1 Block Diagram

INTERTEK TESTING SERVICES

4.2 Schematic Diagram

For electronic filing, the schematic diagram of the transceiver is saved with filename: circuit.pdf

Figure 4.2 Schematic Diagram

INTERTEK TESTING SERVICES

EXHIBIT 5

PRODUCT LABELLING

INTERTEK TESTING SERVICES

5.0 Product Labelling

INTERTEK TESTING SERVICES

5.1 Label Artwork & Location

Figure 5.1 Label Artwork & Location

An engineering drawing of the label which will be permanently affixed to the unit.
For electronic filing, the label artwork & location are saved with filename: label.pdf

INTERTEK TESTING SERVICES

EXHIBIT 6

PHOTOGRAPHS

INTERTEK TESTING SERVICES

6.0 Equipment Photographs

For electronic filing, photographs of the tested EUT are saved with filename: external photos.doc and internal photos.doc

INTERTEK TESTING SERVICES

EXHIBIT 7

INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

7.0 Instruction Manual

This manual will be provided to the end-user with each unit sold/leased in the United States.

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf

INTERTEK TESTING SERVICES

EXHIBIT 8

PART LIST

INTERTEK TESTING SERVICES

8.0 Part List

For electronic filing, a preliminary copy of the Part List is saved with filename: partlist.pdf

INTERTEK TESTING SERVICES

EXHIBIT 9

RF EXPOSURE INFO

INTERTEK TESTING SERVICES

9.0 RF Exposure Info

The RF Safety Information is shown on P.1 of User Manual.

INTERTEK TESTING SERVICES

EXHIBIT 10

CONFIDENTIALITY REQUEST

INTERTEK TESTING SERVICES

10.0 Confidentiality Request

For electronic filing, a confidentiality request of the Instruction Manual is saved with filename: request.pdf