

# Radio Exposure Evaluation Report

FCC ID : RSE-OWM0131  
Equipment : WiFi Extender  
Brand Name : technicolor  
Model Name : OWM0131TCH  
Applicant : Technicolor Delivery Technologies Belgium  
Prins Boudewijnlaan 47  
Edegem B-2650  
Belgium  
Manufacturer : Technicolor Delivery Technologies Belgium  
Prins Boudewijnlaan 47  
Edegem B-2650  
Belgium  
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Jun. 23, 2022, and testing was started from Jun. 23, 2022 and completed on Sep. 08, 2022. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

**SPORTON INTERNATIONAL INC. Hsinhua Laboratory**  
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



# Table of Contents

**HISTORY OF THIS TEST REPORT .....3**

**1 GENERAL DESCRIPTION .....5**

1.1 Information.....5

1.2 Applicable Standards .....7

1.3 Testing Location .....7

**2 MAXIMUM PERMISSIBLE EXPOSURE .....8**

2.1 Limit of Maximum Permissible Exposure .....8

2.2 RF Exposure Exempt Measurement .....9

2.3 Multiple RF Sources Exposure .....10

2.4 MPE Calculation Method .....11

2.5 Calculated Result and Limit.....12

**Photographs of EUT V01**





### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
None

Reviewed by: Ryan Hsiao

Report Producer: Michelle Tsai



# 1 General Description

## 1.1 Information

### 1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)
ZigBee	2400-2483.5	2405-2480	DSSS (O-QPSK)
Z-Wave	902-928	908.4	FSK



1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Support
1	NA	NA	PCB	I-Pex	2.4GHz
2	NA	NA	PCB	I-Pex	2.4GHz
3	NA	NA	PCB	I-Pex	5GHz
4	NA	NA	PCB	I-Pex	5GHz
5	NA	NA	PCB	I-Pex	5GHz
6	NA	NA	PCB	I-Pex	5GHz
7	NA	NA	PCB	I-Pex	Bluetooth
8	NA	NA	PCB	I-Pex	Zigbee
9	NA	NA	PCB	I-Pex	Z-Wave

Ant.	Port	Gain (dBi)					
		2.4G	U-NII-1	U-NII-3	Bluetooth	Zigbee	Z-Wave
1	1	2.28	-	-	-	-	-
2	2	3.20	-	-	-	-	-
3	1	-	4.09	3.29	-	-	-
4	2	-	2.57	2.70	-	-	-
5	3	-	2.33	2.51	-	-	-
6	4	-	3.75	2.65	-	-	-
7	1	-	-	-	2.9	-	-
8	1	-	-	-	-	4.8	-
9	1	-	-	-	-	-	0.9

Composite Gain (dBi)			
Stream	2.4G	U-NII-1	U-NII-3
1SS	3.23	5.23	5.41
2SS	3.2	4.09	3.29
3SS	-	4.09	3.29
4SS	-	4.09	3.29

Note 1: The EUT has nine antennas.

**For 2.4GHz function:**

For IEEE 802.11b mode (1TX/1RX)

Only Ant. 1 (port 1) could transmit/receive.

For IEEE 802.11 b/g/n/VHT/ax mode (2TX/2RX)

Ant. 1 (port 1) ~ Ant. 2 (port 2) could transmit/receive simultaneously.



For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)
Ant. 7 can be used as transmitting/receiving antenna.

For 5GHz function:

For IEEE 802.11 a/n/ac/ax mode (4TX/4RX)
Ant. 3 (port 1) ~ Ant. 6 (port 4) could transmit/receive simultaneously.

For Zigbee function:

For Zigbee mode (1TX/1RX)
Ant. 8 (port 1) could transmit/receive.

For Z-Wave function:

For Z-Wave mode (1TX/1RX)
Ant. 9 (port 1) could transmit/receive.

1.1.3 Accessories

Table with 4 columns: Brand Name, Model Name, Power Rating, Power Cord. Rows include AC Adapter and Stand details.

Reminder: Regarding to more detail and other information, please refer to user manual.

1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR FCC Part 2 Subpart J, section 2.1091
KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- 47 CFR Part 1.1307
47 CFR Part 1.1310

1.3 Testing Location

Table with 2 main rows for testing locations: Hsinhua and Wen 33rd.St. Includes address, contact info, and FCC designation.

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

#### Multiple Transmitters Condition

Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.

Co-transmitting mode: WLAN 2.4GHz + WLAN 5GHz + Bluetooth + Zigbee + Zwave



## 2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x & \rightarrow d \leq 20cm \\ ERP_{20cm} & \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left( \frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040f(mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060(mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ <p>f is in MHz; R is in m; <math>R &gt; \lambda / 2\pi</math></p>

### 2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	<p>The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)</p>
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ <p>a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added.</p> <p>b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.</p> <p>c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.</p> <p>P<sub>i</sub> = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).</p> <p>P<sub>th,i</sub> = the exemption threshold power ( P<sub>th</sub> ) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.</p> <p>ERP<sub>j</sub> = the ERP of fixed, mobile, or portable RF source j.</p> <p>ERP<sub>th,j</sub> = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.</p> <p>Evaluated<sub>k</sub> = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.</p> <p>Evaluated Limit<sub>k</sub> = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.</p>



## 2.4 MPE Calculation Method

The MPE was calculated at 30 cm to show compliance with the power density limit.  
The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

## 2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

### WLAN 2.4GHz (Non-Beamforming)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm2)	Limit (mW/cm2)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	3.20	22.27	25.47	0.00	214.78	30	0.03116	1.00000	B	3060	0.0702
2.4G;D1D	3.20	21.03	24.23	0.00	161.44	30	0.02342	1.00000	B	3060	0.0528

### WLAN 2.4GHz (Beamforming)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm2)	Limit (mW/cm2)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	3.23	22.15	25.38	0.00	210.38	30	0.03052	1.00000	B	3060	0.0688

### WLAN 5GHz(Non-Beamforming)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm2)	Limit (mW/cm2)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	4.09	29.83	33.92	0.00	1503.14	30	0.21805	1.00000	B	3060	0.4914
5.8G;D1D	3.29	29.96	33.25	0.00	1288.25	30	0.18687	1.00000	B	3060	0.4211

### WLAN 5GHz(Beamforming)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm2)	Limit (mW/cm2)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	5.23	29.89	35.12	0.00	1981.53	30	0.28744	1.00000	B	3060	0.6478
5.8G;D1D	5.41	29.79	35.20	0.00	2018.37	30	0.29278	1.00000	B	3060	0.6598

### Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm2)	Limit (mW/cm2)	Option	TL ERP (mW)	TL Ratio
2.4G;BT-LE	2.90	19.12	22.02	0.00	108.8930	30	0.01408	1.00000	B	3060	0.0317

### Zigbee

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm2)	Limit (mW/cm2)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	4.80	18.10	22.90	0.00	118.85	30	0.01724	1.00000	B	3060	0.0389

### Z-Wave

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm2)	Limit (mW/cm2)	Option	TL ERP (mW)	TL Ratio
0.9G;	0.90	-3.95	-3.05	0.00	0.30	30	0.00004	0.60560	B	1853.14	0.0001

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)



**Simultaneous Transmission Analysis Mode: WLAN 2.4GHz + WLAN 5GHz + Bluetooth + Zigbee + Z-Wave**

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm2)	Limit (mW/cm2)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	3.20	22.27	25.47	0.00	214.78	30	0.03116	1.00000	B	3060	0.0702
5.8G;D1D	5.41	29.79	35.20	0.00	2018.37	30	0.29278	1.00000	B	3060	0.6598
2.4G;BT-LE	2.90	19.12	22.02	0.00	108.8930	30	0.01408	1.00000	B	3060	0.0317
2.4G;G1D	4.80	18.10	22.90	0.00	118.85	30	0.01724	1.00000	B	3060	0.0389
0.9G;	0.90	-3.95	-3.05	0.00	0.30	30	0.00004	0.60560	B	1853.14	0.0001
										Sum Ratio	0.8007
										Ratio Limit	1

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

Option	Sum TL Ratio_B	Option	Sum TL Ratio_C	Option	Sum TL Ratio_E
B	$\sum_{i=1}^a \frac{P_i}{P_{th,i}}$	C	$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$	E	$\sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k}$

Note: The above antenna gain was declared by manufacturer.

—————THE END—————