

RF Exposure Report

Report No.: SA151123E05A

FCC ID: RSE-TG788VV3NP

Equipment Name: Technicolor Gateway

Trade Name: technicolor

Model Number: TG788v v3

Product Code: DSLCBH788PR

Received Date: Feb. 24, 2017

Test Date: Mar. 14, 2017

Issued Date: May 08, 2017

Applicant: Technicolor Delivery Technologies Belgium

Address: Prins Boudewijnlaan 47, 2650 EDEGEM BELGIUM

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits For Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA151123E05A	Original release.	May 08, 2017

1 Certificate of Conformity

Product: Technicolor Gateway

Brand: technicolor

Test Model: TG788v v3

Product Code: DSLCBH788PR

Sample Status: Product Unit

Applicant: Technicolor Delivery Technologies Belgium


Test Date: Mar. 14, 2017


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :  _____, **Date:** May 08, 2017
Claire Kuan / Specialist

Approved by :  _____, **Date:** May 08, 2017
May Chen / Manager

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna Information				
Ant.	Brand	Model No.	Antenna Type	Connector
1	-	-	PCB Antenna	NA
2	-	-	PCB Antenna	NA

Frequency	Antenna Gain (dBi)			
	Ant. A1 (J711)		Ant. A2 (J710)	
	20 MHz	40 MHz	20 MHz	40 MHz
2412MHz	3.02	-	3.22	-
2422MHz	-	3.01	-	3.38
2437MHz	3.06	3.06	3.53	3.53
2452MHz	-	3.06	-	3.61
2462MHz	3.15	-	3.74	-

Frequency	Maximum Gain (dBi) for CDD mode			
	CDD mode (1 Stream 2 TX) for Power Gain		CDD mode (1 Stream 2 TX) for PSD Gain	
	20 MHz	40 MHz	20 MHz	40 MHz
2412MHz	3.22	-	6.13	-
2422MHz	-	3.38	-	6.21
2437MHz	3.53	3.53	6.31	6.31
2452MHz	-	3.61	-	6.35
2462MHz	3.74	-	6.46	-

Note:

- Maximum Correlated Directional Gain = $10 \log[(10 G_1 / 20 + 10 G_2 / 20 + \dots + 10 G_N / 20)^2 / N \text{ ANT}] \text{ dBi}$

Number of Transmitter Antennas & Bandwidth

Number of Transmitter Antennas	1TX		2TX	
	20 MHz	40 MHz	20 MHz	40 MHz
802.11b	V	X	X	X
802.11g	V	X	X	X
802.11n	V	V	V	V

2.5 Calculation Result of Maximum Conducted Power

Frequency (MHz)	Max Conducted Power (dBm)	Max Conducted Power (mW)	Directional Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Pass / Fail
2412-2462	20.85	121.545	6.31	20	0.10339	1	Pass

Note:

1. $P_{out} * G = \text{EIRP Power} = \text{Max Conducted Power (mW)} * \text{Gain (numeric)}$
2. $\text{Gain (dBi) to Gain (numeric)} = 10^{(6.31/10)} = 4.2756$
3. $\text{Distance (cm)} = r = \text{declare by manufacture} = 20 \text{ cm}$
4. $P_d = (P_{out} * G) / (4 * \pi * r^2) = (121.545 * 4.2756) / (4 * 3.1416 * 20^2) = 0.10339 \text{ (mW/cm}^2\text{)}$

--- END ---