




technicolor
TG789bvn




SN: CPYYWPPXXX




GW: UNICBSFFFFRI




MAC: AAABCCCDDEEE



Access Key: A1B2C3D4



Intertek
4003278
CONFORMS TO
UL STD 60950-1
CERTIFIED TO
CAN/CSA STD C22.2
NO. 60950-1




FCC ID: RSE-TG789BVNHPNA
US: TMBDL02BC2000T


This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and
(2) this device must accept any interference received, including interference that may cause undesired operation.

Caution: to reduce the risk of fire, use only NO. 26AWG or larger (e.g. 24AWG) UL Listed or CSA Certified Telecommunication Line Cord

wireless user codes




1234-5678




WiFi
CERTIFIED


Network Name: TNCAPVVVVVV
Wireless Key: 1234ABCDEF

Made in Vietnam Rated Input: 12V  2.25A


technicolor
TG789bvn HPNA




SN: CPYYWPPXXX




GW: UNICBSFFFFRI




MAC: AAABCCCDDEEE



Access Key: A1B2C3D4



Intertek
4003278
CONFORMS TO
UL STD 60950-1
CERTIFIED TO
CAN/CSA STD C22.2
NO. 60950-1




FCC ID: RSE-TG789BVNHPNA
US: TMBDL02BC2000T


This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and
(2) this device must accept any interference received, including interference that may cause undesired operation.

Caution: to reduce the risk of fire, use only NO. 26AWG or larger (e.g. 24AWG) UL Listed or CSA Certified Telecommunication Line Cord

wireless user codes




1234-5678



WiFi
CERTIFIED

Network Name: TNCAPVVVVVV
Wireless Key: 1234ABCDEF

Made in Vietnam Rated Input: 12V  2.25A

Label dimensions: 82 mm x 50.5 mm (chamfer 4.5 x 4.5mm)

Label here

