

FCC PART 18

EMI MEASUREMENT AND TEST REPORT

For

Midea Microwave and Electrical Appliances Manufacturing Co., Ltd.

Beijiao, Shunde, Foshan City, Guangdong, P.R. of China.

FCC ID: RSFEM308AYY

| | | | |
|---|--|--|--|
| This Report Concerns: <input checked="" type="checkbox"/> Original Report | | Equipment Type: Microwave oven | |
| Test Engineer: | Jack Wang <i>Jack.wang</i> | | |
| Report No.: | RSZ07091057 | | |
| Test Date: | 2007-09-28 to 2007-12-04 | | |
| Report Date: | 2007-12-04 | | |
| Reviewed By: | EMC Manager: Green Xu <i>Green Xu</i> | | |
| Prepared By: | Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 | | |

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Shenzhen). This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government.

TABLE OF CONTENTS

| | |
|--|-----------|
| GENERAL INFORMATION..... | 3 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3 |
| OBJECTIVE | 3 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 3 |
| TEST METHODOLOGY | 3 |
| TEST FACILITY | 3 |
| OPERATING CONDITION/TEST CONFIGURATION..... | 5 |
| JUSTIFICATION | 5 |
| EQUIPMENT MODIFICATIONS | 5 |
| EXTERNAL CABLE LIST AND DETAILS | 5 |
| CONFIGURATION OF TEST SETUP | 5 |
| BLOCK DIAGRAM OF TEST SETUP | 6 |
| CONDUCTED EMISSIONS | 7 |
| MEASUREMENT UNCERTAINTY | 7 |
| EUT SETUP | 7 |
| EMI TEST RECEIVER SETUP..... | 8 |
| TEST EQUIPMENT LIST AND DETAILS..... | 8 |
| TEST PROCEDURE | 8 |
| TEST RESULTS SUMMARY..... | 8 |
| TEST DATA | 9 |
| PLOT(S) OF TEST DATA | 9 |
| RADIATION HAZARD MEASUREMENT | 12 |
| ENVIRONMENTAL CONDITIONS | 12 |
| RADIATION HAZARD MEASUREMENT | 12 |
| INPUT POWER..... | 12 |
| LOAD FOR MICROWAVE OVENS | 13 |
| RF OUTPUT POWER MEASUREMENT | 13 |
| OPERATING FREQUENCY MEASUREMENT | 14 |
| RADIATED EMISSIONS..... | 20 |
| MEASUREMENT UNCERTAINTY | 20 |
| EUT SETUP | 20 |
| EMI TEST RECEIVER SETUP AND SPECTRUM ANALYZER SETUP..... | 21 |
| TEST EQUIPMENT LIST AND DETAILS..... | 21 |
| TEST PROCEDURE | 21 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 22 |
| TEST RESULTS SUMMARY..... | 22 |
| TEST DATA AND PLOTS..... | 22 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Midea Microwave and Electrical Appliances Manufacturing Co., Ltd.*'s model: *EM308AYY(Y=0-9 or A-Z)*; *Counter-top* or the "EUT" as referred to in this report is a *Microwave Oven* which measures approximately 25.5cm L x 26.5cm W x 29.5cm H, rated input voltage: AC 120 V/60 Hz.

* All measurement and test data in this report was gathered from production sample serial number: 0709010 (Assigned by BAEL, Shenzhen). The EUT was received on 2007-09-10.

Objective

The following test report is prepared on behalf of *Midea Microwave and Electrical Appliances Manufacturing Co., Ltd.* in accordance with Part 2, Subpart J, and Part 18, Subparts A, B and C of the Federal Communication Commissions rules and regulations.

The objective of the manufacturer is to determine compliance with FCC Part 18 limits.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with MP-5, FCC Methods of Measurements of Radio Noise Emissions from ISM Equipment, February 1986. All measurements were performed at Bay Area Compliance Laboratory Corporation. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 04, 2004. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



NVLAP LAB CODE 200707-0

The current scope of accreditations can be found at
<http://ts.nist.gov/Standards/scopes/2007070.htm>

OPERATING CONDITION/TEST CONFIGURATION

Justification

The EUT was provided for tests as a stand-alone device. It was prepared for testing in accordance with the manufacturer's instructions. The EUT was operated at maximum (continuous) RF output power. The loads consisted of water in a glass beaker in the amounts specified in the test procedure.


Equipment Modifications

No modifications were made to the unit tested.


External Cable List and Details

| Cable Description | Length (M) | From/Port | To |
|--|------------|-----------|----------|
| Unshielded Undetachable AC Power Cable | 1.0 | EUT | AC Mains |

Configuration of Test Setup



Block Diagram of Test Setup




CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 2.4 dB.

EUT Setup



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per MP-5: 1986 measurement procedure. Specification used was with the FCC Part 18.

The EUT was connected to a 120 VAC/ 60Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| <i>Frequency Range</i> | <i>IF B/W</i> |
|------------------------|---------------|
| 150 kHz – 30 MHz | 9 kHz |

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|---------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCS30 | 830245/006 | 2007-03-26 | 2008-03-26 |
| Rohde & Schwarz | L.I.S.N. | ESH2-Z5 | 892107/021 | 2007-03-26 | 2008-03-26 |

* Com-Power's LISN were used as the supporting equipment.

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

During the conducted emission test, the EUT power cord was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC PART 18.307, with the worst margin reading of:

3.30 dB at 18.8900 MHz in the **Live** conductor mode.

Test Data**Environmental Conditions**

| | |
|--------------------|----------|
| Temperature: | 25° C |
| Relative Humidity: | 56% |
| ATM Pressure: | 100.0kPa |

The testing was performed by Kidd Yang on 2007-09-28.

Test Mode: Max Power

| Line Conducted Emissions | | | | FCC Part 18.307 | |
|--------------------------|------------------|------------------|----------------------|-----------------|-------------|
| Frequency (MHz) | Amplitude (dBμV) | Detector (QP/AV) | Phase (Live/Neutral) | Limit (dBμV) | Margin (dB) |
| 18.8900 | 56.70 | QP | Live | 60.00 | 3.30 |
| 10.1900 | 56.50 | QP | Neutral | 60.00 | 3.50 |
| 0.6550 | 51.90 | QP | Neutral | 56.00 | 4.10 |
| 0.7800 | 51.60 | QP | Neutral | 56.00 | 4.40 |
| 0.9100 | 51.30 | QP | Neutral | 56.00 | 4.70 |
| 0.7600 | 51.30 | QP | Live | 56.00 | 4.70 |
| 0.5150 | 51.20 | QP | Live | 56.00 | 4.80 |
| 0.5200 | 40.50 | AV | Live | 46.00 | 5.50 |
| 18.6050 | 54.20 | QP | Neutral | 60.00 | 5.80 |
| 0.1500 | 59.90 | QP | Neutral | 66.00 | 6.10 |
| 0.4250 | 51.10 | QP | Live | 57.35 | 6.25 |
| 0.6550 | 38.80 | AV | Neutral | 46.00 | 7.20 |
| 0.1500 | 48.70 | AV | Neutral | 56.00 | 7.30 |
| 0.7600 | 38.60 | AV | Live | 46.00 | 7.40 |
| 0.1550 | 57.00 | QP | Live | 65.73 | 8.73 |
| 10.2350 | 51.00 | QP | Live | 60.00 | 9.00 |
| 0.4250 | 37.80 | AV | Live | 47.35 | 9.55 |
| 0.7800 | 35.80 | AV | Neutral | 46.00 | 10.20 |
| 0.9100 | 35.50 | AV | Neutral | 46.00 | 10.50 |
| 0.1550 | 37.90 | AV | Live | 55.73 | 17.83 |
| 18.8900 | 30.50 | AV | Live | 50.00 | 19.50 |
| 10.1900 | 30.30 | AV | Neutral | 50.00 | 19.70 |
| 18.6050 | 25.30 | AV | Neutral | 50.00 | 24.70 |
| 10.3900 | 20.70 | AV | Live | 50.00 | 29.30 |


Plot(s) of Test Data

Plot(s) of Test Data is presented hereinafter as reference.

Conducted Emission Test FCC Part18

28. Sep 07 19: 43


EUT: Microwave Oven M/N: EM308AYY
Manuf: MD
Op Cond: Max Power
Operator: Kidd Yang
Test Spec: AC 120V/60Hz L
Comment: Temp: 25 Humi 56%



Conducted Emission Test FCC Part18

28. Sep 07 20: 19

EUT: Microwave Oven M/N: EM308AYY
Manuf: MD
Op Cond: Max Power
Operator: Kidd Yang
Test Spec: AC 120V/60Hz N
Comment: Temp: 25 Humi 56%



RADIATION HAZARD MEASUREMENT

Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 26 ° C |
| Relative Humidity: | 56% |
| ATM Pressure: | 100.0 kPa |

Radiation Hazard Measurement

Radiation leakage was measured in the as-received condition with the oven door closed using a microwave leakage meter.

A 275ml water load was placed in the center of the oven and the oven was operated at maximum output power.

There was no microwave leakage exceeding a power level of $0.71\text{mW}/\text{cm}^2$ observed at any point 5cm or more from the external surface of the oven.

A maximum of $1.0\text{mW}/\text{cm}^2$ is allowed in accordance with the applicable Federal Standards. Hence, microwave leakage in the as-received condition with the oven door closed was below the maximum allowed.

Input Power

Input power and current was measured using a power analyzer. A 1000ml water load was placed in the center of the oven and the oven was operated at maximum output power. A 1000ml water load was chosen for its compatibility with the procedure commonly used by manufacturers to determine their input ratings.

| Input Voltage (Vac/Hz) | Input Current (Amps) | Measured Input Power (watts) | Rated Input Power (watts) |
|------------------------|----------------------|------------------------------|---------------------------|
| 120V/60Hz | 4.6 | 550 | 600 |

Based on the measured input power, the EUT was found to be operating within the intended specifications.

Load for Microwave Ovens

For all measurements, the energy developed by the oven was absorbed by a dummy load consisting of a quantity of tap water in a beaker. If the oven was provided with a shelf or other utensil support, this support was in its initial normal position. For ovens rated at 1000 watts or less power output, the beaker contained quantities of water as listed in the following subparagraphs. For ovens rated at more than 1000watts output, each quantity was increased by 50% for each 500watts or fraction thereof in excess of 1000watts. Additional beakers were used if necessary.

- Load for power output measurement: 1000 milliliters of water in the beaker located in the center of the oven.
- Load for frequency measurement: 1000 milliliters of water in the beaker located in the center of the oven.
- Load for measurement of radiation on second and third harmonic: Two loads, one of 700 and the other of 300 milliliters, of water are used. Each load is tested both with the beaker located in the center of the oven and with it in the right front corner.

The RF output power is rated at 1000 watts

Load used for power output measurement = 1000 milliliters of water
 Load used for frequency measurement = 1000 milliliters of water
 Load used for harmonic measurement = 700 & 300 milliliters of water
 Load used for Radiation leakage measurement = 275 milliliters of water

RF Output Power Measurement

The Caloric Method was used to determine maximum RF output power. The initial temperature of the water load was measured. The water load was placed in the center of the oven. The oven was operated at maximum output power for 100 seconds, the temperature of the water was re-measured.

| Load of Water (ml) | Starting Temperature (°C) | Final Temperature (°C) | Elapsed Time (Seconds) |
|--------------------|---------------------------|------------------------|------------------------|
| 500 | 24 | 39.4 | 100 |

RF Output Power = (4.2 joules/calorie)(volume in milliliters)(temperature rise)/(time in seconds)

RF Output Power = 4.2 x 500 x (39.4-24) / 100

RF Output Power = 323.4 Watts

The measurement output power was found to be below 500watts. Therefore, in accordance with Section 18.305 of Subpart-C, the measured out-of-band emissions were compared to the limit of 25µV/meter at a 300-meters measurement distance.

- ☒ The measured output power was found to exceed 500watts. Therefore, in accordance with Section 18.305 of Subpart-C, the measured out-of-band emissions were compared with the limit calculated as following:

$$\text{LFS} = 25 * \text{SQRT} (\text{Power Output}/500) (\mu\text{V}/\text{m})$$

$$\text{LFS} = 25 * \text{SQRT} (323.4/500) (\mu\text{V}/\text{m})$$

$$\text{LFS} = 20.1 (\mu\text{V}/\text{m})$$

Where: LFS is the maximum allowable field strength for out-of-band emissions in $\mu\text{V}/\text{meter}$ at a 300-meters measurement distance. Power Output is the measured output power in watts.

| Manufacturer | Model Number | LFS($\mu\text{V}/\text{m}$) | $\text{dB}\mu\text{V}/\text{m}$ at 300m | $\text{dB}\mu\text{V}/\text{m}$ at 3m |
|---|--|-------------------------------|---|---------------------------------------|
| Midea Microwave and Electrical Appliances Manufacturing Co., Ltd. | EM308AYY (Y=0-9 or A-Z); Counter-top | 20.1 | 26 | 66 |

Operating Frequency Measurement

Variation in Operating Frequency with Time

The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, a 1000ml water load was placed in the center of the oven and the oven was operated at maximum output power. The fundamental operating frequency was monitored until the water load was reduced to 20 percent of the original load.

The results of this test are as follows:

| Manufacturer | Model | Minimum Frequency (MHz) | Maximum Frequency (MHz) |
|---|---|-------------------------|-------------------------|
| Midea Microwave and Electrical Appliances Manufacturing Co., Ltd. | EM308AYY (Y=0-9 or A-Z) ; Counter-top | 2458 | 2460 |

Refer to data pages for details of the variation in operating frequency with time measurement.

Frequency VS Time (Minimum)




*RBW 1 MHz Marker 1 [T1]
VBW 3 MHz 96.26 dBμV
*SWT 1 s 2.45800000 GHz

Ref 112 dBμV

*Att 20 dB

1 PK
VIEW



Start 2.4 GHz

10 MHz/

Stop 2.5 GHz

FREQUENCY VS TIME 1

Date: 26.OCT.2007 22:41:57

Frequency VS Time (Maximum)




*RBW 1 MHz Marker 1 [T1]
VBW 3 MHz 97.64 dB μ V
*SWT 1 s 2.460000000 GHz

Ref 112 dB μ V

*Att 20 dB

1 PK
VIEW



FREQUENCY VS TIME 2

Date: 26.OCT.2007 22:46:06

Variation in Operating Frequency with Line Voltage

The EUT was operated / warmed by at least 10 minutes of use with a 1000ml water load at room temperature at the beginning of the test. Then the operating frequency was monitored as the input voltage was varied between 80 and 125 percent of the nominal rating.

The results of this test are as follows:

Line voltage varied from 96Vac to 150Vac.

| Manufacturer | Model | Minimum Frequency (MHz) | Maximum Frequency (MHz) |
|---|---------------------------------------|--------------------------------|--------------------------------|
| Midea Microwave and Electrical Appliances Manufacturing Co., Ltd. | EM308AYY (Y=0-9 or A-Z) ; Counter-top | 2460.7 | 2463.6 |

Please refer to following pages for details of the variation in operating frequency with line voltage measurement.

Frequency VS Voltage (Minimum)




REW 1 MHz Maskes 1 [T1]
VEW 3 MHz 103.23 dBpV
SWT 1 a 2.460700000 GHz

Ref 112 dBpV

Att 20 dB

1 PK
VIEW



FREQUENCY VS VOLTAGE LOW

Date: 26.OCT.2007 22:33:25

Frequency VS Voltage (Maximum)




RES 1 MHz Marker 1 [T1]
VIEW 3 MHz 99.47 dBμV
SWT 1 a 2.463600000 GHz

Ref 112 dBμV

Att 20 dB

1 PK
VIEW



Start 2.4 GHz

10 MHz/

Stop 2.5 GHz

PS

FREQUENCY VS VOLTAGE HIGH

Date: 26.OCT.2007 22:38:25


RADIATED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 4.0 dB.

EUT Setup



The radiated emission tests were performed in the 3 meters chamber A test site, using the setup accordance with the FCC MP - 5. The specification used was the FCC part 18 limits.

The EUT was connected to 120 VAC/60 Hz power source.

EMI Test Receiver Setup and Spectrum Analyzer Setup

The system was investigated from 30 MHz to 1 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

| <i>Frequency Range</i> | <i>R B/W</i> | <i>Video B/W</i> | <i>IF B/W</i> |
|------------------------|--------------|------------------|---------------|
| 30 – 1000 MHz | 100 kHz | 300 kHz | 120 kHz |

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|-------------|---------------|------------------|----------------------|
| HP | Amplifier | HP8447D | 2944A09795 | 2007-11-15 | 2008-11-15 |
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100035 | 2007-09-29 | 2008-09-29 |
| Sunol Sciences | Broadband Antenna | JB1 | A040904-1 | 2007-08-14 | 2008-08-14 |
| Sunol Sciences | System Controller | SC99V | 041304-1 | N/A | N/A |
| A.H. System | Horn Antenna | SAS-200/571 | 135 | 2007-05-17 | 2008-05-17 |
| Agilent | Spectrum analyzer | 8564E | 3943A01781 | 2007-11-22 | 2008-11-22 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Procedure

For the radiated emissions test, the EUT power cord was connected to the AC floor outlet.

Maximizing procedure was performed on the six (6) highest emissions to ensure that the EUT complied with all installation combinations.

The EUT was in the normal (naïve) operating mode during the final qualification test to represent the worst results.

All data was recorded in the Quasi-peak detection mode from 30 MHz to 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 18, with the worst margin reading of:

3.2 dB at **54.849825 MHz** in the **Vertical** polarization, 30 -1000MHz
1.59 dB at **4900 MHz** in the **Vertical** polarization, above 1 GHz

Test Data and Plots


Environmental Conditions

| | |
|--------------------|----------|
| Temperature: | 25° C |
| Relative Humidity: | 56% |
| ATM Pressure: | 100.0kPa |

The testing was performed by Jack Wang on 2007-12-04.

Test Mode: Max Power

30-1000MHz:



| Frequency (MHz) | Corrected Amplitude (dBµV/m) | Antenna Height (cm) | Polarity (H/V) | Turntable Position (deg) | Correction Factor (dB) | Limit (dBµV/m) | Margin (dB) |
|-----------------|------------------------------|---------------------|----------------|--------------------------|------------------------|----------------|-------------|
| 54.849825 | 35.8 | 103.0 | V | 355.0 | -19.6 | 66 | 3.2 |
| 41.596050 | 32.3 | 103.0 | V | 328.0 | -16.3 | 66 | 6.7 |
| 60.268575 | 31.9 | 104.0 | V | 329.0 | -20.1 | 66 | 7.1 |
| 49.903350 | 31.8 | 103.0 | V | 3.0 | -19.3 | 66 | 7.2 |
| 43.250775 | 30.5 | 104.0 | V | 277.0 | -17.3 | 66 | 8.5 |
| 907.145525 | 30.4 | 292.0 | H | 3.0 | -2.0 | 66 | 14.6 |

*Test Mode: Max Power***Above 1 GHz:**

| Indicated | | Table Angle Degree | Antenna | | Correction Factor | | | FCC Part 18 | | |
|-------------|----------------------------|--------------------|------------|--------------|-----------------------|-----------------|--------------------|-------------------------------|----------------------|-------------|
| Freq. (MHz) | Meter Reading (dB μ V) | | Height (m) | Polar (H/ V) | Antenna Factor (dB/m) | Cable Loss (dB) | Pre-Amp. Gain (dB) | Corrected Amp. (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| 4900 | 60.81 | 180 | 1.2 | V | 32.0 | 4.6 | 33.00 | 64.41 | 66 | 1.59 |
| 4900 | 59.29 | 180 | 1.2 | H | 32.0 | 4.6 | 33.00 | 62.89 | 66 | 3.11 |
| 7350 | 54.81 | 60 | 1.0 | V | 35.3 | 4.7 | 33.40 | 61.41 | 66 | 4.59 |
| 9800 | 49.86 | 180 | 1.2 | H | 38.2 | 5.8 | 34.10 | 59.76 | 66 | 6.24 |
| 7350 | 52.59 | 60 | 1.0 | H | 35.3 | 4.7 | 33.40 | 59.19 | 66 | 6.81 |
| 12250 | 48.02 | 180 | 1.0 | H | 37.2 | 6.1 | 34.64 | 56.68 | 66 | 9.32 |
| 14700 | 43.09 | 45 | 1.2 | V | 38.8 | 6.7 | 33.17 | 55.42 | 66 | 10.58 |
| 9800 | 44.73 | 180 | 1.2 | V | 38.2 | 5.8 | 34.10 | 54.63 | 66 | 11.37 |
| 14700 | 41.35 | 45 | 1.2 | H | 38.8 | 6.7 | 33.17 | 53.68 | 66 | 12.32 |
| 12250 | 38.85 | 180 | 1.0 | V | 37.2 | 6.1 | 34.64 | 47.51 | 66 | 18.49 |

******* END OF REPORT *******