

RF EXPOSURE REPORT

REPORT NO.: SA140714E01B

MODEL NO.: AT-TQ4600

FCC ID: RSL-TQ4600

RECEIVED: July 24, 2014

TESTED: Aug. 05 to Sep. 11, 2014

ISSUED: Dec. 25, 2014

APPLICANT: Allied Telesis R&D Center K.K.

ADDRESS: 2nd TOC Bldg. 7-21-11 Nishi-Gotanda,
Shinagawa-ku, Tokyo 141-0031, Japan

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by any
government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	7




RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA140714E01B	Original release	Dec. 25, 2014



A D T

1. CERTIFICATION

PRODUCT: Access Point
BRAND NAME:  Allied Telesis™
MODEL NO.: AT-TQ4600
TEST SAMPLE: ENGINEERING SAMPLE
APPLICANT: Allied Telesis R&D Center K.K.
TESTED DATE: Aug. 05 to Sep. 11, 2014
STANDARDS: FCC Part 2 (Section 2.1091)
KDB 447498 D03
IEEE C95.1

The above equipment (Model: AT-TQ4600) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** Dec. 25, 2014
(Elsie Hsu, Specialist)

APPROVED BY :  , **DATE:** Dec. 25, 2014
(May Chen, Manager)

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

There are antennas provided to the EUT, please refer to the following table:

For 2.4GHz used						
No.	Transmitter Circuit	Brand	Model	Antenna Type	Antenna Gain(dBi) Including cable loss	Connector type
1	CHAIN (0)	ARISTOT LE	RFA-02-G133-70B-110R	PIFA	3.1	I-PEX(MHF)
2	CHAIN (1)		RFA-02-G133-70B-58		3.17	
3	CHAIN (2)		RFA-02-G133-70B-180		1.75	
For 5GHz used						
No.	Transmitter Circuit	Brand	Model	Antenna Type	Antenna Gain(dBi) Including cable loss	Connector type
1	CHAIN (0)	ARISTOT LE	RFA-05-G134-70-230C	PIFA	2.65	I-PEX(MHF)
2	CHAIN (1)		RFA-05-G134-70-105C		4.15	
3	CHAIN (2)		RFA-05-G134-70-75C		4.04	

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

For 15.247 and 15.407(U-NII-1& U-NII-3) data was copied from the original test report (Report No.: SA140714E01A R1).

For WLAN: 15.247(2.4GHz)

802.11b

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 - 2462	126.474	3.1	20	0.05137	1.00

802.11g

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 - 2462	362.092	7.47	20	0.40230	1.00

Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 7.47

802.11n (HT20)

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 - 2462	275.13	7.47	20	0.30568	1.00

Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 7.47

802.11n (HT40)

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2422 - 2452	118.624	7.47	20	0.13180	1.00

Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 7.47

For WLAN: 15.407(5GHz)

802.11a

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5180 - 5240	204.225	8.41	20	0.28173	1.00
5260 ~ 5320	126.209	8.41	20	0.17411	1.00
5500 ~ 5580 & 5660 ~ 5700	129.524	8.41	20	0.17868	1.00
5745 - 5825	220.019	8.41	20	0.30352	1.00

Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 8.41

802.11n (HT20)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5180 - 5240	164.651	8.41	20	0.22714	1.00
5260 ~ 5320	125.438	8.41	20	0.17304	1.00
5500 ~ 5580 & 5660 ~ 5700	129.643	8.41	20	0.17885	1.00
5745 - 5825	175.42	8.41	20	0.24200	1.00

Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 8.41

802.11n (HT40)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5190 - 5230	130.591	8.41	20	0.18015	1.00
5270 ~ 5310	126.967	8.41	20	0.17515	1.00
5510 ~ 5550 & 5670	129.452	8.41	20	0.17858	1.00
5755 - 5795	132.953	8.41	20	0.18341	1.00

Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 8.41

802.11ac (VHT80)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5210	41.371	8.41	20	0.05707	1.00
5290	64.832	8.41	20	0.08944	1.00
5530	56.168	8.41	20	0.07749	1.00
5775	58.791	8.41	20	0.08110	1.00

Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$

Effective Legacy Gain (dBi) = 8.41

CONCLUSION:

Both of the 2.4GH and 5GHz can transmit simultaneously, the formula of calculated the MPE is:

$$CPD_1 / LPD_1 + CPD_2 / LPD_2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is $0.40230 / 1 + 0.30352 / 1 = 0.706$, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---