

48346 Milmont Dr., Fremont, CA 94538
 Phone: 510-770-0469 Fax: 510-996-7250
 www.surecall.com



Antenna Kitting Information

Fiber Max

Component	Prod No. Description	Gain/Loss					Notes
		LTE-A	LTE-V	800MHz	1900MHz	1700MHz\2100MHz	
Outdoor Antenna*	SC533W	6dBi	6dBi	6dBi	8dBi	8dBi\8dBi	
	SC548W	5dBi	5dBi	6dBi	7dBi	7dBi\7dBi	
	SC588W	3dBi	3dBi	3dBi	4dBi	4dBi\4dBi	
OutdoorCable*	SC-400-NN10Feet	0.7dB	0.7dB	0.7dB	1dB	1dB\1dB	10 Feet or longer
Indoor Antenna*	SC528W	3.5dBi	3.5dBi	3.5dBi	6.5dBi	6.5dBi\6.5dBi	
IndoorCable*	SC-400-NN50Feet	3.01dB	3.01dB	3.14dB	4.31dB	4.07dB\4.56dB	50 Feet or longer
	SC-400-NN100Feet	5.3dB	5.3dB	5.48dB	7.02dB	6.53dB\7.52dB	100 Feet or longer
* All equivalent antennas and cables are suitable for use with the Fiber Max. As above information. Remark: Lower gain antenna can also be used.							

		Maximum Gain	Minimum Gain
Outdoor Antenna	SC588W	4dBi	3dBi
	SC533W	8dBi	6dBi
	SC548W	7dBi	5dBi
Indoor Antenna	SC528W	6.5dBi	3.5dBi