



48346 Milmont Dr., Fremont, CA 94538  
 Phone: 510-770-0469 Fax: 510-996-7250  
 www.surecall.com

## Antenna Kitting Information Fusion5X Max V1.0

Component	Prod No. Description	Gain/Loss					Notes
		LTE-A	LTE-V	800MHz	1900MHz	1700MHz\2100MHz	
Outdoor Antenna*	SC548W	5dBi	5dBi	6dBi	7dBi	7dBi\7dBi	
	SC232W	8.5dBi	8.5dBi	8.5dBi	8.5dBi	8.5dBi\8.5dBi	default
Cable between systems *	SC-400-50NN 50Feet	3.01dB	3.01dB	3.14dB	4.31dB	4.07 dB \4.56dB	50 to 150 feet default
Indoor Cable*	SC240-20NN 20Feet	2.06dB	2.06dB	2.29dB	3.56dB	3.36dB\ 3.76dB	20 Feet or longer
	SC-400-50NN 50Feet	3.01dB	3.01dB	3.14dB	4.31dB	4.07 dB \4.56dB	50 to 150 feet default
Indoor Antenna*	SC222W	3dBi	3dBi	3dBi	6dBi	6dBi\6dBi	
	SC121W	1.2dBi	1.2dBi	1.2dBi	3dBi	3dBi\3dBi	
	SC302W	2.5dBi	2.5dBi	3dBi	5dBi	4dBi\5dBi	
	SC323W	2.5dBi	2.5dBi	3dBi	4dBi	4dBi\4dBi	
	SC-228W	3.5dBi	3.5dBi	3.5dBi	7.5dBi	7.5dBi\7.5dBi	default
	SC548W	5dBi	5dBi	6dBi	7dBi	7dBi\7dBi	default
Two splitter	SC-WS-2	-3.5dB	-3.5dB	-3.5dB	-3.5dB	-3.5dB	default

\*All equivalent antennas and cables are suitable for use with the Fusion5X Max V1.0