## **RF EXPOSURE**

According to §15.247(b)(4) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

| Frequency Range                                     | Electric Field | Magnetic Field | Power Density | Averaging Time |
|---|----------------|----------------|---------------|----------------|
| (MHz)   | Strength (V/m) | Strength (A/m) | $(mW/cm^2)$   | (minute)       |
| Limits for General Population/Uncontrolled Exposure |                |                |               |                |
| 0.3-1.34  | 614            | 1.63           | *(100)        | 30             |
| 1.34-30   | 824/f          | 2.19/f         | $*(180/f^2)$  | 30             |
| 30-300  | 27.5           | 0.073          | 0.2           | 30             |
| 300-1500  | /              | /              | f/1500        | 30             |
| 1500-15000  | /              | /              | 1.0           | 30             |

f = frequency in MHz

## **MPE Prediction**

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S = PG/4\pi R^2$ 

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic

radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: <u>31.4 (dBm)</u> Maximum peak output power at antenna input terminal: <u>1380.38 (mW)</u>

Prediction distance: 25 (cm)
Predication frequency: 850 (MHz)
Antenna Gain (typical): 5.0 (dBi)
Maximum antenna gain: 3.16 (numeric)

Power density at predication frequency at 25 cm: <u>0.555 (mW/cm^2)</u> MPE limit for uncontrolled exposure at prediction frequency: <u>0.567 (mW/cm^2)</u>

<sup>\* =</sup> Plane-wave equivalent power density

Maximum peak output power at antenna input terminal: <u>31.4 (dBm)</u> Maximum peak output power at antenna input terminal: <u>1380.38 (mW)</u>

Prediction distance: 20 (cm)
Predication frequency: 1900 (MHz)
Antenna Gain (typical): 5.0 (dBi)
Maximum antenna gain: 3.16 (numeric)

Power density at predication frequency at 20 cm: <u>0.868 (mW/cm^2)</u> MPE limit for uncontrolled exposure at prediction frequency: <u>1.0 (mW/cm^2)</u>

## **Test Result**

The predicted power density level at 25 cm is 0.555 mW/cm². It is below the uncontrolled exposure limit of 0.567mW/cm² at 850 MHz. The predicted power density level at 20 cm is 0.868 mW/cm². It is below the uncontrolled exposure limit of 1.0mW/cm² at 1900 MHz. The EUT is therefore defined as a mobile device.